

# STATISTICAL STRUCTURED PREDICTION

José Miguel Benedí e-mail: jmbenedi@prhlt.upv.es

Joan Andreu Sánchez e-mail: jandreu@prhlt.upv.es



UNIVERSITAT  
POLITÈCNICA  
DE VALÈNCIA



Statistical Structured Prediction

**VIRTUAL TEACHING**

**Purpose:**  
Provision of the higher education public service (art. 1 LOU)

**Responsible:**  
Universitat Politècnica de València.

**Rights of access, rectification, deletion, portability, limitation or opposition to the treatment in accordance with privacy policies:**  
<http://www.upv.es/contenidos/DPD/>

**Intellectual property:**  
Exclusive use in the virtual classroom environment.

Dissemination, distribution or disclosure of recorded classes, particularly on social networks or services dedicated to sharing notes, is prohibited.

Violation of this prohibition may generate disciplinary, administrative or civil liability.

**DOCENCIA VIRTUAL**

**Finalidad:**  
Prestación del servicio Público de educación superior (art. 1 LOU)

**Responsible:**  
Universitat Politècnica de València.

**Derechos de acceso, rectificación, supresión, portabilidad, limitación u oposición al tratamiento conforme a políticas de privacidad:**  
<http://www.upv.es/contenidos/DPD/>

**Propiedad intelectual:**  
Uso exclusivo en el entorno de aula virtual.

Queda prohibida la difusión, distribución o divulgación de la grabación de las clases y particularmente su compartición en redes sociales o servicios dedicados a compartir apuntes.

La infracción de esta prohibición puede generar responsabilidad disciplinaria, administrativa o civil

J.M. Benedí (2023-2024)

Statistical Structured Prediction 1

## STATISTICAL STRUCTURED PREDICTION

Técnicas Fundamentales	<b>R.F. y Aprendizaje Computacional</b> <b>Lingüística Computacional</b>
Reconocimiento de Formas	<b>Predicción Estructurada Estadística</b> <b>Redes Neuronales Artificiales</b> <b>Aplicaciones de Reconocimiento de Formas</b>
Tecnologías del Lenguaje	<b>Traducción Automática</b> <b>Reconocimiento Automático del Habla</b> <b>Aplicaciones de la Lingüística Computacional</b>
Técnicas Complementarias	<b>Aprendizaje Automático Avanzado</b> <b>Reconocimiento de Escritura</b> <b>Biometría</b> <b>Visión por Computador</b>

J.M. Benedí (2023-2024)

Statistical Structured Prediction 2

## STATISTICAL STRUCTURED PREDICTION

### Focus of Course

- Give students an overview of the different topics that allow them to understand the basic concepts:
  - What is structured prediction?
  - What problems will we try to address?
  - How to make predictions and learn the models in structured output spaces?
  - What are the different computational challenges for structured prediction?
- We will deal with the rigorous design of algorithms and make intensive use of mathematics, but nothing too hard.



*"There is nothing more practical than a good theory".*

Kurt Lewin

J.M. Benedí (2023-2024)

Statistical Structured Prediction 3

Syllabus

- 1. Introduction
- 2. Models for Statistical Structured Prediction
- 3. Making Prediction: Decoding and Inference
- 4. Model Parameter Estimation

Pattern Recognition and Machine Learning

- Christopher M. Bishop: *Pattern Recognition and Machine Learning*. Springer.
- Kevin P. Murphy: *Machine Learning: A Probabilistic Perspective*. The MIT Press.
- Daphne Koller and Nir Friedman: *Probabilistic Graphical Models: Principles and Techniques*. MIT Press.
- Richard O. Duda, Peter E. Hart and David G. Stork: *Pattern Classification* (2nd ed.). Wiley Interscience.

Statistical Models for Natural Language Processing

- Christopher D. Manning and Hinrich Schütze: *Foundations of Statistical Natural Language Processing*. The MIT Press.
- Noah A. Smith: *Linguistic Structure Prediction*. Morgan & Claypool.
- Daniel Jurafsky and James H. Martin: *Speech and Language Processing*. Prentice Hall (2<sup>nd</sup> ed).

Lectures

Monday 18:00 - 21:00 (10 sessions of 3 hours)

**J.M. Benedí** November 06, first session

**J.A. Sánchez** December 11, first session

Assessment

- 2 Collections of selected exercises (theoretical and practical)
- 1 Multiple-choice test 12-02-2024
- 1 Recovery exam 19-02-2024
- [ Multiple-choice test and theoretical/practical exercises ]

	delivery	deadline
Q1	04 - 12 - 2023	22 - 12 - 2023


Tutoring

Tutoring available by previous appointment

José Miguel Benedí <jmbenedi@prhlt.upv.es> (office: 1D13)

1. Introduction

- 1.1. Structured Prediction
- 1.2. Predicting Sequences
  - Weighted Finite-State Transducers and Automata
- 1.3. Syntactic Parsing
  - Context-Free Grammars



- **Input observation**;  $x \in \mathcal{X}$  can be any kind of object.
- **Output hypothesis**;  $y \in \mathcal{Y}$  is a real number:  $\mathcal{Y} = \{1, \dots, K\}$  or  $y \in \mathbb{R}$ .
- (Non-structured) **prediction function**;  $f : \mathcal{X} \rightarrow \mathbb{R}$  assigns a hypothesis  $y = f(x)$  to each entry  $x$ .
  - Binary classification:  $y \in \{-1, 1\}$ .
  - Multiclass classification:  $y \in \{1, \dots, K\}$ .
  - Regression:  $y \in \mathbb{R}$ .


## Algorithms for predicting non-structured output data

Naive Bayes classifier	Regression
Logistic Regression	Fisher's linear discriminant
Perceptron algorithm	K-Nearest Neighbor
Support Vector Machines	Random Forests
Neural Networks	...

What if the space of outputs is much larger and more structured?  
Say trees, or in general, graphs.


## Machine Translation

**Input:** Text sequences  
**Output:** Text sequences




## Syntactic Parsing


**Input:** Text sequences  
**Output:** Parse trees




## Automatic Speech Recognition

**Input:** Speech signals**Output:** Transcribed text sequences

## Handwriting Text Recognition

**Input:** Images**Output:** Transcribed text sequences


## Scene Analysis

**Input:** Images**Output:** Scene layout graphs

## Mathematical Expressions Recognit

**Input:** Images**Output:** Hypergrphs

$$\frac{x_2}{x_3} + \vec{x}$$



⇒ Mathematical Expression Recognition

## STRUCTURED PREDICTION: APPLICATIONS

### Outputs

#### > Natural Language Processing:

- > Part-of-Speech tagging (sentences)
- > Parsing (parse trees)
- > Machine Translation (sentences or hypergraphs)
- > Information Extraction (sentences)

#### > Image Processing:

- > Visual Scene Analysis (sentences or relationship graphs)
- > Handwritten Text Recognition (sentences or word graphs)

#### > Speech Processing:

- > Automatic transcription (sentences or word graphs)
- > Text-to-Speech (audio signal)


#### > Bioinformatics:

- > Protein Structure Prediction (graphs)

#### > Robotics:


- > Planning (sequence of actions)

## STRUCTURED PREDICTION



- > **Input observation;**  $x \in \mathcal{X}$  can be any kind of objects
- > **Output hypothesis;**  $y \in \mathcal{Y}$  is a complex structured object.
- > **(Structured) prediction function;**  $f : \mathcal{X} \rightarrow \mathcal{Y}$  which assigns a hypothesis  $y = f(x)$  to each entry  $x$ .
  - >  $y$  can be a sequence,
  - >  $y$  can be a parse tree,
  - >  $y$  can be a graph.

## STRUCTURED PREDICTION: SEARCH SPACE



- > Typically,  $\mathcal{Y}$  is potentially infinite  $\implies f(x) = y \in \mathcal{Y}$  will often be intractable.
- > **(Structural) Solution:** We assume a specific structure in  $\mathcal{Y}$ , and we define a (finite) model  $M$  that allows us to characterize this structure:  $Y(M) \subseteq \mathcal{Y}$

$$f(x) = y \in Y(M)$$

Depending on  $M$ , we can find polynomial solutions.

## PREDICTING SEQUENCES

### Sequences

- Text is a sequence of words or even letters,
- A spoken utterance is a sequence of parameter vectors,
- A video is a sequence of frames, ...

### Models and motivation

**Finite-State Acceptors:** Compact representations of regular sets that are efficient to search, e.g. pattern matching, tokenization, compression.

**Finite-State Transducers:** Compact representations of rational binary relations that are efficient to search and combine, e.g. dictionaries, context-dependent rules.

**Weighted Automata:** Weights typically encode uncertainty (probabilities), e.g. n-gram language models, Hidden Markov Models.

## PRELIMINARIES

WFSA and WFST-based operations are underpinned by algebraic objects called **semirings**.

**Definition.** A **semiring** is an algebraic system  $(\mathbb{K}, \oplus, \otimes, \bar{0}, \bar{1})$  such that,

- $(\mathbb{K}, \oplus, \bar{0})$  is a **commutative monoid**<sup>a</sup> with  $\bar{0}$  as the identity element for  $\oplus$ ,
- $(\mathbb{K}, \otimes, \bar{1})$  is a **monoid** with  $\bar{1}$  as the identity element for  $\otimes$ ,
- $\otimes$  distributes over  $\oplus$ : for all  $a, b, c \in \mathbb{K}$ ,
 
$$(a \oplus b) \otimes c = (a \otimes c) \oplus (b \otimes c)$$

$$c \otimes (a \oplus b) = (c \otimes a) \oplus (c \otimes b)$$
- $\bar{0}$  is an annihilator for  $\otimes$ : for all  $a \in \mathbb{K}$ ,
 
$$a \otimes \bar{0} = \bar{0} \otimes a = \bar{0}$$

This has implications for optimization, search, and combination algorithms such as determinization, shortest-path, and composition.

<sup>a</sup> A monoid is an algebraic structure that supports a single associative binary operation and an identity element.

## PRELIMINARIES

- **Product**  $\otimes$ : to compute the weight of a path  
(product of the weights of constituent transitions).
- **Sum**  $\oplus$ : to compute the weight of a sequence  
(sum of the weights of the paths labeled with that sequence).

Semiring	Set	$\oplus$	$\otimes$	$\bar{0}$	$\bar{1}$
Boolean	$\{0, 1\}$	$\vee$	$\wedge$	0	1
Probability	$\mathbb{R}_+ \cup \{+\infty\}$	$+$	$\times$	0	1
Log	$\mathbb{R} \cup \{-\infty, +\infty\}$	$\oplus_{\log}$	$+$	$+\infty$	0
Tropical	$\mathbb{R}_+ \cup \{+\infty\}$	$\min$	$+$	$+\infty$	0

- The **log semiring** is isomorphic to the **probability semiring** and  $\oplus_{\log}$  is defined by:  $x \oplus_{\log} y = -\log(e^{-x} + e^{-y})$
- The **tropical semiring** is derived from the **log semiring** using the *Viterbi* approximation

[M. Mohri. *Semiring frameworks and algorithms for shortest-distance problems*. 2002], for more details.

## PRELIMINARIES


### Tropical Semiring example

Definitions	Examples
$a \oplus b \stackrel{\text{def}}{=} \min(a, b)$	$7 \oplus 4 = 4$
$a \otimes b \stackrel{\text{def}}{=} a + b$	$1 \otimes 7 = 8$
$\bar{0} \stackrel{\text{def}}{=} +\infty$	$7 \oplus \bar{0} = 7$
$\bar{1} \stackrel{\text{def}}{=} 0$	$3 \otimes \bar{1} = 3$
	$(4 \otimes 3) \oplus (2 \otimes 3) = 5$
	$4 \oplus \bar{1} = 0$

## WEIGHTED FINITE-STATE TRANSUCER

**Definition.** A **weighted transducer**  $T$  over a semiring  $(\mathbb{K}, \oplus, \otimes, \bar{0}, \bar{1})$  is a tuple  $T = (\Sigma, \Delta, Q, I, F, \delta, \lambda, \rho)$ , where

- Finite input alphabet  $\Sigma$  and finite output alphabet  $\Delta$ .
- States  $Q$ , initial states  $I \subseteq Q$ , and final states  $F \subseteq Q$ .
- Transition function  $\delta: Q \times (\Sigma \cup \{\epsilon\}) \times (\Delta \cup \{\epsilon\}) \times \mathbb{K} \times Q$ .
- Initial weight function  $\lambda: I \rightarrow \mathbb{K}$  and final weight function  $\rho: F \rightarrow \mathbb{K}$ .




Probability semiring $(\mathbb{K}, +, \times, 0, 1)$	Tropical semiring $(\mathbb{K}, \min, +, \infty, 0)$
$[[T]](ab, r) = 16$	$[[T]](ab, r) = 5$

[Obtained from the OpenFst tool documentation]

## WEIGHTED FINITE-STATE AUTOMATON

**Definition.** A **weighted automaton**  $A$  over a semiring  $(\mathbb{K}, \oplus, \otimes, \bar{0}, \bar{1})$  is a tuple  $A = (\Sigma, Q, I, F, \delta, \lambda, \rho)$ , where

- Finite input alphabet  $\Sigma$ .
- States  $Q$ , initial states  $I \subseteq Q$ , and final states  $F \subseteq Q$ .
- Transition function  $\delta : Q \times (\Sigma \cup \{\epsilon\}) \times \mathbb{K} \times Q$ .
- Initial weight function  $\lambda : I \rightarrow \mathbb{K}$  and final weight function  $\rho : F \rightarrow \mathbb{K}$ .



Probability semiring $(\mathbb{K}, +, \times, 0, 1)$	Tropical semiring $(\mathbb{K}, \min, +, \infty, 0)$
$[[T]](ab) = 14$	$[[T]](ab) = 4$

[Obtained from the OpenFst tool documentation]

## DEFINITIONS

**Path**  $\pi$

$p[\pi]$	Path origin state
$n[\pi]$	Path destination state
$w[\pi]$	Path weight

### Sets of paths

$P(I, x, F)$  Set of all paths from  $I$  to  $F$  with input label  $x \in \Sigma^*$

$P(I, x, y, F)$  Set of all paths from  $I$  to  $F$  with input label  $x \in \Sigma^*$  and output label  $y \in \Delta^*$

### Automata and transducers

Given an **automaton**  $A = (\Sigma, Q, I, F, \delta, \lambda, \rho)$ , for all  $x \in \Sigma^*$

$$[[A]](x) = \bigoplus_{\pi \in P(I, x, F)} \lambda(p(\pi)) \otimes w(\pi) \otimes \rho(n(\pi))$$

Given a **transducer**  $T = (\Sigma, \Delta, Q, I, F, \delta, \lambda, \rho)$ , for all  $x \in \Sigma^*, y \in \Delta^*$

$$[[T]](x, y) = \bigoplus_{\pi \in P(I, x, y, F)} \lambda(p(\pi)) \otimes w(\pi) \otimes \rho(n(\pi))$$

## OPERATIONS

### Rational operations

**Sum (union)**  $[[T_1 \oplus T_2]](x, y) = [[T_1]](x, y) \oplus [[T_2]](x, y)$

**Product (Concat.)**  $[[T_1 \otimes T_2]](x, y) = \bigoplus_{\substack{x=x_1x_2 \\ y=y_1y_2}} [[T_1]](x_1, y_1) \otimes [[T_2]](x_2, y_2)$

**Closure**  $[[T^*]](x, y) = \bigoplus_{n=0}^{\infty} [[T^n]](x, y)$

### Unary operations

**Reversal**  $[[T^R]](x, y) = [[T]](x^R, y^R)$

**Inversion**  $[[T^{-1}]](x, y) = [[T]](y, x)$

**Projection**  $[[\downarrow T]](x) = \bigoplus_y [[T]](x, y)$

## OPERATIONS

### Binary Operations

**Composition**  $[[T_1 \circ T_2]](x, y) = \bigoplus_z [[T_1]](x, z) \oplus [[T_2]](z, y)$

**Intersection**  $[[A_1 \cap A_2]](x) = [[A_1]](x) \oplus [[A_2]](x)$

**Difference**  $[[A_1 - A_2]](x) = [[A_1 \cap \overline{A_2}]](x)$

### Optimization algorithms

**$\epsilon$ -Removal:** Creates an equivalent  $\epsilon$ -free transducer.

**Determinization:** Creates an equivalent deterministic transducer.

**Pushing:** Pushes arc weights forward or backward, accumulating and/or distributing them according to the semiring

**Minimization:** Creates an equivalent minimal deterministic transducer.


### Shortest-distance algorithms: **Shortest path**, and **N-Shortest paths**.

[M. Mohri. *Semiring frameworks and algorithms for shortest-distance problems*. 2002], for more details.

## COMPOSITION

**Definition:**  $[[T_i \circ T_2]](x, y) = \bigoplus_z [[T_1]](x, z) \otimes [[T_2]](z, y)$


**Example:** Weighted automaton over the tropical semiring



## DETERMINIZATION

**Definition:** Creates an equivalent deterministic weighted automaton/transducer


**Example:** Weighted automaton over the tropical semiring



## MINIMIZATION

**Definition:** Computes a minimal equivalent deterministic machine while preserving the input language and and weight/path properties of the original

**Example:** Weighted automaton over the tropical semiring



## REFERENCES

### General Background

- J.E.Hopcroft, J.D.Ullman: *Introduction to Automata Theory, Languages, and Computation*. Addison Wesley, 1979.
- T.H. Cormen, C.E.Leiserson, R.L.Rivest: *Introduction to Algorithms*. The MIT Press, 1992.

### WFST and WFSA applications

- M.Mohri, F.Pereira, M.Riley: *Speech Recognition with Weighted Finite-State Transducers*. In *Springer Handbook of Speech Processing*. Springer, 2008.
- M.Mohri: *Weighted Automata Algorithms*. In *Handbook of Weighted Automata*. Monographs in Theoretical Computer Science. Springer, 2009.
- A.Argueta, D.Chiang: *Composing Finite State Transducers on GPUs*. Proc. of the ACL, p.pages 2697–2705. Melbourne, Australia, 2018.

### Software

**OpenFst** is a open-source C++ library for weighted finite state transducers developed at Google.

More information available at <http://www.openfst.org>


- C.Allauzen, M.Riley, J.Schalkwyk, W.Skut, M.Mohri: *OpenFst: A General and Efficient Weighted Finite-State Transducer Library*. Proc. of the CIAA. Prague, CZ, 2007.



## SYNTACTIC PARSING


**Example:** “*Pierre Vinken, 61 years old, will join the board as a nonexecutive director Nov. 29.*” [Marcus et al., 1993]

((S (NP-SBJ (NP (NNP Pierre) (NNP Vinken)) (,) (ADJP (NP (CD 61) (NNS years)) (JJ old)) (,) (VP (MD will) (VP (VB join) (NP (DT the) (NN board)) (PP-CLR (IN as) (NP (DT a) (JJ nonexecutive) (NN director)))) (NP-TMP (NNP Nov.) (CD 29)))))) (..)))



## SYNTACTIC PARSING

### ➤ Parsing as a search problem



### ➤ Grammatical models: reasons for use

- Grammatical models are the simplest and most natural model for tree structures
- Formal (mathematical) framework is well known
- Compact models (small number of free parameters)
- Good behavior against the problem of ambiguity
- Context-free grammatical models represent well long-term dependencies of syntactic and semantic constraints of Natural Language

## CONTEXT-FREE GRAMMARS

### ➤ Context-Free Grammars $G = (\Sigma, N, S, \mathcal{P})$

$\Sigma$  a set of **terminal symbols**

$N$  a set of **non-terminals symbols** (or variables):  $N \cap \Sigma = \emptyset$

$S$  a distinguished **start symbol**:  $S \in N$

$\mathcal{P}$  a set of **rules** (or productions):  $(A \rightarrow \alpha) \in \mathcal{P}$ ;  $A \in N$ ;  $\alpha \in (N \cup \Sigma)^*$

### ➤ Direct derivation: $\delta A \gamma$ **directly derives** $\delta \alpha \gamma$ or

$\delta A \gamma \Rightarrow \delta \alpha \gamma$  **iff**  $\exists (A \rightarrow \alpha) \in \mathcal{P}$ ;  $\delta, \gamma \in (N \cup \Sigma)^*$

### ➤ Derivation: $\alpha$ **derives** $\beta$ or

$\alpha \xRightarrow{*} \beta$  **iff**  $\exists \alpha_0, \dots, \alpha_m \in (N \cup \Sigma)^*$ :  $\alpha = \alpha_0 \Rightarrow \alpha_1 \Rightarrow \dots \Rightarrow \alpha_{m-1} \Rightarrow \alpha_m = \beta$

### ➤ Language generated by a grammar: $L(G) = \{x \mid x \in \Sigma^* : S \xRightarrow{+} x\}$

**Theorem**  $x \in L(G)$  **iff**  $S \xRightarrow{+} x$  **iff**  $\exists t \in \mathcal{T} : \text{yield}(t) = x$


## CONTEXT-FREE GRAMMARS: EXAMPLE

**Example:** A simple Context-Free Grammars

[Manning and Schütze, 2002]

$S \rightarrow NP VP$	$VP \rightarrow V NP$	$V \rightarrow \text{saw}$	$NP \rightarrow \text{saw}$
$NP \rightarrow NP PP$	$VP \rightarrow VP PP$	$NP \rightarrow \text{astronomers}$	$NP \rightarrow \text{stars}$
$PP \rightarrow P NP$	$P \rightarrow \text{with}$	$NP \rightarrow \text{ears}$	$NP \rightarrow \text{telescopes}$

$S \Rightarrow NP VP \Rightarrow \text{astronomers VP} \Rightarrow \text{astronomers V NP} \Rightarrow \text{astronomers saw NP} \Rightarrow$   
 $\text{astronomers saw NP PP} \Rightarrow \text{astronomers saw stars PP} \Rightarrow \text{astronomers saw stars P NP}$   
 $\Rightarrow \text{astronomers saw stars with NP} \Rightarrow \text{astronomers saw stars with telescopes}$



## Algorithm 1: Cocke-Kasami-Younger

**Input:**  $G = (\Sigma, N, S, \mathcal{P})$  in FNC and

$\mathbf{x} = x_1 \dots x_T \in \Sigma^*$

**Output:** Parsing table  $t[i, j]$  ( $1 \leq i, j \leq T$ ) ;

$A \in t[i, i + l]$  iff  $A \xRightarrow{*} x_{i+1} \dots x_{i+l}$

**for**  $i : 0 \dots T - 1$  **do**

$t[i, i + 1] = t[i, i + 1] \cup \{A : (A \rightarrow b) \in P; b = x_{i+1}\}$

**for**  $l : 2 \dots T$  **do**

**for**  $i : 0 \dots T - l$  **do**


**for**  $k : 1 \dots l - 1$  **do**

$t[i, i + l] = t[i, i + l] \cup \{A : (A \rightarrow BC) \in P ;$   
                 $B \in t[i, i + k]; C \in t[i + k, i + l]\} ;$

**if**  $S \in t[0, T]$  **then**  $x \in L(G)$  **else**  $x \notin L(G)$ ;

$S \Rightarrow A S$   
 $S \Rightarrow b$   
 $A \Rightarrow A S$   
 $A \Rightarrow A A$   
 $A \Rightarrow a$

a a b



	$j = 1$	$j = 2$	$j = 3$	
$i = 0$	1: (A, 0, 0)	4: (A, 1, 2)	7: (S, 1, 5) 8: (A, 1, 5) 9: (A, 1, 6) 10: (S, 4, 3) 11: (A, 4, 3)	
$i = 1$		2: (A, 0, 0)	5: (S, 2, 3) 6: (A, 2, 3)	$l = 3$
$i = 2$			3: (S, 0, 0)	$l = 2$
				$l = 1$