



All Domains > Algorithms > Strings > String Construction

Badge Progress (Details)

Points: 1180.76 Rank: 16287

String Construction

by ma5termind

Problem

Submissions

Leaderboard

Discussions

Editorial

Amanda has a string, s , of m lowercase letters that she wants to copy into a new string, p . She can perform the following operations any number of times to construct string p :

- Append a character to the end of string p at a cost of **1** dollar.
- Choose any **substring** of p and append it to the end of p at no charge.

Given n strings (i.e., s_0, s_1, \dots, s_{n-1}), find and print the *minimum* cost of copying each s_i to p_i on a new line.

Input Format

The first line contains a single integer, n , denoting the number of strings.
Each line i of the n subsequent lines contains a single string, s_i .

Constraints

- $1 \leq n \leq 5$
- $1 \leq m \leq 10^5$

Subtasks

- $1 \leq m \leq 10^3$ for 45% of the maximum score.

Output Format

For each string s_i (where $0 \leq i < n$), print the minimum cost of constructing string p_i on a new line.

Sample Input

```
2
abcd
abab
```

Sample Output

```
4
2
```

Explanation

Query 0: We start with $s = \text{"abcd"}$ and $p = \text{""}.$

- Append character 'a' to p at a cost of **1** dollar, $p = \text{"a"}.$
 - Append character 'b' to p at a cost of **1** dollar, $p = \text{"ab"}.$
 - Append character 'c' to p at a cost of **1** dollar, $p = \text{"abc"}.$
 - Append character 'd' to p at a cost of **1** dollar, $p = \text{"abcd"}.$
- Because the total cost of all operations is $1 + 1 + 1 + 1 = 4$ dollars, we print **4** on a new line.

Query 1: We start with $s = \text{"abab"}$ and $p = \text{""}.$

- Append character 'a' to p at a cost of **1** dollar, $p = \text{"a"}.$
- Append character 'b' to p at a cost of **1** dollar, $p = \text{"ab"}.$
- Append substring "ab" to p at no cost, $p = \text{"abab"}.$

Because the total cost of all operations is $1 + 1 = 2$ dollars, we print **2** on a new line.

Note

A substring of a string S is another string S' that occurs "in" S ([Wikipedia](#)). For example, the substrings of the string "**abc**" are "**a**", "**b**", "**c**", "**ab**", "**bc**", and "**abc**".

f t in

Submissions: 7595



Max Score: 25




Difficulty: Easy

Rate This Challenge:

☆☆☆☆☆

[More](#)

Current Buffer (saved locally, editable)  

C#   

```
1 using System;
2 using System.Collections.Generic;
3 using System.IO;
4 using System.Linq;
5 class Solution {
6
7     static void Main(String[] args) {
8         int n = Convert.ToInt32(Console.ReadLine());
9         for(int a0 = 0; a0 < n; a0++){
10             string s = Console.ReadLine();
11
12
13             int costo = 0;
14             for (char ch = 'a'; ch <= 'z'; ch++)
15                 if (s.Contains(ch))
16                     costo++;
17
18             Console.WriteLine(costo);
19
20
21
22         }
23     }
24 }
25
```

Line: 22 Col: 10

 [Upload Code as File](#)

☐ Test against custom input

Run Code

Submit Code

Congrats, you solved this challenge!

✓ Test Case #0

✓ Test Case #3

✓ Test Case #6

✓ Test Case #9

✓ Test Case #1

✓ Test Case #4

✓ Test Case #7

✓ Test Case #10

✓ Test Case #2

✓ Test Case #5

✓ Test Case #8

✓ Test Case #11

Next Challenge

