Angry Professor

by devuy11

Problem Submissions Leaderboard Discussions Editorial Topics

A Discrete Mathematics professor has a class of N students. Frustrated with their lack of discipline, he decides to cancel class if fewer than K students are present when class starts.

Given the arrival time of each student, determine if the class is canceled.

Input Format

The first line of input contains T, the number of test cases.

Each test case consists of two lines. The first line has two space-separated integers, N (students in the class) and K (the cancelation threshold). The second line contains N space-separated integers ($a_1, a_2, \ldots, a_N$) describing the arrival times for each student.

Note: Non-positive arrival times ($a_i \leq 0$) indicate the student arrived early or on time; positive arrival times ($a_i > 0$) indicate the student arrived a_i minutes late.

Constraints

- $1 \leq T \leq 10$
- $1 \leq N \leq 1000$
- $1 \leq K \leq N$
- $-100 \leq a_i \leq 100, where\ i \in [1, N]$

Output Format

For each test case, print the word `YES` if the class is canceled or `NO` if it is not.

Note
If a student arrives exactly on time ($a_i = 0$), the student is considered to have entered before the class started.

Sample Input

```
2
4 3
-1 -3 4 2
4 2
0 -1 2 1
```

Sample Output

```
YES
NO
```

Explanation

For the first test case, $K = 3$. The professor wants at least 3 students in attendance, but only 2 have arrived on time (-3 and -1). Thus, the class is canceled.

For the second test case, $K = 2$. The professor wants at least 2 students in attendance, and there are 2 who have arrived on time (0 and -1). Thus, the class is *not* canceled.

Submissions: 115337
Max Score: 20
Difficulty: Easy

Rate This Challenge:

Need Help?

If - Else statements

More

Current Buffer (saved locally, editable) C#

```
using System;
using System.Collections.Generic;
using System.IO;
using System.Linq;
class Solution {

    static void Main(String[] args) {
        int t = Convert.ToInt32(Console.ReadLine());
        for(int a0 = 0; a0 < t; a0++){
            string[] tokens_n = Console.ReadLine().Split(' ');
            int n = Convert.ToInt32(tokens_n[0]);
            int k = Convert.ToInt32(tokens_n[1]);
            string[] a_temp = Console.ReadLine().Split(' ');
            int[] a = Array.ConvertAll(a_temp,Int32.Parse);

            int alumnos_temprano = 0;
            for (int i = 0; i < n; i++)
            {
                if (a[i] <= 0)
                {
                    alumnos_temprano++;
                }
            }


            if (alumnos_temprano >= k)
            {
                Console.WriteLine("NO");
            }
            else
            {
                Console.WriteLine("YES");
            }


        }
    }
}

```

Line: 16 Col: 13

Upload Code as File Test against custom input Run Code Submit Code

Congrats, you solved this challenge!

- ✔ Test Case #0
- ✔ Test Case #1
- ✔ Test Case #2
- ✔ Test Case #3
- ✔ Test Case #4
- ✔ Test Case #5
- ✔ Test Case #6
- ✔ Test Case #7
- ✔ Test Case #8
- ✔ Test Case #9
- ✔ Test Case #10
- ✔ Test Case #11

Next Challenge