Queen's Attack II

by bishop15

A queen is standing on an $n \times n$ chessboard. The chessboard's rows are numbered from 1 to n, going from bottom to top; its columns are numbered from 1 to n, going from left to right. Each square on the board is denoted by a tuple, (r, c), describing the row, r, and column, c, where the square is located.

The queen is standing at position (r_q, c_q) and, in a single move, she can attack any square in any of the eight directions (left, right, up, down, or the four diagonals). In the diagram below, the green circles denote all the cells the queen can attack from $(4, 4)$:



There are k obstacles on the chessboard preventing the queen from attacking any square that has an obstacle blocking the the queen's path to it. For example, an obstacle at location $(3, 5)$ in the diagram above would prevent the queen from attacking cells $(3, 5)$, $(2, 6)$, and $(1, 7)$:



Given the queen's position and the locations of all the obstacles, find and print the number of squares the queen can attack from her position at (r_q, c_q).

Input Format

The first line contains two space-separated integers describing the respective values of n (the side length of the board) and k (the number of obstacles).
The next line contains two space-separated integers describing the respective values of r_q and c_q, denoting the position of the queen.
Each line i of the k subsequent lines contains two space-separated integers describing the respective values of r_i and c_i, denoting the position of obstacle i.

Constraints

- $0 < n \leq 10^5$
- $0 \leq k \leq 10^5$
- A single cell may contain more than one obstacle; however, it is guaranteed that there will never be an obstacle at position (r_q, c_q) where the queen is located.

Subtasks

For 30% of the maximum score:

- $0 < n \leq 100$
- $0 \leq k \leq 100$

For 55% of the maximum score:

- $0 < n \leq 1000$
- $0 \leq k \leq 10^5$

Output Format

Print the number of squares that the queen can attack from position (r_q, c_q).

Sample Input 0

```
4 0
4 4
```

Sample Output 0

```
9
```

Explanation 0

The queen is standing at position $(4, 4)$ on a 4×4 chessboard with no obstacles:



We then print the number of squares she can attack from that position, which is 9.

Sample Input 1

```
5 3
4 3
5 5
4 2
2 3
```

Sample Output 1

```
10
```

Explanation 1

The queen is standing at position $(4, 3)$ on a 5×5 chessboard with $k = 3$ obstacles:



We then print the number of squares she can attack from that position, which is 10.

Submissions: 2527
Max Score: 30
Difficulty: Medium

Rate This Challenge:

More

Current Buffer (saved locally, editable) C#

```
using System;
using System.Collections.Generic;
using System.IO;
using System.Linq;
class Solution
{


    static int Norte(int rq, int cq, int ro, int co)
    {
        if (cq != co)
        {
            return int.MaxValue;
        }
        if (ro < rq)
        {
            return int.MaxValue;
        }

        return ro - rq - 1;
    }

    static int Sur(int rq, int cq, int ro, int co)
    {
        if (cq != co)
        {
            return int.MaxValue;
        }
        if (ro > rq)
        {
            return int.MaxValue;
        }
        return rq - ro - 1;
    }

    static int Este(int rq, int cq, int ro, int co)
    {
```

```
        if (rq != ro)
        {
            return int.MaxValue;
        }
        if (co < cq)
        {
            return int.MaxValue;
        }
        return co - cq - 1;
    }

    static int Oeste(int rq, int cq, int ro, int co)
    {
        if (rq != ro)
        {
            return int.MaxValue;
        }
        if (co > cq)
        {
            return int.MaxValue;
        }
        return cq - co - 1;
    }

    static int NorEste(int rq, int cq, int ro, int co)
    {
        //if (ro < rq || co < cq)
        //{
        //    return 0;
        //}
        if (ro > rq && co > cq && (ro - rq) == (co - cq))
        {
            return ro - rq - 1;
        }
        return int.MaxValue;
    }

    static int SurEste(int rq, int cq, int ro, int co)
    {

        if (ro < rq && co > cq && (rq - ro) == (co - cq))
        {
            return rq - ro - 1;
        }
        return int.MaxValue;
    }

    static int NorOeste(int rq, int cq, int ro, int co)
    {
        if (ro > rq && co < cq && (ro - rq) == (cq - co))
        {
            return ro - rq - 1;
        }

        return int.MaxValue;
    }

    static int SurOeste(int rq, int cq, int ro, int co)
    {
        if (ro < rq && co < cq && (rq - ro) == (cq - co))
        {
            return rq - ro - 1;
        }
        return int.MaxValue;
    }


    static void Main(String[] args)
    {
        string[] tokens_n = Console.ReadLine().Split(' ');
        int n = Convert.ToInt32(tokens_n[0]);
        int k = Convert.ToInt32(tokens_n[1]);
        string[] tokens_rQueen = Console.ReadLine().Split(' ');
```

```
        int rQueen = Convert.ToInt32(tokens_rQueen[0]);
        int cQueen = Convert.ToInt32(tokens_rQueen[1]);


        int maxNorte = n - rQueen;
        int maxSur = rQueen - 1;
        int maxEste = n - cQueen;
        int maxOeste = cQueen - 1;

        int maxNorEste = n - Math.Max(rQueen, cQueen);
        int maxSurEste = Math.Min(n - cQueen, rQueen - 1);
        int maxNorOeste = Math.Min(n - rQueen, Math.Abs(1 - cQueen));
        int maxSurOeste = Math.Min(rQueen, cQueen) - 1;

        for (int a0 = 0; a0 < k; a0++)
        {
            string[] tokens_rObstacle = Console.ReadLine().Split(' ');
            int ro = Convert.ToInt32(tokens_rObstacle[0]);
            int co = Convert.ToInt32(tokens_rObstacle[1]);
            // your code goes here

            //int ro = elem[0];
            //int co = elem[1];
            maxNorte = Math.Min(maxNorte, Norte(rQueen, cQueen, ro, co));
            maxSur = Math.Min(maxSur, Sur(rQueen, cQueen, ro, co));
            maxEste = Math.Min(maxEste, Este(rQueen, cQueen, ro, co));
            maxOeste = Math.Min(maxOeste, Oeste(rQueen, cQueen, ro, co));

            maxNorEste = Math.Min(maxNorEste, NorEste(rQueen, cQueen, ro, co));
            maxSurEste = Math.Min(maxSurEste, SurEste(rQueen, cQueen, ro, co));
            maxNorOeste = Math.Min(maxNorOeste, NorOeste(rQueen, cQueen, ro, co));
            maxSurOeste = Math.Min(maxSurOeste, SurOeste(rQueen, cQueen, ro, co));

        }

        Console.WriteLine(maxNorte + maxSur + maxEste + maxOeste + maxNorEste +
               maxSurEste + maxNorOeste + maxSurOeste);


    }
}

```

Line: 151 Col: 2

Upload Code as File Test against custom input Run Code Submit Code

Congrats, you solved this challenge!

- ✔ Test Case #0
- ✔ Test Case #1
- ✔ Test Case #2
- ✔ Test Case #3
- ✔ Test Case #4
- ✔ Test Case #5
- ✔ Test Case #6
- ✔ Test Case #7
- ✔ Test Case #8
- ✔ Test Case #9
- ✔ Test Case #10
- ✔ Test Case #11
- ✔ Test Case #12
- ✔ Test Case #13
- ✔ Test Case #14
- ✔ Test Case #15
- ✔ Test Case #16
- ✔ Test Case #17
- ✔ Test Case #18
- ✔ Test Case #19
- ✔ Test Case #20

Next Challenge