

## Mathematically



$$m_i = \frac{1}{2} (a_i + a_{i+1})$$

## With loops (slow)

```
for i in range(len(a)-1):
    m[i] = 0.5 * (a[i] + a[i+1])
```


## Numpy array operations

$$m = 0.5 * (a[:-1] + a[1:])$$



$$0.5 \times \begin{array}{c|c|c|c} 1+2 & 2+3 & 3+4 & 4+5 \\ \hline 1.5 & 2.5 & 3.5 & 4.5 \end{array}$$

## Jacobi algorithm



$$\phi_{ij} = \frac{1}{4} (\phi_{i-1,j} + \phi_{i+1,j} + \phi_{i,j-1} + \phi_{i,j+1})$$

## With loops (slow)

```
phi_new = phi.copy()
for i in range(1, phi.shape[0]-1):
    for j in range(1, phi.shape[1]-1):
        phi_new[i,j] = 0.25 * (phi[i-1,j] +
                                phi[i+1,j] +
                                phi[i,j-1] + phi[i,j+1])
```

## Numpy Arrays

$$\underbrace{\phi[1:-1, 1:-1]}_{\text{inside boundary conditions}} = 0.25 * \left( \underbrace{\phi[:-2, 1:-1]}_{\text{left neighbor}} + \underbrace{\phi[2:, 1:-1]}_{\text{right neighbor}} + \underbrace{\phi[1:-1, :-2]}_{\text{bottom neighbor}} + \underbrace{\phi[1:-1, 2:]}_{\text{top neighbor}} \right)$$



black  $\rightarrow$  white  
 white  $\rightarrow$  black

black 'odd'  
 white 'even'

## Gauss-Seidel algorithm in numpy

1) white ('even') lattice sites only require  $\phi$  from black sites.

Black sites only require data from white sites.

- 2) solve black and white sub-lattices separately with the Jacobi algorithm
- 3) use output of the black lattice as input for the white solution: in effect part of this iteration's solution is mixed in as in the Gauss-Seidel method.

In the implementation, each sublattice is split into a lattice on even and odd lines in order to be able to use slicing.

```
def Poisson_Gauss_Seidel_odd_even(Phi, rho, Delta=1.):
    """One update in the Gauss-Seidel algorithm for Poisson's equation on odd or even fields"""

    a = np.pi * Delta**2
    # odd update (uses old even)
    Phi[1:-2:2, 1:-2:2] = 0.25*(Phi[2::2, 1:-2:2] + Phi[0:-2:2, 1:-2:2] \
        + Phi[1:-2:2, 2::2] + Phi[1:-2:2, 0:-2:2]) \
        + a * rho[1:-2:2, 1:-2:2]
    Phi[2:-1:2, 2:-1:2] = 0.25*(Phi[3::2, 2:-1:2] + Phi[1:-2:2, 2:-1:2] \
        + Phi[2:-1:2, 3::2] + Phi[2:-1:2, 1:-2:2]) \
        + a * rho[2:-1:2, 2:-1:2]

    # even update (uses new odd)
    Phi[1:-2:2, 2:-1:2] = 0.25*(Phi[2::2, 2:-1:2] + Phi[0:-2:2, 2:-1:2] \
        + Phi[1:-2:2, 3::2] + Phi[1:-2:2, 1:-1:2]) \
        + a * rho[1:-2:2, 2:-1:2]
    Phi[2:-1:2, 1:-2:2] = 0.25*(Phi[3::2, 1:-2:2] + Phi[1:-2:2, 1:-2:2] \
        + Phi[2:-1:2, 2::2] + Phi[2:-1:2, 0:-2:2]) \
        + a * rho[2:-1:2, 1:-2:2]

    return Phi
```