Motional Ground-State Cooling Outside the Lamb-Dicke Regime – Supplemental material

Y. Yu,* N. R. Hutzler,† J. T. Zhang, L. R. Liu, T. Rosenband, and K.-K. Ni[‡]

Department of Chemistry and Chemical Biology,

Harvard University, Cambridge, Massachusetts, 02138, USA

Department of Physics, Harvard University, Cambridge, Massachusetts, 02138, USA and

Harvard-MIT Center for Ultracold Atoms, Cambridge, Massachusetts, 02138, USA

(Dated: August 14, 2017)

1. RAMAN SIDEBAND COOLING PULSE PARAMETERS AND SEQUENCE

Here, we list the full Raman sideband cooling (RSC) pulse parameters and sequence used to obtain the result in our paper. A step of RSC contains a Raman pulse and an optical pumping pulse. The full RSC sequence includes about 1000 pulses in 100 ms.

1.1. Optical pumping parameters

The optical pumping is performed with a σ^- -polarized beam aligned with an 8.8 G bias magnetic field. There are two frequencies in the beam: one is on resonance with the $|F=2,m_F=-1\rangle$ of $3^2S_{1/2}$ to $|F'=2,m_{F'}=-2\rangle$ of $3^2P_{1/2}$ D1 transition and the other is on resonance with the $|F=1,m_F=-1\rangle$ of $3^2S_{1/2}$ to $|F'=2,m_{F'}=-2\rangle$ of $3^2P_{3/2}$ D2 transition. All optical pumping pulses have the length of 40 μ s with a scattering rate of 0.14 MHz for atoms in $|F=1,m_F=-1\rangle$ and a scattering rate of 0.39 MHz for atoms in $|F=2,m_F=-1\rangle$.

1.2. Raman pulse parameters

Each Raman pulse in the cooling sequence is followed immediately by an optical pumping pulse. The full parameters for the Raman pulses, including the cooling "axis", the sideband "order (Δn) ", the cooling frequency " δ' ", the carrier $(\Delta n=0)$ frequency " δ'_0 ", the pulse "duration", the pulse strength in "full Rabi frequency", and the beam of which a non-uniform "power ramp" is applied, are listed in 9 groups below. The applied cooling frequency, δ' , is the two-photon detuning given relative to the zero-field F=1 and F=2 hyperfine splitting of 1.7716261288(10)GHz[1]. Due to the Stark shifts of the Raman beams, the carrier transition, δ'_0 , varies with the power of the Raman beams. δ'_0 is given also relative to the zero-field hyperfine splitting. The strength of the pulses given in "Full Rabi frequency" is the measured two-photon Rabi frequency Ω divided by the wave function overlap for each order of cooling. The difference between δ' and δ'_0 gives the motional sideband frequency, δ . Many Raman pulses include a "power ramp" with a Blackman envelope [2] to minimize off-resonant excitations. Because each Raman pulse is a product of two spatial- and temporal-overlapped laser beams, the "power ramp" is applied only to one of the beams for simplicity (we label the beam by the corresponding F number) while the other beam has a square-pulse shape. For a Raman pulse with a power ramp, the full Rabi frequency gives the arithmetics mean over the duration of the pulse.

^{*}Electronic address: vichaoyu@g.harvard.edu

[†]Present address: California Institute of Technology, Division of Physics, Mathematics, and Astronomy. Pasadena, CA, 91125

[‡]Electronic address: ni@chemistry.harvard.edu

1.2.1. Group 1

This group is repeated 5 times.

| Axis | Δn | δ' (MHz) | δ_0' (MHz) | Duration (μs) | Full Rabi frequency (kHz) | Power ramp |
|------|------------|-----------------|-------------------|--------------------|---------------------------|------------|
| x | -2 | -17.6375 | -18.42 | 25 | $2\pi \times 34$ | F1 |
| y | -2 | -17.2825 | -18.47 | 25 | $2\pi \times 34$ | F1 |
| x | -1 | -18.03 | -18.42 | 25 | $2\pi \times 34$ | F1 |
| y | -1 | -17.875 | -18.47 | 21 | $2\pi \times 34$ | F1 |

1.2.2. Group 2

This group is repeated 5 times.

| Axis | Δn | δ' (MHz) | δ_0' (MHz) | Duration (μs) | Full Rabi frequency (kHz) | Power ramp |
|------|------------|-----------------|-------------------|--------------------|---------------------------|------------|
| z | -8 | -17.966 | -18.506 | 80 | $2\pi \times 14$ | |
| x | -2 | -17.6375 | -18.42 | 25 | $2\pi \times 34$ | F1 |
| z | -7 | -18.0335 | -18.506 | 80 | $2\pi \times 14$ | |
| y | -2 | -17.2825 | -18.47 | 25 | $2\pi \times 34$ | F1 |
| z | -8 | -17.966 | -18.506 | 80 | $2\pi \times 14$ | |
| x | -1 | -18.03 | -18.42 | 25 | $2\pi \times 34$ | F1 |
| z | -7 | -18.0335 | -18.506 | 80 | $2\pi \times 14$ | |
| y | -1 | -17.875 | -18.47 | 21 | $2\pi \times 34$ | F1 |

1.2.3. Group 3

This group is repeated 6 times.

| Axis | Δn | δ' (MHz) | δ_0' (MHz) | Duration (μs) | Full Rabi frequency (kHz) | Power ramp |
|------|------------|-----------------|-------------------|--------------------|---------------------------|------------|
| z | -7 | -18.0335 | -18.506 | 80 | $2\pi \times 14$ | |
| x | -2 | -17.6375 | -18.42 | 25 | $2\pi \times 34$ | F1 |
| z | -6 | -18.101 | -18.506 | 80 | $2\pi \times 14$ | |
| y | -2 | -17.2825 | -18.47 | 25 | $2\pi \times 34$ | F1 |
| z | -7 | -18.0335 | -18.506 | 80 | $2\pi \times 14$ | |
| x | -1 | -18.03 | -18.42 | 25 | $2\pi \times 34$ | F1 |
| z | -6 | -18.101 | -18.506 | 80 | $2\pi \times 14$ | |
| y | -1 | -17.875 | -18.47 | 21 | $2\pi \times 34$ | F1 |

1.2.4. Group 4

This group is repeated 7 times.

| Axis | Δn | δ' (MHz) | δ_0' (MHz) | Duration (μs) | Full Rabi frequency (kHz) | Power ramp |
|------|------------|-----------------|-------------------|--------------------|---------------------------|------------|
| z | -6 | -18.101 | -18.506 | 80 | $2\pi \times 14$ | |
| x | -2 | -17.6375 | -18.42 | 25 | $2\pi \times 34$ | F1 |
| z | -5 | -18.1685 | -18.506 | 60 | $2\pi \times 14$ | |
| y | -2 | -17.2825 | -18.47 | 25 | $2\pi \times 34$ | F1 |
| z | -6 | -18.101 | -18.506 | 80 | $2\pi \times 14$ | |
| x | -1 | -18.03 | -18.42 | 25 | $2\pi \times 34$ | F1 |
| z | -5 | -18.1685 | -18.506 | 60 | $2\pi \times 14$ | |
| y | -1 | -17.875 | -18.47 | 21 | $2\pi \times 34$ | F1 |

1.2.5. Group 5

This group is repeated 7 times.

| Axis | Δn | δ' (MHz) | δ_0' (MHz) | Duration (μs) | Full Rabi frequency (kHz) | Power ramp |
|------|------------|-----------------|-------------------|--------------------|---------------------------|------------|
| z | -5 | -18.1685 | -18.506 | 90 | $2\pi \times 17$ | F2 |
| x | -1 | -18.03 | -18.42 | 38 | $2\pi \times 34$ | F1 |
| z | -4 | -18.236 | -18.506 | 75 | $2\pi \times 17$ | F2 |
| y | -1 | -17.875 | -18.47 | 25 | $2\pi \times 34$ | F1 |
| z | -5 | -18.1685 | -18.506 | 90 | $2\pi \times 17$ | F2 |
| x | -1 | -18.03 | -18.42 | 43 | $2\pi \times 34$ | F1 |
| z | -4 | -18.236 | -18.506 | 75 | $2\pi \times 17$ | F2 |
| y | -1 | -17.875 | -18.47 | 28 | $2\pi \times 34$ | F1 |

1.2.6. Group 6

This group is repeated 8 times.

| Axis | Δn | δ' (MHz) | δ_0' (MHz) | Duration (μs) | Full Rabi frequency (kHz) | Power ramp |
|------|------------|-----------------|-------------------|--------------------|---------------------------|------------|
| z | -4 | -18.236 | -18.506 | 75 | $2\pi \times 17$ | F2 |
| x | -1 | -18.03 | -18.42 | 38 | $2\pi \times 34$ | F1 |
| z | -3 | -18.3035 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| y | -1 | -17.875 | -18.47 | 25 | $2\pi \times 34$ | F1 |
| z | -4 | -18.236 | -18.506 | 75 | $2\pi \times 17$ | F2 |
| x | -1 | -18.03 | -18.42 | 43 | $2\pi \times 34$ | F1 |
| z | -3 | -18.3035 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| y | -1 | -17.875 | -18.47 | 28 | $2\pi \times 34$ | F1 |

1.2.7. Group 7

This group is repeated 10 times.

| Axis | Δn | δ' (MHz) | δ_0' (MHz) | Duration (μs) | Full Rabi frequency (kHz) | Power ramp |
|------|------------|-----------------|-------------------|--------------------|---------------------------|------------|
| z | -3 | -18.3035 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| x | -1 | -18.03 | -18.42 | 38 | $2\pi \times 34$ | F1 |
| z | -2 | -18.371 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| y | -1 | -17.875 | -18.47 | 25 | $2\pi \times 34$ | F1 |
| z | -3 | -18.3035 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| x | -1 | -18.03 | -18.42 | 43 | $2\pi \times 34$ | F1 |
| z | -2 | -18.371 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| y | -1 | -17.875 | -18.47 | 28 | $2\pi \times 34$ | F1 |

1.2.8. Group 8

This group is repeated 10 times.

| Axis | Δn | δ' (MHz) | δ_0' (MHz) | Duration (μs) | Full Rabi frequency (kHz) | Power ramp |
|------|------------|-----------------|-------------------|--------------------|---------------------------|------------|
| z | -2 | -18.371 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| x | -1 | -18.03 | -18.42 | 38 | $2\pi \times 34$ | F1 |
| z | -1 | -18.4385 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| y | -1 | -17.875 | -18.47 | 25 | $2\pi \times 34$ | F1 |
| z | -2 | -18.371 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| x | -1 | -18.03 | -18.42 | 43 | $2\pi \times 34$ | F1 |
| z | -1 | -18.4385 | -18.506 | 60 | $2\pi \times 17$ | F2 |
| y | -1 | -17.875 | -18.47 | 28 | $2\pi \times 34$ | F1 |

1.2.9. Group 9

This group is repeated 40 times.

| Axis | Δn | δ' (MHz) | δ_0' (MHz) | Duration (μs) | Full Rabi frequency (kHz) | Power ramp |
|------|------------|-----------------|-------------------|--------------------|---------------------------|------------|
| z | -1 | -18.3615 | -18.429 | 70 | $2\pi \times 9$ | F2 |
| z | -1 | -18.3615 | -18.429 | 100 | $2\pi \times 9$ | F2 |
| x | -1 | -18.03 | -18.42 | 38 | $2\pi \times 34$ | F1 |
| z | -1 | -18.3615 | -18.429 | 70 | $2\pi \times 9$ | F2 |
| z | -1 | -18.3615 | -18.429 | 100 | $2\pi \times 9$ | F2 |
| y | -1 | -17.875 | -18.47 | 25 | $2\pi \times 34$ | F1 |
| z | -1 | -18.3615 | -18.429 | 70 | $2\pi \times 9$ | F2 |
| z | -1 | -18.3615 | -18.429 | 100 | $2\pi \times 9$ | F2 |
| x | -1 | -18.03 | -18.42 | 43 | $2\pi \times 34$ | F1 |
| z | -1 | -18.3615 | -18.429 | 70 | $2\pi \times 9$ | F2 |
| z | -1 | -18.3615 | -18.429 | 100 | $2\pi \times 9$ | F2 |
| y | -1 | -17.875 | -18.47 | 28 | $2\pi \times 34$ | F1 |

^[1] D. A. Steck, Tech. Rep. (2010), URL http://steck.us/alkalidata.

^[2] M. Kasevich and S. Chu, Phys. Rev. Lett. 69, 1741 (1992), URL https://link.aps.org/doi/10.1103/PhysRevLett.69. 1741.