

# Gotex Doc

Saee Apis

#### **Contents:**

Saee A	pis	3
1.1	Create Order	3
1.2	Print Sticker	5
1.3	Get All Cities	6
1.4	Get All User Orders	7
1.5	Cancel Order	8

## **Saee Apis**

#### 1.1 Create Order

• Test URL: <a href="https://dashboard.go-tex.net/gotex-co-test/saee/create-user-order">https://dashboard.go-tex.net/gotex-co-test/saee/create-user-order</a>

Method: POST

#### Header

Field	Туре	Mandatory/Optional	Introduction
Content-Type	application/json;		

#### Body

Field	Туре	Mandatory /Optional	Introduction
userId	string	Mandatory	
Apikey	string	Mandatory	
cashonpickup	Float	Mandatory	value 0 denotes no cash on pickup
cashondelivery	Float	Mandatory	value 0 denotes no COD
p_name	string	Mandatory	Pick up Name
p_mobile	Ints	Mandatory	Pick up Mobile e.g. 966xxxxxxxxx
p_streetaddress	string	Mandatory	Pick up street address
p_city	Sting	Mandatory	Pick up City
c_name	string	Mandatory	Consignee Name
c_mobile	Ints	Mandatory	Consignee Mobile e.g. 966xxxxxxxxx
c_streetaddress	string	Mandatory	Consignee Street Address
c_city	Sting	Mandatory	Consignee City
Weight	Float	Mandatory	weight of package in KG
Quantity	Int	Mandatory	numbers of package of waybill
Description	strings	Mandatory	
Sendername	string	Optional	
Sendermail	string	Optional	

senderphone	string	Optional	
senderaddress	string	Optional	
Sendercity	string	Optional	
Sendercountry	string	Optional	
declared_value	Float	Optional	Shipment value
Cod	Boolean	Mandatory	True means cod (cash on delivery) payment method.
shipmentValue	Number	Mandatory	shipment price by default = 0

The total order price (credit card) = shipmentValue + kgprice if weight > 15kg
In case that is a cod payment method, the **cod price** added to the total order price.

Note: kgprice and cod price is specified by our administration.

#### Response Example

```
Response on success:
{
  "msg": "order created",
  "data": {
      "user": "64fefed86d3f876edc2f42a0",
      "company": "saee",
      "ordernumber": "16/1694522808301gotex",
      "data": {
        "success": true,
        "waybill": "OS42824322KS",
        "epayment_url": "",
        "message": "Pickup Order created successfully"
      },
      "paytype": "cc",
      "price": 22,
      "createdate": "Tue Sep 12 2023 15:46:48 GMT+0300 (Eastern European Summer Time)",
      "_id": "65005db855b3b90eed3d7eff",
      "__v": 0
}Response on error look like this:
  "err": "userId not valid"
                                                 4
}
```

#### 1.2 Print Sticker

■ Test URL: <a href="https://dashboard.go-tex.net/gotex-co-test/saee/print-sticker/:id">https://dashboard.go-tex.net/gotex-co-test/saee/print-sticker/:id</a>

■ Method: POST

#### Header

Field	Туре	Mandatory/Optional	Introduction
Content-Type	application/json;		

#### Body

Field	Туре	Mandatory /Optional	Introduction
userId	string	Mandatory	
Apikey	string	Mandatory	

#### Parameters

Field	Type	Mandatory /Optional	Introduction
orderld	string	Mandatory	

#### Response Example



#### 1.3 Get All Cities

■ Test URL: <a href="https://dashboard.go-tex.net/gotex-co-test/saee/get-cities">https://dashboard.go-tex.net/gotex-co-test/saee/get-cities</a>

■ Method: POST

#### Header

Field	Туре	Mandatory/Optional	Introduction
Content-Type	application/json;		

#### Body

Field	Туре	Mandatory /Optional	Introduction
userId	string	Mandatory	
apikey	string	Mandatory	

#### Response Example

```
Response on success in JSON:
{
  "data": {
     "success": true,
     "cities": [
          "id": 1,
          "province": "Gizan Province",
          "provice_ar": "منطقة جازان",
"name": "Abu Areish",
         ُ"أبو عريش" :"name_ar"
       }
        ]
   }
}
Response on error:
{
  "err": "userId not valid"
}
```

#### 1.4 Get All User Orders

■ **Test URL**: <a href="https://dashboard.go-tex.net/gotex-co-test/saee/get-user-orders">https://dashboard.go-tex.net/gotex-co-test/saee/get-user-orders</a>

■ Method: POST

#### Header

Field	Туре	Mandatory/Optional	Introduction
Content-Type	application/json;		

#### Body

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
apikey	string	Mandatory	

#### Response Example

```
Response on success in JSON:
{
  "data": [
    {
      "_id": "64ffa316969efd5fa3d4510c",
      "user": "64fefed86d3f876edc2f42a0",
      "company": "saee",
      "ordernumber": "14/1694475030010gotex",
      "data": {
        "success": true,
        "waybill": "OS42824316KS",
        "epayment_url": "",
        "message": "Pickup Order created successfully"
      },
      "paytype": "cc",
      "price": 22,
      "createdate": "Tue Sep 12 2023 02:30:30 GMT+0300 (Eastern European Summer Time)",
      " v": 0
    }
  ]
}
Response on error look like this:
{
  "err": "userId not valid"
}
```

#### 1.5 Cancel Order

■ **Test URL**: https://dashboard.go-tex.net/gotex-co-test/saee/cancel-order

■ Method: POST

#### ■ Header

Field	Туре	Mandatory/Optional	Introduction
Content-Type	application/json;		

### Body

Field	Туре	Mandatory /Optional	Introduction
userId	string	Mandatory	
apikey	string	Mandatory	
orderId	string	Mandatory	

#### Response Example

```
Response on success in JSON:

{

"data": {

"success": true,

"message": "This update is done successfully"

}

Response on error look like this:

{

"err": "userId not valid"

}
```