Gotex Doc

J&T Apis

Contents:

J&T Apis

1.1　　Create Order

- **Test URL**: https://dashboard.go-tex.net/gotex-co-test/jt/create-user-order
- **Method:** POST

- **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

- **Body**

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
Apikey	string	Mandatory	
re_address	string	Mandatory	
re_city	string	Mandatory	
re_mobile	string	Mandatory	
re_name	string	Mandatory	
re_prov	string	Mandatory	Province
s_address	Sting	Mandatory	
s_city	string	Mandatory	
s_mobile	string	Mandatory	
s_name	string	Mandatory	
s_prov	Sting	Mandatory	
Description	string	Mandatory	
Weight	string	Mandatory	weight of package in KG
goodsType	strings	Mandatory	
Items	Array of Objects	Mandatory	More details at the next table
Cod	Boolean	Mandatory	True means cod (cash on delivery) payment method.
shipmentValue	Number	Mandatory	Price of products (added in cod only) by default = 0
Order price = shipment price + kgprice if weight > 15kg In case of cod payment method, the **shipmentValue** added to the total order price **in the bill.**			

Note: shipment price and kgprice is specified by our administration.			

- **Items**

Number	Number	Mandatory	Item code number
itemType	Sting	Mandatory	
itemName	string	Mandatory	
priceCurrency	string	Mandatory	
itemValue	strings	Mandatory	
itemUrl	string	Mandatory	
Desc	string	Mandatory	

- **Response Example**

Response on success :

```json
{
  "data": {
    "user": "64fefed86d3f876edc2f42a0",
    "company": "jt",
    "ordernumber": 3,
    "data": {
      "code": "1",
      "msg": "success",
      "data": {
        "txlogisticId": "1695119354337Gotex",
        "billCode": "UTE010007144468",
        "subCodes": [],
        "sortingCode": "--",
        "createOrderTime": "2023-09-19 23:33:06"
      }
    },
    "paytype": "cc",
    "status": "pending",
    "price": 23,
    "createdate": "Tue Sep 19 2023 23:33:06 GMT+0300 (Eastern European Summer Time)",
    "_id": "650a05822221fc307fb5fbf2",
    "__v": 0
  }
}
```

Response on error look like this :

```json
{
  "err": "userId not valid"
}
```

1.2   Print Sticker

▪ **Test URL**: https://dashboard.go-tex.net/gotex-co-test/jt/print-sticker/:id

▪ **Method:** POST

▪ **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

▪ **Body**

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
Apikey	string	Mandatory	

▪ **Parameters**

Field	Type	Mandatory /Optional	Introduction
Id	string	Mandatory	orderId

▪ **Response Example**

Response on success :

{

   "data": String [pdf file in electronic format]

}

Response on error look like this :

{

   "err": "userId not valid"

}

1.3   Get All User Orders

▪ **Test URL**: https://dashboard.go-tex.net/gotex-co-test/jt/get-user-orders

▪ **Method:** POST

▪ **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

▪ **Body**

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
Apikey	string	Mandatory	

▪ **Response Example**

Response on success :

```
{
  "data": [
  {
    "status": "pending",
    "_id": "6509e6531605ab2a1409de5f",
    "user": "64fefed86d3f876edc2f42a0",
    "company": "jt",
    "ordernumber": 2,
    "data": {
      "code": "1",
      "msg": "success",
      "data": {
        "txlogisticId": "1695119354337Gotex",
        "billCode": "UTE010006042014",
        "subCodes": [],
        "sortingCode": "--",
        "createOrderTime": "2023-09-19 21:20:04"
      }
    },
    "paytype": "cc",
    "price": 22,
    "createdate": "Tue Sep 19 2023 21:20:03 GMT+0300 (Eastern European Summer Time)",
    "__v": 0
  }
]
}
```

Response on error look like this :

```
{
  "err": "userId not valid"
}
```

1.4   Cancel Order

- **Test URL**: https://dashboard.go-tex.net/gotex-co-test/jt/cancel-order

- **Method:** POST

- **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

- **Body**

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
Apikey	string	Mandatory	
orderId	string	Mandatory	

- **Response Example**

```
Response on success :
{
   "data": {
     "code": "1",
     "msg": "success",
     "data": {
        "txlogisticId": "1695119354337Gotex",
        "billCode": "UTE010006602811"
     }
   }
}
Response on error look like this :
{
   "err": "userId not valid"
}
```