



Gotex Doc

Imile Apis

Contents:

Imile Apis	3
1.1 Create Order	3
1.2 Print Sticker	6
1.3 Get All Clients.....	7
1.4 Get All User Orders.....	9
1.5 Cancel Order	11
1.6 Add Client	12

Imile Apis

Note: To be able to create order you need to add client first. You will find “add client” Api at the end of the Doc.

1.1 Create Order

- **Test URL:** <https://dashboard.go-tex.net/gotex-co-test/imile/create-user-order>
- **Method:** POST
- **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

- **Body**

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
Apikey	string	Mandatory	
p_company	string	Mandatory	Client companyName
c_company	Float	Mandatory	Customer company name
c_name	string	Mandatory	Pick up Name
c_mobile	string	Mandatory	Pick up Mobile e.g. 966xxxxxxxx
c_street	string	Mandatory	Pick up street address
c_city	String	Mandatory	Pick up City
c_address	string	Mandatory	Consignee Street Address
goodsValue	string	Mandatory	Consignee Street Address
codAmount	string	Mandatory	COD amount to be collected from the customer
paymentMethod	Sting	Mandatory	100: Prepaid(already paided) and 200: COD

weight	string	Mandatory	weight of package in KG
skuName	string	Mandatory	
skuDetailList	Array of Obj	Mandatory	Look at the next table
cod	Boolean	Mandatory	True means cod (cash on delivery) payment method.
shipmentValue	Number	Mandatory	Price of products (added in cod only) by default = 0
<p>Order price = shipment price + kgprice if weight > 15kg In case of cod payment method, the shipmentValue added to the total order price in the bill. Note: shipment price and kgprice is specified by our administration.</p>			

▪ **skuDetailList**

skuName	String	Mandatory	
skuNo	string	Mandatory	product code
skuDesc	string	Mandatory	SKU description
skuQty	string	Mandatory	Number of SKUs
skuUrl	Sting	Mandatory	
skuGoodsValue	string	Mandatory	SKU Value
skuWeight	string	Mandatory	
skuHsCode	string	Mandatory	HSCode

▪ Response Example

Response on success in JSON :

```
{
  "data": {
    "user": "64fefed86d3f876edc2f42a0",
    "company": "imile",
    "ordernumber": 3,
    "data": {
      "code": "200",
      "message": "success",
      "traceId": "4c6c0eac7acc44f6978a07bdf250d8a1.519.16946509283263151",
      "data": {
        "expressNo": "60914230042473996",
        "imileAwb": type String
      },
      "timeZone": "+4"
    },
    "paytype": "cc",
    "price": 9725,
    "createdate": "Thu Sep 14 2023 03:22:07 GMT+0300 (Eastern European Summer Time)",
    "_id": "6502522f4b55b7284032f3be",
    "__v": 0
  }
}
```

Response on error :

```
{
  "msg": {
    "code": "402",
    "message": "access token is empty",
    "timeZone": "+4",
    "traceId": "4c6c0eac7acc44f6978a07bdf250d8a1.523.16946513582893179"
  }
}
```

1.2 Print Sticker

▪ **Test URL:** <https://dashboard.go-tex.net/gotex-co-test/imile/print-sticker/:id>

▪ **Method:** POST

▪ **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

▪ **Body**

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
Apikey	string	Mandatory	

▪ **Parameters**

Field	Type	Mandatory /Optional	Introduction
id	string	Mandatory	Order id

▪ **Response Example**



1.3 Get All Clients

- **Test URL:** <https://dashboard.go-tex.net/gotex-co-test/imile/get-all-clients>
- **Method:** POST

- **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

- **Body**

Field	Type	Mandatory /Optional	Introduction
userId	String	Mandatory	
Apikey	String	Mandatory	

▪ Response Example

Response on success in JSON :

```
{
  "data": [
    {
      "_id": "6502000729c5c0ec0e5e8f3c",
      "companyName": "company 1",
      "contacts": "Soha Ali",
      "country": "KSA",
      "city": "TESt-Southern",
      "address": "test address",
      "phone": "9665442342",
      "email": "imile@google.com",
      "backupPhone": "",
      "attentions": "this is consignor address",
      "defaultOption": "0",
      "__v": 0
    }
  ]
}
```

Response on error :

```
{
  "msg": {
    "code": "402",
    "message": "access token is empty",
    "timeZone": "+4",
    "traceld": "4c6c0eac7acc44f6978a07bdf250d8a1.523.16946513582893179"
  }
}
```


1.4 Get All User Orders

▪ **Test URL:** <https://dashboard.go-tex.net/gotex-co-test/imile/get-user-orders>

▪ **Method:** POST

▪ **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

▪ **Body**

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
apikey	string	Mandatory	

▪ **Response Example**

Response on success in JSON :

```
{
  "data": [
    {
      "_id": "650210006855d3baff754bf5",
      "user": "64fefed86d3f876edc2f42a0",
      "company": "imile",
      "ordernumber": 2,
      "data": {
        "code": "200",
        "message": "success",
        "traceld": "4c6c0eac7acc44f6978a07bdf250d8a1.522.16946339856312039",
        "data": {
          "expressNo": "60914230025531355",
          "imileAwb": type String
        },
        "timeZone": "+4"
      },
      "paytype": "cc",
      "price": 10692,
      "createdate": "Wed Sep 13 2023 22:39:44 GMT+0300 (Eastern European Summer Time)",
      "__v": 0
    }
  ]
}
```

Response on error look like this :

```
{
  "msg": {
    "code": "402",
    "message": "access token is empty",
    "timeZone": "+4",
    "traceld": "4c6c0eac7acc44f6978a07bdf250d8a1.523.16946513582893179"
  }
}
```

1.5 Cancel Order

▪ **Test URL:** <https://dashboard.go-tex.net/gotex-co-test/imile/cancel-order>

▪ **Method:** POST

▪ **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

▪ **Body**

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
apikey	string	Mandatory	
orderId	string	Mandatory	

▪ **Response Example**

Response on success in JSON :

```
{
  "data": {
    "code": "200",
    "message": "success",
    "traceld": "7469731c30b9473db1b825175af41726.520.16948854939519573",
    "data": null,
    "timeZone": "+4"
  }
}
```

Response on error look like this :

```
{
  "err": "userId not valid"
}
```

1.6 Add Client

▪ **Test URL:** <https://dashboard.go-tex.net/gotex-co-test/imile/add-client>

▪ **Method:** POST

▪ **Header**

Field	Type	Mandatory/Optional	Introduction
Content-Type	application/json;		

▪ **Body**

Field	Type	Mandatory /Optional	Introduction
userId	string	Mandatory	
apikey	string	Mandatory	
companyName	string	Mandatory	It's a unique key. Note: You'll need this key in the body of create order api.
Contacts	string	Mandatory	
Country	string	Mandatory	
City	string	Mandatory	
Address	string	Mandatory	
Phone	string	Mandatory	
Email	string	Mandatory	
backupPhone	string	Mandatory	
Attentions	string	Mandatory	
defaultOption	string	Mandatory	

▪ Response Example

Response on success in JSON :

```
{
  "data": {
    "companyName": "company 2",
    "contacts": "Soha Ali",
    "country": "KSA",
    "city": "TESt-Southern",
    "address": "test address",
    "phone": "9665442342",
    "email": "imile@google.com",
    "backupPhone": "",
    "attentions": "this is consignor address",
    "defaultOption": "0",
    "_id": "65025cb24e42286531e9bb9a",
    "__v": 0
  }
}
```

Response on error look like this :

```
{
  "msg": {
    "code": "30036",
    "message": "consignor company has existed",
    "traceId": "451e973149a24d9087531eef283bb8d8.545.16946530893760007",
    "data": null,
    "timeZone": "+4"
  }
}
```