

STRENGTHENING DIGITAL DEFENSE SYSTEMS AT JETBLUE: A STRATEGIC REVIEW OF INFRASTRUCTURE WEAKNESSES AND THREAT REDUCTION STRATEGIES

Executive Summary

This paper presents a comprehensive cybersecurity risk analysis of JetBlue Airways' domestic route network, a critical component of the United States Transportation Systems Sector. Using complex network analysis, Mission-Based Risk Assessment (MBRA), and Fault Tree Analysis (FTA), this study identifies critical vulnerabilities, quantifies risks, and proposes evidence-based mitigation strategies. The analysis reveals that Boston Logan (BOS) and New York JFK represent blocking nodes whose compromise would cascade throughout the network. With a critical vulnerability threshold of 20.45%, JetBlue must maintain robust cybersecurity controls to prevent network-wide failures. The recommended annual cybersecurity budget of \$71.06M across prevention and response controls would reduce total network risk exposure by approximately 75%.

1. Introduction




Fig 1 – Jetblue Network Map (Domestic Route)

1.1 Background

JetBlue Airways, founded in 1998 and headquartered in Long Island City, New York, serves as a critical component of the United States' transportation infrastructure. As the 6th largest U.S. airline operating over 1,000 daily flights to 100+ destinations with 286 aircraft, JetBlue plays a significant role in connecting major cities and contributing approximately \$9 billion annually to the U.S. economy.

The aviation sector faces an unprecedented cybersecurity threat landscape. According to Eurocontrol, cyberattacks on aviation increased 131% between 2022 and 2023, with ransomware groups including LockBit, BlackCat, and Rhysida specifically targeting airline infrastructure. The July 2024 CrowdStrike incident, which cost Delta Air Lines approximately \$550 million, demonstrates the catastrophic financial impact of IT system failures on airline operations.

1.2 Scope and Objectives

This research focuses on JetBlue's primary domestic route network consisting of 14 major nodes representing significant hubs and focus cities that form the backbone of operations. The objectives are to:

1. Model the JetBlue network using complex network analysis techniques
2. Identify critical nodes and links vulnerable to cyber and physical attacks
3. Quantify risks using MBRA methodology
4. Develop prevention and response strategies with budget allocations
5. Provide actionable recommendations for the Department of Homeland Security

1.3 JetBlue Cyber Incident History

JetBlue has experienced several significant cybersecurity incidents:

- **2008-2011 Network Breach:** A network intrusion remained undetected for three years, exposing crew member personal data and demonstrating systemic detection vulnerabilities.
- **2002 Data Sharing Incident:** JetBlue shared 5 million passenger records with a Department of Defense contractor without customer consent, resulting in privacy lawsuits and regulatory scrutiny.
- **Ongoing Threats:** Customer account compromises and loyalty point fraud continue to affect the airline's digital infrastructure.

These historical incidents inform the threat probabilities and vulnerability assessments used in this analysis.

2. Network Model and Adjacency Matrix

2.1 Network Nodes

The JetBlue network is modeled as an undirected cascade network where nodes represent cities and links represent direct flight routes.

Node	Airport Code	City	Type
1	JFK	New York JFK	Primary Hub
2	BOS	Boston Logan	Focus City
3	FLL	Fort Lauderdale	Focus City
4	MCO	Orlando	Focus City
5	LAX	Los Angeles	Focus City
6	SJU	San Juan	Focus City
7	EWR	Newark	Spoke
8	DCA	Washington DCA	Spoke
9	TPA	Tampa	Spoke
10	LAS	Las Vegas	Spoke
11	SFO	San Francisco	Spoke
12	SEA	Seattle	Spoke
13	DEN	Denver	Spoke
14	MIA	Miami	Spoke

2.2 Adjacency Matrix (14 × 14)

The adjacency matrix represents the connectivity structure of the network:

Adjacency Matrix														
	JFK	BOS	FLL	MCO	LAX	SJU	EWL	DCA	TPA	LAS	SFO	SEA	DEN	MIA
JFK	—	1	1	1	1	1	0	1	1	1	1	1	1	1
BOS	1	—	1	1	1	1	1	1	1	1	1	1	1	1
FLL	1	1	—	1	1	1	1	1	1	1	0	0	1	1
MCO	1	1	1	—	1	1	1	1	1	1	0	0	1	0
LAX	1	1	1	1	—	0	1	0	0	1	1	1	1	0
SJU	1	1	1	1	0	—	1	0	1	0	0	0	0	1
EWL	0	1	1	1	1	1	—	0	1	1	1	0	1	1
DCA	1	1	1	1	0	0	0	—	1	0	0	0	0	0
TPA	1	1	1	1	0	1	1	1	—	0	0	0	0	0
LAS	1	1	1	1	1	0	1	0	0	—	0	0	0	0
SFO	1	1	0	0	1	0	1	0	0	0	—	1	0	0
SEA	1	1	0	0	1	0	0	0	0	0	1	—	0	0
DEN	1	1	1	1	1	0	1	0	0	0	0	0	—	0
MIA	1	1	1	0	0	1	1	0	0	0	0	0	0	—

Fig 2 – Jetblue Link Nodes Adjacency Matrix

3. Network Characterization and Metrics

3.1 Basic Network Statistics

The network analysis reveals several key structural characteristics of JetBlue's route system. The airline's infrastructure comprises fourteen nodes, each representing a distinct city within the network. These cities are connected through a total of fifty-five direct flight routes, forming the backbone of the carrier's operations. Among all locations, Boston demonstrates the highest level of connectivity with a maximum network degree of thirteen, indicating it serves as the primary hub with direct links to nearly every other destination. On average, each city in the network maintains approximately eight connections to other nodes, reflected in the mean degree value of 7.857. The overall network density stands at roughly sixty percent, suggesting a moderately interconnected system where more than half of all possible route combinations are actively served. This density level indicates that JetBlue has developed a relatively robust web of connections while still maintaining strategic selectivity in its route offerings.

3.2 Spectral Analysis

The spectral radius is calculated as the largest eigenvalue of the adjacency matrix.

Eigenvalues of Connection Matrix: $\lambda = [-4.127, -2.891, -2.156, -1.734, -1.245, -0.892, -0.456, 0.234, 0.678, 1.123, 1.567, 2.345, 3.012, 7.542]$

Spectral Radius (ρ) = 7.542

This high spectral radius indicates the network is highly susceptible to cascade failures. A higher spectral radius means disruptions can propagate more easily through the network.

3.3 Robustness Metrics

Using standard network robustness formulas:

Metric	Formula	Value	Interpretation
Link Robustness	$1 - (1/\rho)$	86.74%	High link redundancy
Node Robustness	$1/\rho$	13.26%	Low node redundancy
Links that can be removed	55×0.8674	48	Non-critical links
Critical Links	55×0.1326	7	Links requiring protection
Nodes that can be removed	14×0.8674	12	Non-critical nodes
Blocking Nodes	14×0.1326	2	JFK and BOS

3.4 Node Degree and Centrality Rankings

Rank	Node	City	Degree	Degree Centrality	Betweenness Centrality	Eigenvector Centrality
1	2	BOS	13	1	0.182	0.342
2	1	JFK	12	0.923	0.156	0.328
3	3	FLL	11	0.846	0.087	0.312
4	4	MCO	10	0.769	0.065	0.298
5	7	EWR	10	0.769	0.098	0.287
6	5	LAX	9	0.692	0.143	0.256
7	6	SJU	7	0.538	0.043	0.221
8	9	TPA	7	0.538	0.032	0.234
9	10	LAS	6	0.462	0.021	0.198
10	13	DEN	6	0.462	0.028	0.187
11	8	DCA	5	0.385	0.012	0.165
12	11	SFO	5	0.385	0.054	0.154
13	14	MIA	5	0.385	0.015	0.176
14	12	SEA	4	0.308	0.008	0.132

Key Finding: Boston (BOS) emerges as the most critical node, consistently ranking highest across all centrality measures. New York JFK ranks second. These two nodes are identified as blocking nodes whose protection is essential for network integrity.

3.5 Critical Links (Link Betweenness Centrality)

An examination of link betweenness centrality helps identify the most critical connections within JetBlue's route network. The route between New York (JFK) and Boston ranks as the most essential link, with a betweenness centrality score of 0.156, signifying its pivotal role in facilitating traffic flow across the system. Following closely is the New York to Los Angeles corridor, which holds a centrality value of 0.143, underscoring its importance as a key transcontinental connection. The Boston to Los Angeles route ranks third with a score of 0.132, and both of these links are classified as critical to network operations. Several other routes demonstrate high levels of importance, including the Boston to San Francisco connection at 0.098 and the New York to Fort Lauderdale link at 0.087. The Los Angeles to San Francisco route also registers as highly significant with a centrality score of 0.076.

Additionally, the Boston to Seattle connection shows moderate criticality with a value of 0.065. Together, these findings suggest that routes originating from or connecting major hubs like New York, Boston, and Los Angeles serve as the primary arteries of JetBlue's network, and any disruption to these links could substantially impact overall connectivity and operational efficiency.

4. Resilience Equation and Critical Vulnerability

4.1 MBRA-Based Resilience Analysis

Using the Mission-Based Risk Assessment tool, two instances were analyzed with different vulnerability levels to derive the resilience equation.

Instance	Vulnerability (γ)	Total Risk Initial (\$M)	Total Risk Reduced (\$M)	$q = \frac{\text{q Reduced}}{\text{Initial}}$	$\log_{10}(q)$
1	20% = 0.20	36.14	36.52	1.0105	0.00454
2	80% = 0.80	144.53	36.52	0.2527	-0.5974

4.2 Solving for Constants b and k

The resilience equation follows the form: $\log(q) = b + k \times \gamma \times \rho$

Equation 1 ($\gamma = 0.20$): $0.00454 = b + k \times 0.20 \times 7.542$ $0.00454 = b + 1.5084k$

Equation 2 ($\gamma = 0.80$): $-0.5974 = b + k \times 0.80 \times 7.542$ $-0.5974 = b + 6.0336k$

Solving by subtraction: $-0.5974 - 0.00454 = 6.0336k - 1.5084k$ $-0.6019 = 4.5252k$ **$k = -0.1330$**

Substituting k into Equation 1: $0.00454 = b + 1.5084 \times (-0.1330)$ $0.00454 = b - 0.2006$ **$b = 0.2051$**

4.3 Critical Vulnerability Calculation

The critical vulnerability threshold is calculated using:

$$\gamma_0 = -b / (k \times \rho) \quad \gamma_0 = -0.2051 / (-0.1330 \times 7.542) \quad \gamma_0 = -0.2051 / (-1.0031) \quad \gamma_0 = \mathbf{0.2045 = 20.45\%}$$

4.4 Final Resilience Equation

$$q = 10^{(0.2051 - 0.1330 \times \gamma \times 7.542)}$$

$$\text{Simplified: } q = 10^{(0.2051 - 1.0031\gamma)}$$

4.5 Interpretation

The critical vulnerability of $\gamma_0 = 20.45\%$ represents a relatively low threshold, indicating the JetBlue network is highly sensitive to vulnerabilities. Key implications include:

1. **Tipping Point:** When network vulnerability exceeds approximately 20%, the network transitions from stable ($q > 1$) to unstable ($q < 1$)
2. **High Cascade Risk:** The high spectral radius (7.542) combined with hub-and-spoke topology creates rapid cascade propagation potential
3. **Urgent Action Required:** JetBlue must maintain vulnerabilities well below 20% at critical nodes (JFK, BOS)
4. **Safety Margin:** Recommend targeting less than 15% vulnerability at all nodes to maintain a stability buffer

[See Appendix B for Resilience Curve Graph]

5. Discussion of Cyber and Physical Attacks

5.1 Random Cyber and Physical Attacks

Random attacks target nodes without regard to their network importance. Using MBRA analysis, the impact of random attacks on the JetBlue network was assessed.

Random Attack Characteristics:

- Attack probability is uniformly distributed across all nodes
- Expected impact proportional to average node consequence
- Network can absorb random failures of low-centrality nodes (SEA, DCA, SFO, MIA)

MBRA Results for Random Attacks: The network demonstrates moderate resilience to random attacks due to high link redundancy (86.74%). Random removal of any single spoke node results in less than 5% network capacity degradation. However, random attacks on hub nodes (probability $\approx 2/14 = 14.3\%$) would cause significant cascading effects.

Risk Distribution:

- 75% of total network risk (\$87M of \$114.3M) concentrated in top 5 nodes
- Random attacks have 35.7% probability of hitting high-risk nodes
- Expected loss from random attack: \$8.16M per incident

5.2 Targeted Cyber and Physical Attacks

Targeted attacks focus on high-value nodes identified through centrality analysis. The JetBlue network is particularly vulnerable to targeted attacks on blocking nodes.

Targeted Attack Analysis for BOS (Highest Degree Centrality = 1.000):

If Boston Logan is compromised:

- 13 direct routes immediately affected
- 18,000 daily passengers stranded
- Cascade probability to connected nodes: 65% (based on vulnerability)
- Expected consequence: \$40M direct + cascading effects

Targeted Attack Analysis for JFK (Primary Hub):

If New York JFK is compromised:

- 12 direct routes immediately affected
- 25,000 daily passengers stranded
- Headquarters operations disrupted
- Expected consequence: \$52.5M direct + cascading effects

Combined Targeted Attack Scenario:

A coordinated attack on both BOS and JFK would:

- Sever the most critical link (JFK-BOS, BC = 0.156)
- Isolate 85% of the network
- Result in estimated losses exceeding \$100M
- Require 24-48 hours minimum recovery time

5.3 Attack Vector Analysis

Cyber Attack Vectors:

1. Phishing campaigns targeting airline staff (probability: 0.60)
2. Ransomware deployment through vendor systems (probability: 0.50)
3. API exploitation in booking/reservation systems (probability: 0.60)
4. Insider threats from disgruntled employees (probability: 0.40)

Physical Attack Vectors:

1. Terrorism targeting hub airports
2. Runway incursions disrupting operations
3. Infrastructure sabotage
4. Vandalism of ground equipment

6. MBRA Risk Estimation for Random Attacks

6.1 Derivation of Input Values

The Mission-Based Risk Assessment (MBRA) methodology requires careful estimation of threat probabilities, vulnerability probabilities, consequences, and control costs for each network node. This section explains the rationale and data sources used to derive these values for the JetBlue network analysis.

Threat probabilities were assigned based on multiple factors reflecting each node's attractiveness as a target. Nodes with higher degree centrality represent more valuable targets because compromising them disrupts more connections simultaneously. Similarly, nodes with high betweenness centrality serve as critical bridges whose compromise would fragment the network, making them attractive to sophisticated attackers. Historical data on aviation cyber incidents consistently shows that hub airports receive disproportionate attention from threat actors, with major hubs experiencing attack attempts at rates two to three times higher than spoke airports. The Eurocontrol report documenting a 131% increase in aviation cyberattacks between 2022 and 2023 informed the overall threat level calibration, with primary hubs like JFK assigned threat probabilities of 0.95 and peripheral nodes like Seattle assigned probabilities as low as 0.40.

Vulnerability probabilities were derived from JetBlue's documented security history and industry benchmarks. The 2008-2011 network breach that remained undetected for three years demonstrates systemic weaknesses in detection capabilities, particularly at the primary hub infrastructure. Industry analysis from IBM X-Force indicates that airline IT systems have an average vulnerability rate of approximately 60%, which served as a baseline for spoke node assessments. The July 2024 CrowdStrike incident affecting Delta Air Lines revealed the fragility of airline operational technology systems and their susceptibility to cascading failures from third-party software dependencies. Node-specific adjustments accounted for factors including legacy system prevalence, the number of third-party

integration points, and geographic considerations such as infrastructure challenges at remote locations like San Juan.

Consequence values were calculated using a multi-component framework encompassing direct operational losses, passenger compensation requirements, reputation damage, and recovery costs. Direct operational losses were estimated based on JetBlue's approximately \$25 million daily revenue, distributed across nodes according to their share of total network traffic. Passenger compensation estimates assumed an average of \$500 per affected passenger, reflecting Department of Transportation regulations for flight disruptions combined with goodwill gestures typically offered by airlines during major incidents. Reputation damage was estimated at 0.5% to 2% of annual revenue based on documented impacts from similar incidents at other carriers. Recovery costs include IT system restoration, staff overtime, and rebooking system strain. The Delta Air Lines CrowdStrike incident, which resulted in approximately \$550 million in losses over a five-day disruption period, provided a real-world benchmark of roughly \$110 million per day for a major carrier, which was scaled appropriately for JetBlue's network size.

For sector-specific consequence measurement, the analysis employed multiple units beyond dollar amounts. Outage duration was measured in minutes, with hub nodes experiencing estimated 24-hour outages compared to 8-12 hours for spoke nodes. Passenger impact was measured by the number of affected travelers, ranging from 25,000 daily passengers at JFK to 3,000 at Seattle. Flight delays were counted by the number of affected departures, with JFK experiencing up to 200 delayed flights in a full-day outage scenario. All sector-specific metrics were converted to equivalent dollar values for risk aggregation and comparison purposes.

The complete MBRA input values for all fourteen nodes, including threat probabilities, vulnerability probabilities, consequences, prevention costs, and response costs, are provided in Appendix G, Table G-1. The risk score for each node was calculated using the standard formula: $\text{Risk} = \text{Threat} \times \text{Vulnerability} \times \text{Consequence}$.

6.2 Critical Node Rankings and Analysis

The MBRA analysis reveals a highly concentrated risk distribution across the JetBlue network. The complete node ranking table is provided in Appendix G, Table G-2. New York JFK emerges as the highest-risk node with a risk score of \$34.9 million, followed by Boston Logan at \$23.4 million. Together, these two blocking nodes account for \$58.3 million, or 51% of the total network risk of \$114.3 million. This concentration validates the network analysis findings that identified JFK and BOS as blocking nodes requiring priority protection.

The third and fourth ranked nodes, Los Angeles LAX (\$12.1 million) and Fort Lauderdale FLL (\$10.7 million), represent high-priority targets due to their roles as regional gateways. LAX serves as the critical West Coast bridge node, and its compromise would effectively isolate Seattle, San Francisco, Las Vegas, and Denver from the eastern network. Fort Lauderdale anchors the Florida cluster and handles significant seasonal traffic volume.

Medium-risk nodes including Orlando, San Juan, and Newark range from \$5.0 million to \$7.7 million in risk exposure. These nodes require standard security controls but do not demand the enhanced investment levels appropriate for blocking nodes. The remaining seven nodes, classified as low risk, collectively account for only \$16.6 million or 14.5% of total network risk. Seattle, with the lowest risk score of \$0.7 million, reflects its peripheral position in the network with only four connections and minimal bridging function.

6.3 Risk Reduction Through Budget Allocation

The MBRA analysis demonstrates substantial risk reduction potential through strategic allocation of prevention and response budgets. The total recommended prevention budget of \$40.53 million and response budget of \$30.53 million, when optimally allocated across nodes based on risk priority, reduces total network risk from \$114.3 million to approximately \$37 million. This represents a 67.6% risk reduction and yields a return on investment of 1.09 dollars avoided for every dollar invested.

However, the ROI improves dramatically when focusing resources on blocking nodes. Allocating \$12.9 million in prevention and \$10.3 million in response specifically to JFK and BOS addresses 51% of total network risk at only 33% of the total budget, achieving an ROI of 2.52:1. This finding supports a phased implementation approach that prioritizes blocking node protection before expanding to the broader network.

7. Prevention and Response Controls

7.1 Prevention Controls for Critical Nodes

JFK (Primary Hub) - Prevention Budget: \$7.0M

Control	Cost (\$M)	Risk Reduction
Next-generation firewall/IDS	2	25%
Employee security training	0.5	15%
24/7 SOC monitoring	1.5	20%
System redundancy	3	30%

BOS (Focus City) - Prevention Budget: \$5.9M

Control	Cost (\$M)	Risk Reduction
Network segmentation	1.8	25%
MFA implementation	0.4	20%
Continuous monitoring	1.2	20%
Backup systems	2.5	25%

7.3 Network-Wide Controls

The response control framework for critical nodes outlines dedicated resources and capabilities designed to minimize recovery time following a cybersecurity incident. For the JFK hub, a total response budget of 5.8 million dollars has been allocated across four primary control areas. The largest portion of this investment, at 2.0 million dollars, is directed toward disaster recovery systems, which are expected to reduce recovery time by thirty-five percent. An incident response team will be established with a budget of 1.5 million dollars, providing the most significant recovery time improvement at forty percent. Additionally, forensics capabilities will receive 0.8 million dollars in funding and contribute a fifteen percent reduction in recovery duration. The remaining 1.5 million dollars is set aside for public relations and legal reserves, which will help manage reputational and regulatory impacts while offering a ten percent improvement in overall response efficiency.

Similarly, the Boston hub has been assigned a response budget of 4.5 million dollars distributed across the same four categories. The incident response team at this location will receive 1.2 million dollars and is projected to deliver a forty percent reduction in recovery time. Disaster recovery systems will be

funded at 1.5 million dollars with an anticipated thirty-five percent improvement. Forensics capability for the Boston node carries a budget of 0.6 million dollars and offers a fifteen percent reduction in recovery duration. Finally, 1.2 million dollars has been reserved for public relations and legal purposes, contributing an additional ten percent toward faster incident resolution. Together, these investments ensure that the two most critical nodes in the network are well-equipped to respond swiftly and effectively to any cyber threats.

Zero-Trust Architecture Implementation Given JetBlue's history of prolonged undetected breaches (2008-2011), implementing zero-trust architecture across all network management systems is essential. This includes:

- Microsegmentation between airport systems
- Continuous verification of all users and devices
- Least-privilege access controls
- Real-time threat detection and response

Network Segmentation Strategy Implement logical separation between:

- East Coast cluster (JFK, BOS, EWR, DCA)
- Florida cluster (FLL, MCO, TPA, MIA)
- West Coast cluster (LAX, SFO, SEA, LAS, DEN)
- Caribbean operations (SJU)

This segmentation contains potential cascades and prevents network-wide failures.

8. Fault Tree Analysis

8.1 JFK Node Fault Tree

Top Event: JFK Node Compromised ($P = 0.665$)

The fault tree identifies three primary attack paths connected by an OR gate:




Fig 2 – JFK Fault Tree Analysis

Attack Path 1: External Attack (P = 0.45)

- Connected by AND gate:
 - Phishing success (P = 0.60)
 - Weak credentials exploited (P = 0.75)
- Combined: $0.60 \times 0.75 = 0.45$

Attack Path 2: Insider Threat (P = 0.25)

- Connected by AND gate:
 - Disgruntled employee (P = 0.40)
 - Excessive access rights (P = 0.625)
- Combined: $0.40 \times 0.625 = 0.25$

Attack Path 3: Third-Party Breach (P = 0.30)

- Connected by AND gate:
 - Vendor vulnerability (P = 0.50)
 - API exposure (P = 0.60)
- Combined: $0.50 \times 0.60 = 0.30$

Top Event Calculation (OR gate): $P(\text{JFK Compromised}) = 1 - (1-0.45)(1-0.25)(1-0.30)$ $P = 1 - (0.55)(0.75)(0.70) = 1 - 0.289 = 0.711$ Adjusted with $V = 0.70$: **$P = 0.711 \times 0.70 \approx 0.665$**

8.2 BOS Node Fault Tree

Top Event: BOS Node Compromised (P = 0.585)




Fig 2 – BOS Fault Tree Analysis

Attack Path 1: Direct Attack (P = 0.40)

- Connected by AND gate:
 - Ransomware attempt ($P = 0.55$)
 - Unpatched systems ($P = 0.73$)
- Combined: $0.55 \times 0.73 = 0.40$

Attack Path 2: Cascade from JFK ($P = 0.35$)

- Connected by AND gate:
 - JFK breach occurs ($P = 0.665$)
 - JFK-BOS link active ($P = 0.53$)
- Combined: $0.665 \times 0.53 = 0.35$

Attack Path 3: Supply Chain Attack ($P = 0.25$)

- Connected by AND gate:
 - Software flaw introduced ($P = 0.45$)
 - No input validation ($P = 0.55$)
- Combined: $0.45 \times 0.55 = 0.25$

Top Event Calculation: $P(\text{BOS Compromised}) = 1 - (1-0.40)(1-0.35)(1-0.25) = 1 - 0.293 = 0.707$
 Adjusted with $V = 0.65$: $P = 0.707 \times 0.65 \approx 0.585$

8.3 Vulnerability Elimination Costs

JFK Vulnerability Elimination:

Basic Event	Elimination Cost (\$M)	New Probability
Phishing training	0.5	0.25
MFA implementation	1.2	0.2
Access control upgrade	1.5	0.3
Vendor security audit	0.8	0.25
API hardening	1	0.3
Total	5	

BOS Vulnerability Elimination:

Basic Event	Elimination Cost (\$M)	New Probability
Ransomware defense	1	0.2
Patch management	0.6	0.3
Network segmentation	1.8	0.25
Software validation	0.7	0.2
Supply chain security	0.8	0.25
Total	4.9	

8.4 Optimal Budget Allocation

Cost-Benefit Analysis:

- Combined risk exposure (JFK + BOS): \$58.3M
- Total elimination cost: \$9.9M
- **ROI: \$58.3M / \$9.9M = 5.89:1**

For every \$1 invested in vulnerability elimination at blocking nodes, JetBlue avoids \$5.89 in potential losses.

Recommended Allocation (60/40 Split):

- Prevention: $\$9.9\text{M} \times 60\% = \5.94M
- Response: $\$9.9\text{M} \times 40\% = \3.96M

After implementing controls, top event probabilities reduce to:

- JFK: $0.665 \rightarrow \sim 0.20$
- BOS: $0.585 \rightarrow \sim 0.18$

Both nodes would operate below the critical vulnerability threshold of $\gamma_0 = 20.45\%$.

9. Budget Discussion and Recommendations

The comprehensive cybersecurity risk mitigation strategy for JetBlue's domestic route network requires a total annual investment of \$71.06 million, divided between proactive prevention measures and reactive response capabilities. The network prevention budget of \$40.53 million funds proactive security controls including firewalls, intrusion detection systems, employee training programs, continuous monitoring, and system redundancy measures across all fourteen nodes. The network response budget of \$30.53 million supports incident response capabilities including dedicated response teams, disaster recovery systems, forensic investigation resources, and public relations and legal reserves necessary for effective crisis management.

Budget allocation follows a risk-based prioritization framework aligned with the MBRA analysis findings. Critical priority is assigned to the two blocking nodes, JFK and BOS, which together receive \$23.2 million comprising \$12.9 million for prevention and \$10.3 million for response. This allocation reflects their combined risk exposure of \$58.3 million and their essential role in maintaining network connectivity. High priority nodes LAX and FLL receive a combined allocation of \$13.3 million, with \$7.6 million designated for prevention and \$5.7 million for response, recognizing their functions as the West Coast bridge and Florida hub respectively. Medium priority is assigned to MCO, SJU, and EWR, which collectively receive \$15.4 million split between \$9.0 million for prevention and \$6.4 million for response. The remaining seven nodes classified as low priority, including TPA, LAS, SFO, SEA, DEN, DCA, and MIA, share the balance of \$19.16 million with \$11.03 million allocated to prevention and \$8.13 million to response measures.

9.2 Phased Implementation Approach

The proposed cybersecurity enhancement strategy is structured across three distinct phases spanning a three-year timeline. During the first year, efforts will concentrate exclusively on protecting the two most critical nodes in the network: New York's JFK airport and Boston. This initial phase carries a budget allocation of 23.2 million dollars and will involve implementing a zero-trust security architecture alongside the deployment of advanced threat detection systems. Upon completion, this phase is projected to achieve a fifty percent reduction in overall risk exposure.

The second year shifts focus toward expanding protective measures to additional high-priority locations, specifically Los Angeles and Fort Lauderdale. With an investment of 13.3 million dollars, this phase will incorporate network segmentation strategies designed to isolate and contain potential breaches. A comprehensive vendor security program will also be established during this period to address third-party risks. These efforts are anticipated to yield an additional twenty percent reduction in vulnerability.

The third and final phase represents the most substantial investment at 34.56 million dollars, aimed at achieving complete network-wide coverage across all fourteen nodes. This stage will introduce advanced analytics capabilities and artificial intelligence-driven monitoring tools to detect and respond to threats in real time. Full redundancy measures will also be implemented to ensure operational continuity in the event of system failures. By the conclusion of this phase, the organization expects to have achieved a cumulative risk reduction of seventy-five percent across its entire infrastructure.

9.3 Return on Investment Analysis

Scenario	Investment	Risk Reduction	Avoided Loss	ROI
Blocking nodes only	\$9.9M	51%	\$58.3M	5.89:1
Critical + High	\$23.2M	65%	\$81.3M	3.50:1
Full network	\$71.06M	75%	\$85.7M	1.21:1

Recommendation: Prioritize blocking node protection (Phase 1) for maximum ROI, then expand based on available budget.

9.4 Key Recommendations for DHS

1. **Designate JFK and BOS as Critical Aviation Cyber Infrastructure** requiring enhanced federal oversight and support
2. **Mandate Cascade Risk Assessment** for all major airline networks to identify blocking nodes
3. **Establish Information Sharing Protocols** between airlines for threat intelligence on aviation-specific cyber threats
4. **Create Aviation Cyber Reserve Fund** to support rapid response to network-wide incidents
5. **Require Network Segmentation Standards** to contain cascades within airline route networks
6. **Develop Joint Response Capabilities** between DHS, TSA, and airline security operations centers

10. Conclusion

This analysis demonstrates that JetBlue Airways' domestic route network faces significant cybersecurity risks concentrated at two blocking nodes: Boston Logan (BOS) and New York JFK. The network's critical vulnerability threshold of 20.45% indicates high sensitivity to cyber threats, requiring proactive risk management.

Key findings include:

- Total network risk exposure: \$114.3M

- Two blocking nodes (JFK, BOS) account for 51% of total risk
- Critical vulnerability threshold: $\gamma_0 = 20.45\%$
- Spectral radius of 7.542 indicates high cascade susceptibility
- 7 critical links require priority protection

The recommended \$71.06M annual cybersecurity budget, implemented in three phases, would reduce total network risk by approximately 75%. Prioritizing the \$9.9M investment in blocking nodes alone achieves a 5.89:1 return on investment.


For the Department of Homeland Security, this analysis underscores the need for enhanced oversight of aviation network cybersecurity, particularly at hub airports that serve as critical bridges in airline route networks. The interconnected nature of modern aviation infrastructure means that a single point of failure can cascade across the entire network, affecting millions of passengers and causing hundreds of millions of dollars in economic damage.


References

1. Eurocontrol. (2024). Aviation Cybersecurity Annual Report 2023.
2. IBM X-Force. (2024). Threat Intelligence Index - Transportation Sector.
3. Module 4 Readings: Network Centrality Metrics v2.
4. Module 8 Readings: Digraph Analysis.
5. Module 10 Readings: Python Scripts for Network Analysis.
6. JetBlue Airways. (2024). Route Map. <https://www.jetblue.com/route-map>
7. FlightConnections. (2024). JetBlue Routes. <https://www.flightconnections.com/route-map-jetblue-b6>
8. Delta Air Lines. (2024). Form 8-K Filing - CrowdStrike Incident Impact.
9. U.S. Department of Transportation. (2024). Aviation Consumer Protection Regulations.

Appendices


Appendix A: Network Graph Visualization







	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
1	Name	Threat	Vulnerability	Consequence	Prevention	Response	Risk Initial	Risk Reduc	Flow Cons	Prevention	Response	Attack Allo	Vulnerability	Consequence	Calculated Weight	Weight x O	Degrees	Rank	
2	Boston Logan	90	65	40	5.9	4.5	23.4	8.07		2.45	0	0	22.41	40	90	0.683	5.509	4	2
3	Newark	70	60	12	2.5	1.75	5.04	5.04		0	0	0	60	12	70	0.187	0.941	2	12
4	Washington DCA	50	45	7.75	1.65	1.2	1.74	1.74		0	0	0	45	7.75	50	0.715	1.246	4	11
5	Orlando	70	55	20	3.2	2.35	7.7	7.68		0	0	0	54.87	20	70	0.416	3.196	3	4
6	Fort Lauderdale	75	60	23.75	3.8	2.8	10.69	10.69		0	0	0	60	23.75	75	0.192	2.052	2	6
7	Miami	55	60	8.4	1.9	1.35	2.77	2.38		0.12	0	0	51.61	8.4	55	0.768	1.831	4	7
8	San Juan	60	70	16.5	3.3	2.3	6.93	3.74		0.77	0	0	37.81	16.5	60	0.8	2.995	4	5
9	Tampa	55	55	8	1.85	1.3	2.42	2.42		0	0	0	55	8	55	0.64	1.549	4	9
10	Las Vegas	50	55	7.7	1.65	1.2	2.12	1.9		0.07	0	0	49.39	7.7	50	0.867	1.648	5	8
11	San Francisco	55	50	7.5	1.65	1.2	2.06	2.06		0	0	0	50	7.5	55	0.376	0.775	3	13
12	Seattle	40	45	4	1.05	0.7	0.72	0.72		0	0	0	45	4	40	0.472	0.34	3	14
13	NewYorkJFK	95	70	52.5	7	5.8	34.91	19.85		1.5	0	0	39.8	52.5	95	0.32	6.352	3	1
14	LosAngelesLAX	80	65	23.25	3.8	2.9	12.09	11.37		0.09	0	0	61.14	23.25	80	0.312	3.548	3	3
15	Denver	50	50	7.25	1.65	1.2	1.81	1.81		0	0	0	50	7.25	50	0.757	1.373	4	10


Appendix B: Resilience Curve Graph (q vs. γ with critical threshold)






Appendix C: Fault Tree Diagrams for JFK and BOS






Appendix D: MBRA Output Tables (80% and 20% vulnerability scenarios)

20%



80%



Appendix E: Python Code for Network Analysis



jetblue-python-script.
py

Appendix F: Excel Calculations and Formulas

Appendix G: MBRA Risk Estimation Tables

Table G-1: MBRA Input Values Summary

Node	City	Threat (T)	Vuln (V)	Consequence (\$M)	Prevention (\$M)	Response (\$M)	Risk (\$M)	Score
1	JFK	0.95	0.70	52.5	7.0	5.8	34.9	
2	BOS	0.90	0.65	40.0	5.9	4.5	23.4	
3	FLL	0.75	0.60	23.75	3.8	2.8	10.7	
4	MCO	0.70	0.55	20.0	3.2	2.35	7.7	
5	LAX	0.80	0.65	23.25	3.8	2.9	12.1	
6	SJU	0.60	0.70	16.5	3.3	2.3	6.9	
7	EWR	0.70	0.60	12.0	2.5	1.75	5.0	
8	DCA	0.50	0.45	7.75	1.65	1.2	1.7	
9	TPA	0.55	0.55	8.0	1.85	1.3	2.4	
10	LAS	0.50	0.55	7.7	1.65	1.2	2.1	

Node	City	Threat (T)	Vuln (V)	Consequence (\$M)	Prevention (\$M)	Response (\$M)	Risk (\$M)	Score
11	SFO	0.55	0.50	7.5	1.65	1.2	2.1	
12	SEA	0.40	0.45	4.0	1.05	0.7	0.7	
13	DEN	0.50	0.50	7.25	1.65	1.2	1.8	
14	MIA	0.55	0.60	8.4	1.9	1.35	2.8	
TOTAL				238.6	40.53	30.53	114.3	

Risk Score Formula: Risk = Threat × Vulnerability × Consequence

Table G-2: Critical Node Rankings by Risk

Rank	Node	City	Risk (\$M)	Classification
1	JFK	New York	34.9	Critical - Blocking Node
2	BOS	Boston	23.4	Critical - Blocking Node
3	LAX	Los Angeles	12.1	High - West Coast Bridge
4	FLL	Fort Lauderdale	10.7	High - Florida Hub
5	MCO	Orlando	7.7	Medium
6	SJU	San Juan	6.9	Medium - Caribbean Hub
7	EWR	Newark	5.0	Medium
8	MIA	Miami	2.8	Low
9	TPA	Tampa	2.4	Low
10	LAS	Las Vegas	2.1	Low
11	SFO	San Francisco	2.1	Low
12	DEN	Denver	1.8	Low
13	DCA	Washington	1.7	Low
14	SEA	Seattle	0.7	Minimal

6. SUMMARY - MBRA INPUT VALUES FOR JETBLUE

Node	City	Threat (T)	Vuln (V)	Consequence (\$M)	Prevention (\$M)	Response (\$M)	Risk Score
1	JFK	0.95	0.70	52.5	7.0	5.8	34.9
2	BOS	0.90	0.65	40.0	5.9	4.5	23.4
3	FLL	0.75	0.60	23.75	3.8	2.8	10.7
4	MCO	0.70	0.55	20.0	3.2	2.35	7.7
5	LAX	0.80	0.65	23.25	3.8	2.9	12.1
6	SJU	0.60	0.70	16.5	3.3	2.3	6.9
7	EWR	0.70	0.60	12.0	2.5	1.75	5.0
8	DCA	0.50	0.45	7.75	1.65	1.2	1.7
9	TPA	0.55	0.55	8.0	1.85	1.3	2.4
10	LAS	0.50	0.55	7.7	1.65	1.2	2.1
11	SFO	0.55	0.50	7.5	1.65	1.2	2.1
12	SEA	0.40	0.45	4.0	1.05	0.7	0.7
13	DEN	0.50	0.50	7.25	1.65	1.2	1.8
14	MIA	0.55	0.60	8.4	1.9	1.35	2.8

Risk Score Formula: Risk = Threat × Vulnerability × Consequence
Example (JFK): 0.95 × 0.70 × 52.5 = 34.9

Key Finding: JFK and BOS have the highest risk scores, confirming their status as blocking nodes requiring priority protection. Total network risk = \$114.3M potential exposure.

APPENDIX H: MBRA INPUT VALUES & JUSTIFICATION

1. NODE THREAT PROBABILITIES

Threat probability = likelihood of an attack targeting that node (based on criticality, exposure, and historical data)

Node	City	Type	Threat Prob.	Justification
1	JFK	Primary Hub	0.95	Highest value target; primary hub; HQ operations
2	BOS	Focus City	0.90	Second largest hub; highest connectivity (degree=13)
3	FLL	Focus City	0.75	Major Florida hub; high passenger volume
4	MCO	Focus City	0.70	Orlando tourism hub; seasonal peaks
5	LAX	Focus City	0.80	West Coast gateway; critical bridge node
6	SJU	Focus City	0.60	Caribbean hub; isolated geography
7	EWR	Spoke	0.70	NYC metro redundancy; high connectivity
8	DCA	Spoke	0.50	Government/business travel; security focus
9	TPA	Spoke	0.55	Florida network support
10	LAS	Spoke	0.50	Leisure destination; moderate exposure
11	SFO	Spoke	0.55	Tech corridor; West Coast connectivity
12	SEA	Spoke	0.40	Lowest connectivity (degree=4); peripheral
13	DEN	Spoke	0.50	Mountain West hub; moderate traffic
14	MIA	Spoke	0.55	International gateway; Latin America

Justification for Threat Probabilities:
Based on: (1) Node degree centrality rankings, (2) Betweenness centrality (bridge nodes), (3) Historical aviation cyber incidents showing hub airports are primary targets, (4) 131% increase in aviation cyberattacks 2022-2023 per Eurocontrol report.

2. NODE VULNERABILITY PROBABILITIES

Vulnerability probability = likelihood that an attack succeeds given it occurs (based on security posture, system age, exposure)

Node	City	Vuln. Prob.	Justification
1	JFK	0.70	Complex legacy systems; multiple integration points; 2008-2011 breach history
2	BOS	0.65	High traffic volume; extensive third-party connections
3	FLL	0.60	Newer systems but high volume operations
4	MCO	0.55	Tourism focus; standard security implementation
5	LAX	0.65	Multi-carrier environment; complex integrations
6	SJU	0.70	Remote location; infrastructure challenges; hurricane exposure
7	EWR	0.60	Shared airport systems; moderate exposure
8	DCA	0.45	Enhanced federal security due to location
9	TPA	0.55	Standard regional security posture
10	LAS	0.55	High-volume leisure; standard systems
11	SFO	0.50	Tech-savvy region; better cyber awareness
12	SEA	0.45	Lower exposure; simpler operations
13	DEN	0.50	Modern airport infrastructure
14	MIA	0.60	International connections increase attack surface

Justification for Vulnerability Probabilities:

Based on: (1) JetBlue's 2008-2011 undetected network breach demonstrating systemic vulnerabilities, (2) 2002 unauthorized data sharing incident, (3) Industry average of 60% vulnerability rate for airline IT systems per IBM X-Force report, (4) CrowdStrike 2024 incident showing airline system fragility.