Arrive-shipping.com API Documentation

Notes:

1- API and password required for any API to complete request and if not found response will be ‘User Not found’.

2- You get your response as json.

3- Please note that the maximum requests per minute limit for the API is set at 50 requests. Make sure to keep this in mind when using the API to avoid hitting the rate limit.

Add Shipment

هذا ال API يستخدم لارسال شحنة واحدة فقط ولا يصلح لارسال عدة شحنات بشكل مجمع - لارسال مجموعة شحنات بشكل مجمع يرجى استخدام ال API المسمى ب Add Bulk Shipments

POST `https://arrive-shipping.com/api/shipment.php?action=addShipment`

API KEYS

user	API Name (Required)
password	API Password (Required)
sector_id	sector_id (Destination area) ,which come from (Get Sectors) API. (Required)
keyword	keyword for destination area. (Optional) if you don't have the "sector_id", you can sent the area name as text in this variable "keyword"
product_name	Product Name, string(250).
product_desc	Product Description (text).
phone_1	Consignee's mobile number , int(11). (Required)
phone_2	Another phone, int(11) (Optional).
service_type	Service Type Int(11) serive_type 1: تسليم و تحصيل serive_type 2: شحنة استبدال

	serive_type 3: استرجاع طرد
price	Shipment COD Int(11). (Required)
weight	String(20).
address	Text. (Required)
notes	Text.
client_name	String(250). (Required)
order_id	String(255).
email	String(100).
client_id	Int(11).
quantity	String(20).

Response


```
{
  "response": [
    {
      "waybill": "TS8792163",
      "id": "6067",
      "qr_code": "6067-TS8792163-15 مايو-ZJebDU0OMRhdmwNFHloO8cT6VI2yeEv9117909387625"
    }
  ]
}
```


Add Bulk Shipments (Bulk)

يستخدم لارسال مجموعة شحنات بشكل مجمع (تحديد اكتر من شحنة واتخاذ اكشن واحد عليهم) - يجب ارسال ريكويست واحدة فيها كل الشحنات ولا يجب ارسال API هذا ال ريكويست لكل شحنة

POST`https://arrive-shipping.com/api/shipment.php?action=addBulkShipments`

API KEYS

The fields below should be included in each shipment object (array) within the `shipments` array, excluding "user" and "password" ,Note that the maximum number of shipments that can be processed at once is 1000

user	API Name (Required)
password	API Password (Required)
sector_id	sector_id Destination area ,which come from (Get Sectors) API. (Required)
keyword	keyword for destination area. (Optional) if you don't have the "sector_id", you can sent the area name as text in this variable "keyword"
product_name	Product Name, string(250).
product_desc	Product Description (text).
phone_1	Consignee's mobile number , int(11). (Required)
phone_2	Another phone, int(11).
service_type	Service Type Int(11) serive_type 1: تسليم و تحصيل serive_type 2: شحنة استبدال serive_type 3: استرجاع طرد
price	Shipment COD Int(11). (Required)
weight	String(20).
address	Text. (Required)
notes	Text.
client_name	String(250). (Required)
order_id	String(255).
email	String(100).
client_id	Int(11).
quantity	String(20).

Request


```
{
  "request": [
    "user": "user",
    "password": "password",
    "shipments": [
      {
        "sector_id": "100",
        "keyword": "destination keyword",
        "product_name": "Product Name",
        "product_desc": "Product Description",
        "phone_1": "01000000011",
        "phone_2": "01000000022",
        "service_type": 1,
        "price": 300,
        "weight": "5 kg",
        "address": "Address",
        "notes": "Additional notes",
        "client_name": "Client Name",
        "order_id": "12345",
        "email": "client@example.com",
        "client_id": 1,
        "quantity": "2",
      },
      {
        "sector_id": "100",
        "keyword": "destination keyword",
```

```
        "product_name": "Product Name",
        "product_desc": "Product Description",
        "phone_1": "01000000011",
        "phone_2": "01000000022",
        "service_type": 1,
        "price": 300,
        "weight": "5 kg",
        "address": "Address",
        "notes": "Additional notes",
        "client_name": "Client Name",
        "order_id": "12345",
        "email": "client@example.com",
        "client_id": 1,
        "quantity": "2",
      }
    ]
  ]
}
```


Response


```
{
  "response": [
    {
        "waybill": "WY154830",
        "id": "52",
        "qr_code": "52-WY154830--7LpyIfWCebfL6znr9bv0LemKdFdGggjj891009266948"
```

```
    },
    {
        "waybill": "WY154831",
        "id": "53",
        "qr_code": "53-WY154831--oFmd3TfJn9J12e562mfbyT5MoK6TbXhu659207064435"
    }
  ]
}
```


Get Status History

POST`https://arrive-shipping.com/api/shipment.php?action=statusHistory`

API KEYS

user	API Name (Required)
password	API Password (Required)
waybill	Waybill of shipment (string). (Required)

Response


```
{
    "response": [
      {
        "waybill": "TS879292",
        "date_created": "2023-09-17 17:04:01",
        "status_ar": "فشل التسليم",
        "status_en": "Un-Delivered",
        "reason_en": "mobile closed ",
```

```
        "reason_ar": "التليفون مغلق",
        "scheduled_date": "0000-00-00 00:00:00"
      }
    ]
}
```


Get Current Status (Bulk)

POST `https://arrive-shipping.com/api/shipment.php?action=getCurrentStatus`

API KEYS

Notes:

When submitting an array of waybills, please ensure that the maximum number of waybills per request is limited to 50. Make sure your requests adhere to this limit to ensure successful processing.

user	API Name (Required)
password	API Password (Required)
waybill	An array of waybill(s). (Required)

Response


```
[
    "response": [
        {
            "waybill": "TS8792162",
            "name_ar": "شحنة مؤجلة",
            "name_en": "Time Scheduled"
```

```
        },
        {
            "waybill": "TS8792167",
            "name_ar": "طلب بيك أب",
            "name_en": "Pickup Request"
        }
    ]
]
```


Get Sectors

POST`https://arrive-shipping.com/api/shipment.php?action=getAllSectors`

API KEYS

user	API Name (Required)
password	API Password (Required)

Response


```
{
    "response": [
        {
          "id": "105",
          "name": "الأزبكية",
          "key_words": "",
          "gov_id": "29",
          "gov_name": "القاهرة"
```

```
      },
      {
          "id": "110",
          "name": "الأميرية",
          "key_words": "",
          "gov_id": "29",
          "gov_name": "القاهرة"
      },
      {
          "id": "115",
          "name": "البساتين",
          "key_words": "",
          "gov_id": "29",
          "gov_name": "القاهرة"
      },
      {
          "id": "120",
          "name": "التبين",
          "key_words": "",
          "gov_id": "29",
          "gov_name": "القاهرة"
      }
    ]
}
```


Instant Shipment Status Webhook

Shipment Status Webhook

Some Info you may need:

```
'١' => 'طلب بيك أب','٢' => 'تم استلام البيك أب','٣' => 'تم الاستلام في المخزن',
'٤' => 'قيد التوصيل','٥' => 'تسليم ناجح','٦' => 'تأجيل',
'٧' => 'تم الارتجاع للمخزن','٨' => 'تقفيل المرتجع','١٣' => 'مشكلة في التسليم',
'١٤' => 'تم الارتجاع للراسل','١٦' => 'في الطريق للمخزن','١٧' => 'استبدال او استلام طرد',
'١٨' => 'تسليم جزئي','١٩' => 'تهرب بعد الوصول و التنسيق','٢٠' => 'رفض الاستلام و تم دفع الشحن',
'٢١' => 'مرتجع جزئي','٢٢' => 'مرتجع استبدال','٢٤' => 'in transit',
'٢٥' => 'رفض الاستلام و رفض والدفع','٢٦' => 'في الطريق إلي الفرع','٢٧' => 'في الطريق للتاجر',
'٢٨' => 'مرتجعات الى','٢٩' => 'تم حل المشكلة - P' , ' 30 => 'تم حل المشكلة - C',
'٣١' => 'مرتجعات بالفرع','٣٢' => 'تخصيص البيك أب','٣٣' => 'تم التسليم',
'٣٤' => 'اعاده توزيع','٣٩' => 'تحويلات بين الفروع','٤٣' => 'جاري التعويض',
'١٠٠' => 'معلقة','١٠٥' => 'مرتجعات انتجريشن','١١٠' => 'خروج للمخزن وعدم وصول',
'١١٥' => 'استلام انتجريشن','١٢٠' => 'وصول لمخزن خطأ','١٢٥' => 'استلام في الفرع',
'١٣٥' => 'مرتجعات فى الطريق','١٥٠' => 'test'
```

Webhook Response

```
{
    "response": [
        {
          [waybill] => TS879292
          [status_id] => 13
          [status_ar] => فشل التسليم
          [status_en] => English Status
          [notes] => Status Note
          [reason] => فشل التسليم
          [scheduled] => 2024-07-10 05:20 AM
          [store] => فرع المهندسين
          [order_id] => EM12848
          [client_id] => 121845
      }
    ]
}
```