



SOC Analyst Level 1

Lecture 1: What is a SOC? & The Role of the Analyst

Course Syllabus: Practical Security Analysis and Initial Incident Response
Author: Nader Anam

Course & Lecture Overview

Course Title: SOC Analyst Level 1: Practical Security Analysis and Initial Incident Response

Lecture Title: What is a SOC? And What is the Role of the Analyst?

Author: Nader Anam

Duration: 3 Training Hours

CRITICAL INSTRUCTOR NOTE

This lecture does NOT aim to overwhelm students with tools or complex technical jargon. The core purpose is to build the correct analytical mindset from day one:

- No judgment without evidence.
- No escalation without understanding.
- No closing an alert without solid justification.

Learning Objectives

1. Explain the core meaning of a SOC and its strategic role within an organization.
2. Differentiate precisely between an Event, an Alert, and an Incident.
3. Understand the hierarchy and operational tiers of SOC analysts.
4. Explain the standard lifecycle of a security alert from ingestion to closure.
5. Identify key security telemetry sources supplying data to the SOC.
6. Make logical initial decisions: Should the alert be closed or escalated?
7. Compose a professional, clear description of a Tier 1 SOC Analyst's role.

Why This Lecture Matters

The Rookie Mistake vs. Professional Mindset

Many students rush into learning complex tools like Microsoft Sentinel, Splunk, or jumping into advanced labs without understanding foundational workflows. This is a fatal mistake.

A successful SOC Analyst doesn't win because they know which button to click. They win because they know HOW TO THINK.

Every professional investigation requires asking core questions:

- WHAT happened? | WHEN did it happen? | WHO is affected?
- WHAT is the evidence? | Is this behavior normal or anomalous?
- Should I close or escalate? | How do I document this properly?

What is a SOC?

Security Operations Center

A centralized unit within an organization responsible for monitoring the technical environment to discover, analyze, and defend against suspicious activities and security incidents.

Core Responsibilities

- Continuous Security Event Monitoring
- Real-time Alert Ingestion & Triage
- Attack Detection & Validation
- Severity Classification & Risk Assessment
- Evidence Collection & Auditable Documentation
- Incident Escalation & Tactical Response Support

Visualizing the Enterprise Environment

Imagine a typical mid-sized organization with:

- 500 Employee Endpoints (Laptops/Desktops)
- 50 Critical Servers (On-Premise & Database)
- Enterprise Email Gateways
- Internal Local & Corporate Networks
- Identity & Access Management (IAM) Portals
- Next-Gen Firewalls (NGFW)
- Endpoint Detection & Response (EDR) agents
- Cloud Infrastructure (AWS/Azure) environments

Every single one of these components constantly generates system logs. The SOC exists to answer one singular, critical question:
Is there a threat actively developing inside this massive sea of data?

The Telemetry Sources Stack

Primary Data Inputs to the SOC Pipeline:

- 1. Endpoint Systems:** Windows Security logs, process execution telemetry.
- 2. Infrastructure Servers:** Linux auth.log, sudo activities, application logs.
- 3. Network Firewalls:** Allowed vs. blocked connections, source/destination mappings.
- 4. IDS / IPS Ecosystems:** Signatures matching known malicious network exploitation traffic.
- 5. EDR Platforms:** Behavioral analysis logs, proactive containment alerts on hosts.
- 6. Email Gateways:** Phishing campaigns, malicious URL detections, email spoofing flags.
- 7. Cloud Security Tools:** IAM modifications, geolocation deviations, anomalous cloud access.

The Tier 1 Analyst Role

The Critical First Line of Defense

- Alert Ingestion Management: Continuous tracking of security alerts streaming into the SIEM dashboard.
- Initial Triage: Filtering out background environmental noise to focus heavily on suspicious patterns.
- Context Accumulation: Gathering associated system logs, user context, host state, and network data.
- False Positive Validation: Performing structured logic tests to separate benign noise from true threats.
- Auditable Documentation: Writing precise, chronological, and objective logs of findings for each ticket.
- Escalation Dispatch: Handing off validated, complex true positive alerts to Tier 2 incident responders.

Operational Guardrails: What L1 Must NOT Do

Strict Boundaries of Tier 1 Analysts

- ✗ Never execute destructive actions or delete critical files from a host based solely on raw suspicion.
- ✗ Never reboot, power down, or disrupt enterprise production servers without explicit administrative sign-off.
- ✗ Never perform unilateral network isolation on highly critical business systems without escalation approval.
- ✗ Never modify user group permissions or Active Directory configurations without a validated change order ticket.
- ✗ Never make absolute, unbacked claims or accuse users of malicious intent without hard, verifiable evidence.
- ✗ Never ignore an alert simply because it looks small or repetitive; persistent noise often hides a sophisticated attack.
- ✗ Never forward raw, unanalyzed alerts straight to Tier 2 without conducting thorough initial triage and collection.

The Tiered SOC Operational Structure

Tier 1 / Level 1

Triage & Validation

Monitors SIEM dashboards, validates alerts, executes initial data collection, and acts as the gatekeeper of the pipeline.

Tier 2 / Level 2

Incident Responder

Conducts deep-dive forensics, correlates multi-host telemetry, reconstructs attack paths, and orchestrates containment.

Tier 3 / Level 3

Threat Hunter / Expert

Proactively hunts for stealth threats, builds custom detection logic, reverse-engineers malware, and optimizes the SIEM.

SOC Management

Leadership & Quality

Manages SLAs, aligns processes with frameworks, handles executive escalations, and drives reporting metrics.

Monitoring, Detection, Investigation & Response

Monitoring : Continuous oversight of infrastructure telemetry, logs, and events to maintain visibility.

Detection : The automated or algorithmic identification of a potentially malicious anomaly or pattern.

Investigation : The analytical process of dissecting an alert, correlating evidence, and uncovering root cause.

Response : The tactical execution of containment, eradication, and system recovery playbooks.

THE FOUNDATIONAL TRIAD

Mastering the Difference Between Events, Alerts, and Incidents

Understanding: What is an Event?

Definition of an Event

An Event is any observable occurrence or technical action captured and logged within an operating system, network stream, or application interface.

Crucial Rule: An Event is NOT inherently dangerous. It is simply a historical footprint of an action.

Standard Examples of Benign Events:

- A domain user successfully authenticates into their email client.
- A workstation initiates an HTTP outbound connection to an informational news site.
- A legitimate background system service starts up during system boot.
- A local user successfully updates their password.

Understanding: What is an Alert?

Definition of an Alert

An Alert is a notification generated by an internal correlation engine or security control indicating that an Event (or sequence of Events) matches a pre-configured signature or rule of suspicious behavior.

Crucial Rule: An Alert flags something anomalous that explicitly requires human verification.

Standard Examples of Security Alerts:

- 25 authentication failures occur against a single user account within a 3-minute window.
- A local script executes an obfuscated or encoded PowerShell command string.
- An internal host attempts an outbound network mapping query to a known malicious C2 IP.
- An EDR sensor quarantines an unrecognized executable file matching a suspicious heuristic structure.

Understanding: What is an Incident?

Definition of an Incident

An Incident is a confirmed, validated security event (or set of correlated events) that poses a high-probability or realized threat to the Confidentiality, Integrity, or Availability (CIA Triad) of organizational data, assets, or systems.

Standard Examples of Realized Incidents:

- Ransomware successfully executes and begins encryption operations on a network share.
- Validated compromise of a high-privilege corporate administrator account.
- Confirmed bulk database data exfiltration to an unauthorized external repository.
- An active malware strain successfully establishes a command-and-control tunnel from an internal production host.

The Definitive Triad Comparison Matrix

Type	Core Meaning	Practical Example	Requires L1 Triage?
EVENT	Historical log of any action or occurrence.	User logs in successfully.	No (unless tied to alert)
ALERT	Suspicious pattern flagging an anomaly.	20 failed logins in 4 minutes.	Yes, mandatory review
INCIDENT	Confirmed compromise or active threat.	Ransomware executing on endpoint.	Yes, immediate escalation

Quick Drill: Scenario Classification

Classify the following technical events accurately:

1. User 'Ahmed' logged in successfully from his standard workplace PC. → **EVENT (Benign activity)**
2. User 'Ahmed' failed authentication 25 times within a 3-minute window. → **ALERT (Suspicious authentication anomaly)**
3. A malicious script successfully executes and changes system files on Ahmed's laptop. → **INCIDENT (Active confirmed compromise)**
4. User 'Sara' browses an informational public website. → **EVENT (Normal environmental flow)**
5. An internal server initiates an unprompted connection directly to a flagged C2 server IP. → **INCIDENT (High confidence compromise)**

Where Do Alerts Originate?

The Alert Ingestion Core Ecosystem:

SIEM (Security Information & Event Management): The central brain. Aggregates logs from everywhere, runs correlation rules, and raises alerts.

EDR (Endpoint Detection & Response): Monitors host behaviors, process trees, memory space, and flags file-level anomalies directly.

Network Security Gateways (Firewalls / IPS): Analyzes inline traffic flows and logs packet filtering anomalies or bad protocol behavior.

SEG (Secure Email Gateway): Dissects ingress email messages, running heuristic scanning for malicious links and attachment payloads.

Anatomy of a SIEM Alert Document

Alert_Name: Multiple Failed Login Attempts

Target_User: ahmed

Source_IP: 185.44.10.20

Failure_Count: 23

Time_Window: 4 minutes

Target_System: Corporate VPN Portal

Initial_Severity: Medium

The Analyst Triage Mental Process

- ? Is this source IP recognized as a corporate asset or public VPN?
- ? Did a single SUCCESSFUL login occur immediately after these 23 failures?
- ? Does user account 'ahmed' hold high domain administrative privileges?
- ? Are there matching failed logs across other user targets from this same IP?

The Security Alert Investigation Lifecycle

1. Ingest/Receive

Alert registers in dashboard via telemetry stream.

2. Triage Check

Perform parsing and contextual check of parameters.

3. Investigation

Accumulate log files, traces, and indicators of compromise.

4. Final Decision

Determine state: False Positive vs. True Positive Escalation.

5. Document & Act

Complete historical ticket logging and execute routing.

Lifecycle Deep Dive: Ingestion & Triage

Phase 1: Ingestion / Receive

Alerts drop into the dashboard via SIEM correlation rules, specialized EDR detections, malware engine logs, firewall filters, or proactive end-user security reports.

Action: Parse out timestamp, unique IDs, asset names, and trigger logic immediately.

Phase 2: Structured Triage

- Identify exact target classification (Host vs. Service).
- Pinpoint affected user roles and authorization level.
- Isolate precise execution timestamps.
- Assess default out-of-the-box system severity values.
- Crosscheck if matching alerts have fired on this device.

Lifecycle Deep Dive: Investigation

Phase 3: Deep Evidence Accumulation

The investigative block requires hunting down core telemetry variables to reconstruct context. Analysts gather concrete system facts rather than guessing.

- Operational Event Log IDs (e.g., Windows 4625/4688)
- Source and Destination IP Mappings
- Hostnames & Target User Accounts
- File Hashes (MD5/SHA256) & Process Spawning Trees
- URL/URI Request strings and HTTP Headers
- Historical Contextual baselines of Target Behavior

Lifecycle Deep Dive: Decision & Documentation

Phase 4: Case Decision Paths

- ✓ False Positive: Benign alert error; noise.
- ✓ Benign True Positive: Real event but explicitly authorized.
- ✓ Escalate to Tier 2: Confirmed threat or deep analytical complexity required.

Phase 5: Auditable Logging

If an action is not documented, it legally never occurred within security ops. Every single step must be explicitly recorded.

Rule: Always draft a case investigation log with the operating assumption that a separate analyst will have to step in and resume your file immediately.

Playbook: Criteria to Close an Alert

Validated Conditions for Ticket Closure:

- ✓ Zero empirical traces of active malicious intent are located.
- ✓ The flagged system activity perfectly aligns with known corporate operations.
- ✓ The alert correlates explicitly with a pre-arranged, documented network penetration test.
- ✓ Direct verification with the target user establishes a legitimate, authorized action.
- ✓ Zero related malicious lateral indicators are discovered on surrounding hosts.

Example Log Reason:

'Closed as False Positive. Source IP tracks to enterprise gateway VPN pool. User validated execution of administrative login workflow.'

Playbook: Critical Escalation Triggers

Mandatory Conditions for Escalation to Tier 2:

- 🚨 Empirical execution of uncontained suspicious script structures or unrecognized binaries.
- 🚨 A realized successful login occurs immediately after a heavy sequence of authentication failures.
- 🚨 A production host establishes verified data transfers to a known flagged C2 IP node.
- 🚨 High-privilege accounts (Domain Admins) display anomalous, out-of-hours behavioral paths.
- 🚨 Multiple distinct hosts across independent subnets trigger related structural security alerts.
- 🚨 The alert presents complex indicators that cannot be safely validated within Tier 1 SLA windows.

Operational Metrics: Severity vs. Confidence

Alert Severity

Measures the potential scope of impact and operational damage if the flagged threat is true.

Scales: Low, Medium, High, Critical.

Analyst Confidence

Measures the technical weight and trustworthiness of the collected evidence.

- Low Confidence: Single weak log trace.
- High Confidence: Multi-point correlated proof.

Standard Severity Classification Matrix

LOW | Minor anomalies with no active impact. Example: A single isolated password failure from a local host.

MEDIUM | Highly suspicious actions lacking immediate proof of breach. Example: A localized brute force sequence with zero successful logins.

HIGH | Clear operational indicators of compromise or lateral movement. Example: A valid system login occurring directly after a brute force event.

CRITICAL | Severe enterprise threat with massive systemic scope. Example: Active widespread Ransomware propagation or database data leak.

The Analyst Investigation Checklist

1. What is the explicit technical alert classification type?
2. What is the precise chronological timeline of the activity?
3. Which precise assets, servers, or user accounts are targeted?
4. What are the specific network coordinates (Source IP vs. Destination IP)?
5. What concrete audit logs exist to serve as foundational evidence?
6. Does this baseline behavior map onto standard user operational roles?
7. Are there secondary environmental indicators pointing to lateral threat vectors?
8. What is the realistic severity classification within this context?
9. Does the case require immediate handoff escalation or closing?
10. What specific tactical remediation step should be recommended?

Case Study 1: Brute Force Attempt

Alert Telemetry Parameters

Alert Name: Multiple Failed Logins

Target User: khaled

Source IP: 45.77.20.10

Attempts: 30 failures

Timestamp: 02:15 AM (Out of Hours)

Successful Login After: NO

Triage & Verdict Case Analysis

- Fact Analysis: Heavy out-of-hours authentication failure sequence detected. Crucially, no successful follow-up access occurred.
- Breach Status: Zero structural indicators of system compromise.

Proposed Playbook Decision:

- Severity: Medium
- Verdict: Suspicious authentication activity (External Brute Force)
- Action: Close alert after documenting, verify source IP reputation, and monitor for changes.

Case Study 2: Realized Account Compromise

Alert Telemetry Parameters

Alert Name: Failures Followed by Success

Target User: finance.manager

Source IP: 185.20.40.9

Attempts: 18 failures

Successful Login After: YES

Timestamp: 01:40 AM (Anomalous)

Triage & Verdict Case Analysis

- Fact Analysis: Brute force vector immediately followed by an authenticated system access entry. Target possesses deep financial environment permissions.
- Breach Status: High probability of network account compromise.

Proposed Playbook Decision:

- Severity: High
- Verdict: Realized Account Compromise
- Action: Immediate Tier 2 Escalation. Recommend password reset, check MFA token logs, and check historical logs for data leaks.

Classroom Drill 1: Classification Challenge

Environmental Infrastructure Scenario	Classification (Event / Alert / Incident)
A regular domain user authenticates successfully into their workstation at 9:00 AM.	[Student Triage Box]
50 failed authentication attempts register against the 'admin' account within 60 seconds.	[Student Triage Box]
A known active ransomware strain executes and begins local disk modifications on a host.	[Student Triage Box]
An enterprise internal host establishes network streaming outbound to a flagged malicious C2 node.	[Student Triage Box]
An administrative user creates a high-privilege account outside authorized change windows.	[Student Triage Box]
A standard system user initiates a password modification workflow.	[Student Triage Box]

Classroom Drill 1: Solution Key Matrix

Environmental Infrastructure Scenario	Classification (Event / Alert / Incident)
A regular domain user authenticates successfully into their workstation at 9:00 AM.	EVENT (Standard Operational Footprint)
50 failed authentication attempts register against the 'admin' account within 60 seconds.	ALERT (Active Brute Force Signatures)
A known active ransomware strain executes and begins local disk modifications on a host.	INCIDENT (Confirmed System Breach)
An enterprise internal host establishes network streaming outbound to a flagged malicious C2 node.	INCIDENT (Active Command & Control Connection)
An administrative user creates a high-privilege account outside authorized change windows.	ALERT / INCIDENT (Context Dependent Context)
A standard system user initiates a password modification workflow.	EVENT (Benign Administrative Routine)

Classroom Drill 2: Analyzing Live Logs

Ingested Telemetry Parameters

Alert Name: Suspicious PowerShell Command

Affected Host: HR-LAPTOP-12

User Target: rana

Command Line: powershell.exe -enc aQB1AHgA...

Timestamp: 11:43 PM (Anomalous Hours)

EDR Sensor Action: ALLOWED (Not Blocked)

Related Network Trace: External Outbound to 91.200.10.5

Student Assignment Objectives:

- Identify exact risk indicators present within this log.
- Formulate the proper case verdict: Close vs. Escalate?
- Justify your triage decision using objective technical facts.

Classroom Drill 2: Solution Analysis

Professional Forensic Breakdown

- Risk Indicators: Base64 obfuscated (-enc) execution payload, anomalous execution hours, plus matching unprompted external outbound network traffic anomalies.
- System Leak Vector: The EDR engine explicitly recorded an ALLOWED status flag. The payload executed successfully and is uncontained.
- Final Action Playbook Verdict: ESCALATE IMMEDIATELY TO TIER 2.
- Auditable Case Justification: Multiple high-confidence risk vectors align seamlessly (obfuscated administrative commands combined with concurrent external network communication). High probability of system command-and-control exploitation.
- Metrics Matrix Mapping: Severity: HIGH | Confidence: HIGH | Escalation Forwarding: MANDATORY

Top 10 Mistakes of Rookie Analysts

1. Judging a complex alert based purely on its surface name string.
2. Arbitrarily closing high-priority tickets without providing empirical proof log entries.
3. Mass-forwarding unparsed alerts straight onto Tier 2, overloading the pipeline.
4. Utilizing heavy cybersecurity buzzwords without validating clear structural logs.
5. Conflating standard background system events with validated critical incidents.
6. Ignoring situational timestamps and localized administrative behavioral contexts.
7. Failing to compile organized, chronological, and auditable case logs.
8. Analyzing an alert in total isolation without scanning surrounding system assets.
9. Hyper-focusing on UI navigation menus rather than core security investigation logic.
10. Completely losing visibility of business reality and forgetting to assess localized operational impact.

The Golden Rules of Security Operations

Incorrect Phrasing

- ✗ 'This is an absolute hack / compromise!'
- ✗ 'This alert is completely junk and unimportant.'

Professional Phrasing

- ✓ 'Correlated indicators point to an anomalous behavior profile, specifically involving vectors A and B. Escalating for forensic investigation.'
- ✓ 'Review of infrastructure records shows no evidence of threat propagation across paths X or Y. Closing safely as False Positive with evidence log attached.'

Standard Incident Triage Template

Copy and execute this exact structured outline for every practical case lab:

```
Alert_Name: [Ingested Identification String] | Timestamp: [ISO Date-Time Format]
Target_User: [Account Identifiers] | Target_Host: [Asset Hostname Mapping]
Source_IP: [Origin Coordinates] | Destination_IP: [Target Coordinates]
Telemetry_Source: [SIEM / EDR / Firewall Engine Name]
Observed_Activity: [Objective chronological play-by-play narrative of system logs]
Collected_Evidence: [Concrete Log IDs, SHA256 Hashes, URI Strings]
Triage_Verdict: [False Positive / Benign True Positive / Verified Threat Escalation]
Recommended_Action: [Immediate remediation tasks for the environment]
Escalation_Forwarding: [MANDATORY YES / NO]
```

Workshop Breakout Lab Exercises

Interactive Live Classroom Assignment:

Students will break into small operational squads. Each independent team will receive a specific live SIEM alert file to parse out, reconstruct context, determine final case alignment, and compose a 5-line structural log summary using our triage template.

- Operational Team 1 Matrix Focus: Target Alert 'Multiple Failed Logins'
- Operational Team 2 Matrix Focus: Target Alert 'Malware Blocked'
- Operational Team 3 Matrix Focus: Target Alert 'Login From New Geolocation'
- Operational Team 4 Matrix Focus: Target Alert 'Internal Network Reconstruction Port Scan'

Lab Solution: Group 2 'Malware Blocked'

Alert Trigger: Malware Blocked by Host Sensor

Target Host: SALES-PC-08

Target User: omar

Target Binary: invoice_update.exe

Storage Path: C:\Users\omar\Downloads\

Sensor State: BLOCKED & QUARANTINED

Network Stream: Zero outbound matching records

Operational Case Triage Analysis

- Fact Analysis: Executable drops directly into user downloads directory. EDR caught and quarantined the payload immediately before script spawning or initialization occurs.

Playbook Case Resolution:

- Severity: Medium
- Case Verdict: True Positive (Successfully Contained Vector)
- Action: Close case ticket. No escalation required due to active control defense containment. Pivot to mail gateway to find ingestion source.

Lab Solution: Group 3 'Impossible Geolocation'

Alert Trigger: Login From Unrecognized Location

Target User: ali

Source Country: Germany

User Department: Global Corporate Sales

MFA Status: PASSED (Token Authenticated)

Historical Baseline: No travel registry logs found

Operational Case Triage Analysis

- Fact Analysis: Authentication requests originate from overseas. However, target role is sales-heavy and multi-factor challenge tokens validated completely.

Playbook Case Resolution:

- Severity: Medium
- Case Verdict: Validation Required Flow
- Action: Do not close blindly. Contact user to confirm travel profile. Escalate to Tier 2 immediately if user flags access as unauthorized.

Lecture Summary & Core Takeaways

- ✓ The operational architecture of a SOC depends equally on People, Process, and Technology.
- ✓ A Tier 1 Analyst function is to act as the primary structural data filter for the enterprise framework.
- ✓ Events are objective records; Alerts indicate high probability anomalies; Incidents represent verified systemic compromise.
- ✓ Every investigation lifecycle step must transition through clear phases: Receive → Triage → Investigate → Decide → Document.
- ✓ Case playbook conclusions must derive explicitly from hard empirical logs rather than intuition.
- ✓ Auditable case note entries must capture structural answers to: What, When, Who, and Where.

Classroom Review Questions Block

1. Define the operational goal of a Security Operations Center in one sentence.
2. Reconstruct the functional line separating an Alert block from an Incident record.
3. Isolate 5 core technical log telemetry sources supporting modern SOC environments.
4. Outline the exact boundary guardrails constraining Tier 1 Analyst remediation permissions.
5. Under what explicit technical conditions can an alert be securely logged as closed?
6. Define the structural definition of an operational False Positive.
7. Why is mapping an alert based entirely on its textual name a dangerous operation?
8. Explain the exact analytical variance between alert Severity metrics and Confidence values.
9. Defend the absolute necessity of maintaining detailed historical ticket documentation.
10. State the 5 core triage questions that must formulate an analyst's baseline mental framework.

Live Classroom Pop Quiz

Question 1: A validated, successful enterprise user login event originating from a standard production endpoint maps to:

A) Incident | B) Event | C) Malware Execution | D) Command & Control

Question 2: 35 separate authentication failures targeting an active 'admin' account within 45 seconds is classified as:

A) Alert | B) Benign Event Only | C) Standard Maintenance | D) Forensic Summary Report

Question 3: The primary operational mandate bounding a Tier 1 SOC Analyst involves:

A) Application Development | B) Full Sandbox Reversing | C) Alert Triage & Invariant Data Collection | D) Enterprise Architecture Sign-off

Pop Quiz: Rationale & Answer Keys

Answer 1: [B] → Event. Standard system operations displaying matching, legitimate environmental usage map explicitly to benign events.

Answer 2: [A] → Alert. Heavy automated authentication loops match explicit brute-force attack signatures, generating critical monitoring alerts.

Answer 3: [C] → Alert Triage & Invariant Data Collection. Tier 1 analysts execute initial filtering loops and data collection workflows to support the incident response pipeline.

Homework Assignment 1: Analytical Brief

Task Objective: Technical Essay Compilation

Compose a professional analytical brief spanning 10 to 15 structural lines precisely titled:
'The Mechanics of Tier 1 Alert Triage and the Security Ingestion Pipeline'

The final deliverable document must rigorously articulate the following parameters:

- A formalized definition of an enterprise SOC infrastructure ecosystem.
- The specific operational duties constraining a Tier 1 Analyst.
- A clear explanation of the differences between an Event, an Alert, and an Incident.
- Practical scenarios illustrating an alert vs. a realized active incident scenario.
- A clear justification of why rigorous documentation controls protect the pipeline.

Homework Assignment 2: Practical Scenario Matrix

Task Objective: Scenario Classification Matrix

Students must copy, map, and complete a classification grid for these specific real-world production events, detailing exact rationale and required evidence parameters for each item:

- Scenario A: Domain identity account maps successful access credentials from a recognized local host asset.
- Scenario B: 40 distinct authentication failure events register sequentially from an unmapped external host IP.
- Scenario C: A verified malicious payload executes file modification routines on an active workstation share.
- Scenario D: Network firewalls catch and actively filter out an unauthorized ingress tracking connection sweep.
- Scenario E: Target user forwards an anomalous email entity holding an embedded unrecognized URI redirect link.

Standard Homework Submission Template

Enforce this exact engineering framework layout for your scenario matrix submission:

Case_Target: [Scenario String Identifier Context]

Structural_Classification: [Event / Alert / Incident Framework Decision]

Playbook_Rationale: [Clear technical analysis explaining the classification choice]

Evidence_Requirement: [Specify exact system logs, event IDs, or network variables required]

Initial_Severity: [Low / Medium / High / Critical Assessment]

Operational_Verdict: [Close Ticket / Monitor Activity / Immediate Escalation]

Looking Ahead: Lecture 2 Telemetry Mechanics

Next Session: Networking Core Fundamentals for SOC Analysts

We will deep dive into reading and decoding active network log telemetry flows directly:

- IP Addressing Architecture (Public vs. Private Node routing topologies)
- Core Protocol Systems (TCP Handshakes, UDP flows, DNS mappings, HTTP/S headers)
- Network Address Translation (NAT) traffic tracking mechanics

Target Operational Milestone Objective:

Empower students to instantly parse out, dissect, and read raw network connection footprints such as:

10.0.0.15:49220 → 8.8.8.8:53 UDP