

Binary Trees (cont.)

Instructor: Dr. Sunho Lim (Ph.D., Assistant Professor)

Lecture 11

sunho.lim@ttu.edu

Adapted partially from *Data Structures and Algorithms in C++*, Adam Drozdek, 4th Edition, Cengage Learning; and *Algorithms and Data Structures*, Douglas Wilhelm Harder, Mmath


CS2413: Data Structures, Fall 2021



1

Heaps

- A **heap**, a special type of binary tree
 - the value of each node is **greater than or equal** to the values stored in its **children**
 - the tree is perfectly balanced, and the leaves in the last level are **leftmost** in the tree



CS2413: Data Structures




2





Heaps (cont.)

- Different heaps constructed with the same elements



Heaps (cont.)


- A **max heap**;
 - the value of each node is **greater than or equal** to the values stored in its **children**
 - the root of a max heap, the **largest** element
- A **min heap**
 - the value of each node is **less than or equal** to the values stored in its **children**
 - the root of a min heap, the **smallest** element





Heaps (cont.)

- Insert a new element, 99, in **max heap**
 - leftmost in the heap



CS2413: Data Structures, Fall 2021




5



Heaps (cont.)

- Insert a new element, 99, in **max heap** (cont.)
 - heapify



CS2413: Data Structures, Fall 2021




6



Heaps (cont.)

- Build a max heap from the given set of numbers

- 45, 36, 54, 27, 63, 72, 61, 18




CS2413: Data Structures, Fall 2021

7



Heaps (cont.)

- Delete a node in **max heap**
 - always deleted from the root of the heap
 - **replace** the root node with the last node



CS2413: Data Structures, Fall 2021




8



Heaps (cont.)

- Delete a node in **max heap** (cont.)
 - always deleted from the root of the heap
 - **replace** the root node with the last node



CS2413: Data Structures, Fall 2021



9



Heaps (cont.)

- Heaps as **Priority Queues**
 - perfectly balanced trees, the inherent efficiency of searching such structures makes them more useful
 - **enqueue** and **dequeue** operations
 - enqueue,
 - add at the end of the heap as the last leaf
 - may need restructure the heap

heapEnqueue(e1)

```
put e1 at the end of the heap;  
while e1 is not in the root and e1 > parent(e1)  
    swap e1 with its parent;
```


CS2413: Data Structures, Fall 2021



10



Heaps (cont.)



CS2413: Data Str



11



Heaps (cont.)

- Heaps as **Priority Queues** (cont.)
 - dequeue
 - remove the root (since it is the largest value) and replace it by the last leaf
 - need restructure the heap

heapDequeue ()

```

extract the element from the root;
put the element from the last leaf in its place;
remove the last leaf;
// both subtrees of the root are heaps
p = the root;
while p is not a leaf and p < any of its children
  swap p with the larger child;
  
```





CS2413: Data Structures, Fall 2021



12



Heaps (cont.)



CS2413: Data S

