Create Product

product infomation voice SDK

front-end signal processing

Device microphone configuration, packaged SDK optimizes the signal according to different microphone conditions, so that the device can recognize the accurately

Microphone configuration	single MIC / double MIC	distance recognition	Near field 0-1m / Far field 1-5m
AEC echo cancellation	close / open	Steady-state noise reduction	close / open

//消噪

Pin configuration

Through customization, code can be automatically generated, and ports such as GPIO, PWM, and UART can output custom signals according to voice con and external devices can be controlled without code development.

Pin No.	Function	parameter 1	parameter 2	parameter 3	parameter 4	Remar
1	GPIO_B0	default is low level				The pu when t vel
2	GPIO_B1	default is low level				Set the ulse le
3	GPIO_A25	default is low level				The pu when t vel
4	GPIO_A26	default is low level				The pu when t vel
5	GPIO_A27	default is low level				The pu when t vel
6	GPIO_A28	default is low level				It is de ip enal the sta evelop se con dware modifi affect ast fun
7	GPIO_B6	default is low level				The pu when t vel
8	GPIO_B7	default is low level				The pu when t vel

					vel
22	GPIO_B3	default is low level			The pu when t vel

Wake-up word customization

Through customization, code can be automatically generated, and ports such as GPIO, PWM, and UART can output custom signals according to voice commands, and external devices can be controlled without code development. Wake-up Word Custom Rules

Wake-up Word	Pinyin	operation
Hello Homie		delete
Hey Homie		delete
Ni Hao		delete
Hey pudding		delete
Hello Pudding		delete

add one

Wake-up Sensitivity low middle high

reply for wake-up

I am here d

please go ahead d

Tell me what can I do for you d

Welcome d

+add

Customize offline command words and response words

If you want to control your own device, come and configure custom command words to make your device smart.

basic information control details

index	behavior	command word	reply word	operati
1	FirstLightOn	Turn on first light|first light on	First light is turned on for you	delete
2	FirstLightOff	Turn off first light|first light off	First light is turned off for you	delete
3	SecondLightOn	Turn on second light|second light c	second light is turned on for you	delete
4	SecondLightOff	Turn off second light|second light c	second light is turned off for you	delete
5	ThirdLightOn	Turn on Third light|Third light on	Third light is turned on for you	delete

Home product management Official website naga phanind

7	FourthLightOn	Turn on fourth light|fourth light on	fourth light is turned on for you	delete
8	FourthLightOff	Turn off fourth light|fourth light off	fourth light is turned off for you	delete
9	FanOn	Turn On the Fan|Fan On|Turn On	Turning on the fan	delete
10	FanSpeed1	Fan Speed One|Fan Speed Minim	Fan speed set to one	delete
11	FanSpeed2	Fan Speed Two	Fan speed set to two	delete
12	FanSpeed3	Fan Speed Three	Fan speed set to three	delete
13	FanSpeed4	Fan Speed Maximum|Fan Speed I	Fan speed set to four	delete
14	FanOff	Turn Off Fan|Fan Off|Turn Off the I	Turning off the fan	delete
15	AllLightsOn	Turn On all Lights|Turn On all the I	Turning on all the lights	delete
16	AllLightsOff	Turn Off all Lights|Turn Off all the I	Turning off all the lights	delete

Note: If you want to adjust the device volume, please set the action to volumeUpUni (increase volume), volumeDownUni (decrease volume), volumeMaxUni (maximum volume), volumeMidUni (medium volume), volumeMinUni (minimum volume), otherwise it will not take effect.

+add one massive import clear

automatic study commands

recognition sensitivity low middle high

Wake-up-free command words (up to 10 words, otherwise, only the first 10 will be in use)

options 0/26

- Turn on first li...
- Turn off first li...
- Turn on secon...
- Turn off seco...
- Turn on Third ...
- Third light on
- Turn off Third ...
- Third light off

selected options 0/8

- first light on
- first light off
- second light on
- second light off
- Fan On
- Fan Off
- All lights on
- All lights off

reset wakeup-free (If you cannot add 10 items, please click the reset button)

Speaker configuration

Let the device speak in a voice you define

synthesized voice type local synthesized voice

speaker

Home product management Official website naga phanind

sweet girl | Chinese Taiwan girl | lively girl | cute girl | fema anno

xiaofeng male announcer | tiantian naive boy

volume 10

speed of speech 58

brightness 50

other configuration

Let the device speak in a voice you define

boot broadcast has boot broadcast no boot broadcast

Welcome to Home automation by Phani and gı 45/200

quit for timeout timeout time: 20 seconds (Recommended between 5-60 seconds)

reply for quit please call me if necessary

+add

quit

quit command quit

Good bye

stop

+add

reply for quit please call me if necessary

see you next time

see you later

ok,have a nice day

+add

make new version

Technical Skills

> 97 %

General Domain Recognition Rate in Security Environment

0.081

Speech synthesis real-time rate

> 94.2 %

3~5 meters away, speaking recognition distance

(It can be increased by about 3% with the microphone array)

tens of millions level

Support massive concurrency

Contact Us

+86-755-29162996
+86-15989589908(skype)
overseas@aithinker.com
Address: Room408-410, Building C,
Huafeng Intelligence Innovation Port,
Gushu, Xixiang, Baoan District, Shenzhen,518126 ,China