Create Product

product infomation voice SDK

front-end signal processing

Device microphone configuration, packaged SDK optimizes the signal according to different microphone conditions, so that the device can recognize the accurately

Microphone configuration	single MIC / double MIC	distance recognition	Near field 0-1m / Far field 1-5m
AEC echo cancellation	close / open	Steady-state noise reduction	close / open

//消噪

Pin configuration

Through customization, code can be automatically generated, and ports such as GPIO, PWM, and UART can output custom signals according to voice con and external devices can be controlled without code development.

Pin No.	Function	parameter 1	parameter 2	parameter 3	parameter 4	Remar
1	GPIO_B0	default is low level				The pu when t vel
2	GPIO_B1	default is low level				Set the ulse le
3	GPIO_A25	default is low level				The pu when t vel
4	GPIO_A26	default is low level				The pu when t vel
5	GPIO_A27	default is low level				The pu when t vel
6	GPIO_A28	default is low level				It is de ip enal the sta evelop se con dware modifi affect ast fun
7	GPIO_B6	default is low level				The pu when t vel
8	GPIO_B7	default is low level				The pu when t vel

						vel
22	GPIO_B3	default is low level				The pu when t vel

Wake-up word customization

Through customization, code can be automatically generated, and ports such as GPIO, PWM, and UART can output custom signals according to voice commands, and external devices can be controlled without code development. Wake-up Word Custom Rules

Wake-up Word	Pinyin	operation
Hello Homie		delete
Hey Homie		delete
Ni Hao		delete
Hey pudding		delete
Hello Pudding		delete

add one

Wake-up Sensitivity low middle high

reply for wake-up

I am here d

please go ahead d

Tell me what can I do for you d

Welcome d

+add

Customize offline command words and response words

If you want to control your own device, come and configure custom command words to make your device smart.

basic information control details

index	behavior	command word	control type	action	action parameters
1	wakeup_uni	Hello Homie|Hey Homie|Ni Hao|Hey pudding|Hello Pudc	add control		
2	FirstLightOn	Turn on first light|first light on	GPIO_B0	settings	high level
			add control		

					add control
4	SecondLight(	Turn on second light|second light on	GPIO_B1	settings	high level
					add control
5	SecondLight(	Turn off second light|second light off	GPIO_B1	settings	low level
					add control
6	ThirdLightOn	Turn on Third light|Third light on	GPIO_B2	settings	high level
					add control
7	ThirdLightOff	Turn off Third light|Third light off	GPIO_B2	settings	low level
					add control
8	FourthLightO	Turn on fourth light|fourth light on	GPIO_B3	settings	high level
					add control
9	FourthLightO	Turn off fourth light|fourth light off	GPIO_B3	settings	low level
					add control
10	FanOn	Turn On the Fan|Fan On|Turn On Fan	GPIO_B7	settings	high level
			GPIO_A27	settings	low level
			GPIO_B6	settings	low level
					add control
11	FanSpeed1	Fan Speed One|Fan Speed Minimum	GPIO_B7	settings	high level
			GPIO_A27	settings	low level
			GPIO_B6	settings	low level
					add control
12	FanSpeed2	Fan Speed Two	GPIO_B7	settings	low level
			GPIO_A27	settings	low level
			GPIO_B6	settings	high level
					add control

13	FanSpeed3	Fan Speed Three	GPIO_A27	settings	low level
			GPIO_B6	settings	high level
			add control		
14	FanSpeed4	Fan Speed Maximum|Fan Speed Four	GPIO_B7	settings	low level
			GPIO_A27	settings	high level
			GPIO_B6	settings	low level
			add control		
15	FanOff	Turn Off Fan|Fan Off|Turn Off the Fan	GPIO_B7	settings	low level
			GPIO_A27	settings	low level
			GPIO_B6	settings	low level
			add control		
16	AllLightsOn	Turn On all Lights|Turn On all the Lights|All lights on	GPIO_B0	settings	high level
			GPIO_B1	settings	high level
			GPIO_B2	settings	high level
			GPIO_B3	settings	high level
			add control		
17	AllLightsOff	Turn Off all Lights|Turn Off all the Lights|All lights off	GPIO_B0	settings	low level
			GPIO_B1	settings	low level
			GPIO_B2	settings	low level
			GPIO_B3	settings	low level
			add control		

automatic study commands

recognition sensitivity low middle high

Wake-up-free command words (up to 10 words, otherwise, only the first 10 will be in use)

Home product management Official website naga phanind

Turn off first li...
Turn on secon...
Turn off seco...
Turn on Third ...
Third light on
Turn off Third ...
Third light off

first light off
second light on
second light off
Fan On
Fan Off
All lights on
All lights off

reset wakeup-free (If you cannot add 10 items, please click the reset button)

Speaker configuration

Let the device speak in a voice you define

synthesized voice type local synthesized voice

speaker

xuanxuan sweet girl
lingling Chinese Taiwan girl
tangtang lively girl
kiyo cute girl
xiao fema anno
xiaofeng male announcer
tiantian naive boy

volume 10

speed of speech 5

brightness 5

other configuration

Let the device speak in a voice you define

boot broadcast has boot broadcast no boot broadcast

Welcome to Home automation by Phani and gi 45/200

quit for timeout timeout time: 20 seconds (Recommended between 5-60 seconds)

reply for quit please call me if necessary

+add

quit

quit command quit

Good bye

+add

reply for quit

please call me if necessary

see you next time

see you later

ok,have a nice day

+add

make new version

Technical Skills

> 97 %

General Domain Recognition Rate in Security Environment

0.081

Speech synthesis real-time rate

> 94.2 %

3~5 meters away, speaking recognition distance

(It can be increased by about 3% with the microphone array)

tens of millions level

Support massive concurrency

Contact Us

+86-755-29162996
+86-15989589908(skype)
overseas@aithinker.com
Address: Room408-410, Building C,
Huafeng Intelligence Innovation Port,
Gushu, Xixiang, Baoan District, Shenzhen,518126 ,China