

Student 18 **NAGARAJAN SUBHASH** 192312489RB

10 / 10 submitted

Q1. Looping statements

CODE

```
#include<stdio.h>
int main()
{
    int n, rev = 0, digit;
    scanf("%d", &n);
    while(n != 0) {
        digit = n % 10;
        rev = rev * 10 + digit;
        n = n / 10;
    }
    printf("%d", rev);
    return 0;
}
```

INPUT

10
5

OUTPUT

1

Q2. Looping statements

CODE

```
#include<stdio.h>
int main()
{
    int n, original, reverse =0, digit;
    scanf("%d", &n);
    original = n;
    while(n != 0)
    {
        digit = n % 10;
        reverse = reverse * 10 + digit;
        n = n / 10;
    }
    if (original == reverse)
        printf("palindrome");
    else
        printf("not palindrome");
    return 0;
}
```

INPUT

121

OUTPUT

palindrome

Q3. Looping statements

CODE

```
#include<stdio.h>
int main()
{
    int n,original, digit, sum = 0;
    scanf("%d", &n);
    original = n;
    while(n != 0)
    {
        digit = n % 10;
        sum += digit * digit * digit;
        n = n / 10;
    }
    if (sum==digit)
        printf("armstrong number");
    else
        printf("not armstrong number");
    return 0;
}
```

INPUT

105

OUTPUT

not armstrong number

Q4. Looping statements

CODE

```
#include<stdio.h>
int main()
{
    int n,i,j,prime,sum = 0;
    scanf("%d", &n);
    for(i=2;i≤n;i++)
    {
        prime=1;
        for(j=2;j<1;j++)
            if(i%j==0)
            {
                prime=0;
                break;
            }
        if(prime)
            sum+= i;
        printf("%d", sum);
    }
    return 0;
}
```

INPUT

15

OUTPUT

259142027354454657790104119

Q5. Looping statements

CODE

```
#include<stdio.h>
int main ()
{
    int n,i,j;
    scanf("%d", &n);
    for(i = 1;i≤n; i++)
    {
        for(j=1;j≤n;i++ )
        {
            if(i==1||i==n||j==1||j==n)
                printf("*");
            else
                printf(" ");
        }
        printf("\n");
    }
    return 0;
}
```

INPUT

5

OUTPUT

Error: Execution timeout (>5 seconds) – possible infinite loop

Q6. Looping statements

CODE

```
#include<stdio.h>
int main()
{
    int i,n,j;
    scanf("%d", &n);
    for(i=n;i≥1; i++){
        for(j =1; j ≤ i; j++){
            printf("*");
        }
        printf("\n");
    }
    return 0;
}
```

INPUT

1

OUTPUT

Error: Execution timeout (>5 seconds) – possible infinite loop

Q7. Looping statements

CODE

```
#include<stdio.h>
int main()
{
    int n,i,j;
    scanf("%d", &n);
    for(i =1; i ≤n;i++){
        for(j =1; j ≤n -i++)
            printf(" ");
        for(j = 1; j≤2 * 1 -1; j++)
            printf("*");
        printf("/n");
    }
    return 0;
}
```

INPUT

5

OUTPUT

Compilation Error:
C:\Windows\TEMP\sandbox_192312489RB_6a6063e20a6110.85483022\main.c: In functio
n 'main':
C:\Windows\TEMP\sandbox_192312489RB_6a6063e20a6110.85483022\main.c:7:29: erro
r: expected ';' before ')' token
7 | for(j =1; j ≤n -i++)
 | ^
 | ;

Q8. Looping statements

CODE

```
#include<stdio.h>
int main()
{
    int n,i,j;
    scanf("%d", &n);

}
```

OUTPUT

Q9. Looping statements

CODE

```
#include<stdio.h>
int main()
{
    int n,i,j;
    scanf("%d", &n);
}
```

OUTPUT

Q10. Looping statements

CODE

```
#include<stdio.h>
int main()
{
    int n,i,j;
    scanf("%d", &n);
    for()
}
```

OUTPUT