



Spark Lesson 3

6 questions

1
point

1.

Check all true statements about the Directed Acyclic Graph Scheduler

- ☐ The DAG is managed by the cluster manager
- ☒ A DAG is used to track dependencies of each partition of each RDD
- ☐ If a partition is lost, the DAG is traversed forward to check what other steps are affected
- ☐ Each transformation is executed as soon as it is called on a RDD

1
point

2.

Why is building a DAG necessary in Spark but not in MapReduce?

- ☒ Because MapReduce always has the same type of workflow, Spark needs to accommodate diverse workflows.
- ☐ For resiliency: it is necessary to make sure a partition can be recovered in case it is lost.
- ☐ In order to make a computation distributed at large scale

1
point

3.

What are the differences between an action and a transformation? Mark all that apply

- ☐ An action always writes the disk.
 - ☒ A transformation is from worker nodes to worker nodes, an action between worker nodes and the Driver (or a data source like HDFS)
 - ☒ A transformation is lazy, an action instead executes immediately.
 - ☐ An action always triggers a shuffle.
-

1
point

4.

Generally, which are good stages to mark a RDD for caching in memory?

- ☒ After data cleaning, parsing and validation.
 - ☐ Every 2 or 3 transformations, to keep a recent backup.
 - ☐ The first RDD, just after reading from disk, so we avoid reading from disk again.
 - ☒ At the start of an iterative algorithm.
-

1
point

5.

What are good cases for using a broadcast variable? Mark all that apply

- ☒ Copy a small/medium sized RDD for a join
 - ☒ Copy a large configuration dictionary to all worker nodes
 - ☒ Copy a large lookup table to all worker nodes
 - ☐ Broadcast a Python module to all worker nodes
-

1
point

6.

We would like to count the number of invalid entries in this example dataset:

```
1 invalid = sc.accumulator(0)
2 d = sc.parallelize(["3", "23", "S", "99", "TT"]).foreach(count_invalid)
```

What would be a good implementation of the count_invalid function?



```
1 def count_invalid(element):
2     try:
3         int(element)
4     except:
5         invalid.accumulate(1)
```



```
1 def count_invalid(element):
2     try:
3         int(element)
4     except:
5         invalid.add(1)
```



```
1 def count_invalid(element):
2     try:
3         int(element)
4     except:
5         invalid = invalid + 1
```



```
1 def count_invalid(element):
2     try:
3         int(element)
4     except:
5         invalid = invalid.add(1)
```

Submit Quiz

