NAGDEV PRODUCTS

OFFICIAL TECHNICAL DATA SHEET

Document Ref: NPPL-TDS-23
Brand: NDEVSOAP™ LI12
Origin: North Gujarat Castor Belt, India

Lithium 12-Hydroxystearate (Lithium 12-HSA)

SPECIALTY RANGE · PROPRIETARY GRADE: NDEVSOAP™ LI12

CAS Number:	7620-77-1	HS Tariff Code:	Available on request
Physical Form:	Fine Powder / Flakes	Typical Colour:	White to Off-White
Feedstock / Raw Material:	12-Hydroxystearic Acid (12-HSA), derived from Castor Oil	Shelf Life:	24 months in sealed, moisture-protected packaging.
Quality System:	Quality systems aligned to ISO 9001		

ANALYTICAL PARAMETERS & SPECIFICATIONS

SR. NO.	TEST PARAMETER	SPECIFICATION	TEST METHOD
1	Appearance	White to Off-White Fine Powder / Flakes	Visual
2	Lithium Content, %	2.0 – 3.0	ICP-OES / AAS
3	12-Hydroxystearic Acid Content, %	85.0 Min	GC / GLC
4	Precursor Fatty Acid Value, mg KOH/g	175 – 190	AOCS Cd 3d-63
5	Hydroxyl Value, mg KOH/g	145 – 165	AOCS Cd 13-60
6	Melting Point, °C	210 Min (Decomposition)	Standard Laboratory Method
7	Moisture, %	1.0 Max	ASTM E203
8	Free Fatty Acids, %	2.0 Max	AOCS Ca 5a-40
9	Ash, %	10.0 Max	ASTM D482
10	Water-Insoluble Matter, %	1.0 Max	Standard Laboratory Method
11	Free Alkali, %	0.5 Max	Standard Laboratory Method
12	Particle Size, Passing Through 100 Mesh, %	95 Min	Sieve Test
13	Penetration of Grease Prepared from Product, 0.1 mm	As per Grade / Customer Requirement	ASTM D217

STANDARD PACKAGING & BULK LOGISTICS

20 / 25 kg HDPE-Lined Paper / PP Bags • 500 kg HDPE Jumbo Bags • 1,000 kg HDPE Jumbo Bags • Or as recommended / specified by client

TARGET INDUSTRIAL APPLICATIONS

Lithium 12-Hydroxystearate is primarily used as a thickener / lubricating soap for lithium-based greases. It provides good mechanical stability, water resistance and high-temperature performance and is used in automotive, industrial, bearing and general-purpose lubricating grease formulations.

Nagdev Products Private Limited · Survey No. 301 P-2, Jada-Kotarwada Road, Village – Sardarpura, Post – Ravel, Taluka – Deodar, District – Vav-Tharad, Gujarat – 385330, India
Email: nagdevproducts@gmail.com | Phone / WhatsApp: +91 63520 98306 | Web: www.nagdevproducts.com
Disclaimer: The specifications above reflect typical quality values tested according to standardized AOCS / ASTM

compendia. Every shipment is accompanied by a batch Certificate of Analysis (COA). HS tariff classification is indicative; final code confirmed at time of export.

Nagdev Products Pvt. Ltd.
Quality Assurance Laboratory