NAGDEV PRODUCTS PRIVATE LIMITED
Manufacturer of Castor Oil & Specialty Oleochemical Derivatives · Gujarat, India
Survey No. 301 P-2, Sardarpura, Taluka · Deodar, Dist. Vav-Tharad · 385330 | nagdevproducts@gmail.com
Hotline / WhatsApp: +91 63520 98306 | Web: www.nagdevproducts.com

TECHNICAL DATA SHEET
Doc Ref: NPPL-TDS-16
Date: October 2026
Status: Advance Specification

Blown / Oxidized Castor Oil

Proprietary Grade: NDEVOX· BLO | CAS No: 68187-84-8 | Category: Under Development

Physical Form:	Viscous Liquid	Raw Material:	Refined Castor Oil
Typical Colour:	Pale Yellow to Amber	Shelf Life:	18-24 months
Standard Packing:	Bulk in ISO Tank / Flexi Tank · 200 / 225 kg MS Drums / HDPE Drums ·		

GUARANTEED ANALYTICAL SPECIFICATIONS

SR	TEST PARAMETER	SPECIFICATION LIMIT	STANDARD METHOD
1	Appearance	Clear to Slightly Hazy, Viscous Liqu	Visual
2	Colour, Gardner	8.0 Max	ASTM D1544
3	Acid Value, mg KOH/g	5.0 Max	AOCS Cd 3d-63
4	Iodine Value, g I·/100g	65 · 80	AOCS Cd 1d-92
5	Hydroxyl Value, mg KOH/g	130 · 155	AOCS Cd 13-60
6	Saponification Value, mg KOH/g	175 · 190	AOCS Cd 3-25
7	Moisture & Volatile Matter, %	0.50 Max	AOCS Ca 2c-25
8	Specific Gravity at 30°C	0.950 · 0.970	ASTM D4052
9	Refractive Index at 40°C	1.475 · 1.485	ASTM D1218
10	Viscosity at 25°C	1,000 · 3,000 cP	ASTM D445 / Brookfie
11	Unsaponifiable Matter, %	1.0 Max	AOCS Ca 6a-40
12	Oxidation / Blowing Level	As per Grade / Customer Requirement	Standard Laboratory

PRODUCT APPLICATION & CHARACTERISTICS

Used in paints, varnishes, coatings, printing inks, lubricants, adhesives, sealants and specialty chemical formulations where increased viscosity ('body'), tack and film-forming properties are required. Grade is selected by target viscosity.

IMPORTANT NOTICE & COMMERCIAL AVAILABILITY:
Commercial production begins in 2027 at our new integrated manufacturing facility in Vav-Tharad, Gujarat.
Advance bulk inquiries, long-term supply agreements, and 500g/1kg R&D lab samples are currently accepted.