NAGDEV PRODUCTS PRIVATE LIMITED
Manufacturer of Castor Oil & Specialty Oleochemical Derivatives · Gujarat, India
Survey No. 301 P-2, Sardarpura, Taluka · Deodar, Dist. Vav-Tharad · 385330 | nagdevproducts@gmail.com
Hotline / WhatsApp: +91 63520 98306 | Web: www.nagdevproducts.com

TECHNICAL DATA SHEET
Doc Ref: NPPL-TDS-03
Date: October 2026
Status: Advance Specification

Refined Castor Oil (First Special Grade · F.S.G / B.S.S)

Proprietary Grade: NDEV-FSG | CAS No: 8001-79-4 | Category: Castor Oil

Physical Form:	Viscous Transparent Liquid	Raw Material:	Castor Seed (Ricinus communis)
Typical Colour:	Yellow / Pale Straw	Shelf Life:	24 months from date of manufactu
Standard Packing:	Bulk in ISO Tank / Flexi Tank / Vessel · 200 / 225 kg MS Drums / HDPE Drums · 95		

GUARANTEED ANALYTICAL SPECIFICATIONS

SR	TEST PARAMETER	SPECIFICATION LIMIT	STANDARD METHOD
1	Appearance	Viscous Transparent Liquid	AOCS / ASTM / BIS
2	Colour	Yellow / Pale Straw	AOCS / ASTM / BIS
3	Colour on 5¼" Lovibond Cell	Max 20Y + 2R	AOCS / ASTM / BIS
4	Free Fatty Acid (FFA)	1% Max	AOCS / ASTM / BIS
5	Acid Value	2.0 mg KOH/g Max	AOCS / ASTM / BIS
6	Refractive Index @ 20°C	1.477 · 1.481	AOCS / ASTM / BIS
7	Relative Density @ 20°C	0.954 · 0.960	AOCS / ASTM / BIS
8	Saponification Value	177 · 185 mg KOH/g	AOCS / ASTM / BIS
9	Unsaponifiable Matter	1.0% Max	AOCS / ASTM / BIS
10	Hydroxyl Number	160 · 168 mg KOH/g	AOCS / ASTM / BIS
11	Iodine Number	82 · 90 g I·/100g	AOCS / ASTM / BIS
12	Ricinoleic Acid Content	85% Min	AOCS / ASTM / BIS
13	Moisture	0.25% Max	AOCS / ASTM / BIS

PRODUCT APPLICATION & CHARACTERISTICS

High-purity refined, neutralized and bleached castor oil manufactured to British Standard Specifications (B.S.S). Premier grade for manufacturing HCO, 12-HSA, clear coatings, urethanes, cosmetic formulations, and premium specialty lubricants.

IMPORTANT NOTICE & COMMERCIAL AVAILABILITY:
Commercial production begins in 2027 at our new integrated manufacturing facility in Vav-Tharad, Gujarat.
Advance bulk inquiries, long-term supply agreements, and 500g/1kg R&D lab samples are currently accepted.