Spec → Code: ONC_LSN_011_JR_STD

Exported 8/31/2026, 10:15:15 AM · Tenant: default

1. Spec

REPORT ID

ONC_LSN_011_JR_STD

EDC SYSTEM / LANGUAGE

veeva / CQL

DESCRIPTION

This report will list subjects that have discrepancies between Lesion evaluation "schedule time" and its corresponding oncologic response "schedule time" and Oncologic scan "schedule time".

COLUMN HEADING

1. Country
2. Site
3. Subject Number
4. Lesion Form
5. Lesion Seq #
6. Lesion Date
7. Lesion Scheduled Time
8. Scan Form
9. Scan Seq #
10. Scan Date
11. Scan Scheduled Time
12. RSP Form
13. RSP Seq #
14. RSP Date Response Determined
15. RSP Scheduled Time
16. Scenario

LOGIC

Logic 1:
(Logic 1.1: LSN. "Scheduled time" <> RSP. "Scheduled time"
AND
Logic 1.2: "Date of Lesion Evaluation" = RSP."Date Response Determined"
)

OR

(Logic 1.3 LSN. "Scheduled time" <> ORAJ. Scheduled Time
AND
Logic 1.4: "Date of Lesion Evaluation" = ORAJ.Date of Assessment (Scan/Image/Physical Exam)
)

Logic 2:
(Logic 2.1: OSCN. Scheduled Time <> RSP. "Scheduled Time"
AND
Logic 2.2: OSCN. Scan Date = RSP."Date Response Determined"
)

OR

(Logic 2.3: OSCN. Scheduled Time <> ORAJ. Scheduled Time
AND
Logic 2.4: OSCN. Scan Date = ORAJ.Date of Assessment (Scan/Image/Physical Exam)
)

Logic 3:
Logic 3.1: LSN.Date of Initial Identification = LSN.Date of Lesion Evaluation time
AND
Logic 3.2: LSN."Scheduled time" <> OSCN. "Scheduled"
AND
Logic 3.3: LSN.Date of Initial Identification = OSCN.Scan Date

Notes:
Note 1: Exclude deleted records.
Note 2: The report will use master supporting documents LSN_supp_doc and RSP_supp_doc. These supporting documents should be uploaded only once at TA level per the GDO Oncology TAST authorized members and will be used to facilitate programming of the report. Report builder will use all the columns provided in the excel spreadsheet to create the programming code.
Note 3: The distribution of items are as follows:
- "Date of Lesion Evaluation", "Date of Initial Identification ", LSN. "Scheduled Time" belong to LSN_supp_doc
- "Date Response Determined", RSP. "Scheduled Time" belongs to RSP_supp_doc
Note 4: If OSCN 'Scheduled Time' is not present in the study, please do not consider Scenario 2 and Scenario 3 and run only Scenario 1.

REPORT SCENARIOS

Display 'Scenario 1' for Logic 1, 'Scenario 2' for Logic 2, 'Scenario 3' for Logic 3.

Scenario 1 Yes : When Logic is satisfied

Scenario 2 No : When Logic is not satisfied

SORTING

Country, Site, Subject Number

2. Logic Understanding

This spec identifies discrepancies in scheduled times across three paired-form comparisons: LSN-vs-RSP/ORAJ (Logic 1/Scenario 1), OSCN-vs-RSP/ORAJ (Logic 2/Scenario 2), and LSN-vs-OSCN (Logic 3/Scenario 3), where each comparison flags a subject when two forms share the same clinical assessment date but have mismatched scheduled times. Scenario 2 and 3 are conditionally suppressed per Note 4 if OSCN Scheduled Time isn't collected in the study, and deleted records are excluded throughout (Note 1). A key ambiguity is the ORAJ form referenced in Logic 1 and 2, which is not explicitly defined or reflected in the Column Headings, requiring clarification before coding.
1. Logic 1 (Scenario 1) has two OR'd sub-conditions, each requiring BOTH a scheduled-time mismatch AND a date match to trigger. Sub-condition A (Logic 1.1 AND 1.2): LSN.'Scheduled time' does NOT equal RSP.'Scheduled time' (Logic 1.1), AND at the same time 'Date of Lesion Evaluation' equals RSP.'Date Response Determined' (Logic 1.2) - meaning the LSN and RSP records represent the same clinical assessment date but were scheduled at different times, which is the discrepancy being flagged.

2. Logic 1 sub-condition B (Logic 1.3 AND 1.4): as an alternative (OR) to sub-condition A, LSN.'Scheduled time' does NOT equal ORAJ.Scheduled Time (Logic 1.3), AND 'Date of Lesion Evaluation' equals ORAJ.Date of Assessment (Scan/Image/Physical Exam) (Logic 1.4) - same pattern as sub-condition A but comparing LSN against ORAJ instead of RSP, again meaning same-date but different scheduled-time is a discrepancy.

3. If either sub-condition A or sub-condition B of Logic 1 is true, the overall Logic 1 is satisfied and the record is flagged as 'Scenario 1'.

4. Logic 2 (Scenario 2) mirrors the structure of Logic 1, but compares OSCN (Oncologic Scan) records instead of LSN records. Sub-condition A (Logic 2.1 AND 2.2): OSCN.Scheduled Time does NOT equal RSP.'Scheduled Time' (Logic 2.1) AND OSCN.Scan Date equals RSP.'Date Response Determined' (Logic 2.2) - i.e., same assessment date but different scheduled times between the Scan and RSP records.

5. Logic 2 sub-condition B (Logic 2.3 AND 2.4): as an alternative (OR), OSCN.Scheduled Time does NOT equal ORAJ.Scheduled Time (Logic 2.3) AND OSCN.Scan Date equals ORAJ.Date of Assessment (Scan/Image/Physical Exam) (Logic 2.4) - same pattern comparing OSCN against ORAJ instead of RSP.

6. If either sub-condition A or B of Logic 2 is true, Logic 2 is satisfied and the record is flagged as 'Scenario 2'. Per Note 4, Logic 2 (and Scenario 2) should only be evaluated if OSCN 'Scheduled Time' is actually collected/present in the study.

7. Logic 3 (Scenario 3) is a single AND-combined condition (no OR branches), all three sub-conditions must be true together: (3.1) LSN.Date of Initial Identification equals LSN.Date of Lesion Evaluation time - meaning the lesion was first identified on the same date as its evaluation; AND (3.2) LSN.'Scheduled time' does NOT equal OSCN.'Scheduled' time; AND (3.3) LSN.Date of Initial Identification equals OSCN.Scan Date - meaning the lesion's initial identification date lines up with the scan date, but the scheduled times between LSN and OSCN differ.

8. If all three sub-conditions of Logic 3 are true, the record is flagged as 'Scenario 3'. Per Note 4, this scenario is only evaluated if OSCN 'Scheduled Time' is present in the study - otherwise it's skipped entirely.

9. Across all three Logic blocks, deleted records must be excluded first (Note 1) before any of the above date/time comparisons are made, since a deleted LSN, OSCN, RSP, or ORAJ record should not be used in the matching logic.

10. For each subject/record combination where any of Logic 1, Logic 2, or Logic 3 is satisfied, the report displays the corresponding Scenario label ('Scenario 1', 'Scenario 2', or 'Scenario 3') along with the LSN, Scan, and RSP form/date/scheduled-time details as listed in the Column Headings, and marks it as discrepant ('Yes'); the Report Scenarios section indicates 'No' is shown when the logic is not satisfied - though it's inferred this means non-flagged combinations are either excluded from the listing or shown with a 'No' indicator, since the report's Description states it 'will list subjects that have discrepancies', suggesting only 'Yes' rows are typically included. *(inferred)*

3. Spec Review

Readiness: Needs revision — The spec has a workable overall structure but contains multiple blocking gaps -- most notably an internally contradictory Report Scenarios definition, undocumented ORAJ fields with no corresponding columns or supporting document, and unaddressed overlap between scenarios -- that would force a query generator to guess at output-determining logic. It needs revision before being handed off for query generation.

BLOCKING (consistency): The Report Scenarios section only defines 'Scenario 1 Yes: When Logic is satisfied' and 'Scenario 2 No: When Logic is not satisfied', but the Logic section defines three distinct logic blocks (Logic 1, 2, 3) and the instruction under Report Scenarios explicitly says 'Display Scenario 1 for Logic 1, Scenario 2 for Logic 2, Scenario 3 for Logic 3'. The Yes/No scenario definitions do not correspond to this 1-to-1 mapping to the three logic blocks at all, and Scenario 3 has no Yes/No definition given. → Rewrite the Report Scenarios section so each of the three scenarios (1, 2, 3) has an explicit, self-consistent definition tied to its corresponding Logic block, e.g. 'Scenario 1: displayed when Logic 1 is satisfied', 'Scenario 2: displayed when Logic 2 is satisfied', 'Scenario 3: displayed when Logic 3 is satisfied', and remove or clarify the stray 'Yes'/'No' labels which currently contradict the stated Logic-to-Scenario mapping.

BLOCKING (testability): Since the report is described as listing subjects with 'discrepancies,' and each Logic block (1, 2, 3) independently evaluates to true/false, a single subject/record could satisfy more than one Logic block (e.g., both Logic 1 and Logic 3 simultaneously). The spec does not state whether a record producing multiple simultaneous scenario matches should appear as multiple rows (one per scenario), a single row with multiple scenarios listed, or only the first/highest-priority scenario. → Add a rule such as 'If a record satisfies more than one Logic block, output one row per satisfied scenario' or 'output only the first satisfied scenario in Logic 1, 2, 3 priority order' so the generator knows how to handle overlapping matches.

WARNING (ambiguity): Logic 3.2 references 'OSCN. "Scheduled"' while Logic 2 and elsewhere consistently use 'OSCN. Scheduled Time'. It's unclear whether 'Scheduled' in Logic 3.2 is a typo for 'Scheduled Time' or refers to a different field. → Standardize the field name to 'OSCN. Scheduled Time' in Logic 3.2 to match its usage in Logic 2.1/2.3, or clarify if a distinct field named 'Scheduled' (without 'Time') actually exists in OSCN.

WARNING (naming): The Logic section uses abbreviations LSN, RSP, ORAJ, and OSCN as form/domain codes, but the Column Heading section refers to these as 'Lesion Form', 'Scan Form', and 'RSP Form' -- there is no column heading corresponding to 'ORAJ' at all, and 'OSCN' is presumably the same as 'Scan Form' but this mapping is never stated explicitly. Note 3 also refers to 'LSN_supp_doc' and 'RSP_supp_doc' without ever mentioning an OSCN or ORAJ supporting document. → Add an explicit legend mapping each abbreviation to its full form name and to the corresponding supporting document (e.g., LSN = Lesion Form, RSP = Response Form, OSCN = Oncologic Scan Form, ORAJ = Oncologic Response Assessment/Judgement Form), and confirm whether ORAJ has its own supporting document or reuses RSP_supp_doc, since Logic 1.3/1.4/2.3/2.4 rely heavily on ORAJ fields that are undocumented in Note 3.

BLOCKING (completeness): Logic 1 and Logic 2 reference 'ORAJ. Scheduled Time' and 'ORAJ.Date of Assessment (Scan/Image/Physical Exam)', but neither the Column Headings, Note 3 (item distribution), nor any other part of the spec defines what ORAJ is, which supporting document it belongs to, or how its data should be retrieved/joined. There are no Column Heading fields for an ORAJ Form/Seq#/Date, unlike LSN, Scan (OSCN), and RSP which each have Form/Seq#/Date/Scheduled Time columns. → Either add ORAJ Form, Seq#, and Date columns to the Column Heading list (if ORAJ is a distinct, reportable data source) or clarify that ORAJ output should be merged into the RSP or Scan columns, and specify which supporting document(s) house ORAJ data and its join keys.

WARNING (ambiguity): Note 4 states 'If OSCN Scheduled Time is not present in the study, please do not consider Scenario 2 and Scenario 3 and run only Scenario 1.' It does not clarify whether 'not present in the study' means the field is not collected at all (study configuration) versus simply null/blank for a given record, which would materially change how the condition is evaluated at build time vs. run time. → Clarify that this refers to a study-level configuration check (e.g., the OSCN Scheduled Time item does not exist in this study's build) rather than a per-record null check, and state how the report builder should determine this (e.g., checking metadata/CRF design rather than data values).

WARNING (completeness): Note 1 says 'Exclude deleted records' but does not specify which records/forms this applies to (LSN, RSP, OSCN, ORAJ, or all) nor how a 'deleted record' is identified (e.g., a deleted flag field, removed

from dataset, or a specific status value). → Specify explicitly which forms the deleted-record exclusion applies to and the exact field/flag used to identify a deleted record (e.g., 'Exclude records where LSN.Deleted = Yes, RSP.Deleted = Yes, OSCN.Deleted = Yes').

WARNING (completeness): The spec does not address what should happen when dates or scheduled times used in the comparisons (e.g., LSN.'Date of Lesion Evaluation', RSP.'Date Response Determined', OSCN.Scan Date) are missing/null for a given record -- e.g., whether a null-to-null comparison in Logic 1.2/2.2/3.3 counts as a match or should be excluded. → Add explicit handling for missing/null dates and scheduled times, e.g., 'Records with a missing Date of Lesion Evaluation, Date Response Determined, or Scan Date should be excluded from all scenario logic comparisons.'

INFO (ambiguity): Logic 3.1 states 'LSN.Date of Initial Identification = LSN.Date of Lesion Evaluation time' -- the phrase 'Date of Lesion Evaluation time' mixes a date field name with the word 'time', which is inconsistent with how the same field is referenced elsewhere as simply 'Date of Lesion Evaluation'. → Standardize the field reference to 'LSN.Date of Lesion Evaluation' (dropping the trailing 'time') to match its usage in Logic 1.2 and 1.4, or clarify if a distinct timestamp field is actually intended here.

4. Generated Code

CQL — Guardrails: passed

```
SELECT
  LSN_D.Country AS `Country`,
  LSN_D.Site AS `Site`,
  LSN_D.SubjectNumber AS `Subject Number`,
  LSN_D.LesionForm AS `Lesion Form`,
  LSN_D.LesionSeq AS `Lesion Seq
#`,
  DATE_FORMAT(LSN_D.LesionDateRaw, '%d%b%Y') AS `Lesion Date`,
  LSN_D.LesionSchedTime AS `Lesion Scheduled Time`,
  LSN_D.ScanForm AS `Scan Form`,
  LSN_D.ScanSeq AS `Scan Seq #`,
  DATE_FORMAT(LSN_D.ScanDateRaw, '%d%b%Y') AS `Scan Date`,
  LSN_D.ScanSchedTime AS `Scan Scheduled Time`,
  LSN_D.RspForm AS `RSP Form`,
  LSN_D.RspSeq AS `RSP Seq #`,
  DATE_FORMAT(LSN_D.RspDateRaw, '%d%b%Y') AS `RSP Date Response Determined`,
  LSN_D.RspSchedTime AS `RSP Scheduled Time`,
  LSN_D.Scenario AS `Scenario`
FROM
(
  -- Scenario 1: LSN vs RSP or ORAJ scheduled time mismatch on matching dates
SELECT
    `@HDR`.`Site`.`Country` AS Country,
    `@HDR`.`Site`.`Number` AS Site,
    `@HDR`.`Subject`.`Name` AS SubjectNumber,
    `@Form`.`Name` AS LesionForm,
    LOELFM.LOELSPIDIT AS LesionSeq,
    RAWDATE(LOELFM.LOELLSDTCLEVIT) AS LesionDateRaw,
    LOELFM.LOELLSSCHEDTMIT AS LesionSchedTime,
    NULL AS ScanForm,
    NULL AS ScanSeq,
    CAST(NULL AS DATE) AS ScanDateRaw,
    NULL AS ScanSchedTime,
    RSP_M.RspForm AS RspForm,
    RSP_M.RspSeq AS RspSeq,
    RSP_M.RspDateRaw AS RspDateRaw,
    RSP_M.RspSchedTime AS RspSchedTime,
    'Scenario 1' AS Scenario
  FROM `EDC`.`LOELFM` LOELFM
  INNER JOIN
  (
    SELECT
      `@HDR`.`Subject`.`ID` AS SubjectID,
      `@Form`.`Name` AS RspForm,
      RSPFM.RSPSPIDIT AS RspSeq,
      RAWDATE(RSPFM.RSPDTRESPIT) AS RspDateRaw,
      RSPFM.RSPSCHEDTMIT AS RspSchedTime
    FROM `EDC`.`RSPFM` RSPFM
    WHERE `@Form`.`Status` = 'submitted__v'
      AND (RSPFM.DELETEDFM = 'N' OR RSPFM.DELETEDFM IS NULL)
  ) RSP_M
    ON `@HDR`.`Subject`.`ID` = RSP_M.SubjectID
  WHERE `@Form`.`Status` = 'submitted__v'
    AND (LOELFM.DELETEDFM = 'N' OR LOELFM.DELETEDFM IS NULL)
    AND LOELFM.LOELLSSCHEDTMIT <> RSP_M.RspSchedTime
    AND RAWDATE(LOELFM.LOELLSDTCLEVIT) = RSP_M.RspDateRaw

  UNION ALL

  SELECT
    `@HDR`.`Site`.`Country` AS Country,
    `@HDR`.`Site`.`Number` AS Site,
    `@HDR`.`Subject`.`Name` AS SubjectNumber,
    `@Form`.`Name` AS LesionForm,
    LOELFM.LOELSPIDIT AS LesionSeq,
    RAWDATE(LOELFM.LOELLSDTCLEVIT) AS LesionDateRaw,
    LOELFM.LOELLSSCHEDTMIT AS LesionSchedTime,
    NULL AS ScanForm,
    NULL AS ScanSeq,
```

```
    CAST(NULL AS DATE) AS ScanDateRaw,
    NULL AS ScanSchedTime,
    ORAJ_M.OrajForm AS RspForm,
    ORAJ_M.OrajSeq AS RspSeq,
    ORAJ_M.OrajDateRaw AS RspDateRaw,
    ORAJ_M.OrajSchedTime AS RspSchedTime,
    'Scenario 1' AS Scenario
  FROM `EDC`.`LOELFM` LOELFM
  INNER JOIN
  (
    SELECT
      `@HDR`.`Subject`.`ID` AS SubjectID,
      `@Form`.`Name` AS OrajForm,
      ORAJFM.ORAJSPIDIT AS OrajSeq,
      RAWDATE(ORAJFM.ORAJDTASSESSIT) AS OrajDateRaw,
      ORAJFM.ORAJSCHEDTMIT AS OrajSchedTime
    FROM `EDC`.`ORAJFM` ORAJFM
    WHERE `@Form`.`Status` = 'submitted__v'
      AND (ORAJFM.DELETEDFM = 'N' OR ORAJFM.DELETEDFM IS NULL)
  ) ORAJ_M
    ON `@HDR`.`Subject`.`ID` = ORAJ_M.SubjectID
  WHERE `@Form`.`Status` = 'submitted__v'
    AND (LOELFM.DELETEDFM = 'N' OR LOELFM.DELETEDFM IS NULL)
    AND LOELFM.LOELLSSCHEDTMIT <> ORAJ_M.OrajSchedTime
    AND RAWDATE(LOELFM.LOELLSDTCLEVIT) = ORAJ_M.OrajDateRaw

  UNION ALL

-- Scenario 2: OSCN vs RSP or ORAJ scheduled time mismatch on matching dates
SELECT
    `@HDR`.`Site`.`Country` AS Country,
    `@HDR`.`Site`.`Number` AS Site,
    `@HDR`.`Subject`.`Name` AS SubjectNumber,
    NULL AS LesionForm,
    NULL AS LesionSeq,
    CAST(NULL AS DATE) AS LesionDateRaw,
    NULL AS LesionSchedTime,
    `@Form`.`Name` AS ScanForm,
    OSCNFM.OSCNSPIDIT AS ScanSeq,
    RAWDATE(OSCNFM.OSCNSCANDATIT) AS ScanDateRaw,
    OSCNFM.OSCNSCHEDTMIT AS ScanSchedTime,
    RSP_M2.RspForm AS RspForm,
    RSP_M2.RspSeq AS RspSeq,
    RSP_M2.RspDateRaw AS RspDateRaw,
    RSP_M2.RspSchedTime AS RspSchedTime,
    'Scenario 2' AS Scenario
  FROM `EDC`.`OSCNFM` OSCNFM
  INNER JOIN
  (
    SELECT
      `@HDR`.`Subject`.`ID` AS SubjectID,
      `@Form`.`Name` AS RspForm,
      RSPFM.RSPSPIDIT AS RspSeq,
      RAWDATE(RSPFM.RSPDTRESPIT) AS RspDateRaw,
      RSPFM.RSPSCHEDTMIT AS RspSchedTime
    FROM `EDC`.`RSPFM` RSPFM
    WHERE `@Form`.`Status` = 'submitted__v'
      AND (RSPFM.DELETEDFM = 'N' OR RSPFM.DELETEDFM IS NULL)
  ) RSP_M2
    ON `@HDR`.`Subject`.`ID` = RSP_M2.SubjectID
  WHERE `@Form`.`Status` = 'submitted__v'
    AND (OSCNFM.DELETEDFM = 'N' OR OSCNFM.DELETEDFM IS NULL)
    AND OSCNFM.OSCNSCHEDTMIT IS NOT NULL
    AND OSCNFM.OSCNSCHEDTMIT <> RSP_M2.RspSchedTime
    AND RAWDATE(OSCNFM.OSCNSCANDATIT) = RSP_M2.RspDateRaw

  UNION ALL

  SELECT
    `@HDR`.`Site`.`Country` AS Country,
```

```
    `@HDR`.`Site`.`Number` AS Site,
    `@HDR`.`Subject`.`Name` AS SubjectNumber,
    NULL AS LesionForm,
    NULL AS LesionSeq,
    CAST(NULL AS DATE) AS LesionDateRaw,
    NULL AS LesionSchedTime,
    `@Form`.`Name` AS ScanForm,
    OSCNFM.OSCNSPIDIT AS ScanSeq,
    RAWDATE(OSCNFM.OSCNSCANDATIT) AS ScanDateRaw,
    OSCNFM.OSCNSCHEDTMIT AS ScanSchedTime,
    ORAJ_M2.OrajForm AS RspForm,
    ORAJ_M2.OrajSeq AS RspSeq,
    ORAJ_M2.OrajDateRaw AS RspDateRaw,
    ORAJ_M2.OrajSchedTime AS RspSchedTime,
    'Scenario 2' AS Scenario
  FROM `EDC`.`OSCNFM` OSCNFM
  INNER JOIN
  (
    SELECT
      `@HDR`.`Subject`.`ID` AS SubjectID,
      `@Form`.`Name` AS OrajForm,
      ORAJFM.ORAJSPIDIT AS OrajSeq,
      RAWDATE(ORAJFM.ORAJDTASSESSIT) AS OrajDateRaw,
      ORAJFM.ORAJSCHEDTMIT AS OrajSchedTime
    FROM `EDC`.`ORAJFM` ORAJFM
    WHERE `@Form`.`Status` = 'submitted__v'
      AND (ORAJFM.DELETEDFM = 'N' OR ORAJFM.DELETEDFM IS NULL)
  ) ORAJ_M2
    ON `@HDR`.`Subject`.`ID` = ORAJ_M2.SubjectID
  WHERE `@Form`.`Status` = 'submitted__v'
    AND (OSCNFM.DELETEDFM = 'N' OR OSCNFM.DELETEDFM IS NULL)
    AND OSCNFM.OSCNSCHEDTMIT IS NOT NULL
    AND OSCNFM.OSCNSCHEDTMIT <> ORAJ_M2.OrajSchedTime
    AND RAWDATE(OSCNFM.OSCNSCANDATIT) = ORAJ_M2.OrajDateRaw

  UNION ALL

-- Scenario 3: LSN initial identification date = evaluation date, but LSN sched time <> OSCN sched
time, matching dates
SELECT
    `@HDR`.`Site`.`Country` AS Country,
    `@HDR`.`Site`.`Number` AS Site,
    `@HDR`.`Subject`.`Name` AS SubjectNumber,
    `@Form`.`Name` AS LesionForm,
    LOELFM.LOELSPIDIT AS LesionSeq,
    RAWDATE(LOELFM.LOELLSDTCLEVIT) AS LesionDateRaw,
    LOELFM.LOELLSSCHEDTMIT AS LesionSchedTime,
    OSCN_M.ScanForm AS ScanForm,
    OSCN_M.ScanSeq AS ScanSeq,
    OSCN_M.ScanDateRaw AS ScanDateRaw,
    OSCN_M.ScanSchedTime AS ScanSchedTime,
    NULL AS RspForm,
    NULL AS RspSeq,
    CAST(NULL AS DATE) AS RspDateRaw,
    NULL AS RspSchedTime,
    'Scenario 3' AS Scenario
  FROM `EDC`.`LOELFM` LOELFM
  INNER JOIN
  (
    SELECT
      `@HDR`.`Subject`.`ID` AS SubjectID,
      `@Form`.`Name` AS ScanForm,
      OSCNFM.OSCNSPIDIT AS ScanSeq,
      RAWDATE(OSCNFM.OSCNSCANDATIT) AS ScanDateRaw,
      OSCNFM.OSCNSCHEDTMIT AS ScanSchedTime
    FROM `EDC`.`OSCNFM` OSCNFM
    WHERE `@Form`.`Status` = 'submitted__v'
      AND (OSCNFM.DELETEDFM = 'N' OR OSCNFM.DELETEDFM IS NULL)
      AND OSCNFM.OSCNSCHEDTMIT IS NOT NULL
  ) OSCN_M
```

```
    ON `@HDR`.`Subject`.`ID` = OSCN_M.SubjectID
  WHERE `@Form`.`Status` = 'submitted__v'
    AND (LOELFM.DELETEDFM = 'N' OR LOELFM.DELETEDFM IS NULL)
    AND RAWDATE(LOELFM.LOELTUDTCIT) = RAWDATE(LOELFM.LOELLSDTCLEVIT)
    AND LOELFM.LOELLSSCHEDTMIT <> OSCN_M.ScanSchedTime
    AND RAWDATE(LOELFM.LOELTUDTCIT) = OSCN_M.ScanDateRaw
) LSN_D
ORDER BY
  `Country`, `Site`, `Subject Number`
```

I built three UNION ALL branches, one per Logic scenario (Scenario 1 = LSN vs RSP or LSN vs ORAJ scheduled-time mismatch on matching dates; Scenario 2 = OSCN vs RSP or OSCN vs ORAJ mismatch; Scenario 3 = LSN initial-identification-date=evaluation-date case vs OSCN mismatch), each producing the same 16-column shape with NULLs for the non-applicable Lesion/Scan/RSP block, then wrapped in an outer SELECT applying display aliases and the requested sort. Per Note 4, since I have no metadata confirming OSCN's "Scheduled Time" item exists, I include Scenario 2/3 branches but flag that they should be dropped (leaving only Scenario 1) if OSCN has no such item in the actual study. Form/Item names are inferred/assumed since no study-metadata block was provided: LOELFM (Lesion), RSPFM (Response), ORAJFM (Oncologic Assessment), OSCNFM (Oncologic Scan) with plausible CDISC-style item suffixes (e.g. LOELLSSCHEDTMIT, LOELLSDTCLEVIT, LOELTUDTCIT, RSPDTRESPIT, RSPSCHEDTMIT, ORAJDTASSESSIT, ORAJSCHEDTMIT, OSCNSCANDATIT, OSCNSCHEDTMIT) plus a DELETEDFM flag on each Form for the deleted-records exclusion — these should be confirmed via DESCRIBE FORM before running. Note that the spec's "Yes/No" Scenario display logic (satisfied vs not) is handled implicitly by only returning rows where the mismatch condition is true (i.e., only "Yes" discrepancy rows are output), consistent with the report's stated purpose of listing discrepancies.