

API Documentation

Base URL (Liberty): `http://localhost:9080`

Auth header: `Authorization: Bearer <jwt>`

Unless noted, all endpoints require authentication.

Authentication — `/auth`

Method	Path	Roles	Body / params	Response
POST	<code>/auth/login</code>	Public	<code>{ username, password }</code>	<code>{ token, ... }</code> (<code>LoginResponse</code>)
GET	<code>/auth/me</code>	Authenticated	—	<code>UserProfileResponse</code>
PUT	<code>/auth/password</code>	Authenticated	<code>ChangePasswordRequest</code>	204

Dashboard — `/dashboard`

Method	Path	Roles	Response
GET	<code>/dashboard</code>	Authenticated	Dashboard summary DTO

Customers — `/customers`

Method	Path	Roles	Notes
GET	<code>/customers? search&page&size&sortBy&sortDir</code>	ADMIN, EMPLOYEE, MANAGER	Page of <code>Customer</code>
GET	<code>/customers/{id}</code>	ADMIN, EMPLOYEE, MANAGER	
POST	<code>/customers</code>	ADMIN, EMPLOYEE	<code>CreateCustomerRequest</code> (optional account fields)
PUT	<code>/customers/{id}</code>	ADMIN, EMPLOYEE	<code>@Valid</code> <code>UpdateCustomerRequest</code>
DELETE	<code>/customers/{id}</code>	ADMIN	

CreateCustomerRequest (key fields)

`firstName`, `lastName`, `email`, `phoneNumber`, `dateOfBirth`, `address`, `status`, optional `branchCode`,
`accountType`, `currencyCode`, `openingDeposit`

Accounts — /accounts

Method	Path	Roles	Notes
POST	/accounts	ADMIN, EMPLOYEE	OpenAccountRequest
GET	/accounts?search&page&size&sortBy&sortDir	ADMIN, EMPLOYEE, MANAGER	Search page
GET	/accounts/customer/{customerId}?page&size&sortBy&sortDir	ADMIN, EMPLOYEE, MANAGER	
GET	/accounts/{accountId}	ADMIN, EMPLOYEE, MANAGER	Single AccountResponse
GET	/accounts/{accountId}/transactions?page&size&sortBy&sortDir	ADMIN, EMPLOYEE, MANAGER	page of TransactionResponse
PUT	/accounts/{accountId}/status	ADMIN, EMPLOYEE	UpdateAccountStatusRequest
POST	/accounts/{accountId}/deposit	ADMIN, EMPLOYEE	DepositRequest { amount }

OpenAccountRequest

customerId, branchCode, accountType, currencyCode, openingDeposit, createdBy

AccountResponse

Includes accountId, accountNumber, balances, status, customerId, timestamps, etc.

TransactionResponse (list under account)

transactionId, accountId, transactionType, amount, balanceAfter, currencyCode, narration, createdAt, createdBy.

Sort whitelist for transactions: createdAt, amount, transactionId, transactionType (default createdAt desc). 404-style business error if account id does not exist.

Account policies — `/account-policies`

Method	Path	Roles	Notes
POST	<code>/account-policies</code>	Authenticated only*	CreateAccountPolicyRequest
GET	<code>/account-policies?accountType=&currencyCode=</code>	Authenticated only*	Active policy; default currency INR

*Deferred hardening: restrict create (and possibly GET) to ADMIN.

AccountPolicyResponse

`policyId`, `accountType`, `currencyCode`, `openingDepositRequired`, `requiredOpeningDeposit`, `minimumBalance`, `active`, `effectiveFrom`, `effectiveTo`

Users (employees) — `/users`

Method	Path	Roles	Notes
GET	<code>/users</code>	ADMIN	
POST	<code>/users</code>	ADMIN	
PUT	<code>/users/{id}</code>	ADMIN	

Misc

Method	Path	Roles
GET	<code>/api/hello</code>	Authenticated

Error shape

Handled by `GlobalExceptionHandler` under `com.bankone.common` (business exceptions → 4xx with message body). Exact payload may vary by exception type.

Frontend API clients

Service	File
Auth	<code>BankOne-Frontend/src/app/core/services/auth.ts</code>
Customer	<code>.../customer.ts</code>
Account	<code>.../account.ts</code>
Account policy	<code>.../account-policy.ts</code>
User	<code>.../user.ts</code>
Dashboard	<code>.../dashboard.service.ts</code>