

API Documentation

Base URL (Liberty): `http://localhost:9080`

Auth header: `Authorization: Bearer <jwt>`

Unless noted, all endpoints require authentication.

Side effect (implemented): successful open account / deposit / withdraw / transfer publishes a Kafka `BankActionEvent` and emails the **customer** (`customers.email`). Not a separate REST resource — see `MODULES/Notification.md` .

Authentication — `/auth`

Method	Path	Roles	Body / params	Response
POST	<code>/auth/login</code>	Public	<code>{ username, password }</code>	<code>{ token, ... }</code> (<code>LoginResponse</code>)
POST	<code>/auth/logout</code>	Authenticated	—	204 (writes AUTH LOGOUT audit)
GET	<code>/auth/me</code>	Authenticated	—	<code>UserProfileResponse</code>
PUT	<code>/auth/password</code>	Authenticated	<code>ChangePasswordRequest</code>	204

Dashboard — `/dashboard`

Method	Path	Auth	Response
GET	<code>/dashboard</code>	Authenticated	Dashboard summary DTO

Caching (local): response may be served from Redis (`dashboard / summary` , ~60s TTL) when `app.cache.redis-enabled=true` . See [MODULES/Caching.md](#) . Other major GET list / by-id APIs (customers, accounts, roles, ...) use the same cache-aside pattern with per-region TTLs and write-time eviction.

Customers — /customers

Method	Path	Roles	Notes
GET	/customers? search&page&size&sortBy&sortDir	ADMIN, EMPLOYEE, MANAGER	Page of Customer
GET	/customers/{id}	ADMIN, EMPLOYEE, MANAGER	
POST	/customers	ADMIN, EMPLOYEE	CreateCustomerRequest (optional account fields)
PUT	/customers/{id}	ADMIN, EMPLOYEE	@Valid UpdateCustomerRequest
DELETE	/customers/{id}	ADMIN	

CreateCustomerRequest (key fields)

firstName, lastName, email, phoneNumber, dateOfBirth, address, status, optional branchCode, accountType, currencyCode, openingDeposit

Accounts — /accounts

Method	Path	Roles	Notes
POST	/accounts	ADMIN, EMPLOYEE	OpenAccountRequest
GET	/accounts?search&page&size&sortBy&sortDir	ADMIN, EMPLOYEE, MANAGER	Search page
GET	/accounts/customer/{customerId}?page&size&sortBy&sortDir	ADMIN, EMPLOYEE, MANAGER	
GET	/accounts/{accountId}	ADMIN, EMPLOYEE, MANAGER	Single AccountResponse
GET	/accounts/{accountId}/transactions?page&size&sortBy&sortDir	ADMIN, EMPLOYEE, MANAGER	page of TransactionResponse
PUT	/accounts/{accountId}/status	ADMIN, EMPLOYEE	UpdateAccountStatusRequest
POST	/accounts/{accountId}/deposit	ADMIN, EMPLOYEE	DepositRequest { amount }
POST	/accounts/{accountId}/withdraw	ADMIN, EMPLOYEE	WithdrawRequest { amount }
POST	/accounts/{accountId}/transfer	ADMIN, EMPLOYEE	TransferRequest { toAccountId, amount }

OpenAccountRequest

customerId, branchCode, accountType, currencyCode, openingDeposit, createdBy

AccountResponse

Includes accountId, accountNumber, balances, status, customerId, timestamps, etc.

TransactionResponse (list under account)

transactionId, accountId, transactionType, amount, balanceAfter, currencyCode, narration, createdAt, createdBy.

Sort whitelist for transactions: `createdAt` , `amount` , `transactionId` , `transactionType` (default `createdAt` desc). 404-style business error if account id does not exist.

Account policies — `/account-policies`

Method	Path	Access	Notes
GET	<code>/account-policies?</code> <code>accountType=&currencyCode=</code>	POLICIES_MANAGE or ACCOUNTS_READ/WRITE	Active policy; default currency <code>INR</code>
GET	<code>/account-policies/all</code>	same	All policies (mgmt UI)
PUT	<code>/account-policies/{id}</code>	POLICIES_MANAGE	Update policy
POST	<code>/account-policies</code>	POLICIES_MANAGE	Create (if exposed)

AccountPolicyResponse

`policyId` , `accountType` , `currencyCode` , `openingDepositRequired` , `requiredOpeningDeposit` , `minimumBalance` , `active` , `effectiveFrom` , `effectiveTo`

Users (employees) — `/users`

Requires `ACCESS_USERS_MANAGE` (typically ADMIN).

Method	Path	Notes
GET	<code>/users</code>	Paged employees + search
POST	<code>/users</code>	Staff or portal user (<code>userType</code> , <code>roleNames[]</code>)
PUT	<code>/users/{id}</code>	Update profile / roles / enabled

Roles — `/roles`

`ACCESS_ROLES_MANAGE` or `ACCESS_USERS_MANAGE` .

Method	Path	Notes
GET	<code>/roles</code>	List roles + access codes
GET	<code>/roles/{id}</code>	Detail
POST	<code>/roles</code>	Create
PUT	<code>/roles/{id}</code>	Update description / accesses

Transactions (staff) — `/transactions`

`ACCESS_ACCOUNTS_READ` . Paged search across ledger.

GET `/transactions?accountId&txType&search&page&size&sortBy&sortDir`

Portal — /portal

`ACCESS_PORTAL_ACCOUNTS` . See [MODULES/Portal.md](#).

Transfer approvals — /transfer-approvals

`ACCESS_ACCOUNTS_WRITE` . Pending / my-history / approve / reject. See Portal module doc.

Audit — /audit

ADMIN | MANAGER | AUDITOR. See [MODULES/Audit.md](#).

GET `/audit/events?category&action&actor&page&size`

GET `/audit/transfer-approvals`

POST `/audit/backfill` (ADMIN)

Reports — /reports

See [MODULES/Reports.md](#).

GET `/reports/transaction-trends` (+ `/pdf`)

GET `/reports/account-mix` (+ `/pdf`)

GET `/reports/approvals` (+ `/pdf`) — Admin/Manager/Auditor

Misc

Method	Path	Roles
GET	<code>/api/hello</code>	Authenticated

Error shape

Handled by `GlobalExceptionHandler` under `com.bankone.common` (business exceptions → 4xx with message body). Exact payload may vary by exception type. Rate-limit learning work will add HTTP 429 later ([TECH_LEARNING_PLAN.md](#)).

Frontend API clients

Service	File
Auth	BankOne-Frontend/src/app/core/services/auth.ts
Customer	.../customer.ts
Account	.../account.ts
Account policy	.../account-policy.ts
User	.../user.ts
Dashboard	.../dashboard.service.ts
Portal / approvals / audit	.../portal.ts
Reports	features/reports (+ HTTP in component/service)