

API Documentation

Base URL (Liberty): `http://localhost:9080`

Auth header: `Authorization: Bearer <jwt>`

Unless noted, all endpoints require authentication.

Side effect (implemented): successful open account / deposit / withdraw / transfer publishes a Kafka `BankActionEvent` and emails the **customer** (`customers.email`). Not a separate REST resource — see `MODULES/Notification.md` .

Authentication — `/auth`

Method	Path	Roles	Body / params	Response
POST	<code>/auth/login</code>	Public	<code>{ username, password }</code>	<code>{ token, ... }</code> (<code>LoginResponse</code>)
GET	<code>/auth/me</code>	Authenticated	—	<code>UserProfileResponse</code>
PUT	<code>/auth/password</code>	Authenticated	<code>ChangePasswordRequest</code>	204

Dashboard — `/dashboard`

Method	Path	Roles	Response
GET	<code>/dashboard</code>	Authenticated	Dashboard summary DTO

Customers — `/customers`

Method	Path	Roles	Notes
GET	<code>/customers?</code> <code>search&page&size&sortBy&sortDir</code>	ADMIN, EMPLOYEE, MANAGER	Page of <code>Customer</code>
GET	<code>/customers/{id}</code>	ADMIN, EMPLOYEE, MANAGER	
POST	<code>/customers</code>	ADMIN, EMPLOYEE	<code>CreateCustomerRequest</code> (optional account fields)
PUT	<code>/customers/{id}</code>	ADMIN, EMPLOYEE	<code>@Valid</code> <code>UpdateCustomerRequest</code>
DELETE	<code>/customers/{id}</code>	ADMIN	

CreateCustomerRequest (key fields)

firstName, lastName, email, phoneNumber, dateOfBirth, address, status, optional branchCode, accountType, currencyCode, openingDeposit

Accounts — /accounts

Method	Path	Roles	Notes
POST	/accounts	ADMIN, EMPLOYEE	OpenAccountRequest
GET	/accounts?search&page&size&sortBy&sortDir	ADMIN, EMPLOYEE, MANAGER	Search page
GET	/accounts/customer/{customerId}?page&size&sortBy&sortDir	ADMIN, EMPLOYEE, MANAGER	
GET	/accounts/{accountId}	ADMIN, EMPLOYEE, MANAGER	Single AccountResponse
GET	/accounts/{accountId}/transactions?page&size&sortBy&sortDir	ADMIN, P EMPLOYEE, MANAGER	age of TransactionResponse
PUT	/accounts/{accountId}/status	ADMIN, EMPLOYEE	UpdateAccountStatusRequest
POST	/accounts/{accountId}/deposit	ADMIN, EMPLOYEE	DepositRequest { amount }
POST	/accounts/{accountId}/withdraw	ADMIN, EMPLOYEE	WithdrawRequest { amount }
POST	/accounts/{accountId}/transfer	ADMIN, EMPLOYEE	TransferRequest { toAccountId, amount }

OpenAccountRequest

customerId, branchCode, accountType, currencyCode, openingDeposit, createdBy

AccountResponse

Includes accountId, accountNumber, balances, status, customerId, timestamps, etc.

TransactionResponse (list under account)

transactionId, accountId, transactionType, amount, balanceAfter, currencyCode, narration, createdAt, createdBy.

Sort whitelist for transactions: createdAt, amount, transactionId, transactionType (default createdAt desc). 404-style business error if account id does not exist.

Account policies — /account-policies

Method	Path	Roles	Notes
POST	/account-policies	Authenticated only*	CreateAccountPolicyRequest
GET	/account-policies?accountType=¤cyCode=	Authenticated only*	Active policy; default currency INR

*Deferred hardening: restrict create (and possibly GET) to ADMIN.

AccountPolicyResponse

policyId, accountType, currencyCode, openingDepositRequired, requiredOpeningDeposit, minimumBalance, active, effectiveFrom, effectiveTo

Users (employees) — /users

Method	Path	Roles	Notes
GET	/users	ADMIN	
POST	/users	ADMIN	
PUT	/users/{id}	ADMIN	

Misc

Method	Path	Roles
GET	/api/hello	Authenticated

Error shape

Handled by GlobalExceptionHandler under com.bankone.common (business exceptions → 4xx with message body). Exact payload may vary by exception type.

Frontend API clients

Service	File
Auth	BankOne-Frontend/src/app/core/services/auth.ts
Customer	.../customer.ts
Account	.../account.ts
Account policy	.../account-policy.ts
User	.../user.ts
Dashboard	.../dashboard.service.ts