

comm and sort Commands in Linux/Unix

Both comm and sort are powerful tools for working with text data in Linux and Unix-like systems. Here's a breakdown of their usage and common flags:

sort

- **Purpose:** Sorts lines in text files based on specified criteria.
- **Flags:**
 - -n (numeric sort): Sorts data according to numerical values (ascending order).
 - -r (reverse): Sorts in descending order.
 - -k POS,LEN (sort by key): Sorts by a specific field/column.
 - POS: Starting position (1-based) of the field within a line.
 - LEN (optional): The length of the field (defaults to entire line).
 - -t DELIM (field separator): Defines the character separating fields (default is whitespace).
 - -u (unique): Removes duplicate lines.
 - -o OUTPUT_FILE (output file): Saves sorted data to a specified file.

Example:

Bash

```
sort -n numbers.txt # Sort numbers.txt numerically (ascending)
sort -r names.txt   # Sort names.txt in reverse alphabetical order
```

comm

- **Purpose:** Compares two sorted text files and identifies lines that are **present in only one file, present in both files, or not present in either file.**
- **Flags:**
 - -1 (suppress first column): Hides lines only in the first file.
 - -2 (suppress second column): Hides lines only in the second file.
 - -3 (suppress third column): Hides lines common to both files.

Workflow:

1. **Sort both files:** Since comm requires sorted inputs, use sort beforehand.
2. **Use comm:** Compare the sorted files to identify differences.

Example:

1. Sort files file1.txt and file2.txt:

Bash

```
sort file1.txt > sorted_file1.txt
sort file2.txt > sorted_file2.txt
```

2. Use comm to compare the sorted files:

Bash

```
comm sorted_file1.txt sorted_file2.txt
```

This will display lines:

- In the first column (unless suppressed by -1): Lines only in file1.txt.
- In the second column (unless suppressed by -2): Lines only in file2.txt.
- In the third column (unless suppressed by -3): Lines common to both files.

Remember:

- comm works best with pre-sorted files, so use sort before comm.
- Flags like -1, -2, and -3 allow you to focus on specific differences between the files.

By effectively combining sort and comm, you can analyze and compare text data efficiently.