3 Derivability in SOGATs

Second-order GATs (SOGATs) allow second-order operations. Second-order operations are also called binders. In this section, we define several languages with binders as SOGATs, and show how to define derivable operations and prove derivable equations in second-order models. The phrase "second-order" is a negative qualifier: second-order algebraic theories are not really algebraic (this is like people's democracy, which is not really democracy). For example, there is no good notion of morphism between second-order models. However, for derivability, second-order models are good enough. We will treat this problem in Section 4.

3.1 Simply typed lambda calculus

Definition 54 (Simply typed lambda calculus, STLC)**.** *A second-order model of STLC comprises the following components:*

$$\begin{aligned}
&\mathsf{Ty} && : \mathsf{Set}\\
&\mathsf{Tm} && : \mathsf{Ty} \to \mathsf{Set}\\
&\iota && : \mathsf{Ty}\\
&- \Rightarrow - && : \mathsf{Ty} \to \mathsf{Ty} \to \mathsf{Ty}\\
&\mathsf{lam} && : (\mathsf{Tm}\, A \to \mathsf{Tm}\, B) \to \mathsf{Tm}\,(A \Rightarrow B)\\
&- \cdot - && : \mathsf{Tm}\,(A \Rightarrow B) \to \mathsf{Tm}\, A \to \mathsf{Tm}\, B\\
&\beta && : \mathsf{lam}\, b \cdot a = b\, a\\
&\eta && : f = \mathsf{lam}\, \lambda x.\, f \cdot x
\end{aligned}$$

The operators lam and $- \cdot -$ take *implicit arguments*, A and B. E.g. the explicit type of lam is $\{A : \mathsf{Ty}\}\{B : \mathsf{Ty}\} \to (\mathsf{Tm}\, A \to \mathsf{Tm}\, B) \to \mathsf{Tm}\,(A \Rightarrow B)$. All the arguments of the equations β and η are implicit. E.g. the explicit type of β is $\{A : \mathsf{Ty}\}\{B : \mathsf{Ty}\}\{b : \mathsf{Tm}\, A \to \mathsf{Tm}\, B\}\{a : \mathsf{Tm}\, A\} \to (- \cdot -)\,\{A\}\{B\}\,(\mathsf{lam}\,\{A\}\,\{B\}\, b)\, a = b\, a$. Note that in the equation η, f has to be in $\mathsf{Tm}\,(A \Rightarrow B)$ for some A and B for the equation to make sense.

The operation lam is second-order (also called a *binder*): its third input (after the two implicit inputs A, B) is a function.

Notation 55 (Isomorphism)**.** *The last four lines can be written more consisely:*

$$\mathsf{lam} : (\mathsf{Tm}\, A \to \mathsf{Tm}\, B) \cong \mathsf{Tm}\,(A \Rightarrow B) : - \cdot -$$

We say that the sets $(\mathsf{Tm}\, A \to \mathsf{Tm}\, B)$ *and* $\mathsf{Tm}\,(A \Rightarrow B)$ *are isomorphic. We write the maps on the two sides of* $\cong$*, the notation in general is*

$$(f : X \cong Y : g) \;:=\; (f : X \to Y) \times (g : Y \to X) \times \big((x : X) \to g\,(f\, x) = x\big) \times \big((y : Y) \to f\,(g\, y) = y\big).$$

Derivability is programming: we can program in a SOGAT by postulating a second-order model in Agda or Coq and combining the components to build new programs. We can run the programs by proving (deriving) equalities between them.

Example 56. *In any second-order model of STLC, we define the identity function on* ι *by* $\mathsf{lam}\,\{\iota\}\{\iota\}\,(\lambda x.\, x)$*, which is in* $\mathsf{Tm}\,(\iota \Rightarrow \iota)$*. Note the difference between the object theory* lam *and meta* λ*. Actually, we can define the identity function on any type using meta quantification:*

$$\lambda A.\, \mathsf{lam}\,\{A\}\{A\}\,(\lambda x.\, x) : (A : \mathsf{Ty}) \to \mathsf{Tm}\,(A \Rightarrow A).$$

We compute (run the programs) in a second-order model deriving equalities. E.g. given $u : \mathsf{Tm}\,\iota$ *we argue*

$$(\mathsf{lam}\,(\lambda x.\, x)) \cdot u \overset{\beta}{=} (\lambda x.\, x)\, u \overset{\text{meta function application}}{=} u.$$

This seems like cheating: we avoided writing substitution by pushing it into the metatheory. But this is OK, we do not want to fully bootstrap STLC, we just want to define it. In the metatheory we of course assume (higher-order) functions, function application, its β *rule, and so on.*

Notation 57 (Derivation rules for SOGATs)**.** *Similarly to GATs, the derivation rule notation uses uncurried function space, named parameters and horizontal lines instead of the arrow* $\to$ *symbol. For arrows in second-order positions, we use the turnstile* $\vdash$*, and we use named function application for the* $\vdash$ *function space. Second-order models of STLC are described by the following derivation rules:*

$$\frac{}{\mathsf{Ty} : \mathsf{Set}} \qquad \frac{A : \mathsf{Ty}}{\mathsf{Tm}\, A : \mathsf{Set}} \qquad \frac{}{\iota : \mathsf{Ty}} \qquad \frac{A : \mathsf{Ty} \qquad B : \mathsf{Ty}}{A \Rightarrow B : \mathsf{Ty}} \qquad \frac{x : \mathsf{Tm}\, A \vdash t : \mathsf{Tm}\, B}{\mathsf{lam}\, x.t : \mathsf{Tm}\,(A \Rightarrow B)}$$

$$\frac{t : \mathsf{Tm}\,(A \Rightarrow B) \qquad a : \mathsf{Tm}\,A}{t \cdot a : \mathsf{Tm}\,B} \qquad \frac{}{(\mathsf{lam}\,x.b) \cdot a = b[x \mapsto a]}\,\beta \qquad \frac{}{f = \mathsf{lam}\,x.f \cdot x}\,\eta$$

Some arguments of the horizontal line function space can be implicit. Sometimes the name of the rule is written on the right hand side of the horizontal line.

We can omit the $: \mathsf{Ty}$ *and* Tm *parts and more concisely write the following without sacrificing precision (this is always the case when there are two sorts* $\mathsf{Ty} : \mathsf{Set}$, $\mathsf{Tm} : \mathsf{Ty} \to \mathsf{Set}$*).*

$$\bar{\iota} \qquad \frac{A \qquad B}{A \Rightarrow B} \qquad \frac{x : A \vdash t : B}{\mathsf{lam}\,x.t : A \Rightarrow B} \qquad \frac{t : A \Rightarrow B \qquad a : A}{t \cdot a : B} \qquad \frac{}{(\mathsf{lam}\,x.b) \cdot a = b[x \mapsto a]} \qquad \frac{}{f = \mathsf{lam}\,x.f \cdot x}$$

Example 58 (Second-order operations in mathematics)**.** *For the integral operation, the derivation rule notation is on the left and the second-order algebraic notation is on the right:*

$$\frac{a : \mathbb{R} \qquad b : \mathbb{R} \qquad x : \mathbb{R} \vdash t : \mathbb{R}}{\int_a^b t\,dx} \qquad\qquad \int : \mathbb{R} \to \mathbb{R} \to (\mathbb{R} \to \mathbb{R}) \to \mathbb{R},$$


the expression $\int_0^1 \frac{1}{x^2}\,dx$ *corresponds to* $\int 0\,1\,(\lambda x.\,\frac{1}{x^2})$*.*

Notation 59 (Derivation trees for SOGATs)**.** *When we write derivation trees, the second-order arguments are collected on the left hand side of the* $\vdash$*. For example, given* $A : \mathsf{Ty}$ *and* $B : \mathsf{Ty}$*, we derive the constant function as follows: the verbose notation is on the left, the concise is on the right. In the concise notation we also omit the* λ*s.*

$$\frac{\dfrac{\dfrac{}{x : \mathsf{Tm}\,A, y : \mathsf{Tm}\,B \vdash x : \mathsf{Tm}\,A}}{x : \mathsf{Tm}\,A \vdash \mathsf{lam}\,\lambda y.x : \mathsf{Tm}\,(B \Rightarrow A)}}{\mathsf{lam}\,\lambda x.\,\mathsf{lam}\,\lambda y.\,x : \mathsf{Tm}\,(A \Rightarrow B \Rightarrow A)} \qquad\qquad \frac{\dfrac{\dfrac{}{x : A, y : B \vdash x : A}}{x : A \vdash \mathsf{lam}\,y.x : B \Rightarrow A}}{\mathsf{lam}\,x.\,\mathsf{lam}\,y.\,x : A \Rightarrow B \Rightarrow A}$$

Now the leaves of the tree can be assumptions from the left hand side of the turnstile in addition to derivation rules without arguments. The algebraic (or Coq/Agda) version of this is simply the conclusion $\mathsf{lam}\,\lambda x.\,\mathsf{lam}\,\lambda y.\,x$*, or* $\mathsf{lam}\,(\lambda x.\,\mathsf{lam}\,(\lambda y.\,x))$ *with more brackets.*


Notation 60 (Abstract binding trees (ABTs))**.** *Another notation for SOGAT-derivation trees is abstract* binding *trees where variables are pointers to the binders which are reachable through the path to the root. The constant function is drawn as follows.*



Abstract binding tree notation has the same issue as abstract syntax trees: the restriction that trees can only be put together in well-typed ways is not apparent.

Example 61. *We define the "double" function using short derivation rule and abstract binding tree notation.*

$$\frac{\dfrac{\dfrac{\dfrac{}{f : A \Rightarrow A, x : A \vdash f : A \Rightarrow A} \qquad \dfrac{\dfrac{}{f : A \Rightarrow A, x : A \vdash f : A \Rightarrow A} \qquad \dfrac{}{f : A \Rightarrow A, x : A \vdash x : A}}{f : A \Rightarrow A, x : A \vdash f \cdot x : A}}{f : A \Rightarrow A, x : A \vdash f \cdot (f \cdot x) : A}}{f : A \Rightarrow A \vdash \mathsf{lam}\,x.f \cdot (f \cdot x) : A \Rightarrow A}}{\mathsf{lam}\,f.\mathsf{lam}\,x.f \cdot (f \cdot x) : (A \Rightarrow A) \Rightarrow A \Rightarrow A}$$



Example 62. *Function composition:*

$$\frac{\dfrac{\dfrac{\dfrac{}{f : B \Rightarrow A, g : C \Rightarrow B, x : C \vdash f : B \Rightarrow A} \qquad \dfrac{\dfrac{}{f : B \Rightarrow A, g : C \Rightarrow B, x : C \vdash g : C \Rightarrow B} \qquad \dfrac{}{\ldots, x : C \vdash x : C}}{f : B \Rightarrow A, g : C \Rightarrow B, x : C \vdash g \cdot x : B}}{f : B \Rightarrow A, g : C \Rightarrow B, x : C \vdash f \cdot (g \cdot x) : A}}{f : B \Rightarrow A, g : C \Rightarrow B \vdash \mathsf{lam}\,x.f \cdot (g \cdot x) : C \Rightarrow A}}{f : B \Rightarrow A \vdash \mathsf{lam}\,g.\mathsf{lam}\,x.f \cdot (g \cdot x) : (C \Rightarrow B) \Rightarrow C \Rightarrow A}}{\mathsf{lam}\,f.\mathsf{lam}\,g.\mathsf{lam}\,x.f \cdot (g \cdot x) : (B \Rightarrow A) \Rightarrow (C \Rightarrow B) \Rightarrow C \Rightarrow A}$$

Example 63. *We define a model of STCC (Definition 32) assuming a second-order model of STLC.*

$$\begin{aligned}
\mathsf{Ty} &:= \mathsf{Ty}\\
\mathsf{Tm}\,A &:= \mathsf{Tm}\,A\\
\iota &:= \iota\\
A \Rightarrow B &:= A \Rightarrow B\\
\mathsf{K} &:= \mathsf{lam}\left(\lambda u.\,\mathsf{lam}\left(\lambda f.\,u\right)\right)\\
\mathsf{S} &:= \mathsf{lam}\left(\lambda f.\,\mathsf{lam}\left(\lambda g.\,\mathsf{lam}\left(\lambda u.\,f\cdot u\cdot(g\cdot u)\right)\right)\right)
\end{aligned}$$

The equations hold, e.g.:

$$\begin{aligned}
\mathsf{K}\beta : \mathsf{K}\cdot u\cdot f &&=&(\textit{definition of } \mathsf{K})\\
\left(\left(\mathsf{lam}\left(\lambda u.\,\mathsf{lam}\left(\lambda f.\,u\right)\right)\right)\cdot u\right)\cdot f &&=&(\beta)\\
\left(\left(\lambda u.\,\mathsf{lam}\left(\lambda f.\,u\right)\right)u\right)\cdot f &&=&(\textit{meta function application})\\
\left(\mathsf{lam}\left(\lambda f.\,u\right)\right)\cdot f &&=&(\beta)\\
(\lambda f.\,u)\,f &&=&(\textit{meta function application})\\
u
\end{aligned}$$

Exercise 64. *Prove that* $\mathsf{S}\beta$ *holds.*

Food for thought 65. *Can we derive a second-order model of STLC from a model of STCC? What if we start with a second-order model having some extra equations [AKSV23]?*

Example 66. *We can use derivation tree building to do informal type inference. For example, we don't know whether the expression*

$$\mathsf{lam}\,\lambda x.\mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z$$

has a type (makes sense in a second-order model of STLC), so we try to build its derivation tree from the bottom. Let's say it has an arbitrary type A*.*

$$\frac{?}{\mathsf{lam}\,\lambda x.\mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z : A}$$

As the expression starts with lam*, we use its derivation rule and we learn that* $A = B \Rightarrow C$ *for some* B *and* C*:*

$$\frac{\dfrac{?}{x : B \vdash \mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z : C}}{\mathsf{lam}\,\lambda x.\mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z : B \Rightarrow C}$$

We use lam *again and we learn* $C = D \Rightarrow E$*, so we replace all occurrences of* C *with* $D \Rightarrow E$*:*

$$\frac{\dfrac{\dfrac{?}{x : B, y : D \vdash \mathsf{lam}\,\lambda z.y\cdot x\cdot z : E}}{x : B \vdash \mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z : D \Rightarrow E}}{\mathsf{lam}\,\lambda x.\mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z : B \Rightarrow (D \Rightarrow E)}$$

We use lam *again and we learn* $E = F \Rightarrow G$*:*

$$\frac{\dfrac{\dfrac{\dfrac{?}{x : B, y : D, z : F \vdash y\cdot x\cdot z : G}}{x : B, y : D \vdash \mathsf{lam}\,\lambda z.y\cdot x\cdot z : F \Rightarrow G}}{x : B \vdash \mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z : D \Rightarrow (F \Rightarrow G)}}{\mathsf{lam}\,\lambda x.\mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z : B \Rightarrow (D \Rightarrow (F \Rightarrow G))}$$

Now we can only use the derivation rule of application $(\cdot)$*, and we introduce a new metavariable* H *because we cannot read off the domain of the function from its conclusion. Recall that* $y\cdot x\cdot z = (y\cdot x)\cdot z$*.*

$$\frac{\dfrac{\dfrac{\dfrac{\dfrac{?}{x : B, y : D, z : F \vdash y\cdot x : H \Rightarrow G} \qquad \dfrac{?}{x : B, y : D, z : F \vdash z : H}}{x : B, y : D, z : F \vdash y\cdot x\cdot z : G}}{x : B, y : D \vdash \mathsf{lam}\,\lambda z.y\cdot x\cdot z : F \Rightarrow G}}{x : B \vdash \mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z : D \Rightarrow (F \Rightarrow G)}}{\mathsf{lam}\,\lambda x.\mathsf{lam}\,\lambda y.\mathsf{lam}\,\lambda z.y\cdot x\cdot z : B \Rightarrow (D \Rightarrow (F \Rightarrow G))}$$

We first reach a leaf on the right hand side: z is to the left of the turnstile, so we learn $H = F$:

$$\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{?}{x : B, y : D, z : F \vdash y \cdot x : F \Rightarrow G} \quad \overline{x : B, y : D, z : F \vdash z : F}}{x : B, y : D, z : F \vdash y \cdot x \cdot z : G}}{x : B, y : D \vdash \mathsf{lam}\, \lambda z.y \cdot x \cdot z : F \Rightarrow G}}{x : B \vdash \mathsf{lam}\, \lambda y.\mathsf{lam}\, \lambda z.y \cdot x \cdot z : D \Rightarrow (F \Rightarrow G)}}{\mathsf{lam}\, \lambda x.\mathsf{lam}\, \lambda y.\mathsf{lam}\, \lambda z.y \cdot x \cdot z : B \Rightarrow (D \Rightarrow (F \Rightarrow G))}$$

On the left hand side, there is an application $\cdot$, we introduce a new metavariable I:

$$\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{?}{x : B, y : D, z : F \vdash y : I \Rightarrow F \Rightarrow G} \quad \dfrac{?}{x : B, y : D, z : F \vdash x : I}}{x : B, y : D, z : F \vdash y \cdot x : F \Rightarrow G} \quad \overline{x : B, y : D, z : F \vdash z : F}}{x : B, y : D, z : F \vdash y \cdot x \cdot z : G}}{x : B, y : D \vdash \mathsf{lam}\, \lambda z.y \cdot x \cdot z : F \Rightarrow G}}{x : B \vdash \mathsf{lam}\, \lambda y.\mathsf{lam}\, \lambda z.y \cdot x \cdot z : D \Rightarrow (F \Rightarrow G)}}{\mathsf{lam}\, \lambda x.\mathsf{lam}\, \lambda y.\mathsf{lam}\, \lambda z.y \cdot x \cdot z : B \Rightarrow (D \Rightarrow (F \Rightarrow G))}$$

The solution to the right hand side ? forces $I = B$, because this is the type of x:

$$\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{?}{x : B, y : D, z : F \vdash y : B \Rightarrow F \Rightarrow G} \quad \overline{x : B, y : D, z : F \vdash x : B}}{x : B, y : D, z : F \vdash y \cdot x : F \Rightarrow G} \quad \overline{x : B, y : D, z : F \vdash z : F}}{x : B, y : D, z : F \vdash y \cdot x \cdot z : G}}{x : B, y : D \vdash \mathsf{lam}\, \lambda z.y \cdot x \cdot z : F \Rightarrow G}}{x : B \vdash \mathsf{lam}\, \lambda y.\mathsf{lam}\, \lambda z.y \cdot x \cdot z : D \Rightarrow (F \Rightarrow G)}}{\mathsf{lam}\, \lambda x.\mathsf{lam}\, \lambda y.\mathsf{lam}\, \lambda z.y \cdot x \cdot z : B \Rightarrow (D \Rightarrow (F \Rightarrow G))}$$

On the left hand side we learn $D = B \Rightarrow F \Rightarrow G$:

$$\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{\overline{x : B, y : B \Rightarrow F \Rightarrow G, z : F \vdash y : B \Rightarrow F \Rightarrow G} \quad \overline{x : B, y : B \Rightarrow F \Rightarrow G, z : F \vdash x : B}}{x : B, y : B \Rightarrow F \Rightarrow G, z : F \vdash y \cdot x : F \Rightarrow G} \quad \overline{\ldots, z : F \vdash z : F}}{x : B, y : B \Rightarrow F \Rightarrow G, z : F \vdash y \cdot x \cdot z : G}}{x : B, y : B \Rightarrow F \Rightarrow G \vdash \mathsf{lam}\, \lambda z.y \cdot x \cdot z : F \Rightarrow G}}{x : B \vdash \mathsf{lam}\, \lambda y.\mathsf{lam}\, \lambda z.y \cdot x \cdot z : (B \Rightarrow F \Rightarrow G) \Rightarrow (F \Rightarrow G)}}{\mathsf{lam}\, \lambda x.\mathsf{lam}\, \lambda y.\mathsf{lam}\, \lambda z.y \cdot x \cdot z : B \Rightarrow ((B \Rightarrow F \Rightarrow G) \Rightarrow (F \Rightarrow G))}$$

So the most general type of the expression is $B \Rightarrow ((B \Rightarrow F \Rightarrow G) \Rightarrow (F \Rightarrow G))$ for some types B, F, G.

Exercise 67. *Using the above method, try to infer the type of the following epxressions (we assume Razor extended with functions merging Definitions 14 and 54):*

$$\mathsf{lam}\, \lambda x.\, x \cdot x$$
$$\mathsf{lam}\, \lambda f.\, f \cdot (\mathsf{num}\, 1 + f \cdot \mathsf{true})$$
$$\mathsf{lam}\, \lambda f.\, f \cdot (\mathsf{num}\, 1 + f \cdot \mathsf{num}\, 2)$$

Exercise 68. *Show that function composition (Example 62) is associative. That is, abbreviating* $\mathsf{comp} := \mathsf{lam}\, f.\mathsf{lam}\, g.\mathsf{lam}\, x.f \cdot (g \cdot x)$*, for every u, v, w we have* $\mathsf{comp} \cdot (\mathsf{comp} \cdot u \cdot v) \cdot w = \mathsf{comp} \cdot u \cdot (\mathsf{comp} \cdot v \cdot w)$.

Exercise 69. *Show that for any $A : \mathsf{Ty}$, $\mathsf{Tm}\,(A \Rightarrow A)$ is a monoid with function composition and identity.*

Exercise 70. *Show that we can define a category where objects are* Ty*, a morphism from A to B is* $\mathsf{Tm}\,(A \Rightarrow B)$*, composition is function composition (a refined version of the previous exercise).*

We cannot prove logical consistency just assuming a second-order model, because it might be the trivial model (where all sorts are $\mathbb{1}$). We also cannot prove equational consistency saying that there are terms a, a' such that $a = a' \to \mathbb{0}$, but we can get something similar: instead of obtaining a meta $\mathbb{0}$, we obtain that the second-order model is trivial:

Exercise 71. *Prove that for any $B : \mathsf{Ty}$ we have a $A : \mathsf{Ty}$ and $a, a' : \mathsf{Tm}\, A$ where $a = a'$ implies that any $b, b' : \mathsf{Tm}\, B$, $b = b'$.*

Exercise 72. *There is a second-order model of STLC where there is an $A : \mathsf{Ty}$ and $a, a' : \mathsf{Tm}\, A$ such that $a \neq a'$.*

3.1.1 Bidirectional type checking

The ABT-level (well-scoped) definition of STLC is the following.

Definition 73 (Well-scoped STLC)**.** *A first-order model of well-scoped STLC with De Bruijn indices comprises the following components:*

$$
\begin{array}{ll}
\mathsf{Con} & : \mathsf{Set} \\
\diamond & : \mathsf{Con} \\
- \triangleright & : \mathsf{Con} \to \mathsf{Con} \\
\mathsf{Var} & : \mathsf{Con} \to \mathsf{Set} \\
\mathsf{vz} & : \mathsf{Var}\,(\Gamma \triangleright) \\
\mathsf{vs} & : \mathsf{Var}\,\Gamma \to \mathsf{Var}\,(\Gamma \triangleright) \\
\mathsf{Tm} & : \mathsf{Con} \to \mathsf{Set} \\
\mathsf{var} & : \mathsf{Var}\,\Gamma \to \mathsf{Tm}\,\Gamma \\
\mathsf{lam} & : \mathsf{Tm}\,(\Gamma \triangleright) \to \mathsf{Tm}\,\Gamma \\
- \cdot - & : \mathsf{Tm}\,\Gamma \to \mathsf{Tm}\,\Gamma \to \mathsf{Tm}\,\Gamma \\
\mathsf{Ty} & : \mathsf{Set} \\
\iota & : \mathsf{Ty} \\
- \Rightarrow - & : \mathsf{Ty} \to \mathsf{Ty} \to \mathsf{Ty} \\
\mathsf{ann} & : \mathsf{Tm}\,\Gamma \to \mathsf{Ty} \to \mathsf{Tm}\,\Gamma
\end{array}
$$

Contexts (Con) give the information about the number of variables: $\diamond$ is the empty context, $\diamond \triangleright$ is the context containing one variable, $\diamond \triangleright \triangleright$ contains two variables, and so on. In the syntax of well-scoped STLC, Con is isomorphic to natural numbers. Var contains well-scoped De-Bruijn indices. In the syntax, $\mathsf{Var}\,\Gamma$ is the finite set containing Γ many elements. Terms are indexed by the context: in the syntax, $\mathsf{Tm}\,\Gamma$ is a term that can refer to Γ many variables. In particular, $\mathsf{Tm}\,\diamond$ is a closed term. Terms include annotated terms (ann) where a type for the term is specified.

Some examples for terms in the above well-scoped language (left) and the corresponding terms in a second-order model of STLC:

$\mathsf{lam}\,(\mathsf{var}\,\mathsf{vz})$	$\mathsf{lam}\,\lambda x.\,x$
$\mathsf{lam}\,(\mathsf{lam}\,(\mathsf{var}\,(\mathsf{vs}\,\mathsf{vz})))$	$\mathsf{lam}\,\lambda x.\,\mathsf{lam}\,\lambda y.\,x$
$\mathsf{lam}\,(\mathsf{lam}\,(\mathsf{var}\,\mathsf{vz}))$	$\mathsf{lam}\,\lambda x.\,\mathsf{lam}\,\lambda y.\,y$
$\mathsf{lam}\,(\mathsf{lam}\,(\mathsf{var}\,(\mathsf{vs}\,\mathsf{vz}) \cdot (\mathsf{var}\,(\mathsf{vs}\,\mathsf{vz}) \cdot \mathsf{var}\,\mathsf{vz})))$	$\mathsf{lam}\,\lambda f.\,\mathsf{lam}\,\lambda x.\,f \cdot (f \cdot x)$

Type checking should map the left hand side untyped terms to the right hand side typed terms. However there is not enough information in these untyped terms to guess the type in the right hand side (which are implicit arguments). This is why we have annotated terms. The type inference algorithm will map the following untyped terms (left) to the typed terms (right). We added some implicit arguments.

$\mathsf{ann}\,(\mathsf{lam}\,(\mathsf{var}\,\mathsf{vz}))\,(\iota \Rightarrow \iota)$	$\mathsf{lam}\,\{\iota\}\,\lambda x.\,x$
$\mathsf{ann}\,(\mathsf{lam}\,(\mathsf{lam}\,(\mathsf{var}\,(\mathsf{vs}\,\mathsf{vz}))))\,(\iota \Rightarrow \iota \Rightarrow \iota)$	$\mathsf{lam}\,\{\iota\}\,\lambda x.\,\mathsf{lam}\,\{\iota\}\,\lambda y.\,x$
$\mathsf{ann}\,(\mathsf{lam}\,(\mathsf{lam}\,(\mathsf{var}\,\mathsf{vz})))\,(\iota \Rightarrow \iota \Rightarrow \iota)$	$\mathsf{lam}\,\{\iota\}\,\lambda x.\,\mathsf{lam}\,\{\iota\}\,\lambda y.\,y$
$\mathsf{ann}\,(\mathsf{lam}\,(\mathsf{lam}\,(\mathsf{var}\,(\mathsf{vs}\,\mathsf{vz}) \cdot (\mathsf{var}\,(\mathsf{vs}\,\mathsf{vz}) \cdot \mathsf{var}\,\mathsf{vz}))))\,((\iota \Rightarrow \iota) \Rightarrow \iota \Rightarrow \iota)$	$\mathsf{lam}\,\{\iota \Rightarrow \iota\}\lambda f.\,\mathsf{lam}\,\{\iota\}\,\lambda x.\,f \cdot (f \cdot x)$

Definition 74 (Typechecking and inference model)**.** *The following is a model of well-scoped STLC, referring to a second-order model of STLC. We rely on decidability of equality of* Ty *denoted by* $\stackrel{?}{=}$ *and by matching on its*

elements by λ, and we use the monadic operations of Maybe *denoted* $\gg\!=$, $\gg$, guard.

$$
\begin{aligned}
&\mathsf{Con} && := (U : \mathsf{Set}) \times (El : U \to \mathsf{Set})\\
&\diamond && := (\mathbb{1}, \lambda_.\, \mathbb{1})\\
&(U, El) \triangleright && := (U \times \mathsf{Ty}, \lambda(\Gamma, A).\, El\, \Gamma \times \mathsf{Tm}\, A)\\
&\mathsf{Var}\, (U, El) && := (\Gamma : U) \to (A : \mathsf{Ty}) \times (El\, \Gamma \to \mathsf{Tm}\, A)\\
&\mathsf{vz} && := \lambda(\Gamma, A).\, (A, \lambda(\gamma, a).\, a)\\
&\mathsf{vs}\, x && := \lambda(\Gamma, B).\, \mathsf{match}\, (x\, \Gamma)\, \{(A, a) \mapsto (A, \lambda(\gamma, b).\, a\, \gamma)\}\\
&\mathsf{Tm}\, (U, El) && := (\Gamma : U) \to \big((A : \mathsf{Ty}) \to \mathsf{Maybe}\, (\mathsf{El}\, \Gamma \to \mathsf{Tm}\, A)\big) \times \mathsf{Maybe}\, \big((A : \mathsf{Ty}) \times (\mathsf{El}\, \Gamma \to \mathsf{Tm}\, A)\big)\\
&\mathsf{var}\, x\, \Gamma && := \mathsf{match}\, (x\, \Gamma)\, \big\{(A, a) \mapsto \big((\lambda A'.\, \mathsf{guard}\, (A \overset{?}{=} A') \gg \mathsf{just}\, (A, a)), \mathsf{just}\, (A, a)\big)\big\}\\
&\mathsf{lam}\, t\, \Gamma && := \big((\lambda(A \Rightarrow B).\, (t\, (\Gamma, A))_{.1}\, B \gg\!= \lambda f.\, \mathsf{just}\, \lambda\gamma.\, \mathsf{lam}\, \lambda a.\, f\, (\gamma, a)), \mathsf{nothing}\big)\\
&(t \cdot u)\, \Gamma && := \mathsf{match}\, (t\, \Gamma, u\, \Gamma)\, \big\{((_, \mathsf{just}\, (A \Rightarrow B, t')), (chk_u, _)) \mapsto\\
&&&\quad \big((\lambda B'.\, chk_u\, A \gg\!= \lambda u'.\, \mathsf{guard}\, (B \overset{?}{=} B') \gg \mathsf{just}\, \lambda\gamma.\, t'\, \gamma \cdot u'\, \gamma), chk_u\, A \gg\!= \lambda u'.\, \mathsf{just}\, \lambda\gamma.\, t'\gamma \cdot u'\gamma\big)\big\}\\
&\mathsf{Ty} && := \mathsf{Ty}\\
&\iota && := \iota\\
&A \Rightarrow B && := A \Rightarrow B\\
&\mathsf{ann}\, t\, A\, \Gamma && := \big(\lambda A'.\, \mathsf{guard}\, (A \overset{?}{=} A') \gg (t\, \Gamma)_{.1}\, A, (t\, \Gamma)_{.1}\, A \gg\!= \lambda a.\, \mathsf{just}\, (A, a)\big)
\end{aligned}
$$

Interpretation into this model are the following functions:

$$
\begin{aligned}
&\mathsf{Tys} && : \mathsf{Con_I} \to \mathsf{Set}\\
&\mathsf{Tms} && : (n : \mathsf{Con_I}) \to \mathsf{Tys}\, n \to \mathsf{Set}\\
&\mathsf{check} && : \mathsf{Tm_I}\, n \to (\Gamma : \mathsf{Tys}\, n) \to (A : \mathsf{Ty}) \to \mathsf{Maybe}\, (\mathsf{Tms}\, \Gamma \to \mathsf{Tm}\, A)\\
&\mathsf{infer} && : \mathsf{Tm_I}\, n \to (\Gamma : \mathsf{Tys}\, n) \to \mathsf{Maybe}\, \big((A : \mathsf{Ty}) \times (\mathsf{Tms}\, \Gamma \to \mathsf{Tm}\, A)\big)
\end{aligned}
$$

For a closed preterm $t : \mathsf{Tm_I}\, \diamond$, the last two specialise as follows:

$$
\begin{aligned}
&\mathsf{check}\, t && : \mathbb{1} \to (A : \mathsf{Ty}) \to \mathsf{Maybe}\, (\mathbb{1} \to \mathsf{Tm}\, A)\\
&\mathsf{infer}\, t && : \mathbb{1} \to \mathsf{Maybe}\, \big((A : \mathsf{Ty}) \times (\mathbb{1} \to \mathsf{Tm}\, A)\big)
\end{aligned}
$$

Exercise 75. *Do type checking and inference on some example preterms.*

3.2 System T

The following language has a proper type of natural numbers, it does not simply inherit $\mathbb{N}$ from the metatheory, like Razor did.

Definition 76 (System T)**.** *A second-order model of System T comprises the following components:*

$$
\begin{aligned}
&\mathsf{Ty} && : \mathsf{Set}\\
&\mathsf{Tm} && : \mathsf{Ty} \to \mathsf{Set}\\
&- \Rightarrow - && : \mathsf{Ty} \to \mathsf{Ty} \to \mathsf{Ty}\\
&\mathsf{lam} && : (\mathsf{Tm}\, A \to \mathsf{Tm}\, B) \cong \mathsf{Tm}\, (A \Rightarrow B) : - \cdot -\\
&\mathsf{Nat} && : \mathsf{Ty}\\
&\mathsf{zero} && : \mathsf{Tm}\, \mathsf{Nat}\\
&\mathsf{suc} && : \mathsf{Tm}\, \mathsf{Nat} \to \mathsf{Tm}\, \mathsf{Nat}\\
&\mathsf{ite} && : \mathsf{Tm}\, A \to (\mathsf{Tm}\, A \to \mathsf{Tm}\, A) \to \mathsf{Tm}\, \mathsf{Nat} \to \mathsf{Tm}\, A\\
&\mathsf{Nat}\beta_1 && : \mathsf{ite}\, z\, s\, \mathsf{zero} = z\\
&\mathsf{Nat}\beta_2 && : \mathsf{ite}\, z\, s\, (\mathsf{suc}\, t) = s\, (\mathsf{ite}\, z\, s\, t)
\end{aligned}
$$

Natural numbers are now given by zero and successor suc, for example, three is $\mathsf{suc}\, (\mathsf{suc}\, (\mathsf{suc}\, \mathsf{zero}))$. Functions out of natural numbers can be defined via ite (iterator, also called recursor, fold).

Definition 77 (Constructors, destructors, computation and uniqueness rules)**.** *Operators for each type can be grouped into constructors (introduction rules) and destructors (elimination rules, eliminators). Equations can be grouped into β (computation) and η (uniqueness) rules. β rules explain how to compute if a destructor is applied to a constructor, η rules express what happens if a constructor is applied to a destructor.*

We group our rules for System T and Razor for comparison.

language	type	constructor	destructor	computation	uniqueness
System T (Def. 76)	$- \Rightarrow -$	lam	$- \cdot -$	$\Rightarrow\beta$	$\Rightarrow\eta$
	Nat	$\mathsf{zero}, \mathsf{suc}$	ite	$\mathsf{Nat}\beta_1, \mathsf{Nat}\beta_2$	
Razor (Def. 14)	Bool	$\mathsf{true}, \mathsf{false}$	ite	$\mathsf{ite}\beta_1, \mathsf{ite}\beta_2$	
	Nat	num	$- + -, \mathsf{isZero}$	$+\beta, \mathsf{isZero}\beta_1, \mathsf{isZero}\beta_2$	

Nat does not come with an η rule, but this will be fixed in Section 3.5.

Example 78. *The double function:*

$$\begin{aligned}&\mathsf{double} : \mathsf{Tm}\,(\mathsf{Nat} \Rightarrow \mathsf{Nat})\\&\mathsf{double} := \mathsf{lam}\,\lambda x.\mathsf{ite}\,\mathsf{zero}\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,x\end{aligned}$$

Computing the double of 2:

$$\begin{aligned}&\mathsf{double} \cdot \mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero}) && =(\textit{abbreviation})\\&\big(\mathsf{lam}\,\lambda x.\mathsf{ite}\,\mathsf{zero}\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,x\big) \cdot \mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero}) && =(\beta)\\&\big(\lambda x.\mathsf{ite}\,\mathsf{zero}\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,x\big)\,(\mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero})) && =(\textit{meta application})\\&\mathsf{ite}\,\mathsf{zero}\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,(\mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero})) && =(\mathsf{Nat}\beta_2)\\&(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,\big(\mathsf{ite}\,\mathsf{zero}\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,(\mathsf{suc}\;\mathsf{zero})\big) && =(\textit{meta aplication})\\&\mathsf{suc}\,\Big(\mathsf{suc}\,\big(\mathsf{ite}\,\mathsf{zero}\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,(\mathsf{suc}\;\mathsf{zero})\big)\Big) && =(\mathsf{Nat}\beta_2)\\&\mathsf{suc}\,\Big(\mathsf{suc}\,\big((\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,(\mathsf{ite}\,\mathsf{zero}\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,\mathsf{zero})\big)\Big) && =(\textit{meta application})\\&\mathsf{suc}\,\Big(\mathsf{suc}\,\big(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{ite}\,\mathsf{zero}\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,\mathsf{zero}))\big)\Big) && =(\mathsf{Nat}\beta_1)\\&\mathsf{suc}\,\Big(\mathsf{suc}\,\big(\mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero})\big)\Big)\end{aligned}$$

Definition 79 (Embedding $\mathbb{N}$ into $\mathsf{Tm}\,\mathsf{Nat}$)**.** *The meta function* $\ulcorner - \urcorner : \mathbb{N} \to \mathsf{Tm}\,\mathsf{Nat}$ *is defined as* $\ulcorner n \urcorner := \mathsf{suc}^n\,\mathsf{zero}$*, e.g.* $\ulcorner 3 \urcorner = \mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero}))$*.*

Definition 80 (Definability)**.** *An* $f : \mathbb{N} \to \mathbb{N}$ *is definable in a second-order model of System T if there is a* $t : \mathsf{Tm}\,(\mathsf{Nat} \Rightarrow \mathsf{Nat})$ *such that for all* n*,* $\ulcorner f\,n \urcorner = t \cdot \ulcorner n \urcorner$*. An* $f : \mathbb{N} \to \mathbb{N} \to \mathbb{N}$ *is definable if there is a* $t : \mathsf{Tm}\,(\mathsf{Nat} \Rightarrow \mathsf{Nat} \Rightarrow \mathsf{Nat})$ *such that for all* m*,* n*,* $\ulcorner f\,m\,n \urcorner = t \cdot \ulcorner m \urcorner \cdot \ulcorner n \urcorner$*.*

Exercise 81. *Addition, multiplication, exponentiation, the Ackermann function are definable in any second-order model of System T.*

Exercise 82. *Which of the following terms define identity?*

$$\begin{aligned}&\mathsf{lam}\,\lambda x.x\\&\mathsf{lam}\,\lambda x.\mathsf{ite}\,\mathsf{zero}\,\mathsf{suc}\,x\\&\mathsf{lam}\,\lambda x.\mathsf{ite}\,x\,(\lambda y.y)\,x\\&\mathsf{lam}\,\lambda x.\mathsf{ite}\,\mathsf{zero}\,(\lambda y.y)\,x\\&\mathsf{lam}\,\lambda x.\mathsf{ite}\,(\mathsf{suc}\,\mathsf{zero})\,\mathsf{suc}\,x\\&\mathsf{lam}\,\lambda x.\mathsf{ite}\,(\mathsf{suc}\,\mathsf{zero})\,(\lambda y.y)\,x\end{aligned}$$

Exercise 83. *Which of the following terms define the function* $x \mapsto 2 * x + 1$*?*

$$\begin{aligned}&\mathsf{lam}\,\lambda x.\mathsf{suc}\,x\\&\mathsf{lam}\,\lambda x.\mathsf{suc}\,(\mathsf{ite}\,x\,\mathsf{suc}\,x)\\&\mathsf{lam}\,\lambda x.\mathsf{ite}\,(\mathsf{suc}\,x)\,\mathsf{suc}\,x\\&\mathsf{lam}\,\lambda x.\mathsf{ite}\,(\mathsf{suc}\,\mathsf{zero})\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,x\\&\mathsf{lam}\,\lambda x.\mathsf{suc}\,(\mathsf{ite}\,\mathsf{zero}\,(\lambda y.\mathsf{suc}\,(\mathsf{suc}\,y))\,x)\end{aligned}$$

Exercise 84. *Show that if* $\mathsf{zero} = \mathsf{suc}\,t$*, then for any* $u, v : \mathsf{Tm}\,A$*, we have* $u = v$*.*

Exercise 85. *Show that the predecessor function is definable (difficult, but it will become easier once we have product types).*

It is not possible to define a term $\mathsf{pred} : \mathsf{Tm}\,(\mathsf{Nat} \Rightarrow \mathsf{Nat})$ such that $\mathsf{pred} \cdot \mathsf{suc}\, t = t$ for any $t : \mathsf{Tm}\,\mathsf{Nat}$. [Par89]. For this, we would need the recursor for Nat which in its method for successor receives the natural number, not only the result of the recursive call:

$$\begin{aligned}
&\mathsf{rec} : \mathsf{Tm}\,A \to (\mathsf{Tm}\,\mathsf{Nat} \to \mathsf{Tm}\,A \to \mathsf{Tm}\,A) \to \mathsf{Tm}\,\mathsf{Nat} \to \mathsf{Tm}\,A\\
&\mathsf{rec}\,z\,s\,\mathsf{zero} = z\\
&\mathsf{rec}\,z\,s\,(\mathsf{suc}\,t) = s\,t\,(\mathsf{rec}\,z\,s\,t)
\end{aligned}$$

Now we can define $\mathsf{pred} := \mathsf{lam}\,\lambda x.\,\mathsf{rec}\,\mathsf{zero}\,(\lambda n\,_.\,n)\,x$ and it satisfies

$$\begin{aligned}
&\mathsf{pred} \cdot\ \mathsf{suc}\,t && =\text{(abbreviation)}\\
&(\mathsf{lam}\,\lambda x.\mathsf{rec}\,\mathsf{zero}\,(\lambda y\,_.y)\,x) \cdot \mathsf{suc}\,t && =(\Rightarrow\beta)\\
&(\lambda x.\mathsf{rec}\,\mathsf{zero}\,(\lambda y\,_.y)\,x)\,(\mathsf{suc}\,t) && =\text{(meta application)}\\
&\mathsf{rec}\,\mathsf{zero}\,(\lambda y\,_.y)\,(\mathsf{suc}\,t) && =(\mathsf{Nat}\beta_2)\\
&(\lambda y\,_.y)\,t\,(\mathsf{rec}\,\mathsf{zero}\,(\lambda y\,_.y)\,t) && =\text{(meta application)}\\
&t.
\end{aligned}$$

Exercise 86. *Show that the iterator can be derived from the recursor.*

Exercise 87. *Show that the factorial is definable in System T with recursor.*

Exercise 88. *Define a model of Razor (Definition 14) assuming a second-order model of System T with recursor.*

Theorem 89. *There is an $\mathbb{N} \to \mathbb{N} \to \mathbb{N}$ function, and if this function is definable in System T, then there is a $v : \mathsf{Tm}\,\mathsf{Nat}$, such that $v = \mathsf{suc}\,v$.*

Proof. First we fix a Gödel coding which takes an arbitrary term of type $\mathsf{Nat} \Rightarrow \mathsf{Nat}$ and turns it into a natural number: $\mathsf{code} : \mathsf{Tm}\,(\mathsf{Nat} \Rightarrow \mathsf{Nat}) \to \mathbb{N}$.

An evaluator for System T is an $\mathsf{eval} : \mathbb{N} \to \mathbb{N} \to \mathbb{N}$ function with the following property: for every u and n, we have $\ulcorner \mathsf{eval}\,(\mathsf{code}\,u)\,n \urcorner = u \cdot \ulcorner n \urcorner$. Now eval being definable means that there is a t with $\ulcorner \mathsf{eval}\,m\,n \urcorner = t \cdot \ulcorner m \urcorner \cdot \ulcorner n \urcorner$ for every m and n. Now we define u as follows: $u := \mathsf{lam}\,\lambda x.\mathsf{suc}\,(t \cdot x \cdot x)$. And we reason:

$$\begin{aligned}
&t \cdot \ulcorner \mathsf{code}\,u \urcorner \cdot \ulcorner \mathsf{code}\,u \urcorner && =(\mathsf{eval}\text{ definable})\\
&\ulcorner \mathsf{eval}\,(\mathsf{code}\,u)\,(\mathsf{code}\,u) \urcorner && =\text{(property of eval)}\\
&u \cdot \ulcorner \mathsf{code}\,u \urcorner && =\text{(definition of } u)\\
&(\mathsf{lam}\,\lambda x.\mathsf{suc}\,(t \cdot x \cdot x)) \cdot \ulcorner \mathsf{code}\,u \urcorner && =(\Rightarrow\beta)\\
&\mathsf{suc}\,(t \cdot \ulcorner \mathsf{code}\,u \urcorner \cdot \ulcorner \mathsf{code}\,u \urcorner)
\end{aligned}$$

So we choose $v := t \cdot \ulcorner \mathsf{code}\,u \urcorner \cdot \ulcorner \mathsf{code}\,u \urcorner$ and then $v = \mathsf{suc}\,v$. □

Remark 90. *Unlike $\mathsf{zero} = \mathsf{suc}\,\mathsf{zero}$, the existence of a v with $v = \mathsf{suc}\,v$ in a second-order model does not imply that any two terms are equal. However, the above result implies that an evaluator for System T cannot be defined in the syntax of System T. For the notion of syntax for second-order languages (like System T), see Section 4. If we have $\mathsf{Nat}\eta$ in a second-order model, then the existence of v with $v = \mathsf{suc}\,v$ implies that any two terms are equal. However, in the syntax of System T with $\mathsf{Nat}\eta$, equality of terms is undecidable, and thus a Gödel-coding function is not possible.*

3.3 Finite types

We extend STLC with nullary and binary sums and products.

Definition 91 (Language with finite types)**.** *A second-order model of Fin is STLC (Definition 54) extended*

with the following components:

$$
\begin{array}{ll}
\bot & : \mathsf{Ty} \\
\mathsf{exfalso} & : \mathsf{Tm}\,\bot \to \mathsf{Tm}\,A \\
\bot\eta & : (t : \mathsf{Tm}\,\bot \to \mathsf{Tm}\,A) \to t = \mathsf{exfalso} \\
- + - & : \mathsf{Ty} \to \mathsf{Ty} \to \mathsf{Ty} \\
\mathsf{inl} & : \mathsf{Tm}\,A \to \mathsf{Tm}\,(A + B) \\
\mathsf{inr} & : \mathsf{Tm}\,B \to \mathsf{Tm}\,(A + B) \\
\mathsf{case} & : (\mathsf{Tm}\,A \to \mathsf{Tm}\,C) \to (\mathsf{Tm}\,B \to \mathsf{Tm}\,C) \to \mathsf{Tm}\,(A + B) \to \mathsf{Tm}\,C \\
+\beta_1 & : \mathsf{case}\,f\,g\,(\mathsf{inl}\,a) = f\,a \\
+\beta_2 & : \mathsf{case}\,f\,g\,(\mathsf{inr}\,b) = g\,b \\
+\eta & : (t : \mathsf{Tm}\,(A + B) \to \mathsf{Tm}\,C) \to t = \mathsf{case}\,(\lambda a.\,t\,(\mathsf{inl}\,a))\,(\lambda b.\,t\,(\mathsf{inr}\,b)) \\
\top & : \mathsf{Ty} \\
\mathsf{tt} & : \mathsf{Tm}\,\top \\
\top\eta & : t = tt \\
- \times - & : \mathsf{Ty} \to \mathsf{Ty} \to \mathsf{Ty} \\
-, - & : \mathsf{Tm}\,A \to \mathsf{Tm}\,B \to \mathsf{Tm}\,(A \times B) \\
\mathsf{fst} & : \mathsf{Tm}\,(A \times B) \to \mathsf{Tm}\,A \\
\mathsf{snd} & : \mathsf{Tm}\,(A \times B) \to \mathsf{Tm}\,B \\
\times\beta_1 & : \mathsf{fst}\,(a, b) = a \\
\times\beta_2 & : \mathsf{snd}\,(a, b) = b \\
\times\eta & : t = (\mathsf{fst}\,t, \mathsf{snd}\,t)
\end{array}
$$

Exercise 92. *Group the above operators into constructors and destructors. Check that the β and η rules adhere to their specification.*

Exercise 93. *Define* Bool *by* $\top + \top$ *and show that the following operations are definable and equations are provable:*

$$
\begin{array}{ll}
\mathsf{true} & : \mathsf{Tm}\,\mathsf{Bool} \\
\mathsf{false} & : \mathsf{Tm}\,\mathsf{Bool} \\
\mathsf{ite} & : \mathsf{Tm}\,A \to \mathsf{Tm}\,A \to \mathsf{Tm}\,\mathsf{Bool} \to \mathsf{Tm}\,A \\
\mathsf{Bool}\beta_1 & : \mathsf{ite}\,a\,a'\,\mathsf{true} = a \\
\mathsf{Bool}\beta_2 & : \mathsf{ite}\,a\,a'\,\mathsf{false} = a' \\
\mathsf{Bool}\eta & : (t : \mathsf{Tm}\,\mathsf{Bool} \to \mathsf{Tm}\,A) \to t = \mathsf{ite}\,(t\,\mathsf{true})\,(t\,\mathsf{false})
\end{array}
$$

Exercise 94. *Show that the terms* $\mathsf{lam}\,\lambda x.\mathsf{ite}\,x\,\mathsf{false}\,\mathsf{true}$ *and* $\mathsf{lam}\,\lambda x.(\mathsf{ite}\,x\,\mathsf{false}\,(\mathsf{ite}\,x\,\mathsf{true}\,\mathsf{true}))$ *are equal (you will need* $\mathsf{Bool}\eta$*).*

Exercise 95. *Define four terms of type* $\mathsf{Bool} \Rightarrow \mathsf{Bool}$ *such that if any two are equal, then* $\mathsf{true} = \mathsf{false}$*!*

Exercise 96. *Show that every term of type* $\mathsf{Bool} \Rightarrow \mathsf{Bool}$ *is equal to one of the four terms defined in the previous exercise.*

Exercise 97. *Define the three element type with a case operator and use it to define modulo 3 addition.*

Exercise 98. *Using* Bool *and product types, define homogeneous binary sums (that is, $A+A$ for any A). Define its constructors, destructor and derive its β and η rules.*

Exercise 99. *Define the option (maybe) type former which adds an extra element to an existing type.*

Exercise 100. *For every $n : \mathbb{N}$, define the* $\mathsf{Fin}\,n$ *type which contains exactly n elements. Define its constructors, destructor.*

Exercise 101. *For every n, define n-ary product and sum types.*

Exercise 102. *Derive* $h\,(\mathsf{case}\,f\,g\,w) = \mathsf{case}\,(\lambda a.\,h\,(f\,a))\,(\lambda b.\,h\,(g\,b))\,w$ *(this is called naturality of* case *in C).*

Exercise 103. *Show that there is exactly one term of the following types: $A \Rightarrow \top$ and $\bot \Rightarrow A$ (for arbitrary A).*

Definition 104 (Type isomorphism)**.** *A and B types are isomorphic, if there are $t : \mathsf{Tm}\, A \to \mathsf{Tm}\, B$ and $t' : \mathsf{Tm}\, B \to \mathsf{Tm}\, A$, such that $t'\,(t\,a) = a$ $t\,(t'\,b) = b$ for all a, b. We denote this by $A \cong B$.*

Exercise 105. *Show $(A \times \top) \cong A$ for every A.*

Exercise 106. *Show that for any A, B we have $A + B \cong B + A$.*

The next exercise is the type theory version of the algebraic equation $(a+b)^2 = a^2 + 2ab + b^2$.

Exercise 107. *Show that for arbitrary A, B types, $\mathsf{Bool} \Rightarrow (A + B) \cong \mathsf{Bool} \Rightarrow A + \mathsf{Bool} \times A \times B + \mathsf{Bool} \Rightarrow B$.*

Exercise 108. *Show that the $\cong$ relation is reflexive, symmetric and transitive (equivalence relation), and it is a congruence for $\times$ and $+$. (For example $A \cong A'$ implies $A \times B \cong A' \times B$.)*

Definition 109 (Commutative exponential semiring)**.** *A commutative exponential semiring (commutative exponential ring without negation, commutative exponential rig) is a $\mathsf{C} : \mathsf{Set}$ with the following operations and equations. As $+$ and $*$ are commutative, we only list one identity and distributivity law. We don't give names to the equations.*

$$
\begin{aligned}
- + - &: \mathsf{C} \to \mathsf{C} \to \mathsf{C}\\
0 &: \mathsf{C}\\
- * - &: \mathsf{C} \to \mathsf{C} \to \mathsf{C}\\
1 &: \mathsf{C}\\
-^{-} &: \mathsf{C} \to \mathsf{C} \to \mathsf{C}\\
&: (a+b)+c = a+(b+c)\\
&: a+b = b+a\\
&: 0+a = a\\
&: (a*b)*c = a*(b*c)\\
&: a*b = b*a\\
&: 1*a = a\\
&: a*(b+c) = a*b+a*c\\
&: a^{b+c} = a^b * a^c\\
&: a^0 = 1\\
&: (a*b)^c = a^c * b^c\\
&: 1^c = 1\\
&: a^{b*c} = (a^b)^c\\
&: a^1 = a
\end{aligned}
$$

Exercise 110. *(Meta) natural numbers form a commutative exponential semiring with addition, multiplication and exponentiation. They also form a commutative semiring with maximum and addition. Natural numbers extended with infinity form a commutative semiring with minimum and addition.*

Exercise 111. *In the language Fin, types form a commutative semiring where equations are isomorphisms.*

Remark 112. *Commutative exponential semirings are what Tarski calls high school algebra [BL93] (although they omit the operation 0). A related interesting completeness problem was settled by Wilkie [Wil01]. The dependently typed analogue is still open [Alt08].*

3.4 Generic programming

In this section we follow the book of Robert Harper [Har16].

Assume we have a $\mathsf{Bool} \Rightarrow \mathsf{Nat}$ function, one which maps true to 1 and false to 0 (e.g. $\mathsf{lam}\,(\mathsf{ite}\,(\mathsf{suc}\,\mathsf{zero})\,\mathsf{zero})$). We can apply this to a term of type Bool. But we can also apply it to a term in $\mathsf{Bool} \times \mathsf{Nat}$ in a way that the Nat part is not touched, i.e. (t, t') is mapped to $(\mathsf{ite}\,(\mathsf{suc}\,\mathsf{zero})\,\mathsf{zero}\,t, t')$. Or we can apply it to a term in $(\mathsf{Nat} + \mathsf{Bool}) \times \mathsf{Bool}$ where we apply it to the two Bools and we leave the Nat.

In general: we want to extend an $A \Rightarrow B$ function to an $F : \mathsf{Ty} \to \mathsf{Ty}$ type operator (a type depending on a type) in such a way that we obtain an $F\,A \Rightarrow F\,B$ function. This is what generic programming allows us for certain F type operators. An $F = \lambda X.\, A$, where A can only contain X, nullary and binary (co)products is called a polynomial type operator. If A contains function types, then the positive type operators are those for which the function can be extended to.

The type operator corresponding to the polynomial $\lambda x. 2x^3 + x^2 + 3x + 1$ is $\lambda X.(\top + \top) \times (X \times X \times X) + X \times X + (\top + \top + \top) \times X + \top$.

Definition 113 (Map for polynomial type operators)**.** *For a second-order model of Fin (Definition 91), a model of map for polynomial type operators has one sort* Poly*, and some unnamed operators:*

$$\begin{aligned}
&\mathsf{Poly} : (\mathsf{Ty} \to \mathsf{Ty}) \to \mathsf{Set}\\
&\quad : \mathsf{Poly}\,(\lambda X.X)\\
&\quad : \mathsf{Poly}\,(\lambda X.\top)\\
&\quad : \mathsf{Poly}\,F \to \mathsf{Poly}\,G \to \mathsf{Poly}\,(\lambda X.F\,X \times G\,X)\\
&\quad : \mathsf{Poly}\,(\lambda X.\bot)\\
&\quad : \mathsf{Poly}\,F \to \mathsf{Poly}\,G \to \mathsf{Poly}\,(\lambda X.F\,X + G\,X)
\end{aligned}$$

There is also an operator map *with some unnamed equations:*

$$\begin{aligned}
&\mathsf{map} : (F : \mathsf{Ty} \to \mathsf{Ty}) \to \{\mathsf{Poly}\,F\} \to (\mathsf{Tm}\,A \to \mathsf{Tm}\,B) \to \mathsf{Tm}\,(F\,A) \to \mathsf{Tm}\,(F\,B)\\
&\mathsf{map}\,(\lambda X.X)\quad\quad\quad\quad f\,a = f\,a\\
&\mathsf{map}\,(\lambda X.\top)\quad\quad\quad\quad f\,t = \mathsf{tt}\\
&\mathsf{map}\,(\lambda X.F\,X \times G\,X)\;f\,w = \big(\mathsf{map}\,F\,f\,(\mathsf{fst}\,w), \mathsf{map}\,G\,f\,(\mathsf{snd}\,w)\big)\\
&\mathsf{map}\,(\lambda X.\bot)\quad\quad\quad\quad f\,t = \mathsf{exfalso}\,t\\
&\mathsf{map}\,(\lambda X.F\,X + G\,X)\;f\,w = \mathsf{case}\,w\,\big(\lambda u.\mathsf{inl}\,(\mathsf{map}\,F\,f\,u)\big)\,\big(\lambda v.\mathsf{inr}\,(\mathsf{map}\,G\,f\,v)\big)
\end{aligned}$$

Exercise 114. *Show that the following type operator is polynomial.*

$$\lambda X.\bot + (\top \times X + X \times X)$$

Exercise 115. *Derive* $\mathsf{map}\,(\lambda X.\top + (\mathsf{Bool} \times X))\,f\,(\mathsf{inr}\,(\mathsf{true}, t)) = \mathsf{inr}\,(\mathsf{true}, f\,t)$.

Exercise 116. *Assuming* Poly *is the initial* Poly *model (that is, a meta inductive type), define* map *as iteration into a* Poly *model.*

Exercise 117. *Assuming* map *is defined as in Exercise 123, show that if* $A : \mathsf{Ty}$*, then* $\mathsf{map}\,(\lambda X.A)\,f\,w = w$.

Exercise 118. *Assuming* map *is defined as in Exercise 123, show that it is a functor:* $\mathsf{map}\,F\,(\lambda x.f\,(g\,x))\,w = \mathsf{map}\,F\,f\,(\mathsf{map}\,F\,g\,w)$ *and* $\mathsf{map}\,F\,(\lambda x.x)\,u = u$.

If we also allow functions in the type operator, then sometimes we cannot extend our type operator. For example there is no map function for the type operators

- $F\,X = X \Rightarrow \bot$,
- $F\,X = X \Rightarrow X$,

however there is a map function for

- $F\,X = \mathsf{Bool} \Rightarrow X$,
- $F\,X = ((X + X) \Rightarrow \mathsf{Bool}) \Rightarrow X$.

In the following language we introduce the notions of positive and negative type operators. We have a (covariant) map for the positive type operators while we have a contravariant map for the negative ones.


Definition 119 (Map for positive type operators)**.** *For a second-order model of Fin (Definition 91), a model of map for positive type operators has two sorts* Pos *and* Neg *and some unnamed operators:*

$$\begin{aligned}
&\mathsf{Pos} : (\mathsf{Ty} \to \mathsf{Ty}) \to \mathsf{Set}\\
&\mathsf{Neg} : (\mathsf{Ty} \to \mathsf{Ty}) \to \mathsf{Set}\\
&\quad : \mathsf{Pos}\,(\lambda X.X)\\
&\quad : (C : \mathsf{Ty}) \to \mathsf{Pos}\,(\lambda_.C)\\
&\quad : (C : \mathsf{Ty}) \to \mathsf{Neg}\,(\lambda_.C)\\
&\quad : \mathsf{Pos}\,F \to \mathsf{Pos}\,G \to \mathsf{Pos}\,(\lambda X.F\,X + G\,X)\\
&\quad : \mathsf{Neg}\,F \to \mathsf{Neg}\,G \to \mathsf{Neg}\,(\lambda X.F\,X + G\,X)\\
&\quad : \mathsf{Pos}\,F \to \mathsf{Pos}\,G \to \mathsf{Pos}\,(\lambda X.F\,X \times G\,X)\\
&\quad : \mathsf{Neg}\,F \to \mathsf{Neg}\,G \to \mathsf{Neg}\,(\lambda X.F\,X \times G\,X)\\
&\quad : \mathsf{Neg}\,F \to \mathsf{Pos}\,G \to \mathsf{Pos}\,(\lambda X.F\,X \Rightarrow G\,X)\\
&\quad : \mathsf{Pos}\,F \to \mathsf{Neg}\,G \to \mathsf{Neg}\,(\lambda X.F\,X \Rightarrow G\,X)
\end{aligned}$$

There are also two operators satisfying the equations below:

$$\begin{aligned}
&\mathsf{map}^{\mathsf{P}} : (F : \mathsf{Ty} \to \mathsf{Ty}) \to \{\mathsf{Pos}\, F\} \to (\mathsf{Tm}\, A \to \mathsf{Tm}\, B) \to \mathsf{Tm}\,(F\, A) \to \mathsf{Tm}\,(F\, B)\\
&\mathsf{map}^{\mathsf{N}} : (F : \mathsf{Ty} \to \mathsf{Ty}) \to \{\mathsf{Neg}\, F\} \to (\mathsf{Tm}\, A \to \mathsf{Tm}\, B) \to \mathsf{Tm}\,(F\, B) \to \mathsf{Tm}\,(F\, A)\\
&\mathsf{map}^{\mathsf{P}}\ (\lambda X.X) \qquad\quad f\ a = f\ a\\
&\mathsf{map}^{\mathsf{P}}\ (\lambda X.C) \qquad\quad f\ c = c\\
&\mathsf{map}^{\mathsf{N}}\ (\lambda X.C) \qquad\quad f\ c = c\\
&\mathsf{map}^{\mathsf{P}}\ (\lambda X.F\ X + G\ X)\ \ f\ w = \mathsf{case}\ w\ \big(\lambda u.\mathsf{inl}\ (\mathsf{map}^{\mathsf{P}}\ F\ f\ u)\big)\ \big(\lambda v.\mathsf{inr}\ (\mathsf{map}^{\mathsf{P}}\ G\ f\ v)\big)\\
&\mathsf{map}^{\mathsf{N}}\ (\lambda X.F\ X + G\ X)\ \ f\ w = \mathsf{case}\ w\ \big(\lambda u.\mathsf{inl}\ (\mathsf{map}^{\mathsf{N}}\ F\ f\ u)\big)\ \big(\lambda v.\mathsf{inr}\ (\mathsf{map}^{\mathsf{N}}\ G\ f\ v)\big)\\
&\mathsf{map}^{\mathsf{P}}\ (\lambda X.F\ X \times G\ X)\ \ f\ w = \big(\mathsf{map}^{\mathsf{P}}\ F\ f\ (\mathsf{fst}\ w), \mathsf{map}^{\mathsf{P}}\ G\ f\ (\mathsf{snd}\ w)\big)\\
&\mathsf{map}^{\mathsf{N}}\ (\lambda X.F\ X \times G\ X)\ \ f\ w = \big(\mathsf{map}^{\mathsf{N}}\ F\ f\ (\mathsf{fst}\ w), \mathsf{map}^{\mathsf{N}}\ G\ f\ (\mathsf{snd}\ w)\big)\\
&\mathsf{map}^{\mathsf{P}}\ (\lambda X.F\ X \Rightarrow G\ X)\ f\ g\ = \mathsf{lam}\ \lambda x.\mathsf{map}^{\mathsf{P}}\ G\ f\ \big(g \cdot (\mathsf{map}^{\mathsf{N}}\ F\ f\ x)\big)\\
&\mathsf{map}^{\mathsf{N}}\ (\lambda X.F\ X \Rightarrow G\ X)\ f\ g\ = \mathsf{lam}\ \lambda x.\mathsf{map}^{\mathsf{N}}\ G\ f\ \big(g \cdot (\mathsf{map}^{\mathsf{P}}\ F\ f\ x)\big)
\end{aligned}$$

We illustrate the $\mathsf{map}^{\mathsf{P}}$-equation for $\Rightarrow$ by the following diagram.



Exercise 120. *Show that the following type operators are positive, negative or both.*

- $FX = X \Rightarrow \mathsf{Bool} \Rightarrow \mathsf{Bool}$
- $FX = (X \Rightarrow \mathsf{Bool}) \Rightarrow X$
- $FX = ((X \Rightarrow \mathsf{Bool}) \Rightarrow \mathsf{Bool}) \Rightarrow \mathsf{Bool}$
- $FX = (\mathsf{Bool} \Rightarrow \mathsf{Bool}) \Rightarrow X + X$
- $FX = (X \times (X + \top)) \Rightarrow \mathsf{Bool}$
- $FX = (\mathsf{Bool} \Rightarrow \mathit{Bool}) \Rightarrow \top$

Exercise 121. *Show that if the type operator $F\ X = X \Rightarrow \bot$ comes with a $\mathsf{map}^{\mathsf{P}}$ function, then $\mathsf{Tm} \bot$ has an element.*

Food for thought 122. *The following type operators are not positive, nor negative. What sort of contradiction do we get if they come equipped with $\mathsf{map}^{\mathsf{P}}$ or $\mathsf{map}^{\mathsf{N}}$ functions?*

- $FX = X \Rightarrow X$
- $FX = (\mathsf{Bool} \Rightarrow X) \Rightarrow X$

Exercise 123. *Assuming* Pos *and* Neg *are the initial* Pos–Neg *model (that is, two mutually defined meta inductive types), define $\mathsf{map}^{\mathsf{P}}$ and $\mathsf{map}^{\mathsf{N}}$ by iteration into a* Pos–Neg *model.*

Exercise 124. *Prove that $\mathsf{map}^{\mathsf{P}}$ is a covariant functor, while $\mathsf{map}^{\mathsf{N}}$ is contravariant:*


$$\begin{aligned}
&\mathsf{map}^{\mathsf{P}}\ F\ (\lambda x.f\ (g\ x))\ w = \mathsf{map}^{\mathsf{P}}\ F\ f\ (\mathsf{map}^{\mathsf{P}}\ F\ g\ w) \qquad &&\mathsf{map}^{\mathsf{P}}\ F\ (\lambda x.x)\ u = u\\
&\mathsf{map}^{\mathsf{N}}\ F\ (\lambda x.f\ (g\ x))\ w = \mathsf{map}^{\mathsf{N}}\ F\ g\ (\mathsf{map}^{\mathsf{N}}\ F\ f\ w) \qquad &&\mathsf{map}^{\mathsf{N}}\ F\ (\lambda x.x)\ u = u
\end{aligned}$$

3.5 Inductive types

Bool in Razor (Definition 14) and Nat in System T (Definition 76) were *inductive types*. Another example is the type of binary trees Tree which has two constructors:

$$\begin{aligned}
&\mathsf{Tree} : \mathsf{Ty}\\
&\mathsf{leaf}\ \ : \mathsf{Tm}\ \mathsf{Tree}\\
&\mathsf{node} : \mathsf{Tm}\ \mathsf{Tree} \to \mathsf{Tm}\ \mathsf{Tree} \to \mathsf{Tm}\ \mathsf{Tree}
\end{aligned}$$

The trees in Tree have binary branching and there is no information at the branching nodes or at the leaves. For example, the trees node leaf (node leaf leaf) and node (node leaf leaf) leaf are depicted as follows.



A Tree algebra (also called a Tree model inside our object language) is given by the following components:

$$A : \mathsf{Ty} \qquad u : \mathsf{Tm}\, A \qquad v : \mathsf{Tm}\, A \to \mathsf{Tm}\, A \to \mathsf{Tm}\, A,$$

A homomorphism from the algebra (Tree, leaf, node) to the algebra (A, u, v) is given by a function which respects the operations as follows:

$$\begin{aligned} &t : \mathsf{Tm}\,\mathsf{Tree} \to \mathsf{Tm}\, A \\ &t\,\mathsf{leaf} = u \\ &t\,(\mathsf{node}\, l\, r) = v\,(t\, l)\,(t\, r) \end{aligned}$$

The iterator of Tree says that for any algebra (A, u, v), there is such a homomorphism. The two equations that the homomorphism satisfies are called computation (β) rules. The uniqueness (η) rule says that every other homomorphism from (Tree, leaf, node) to (A, u, v) is equal to the iterator.

The two constructors of Tree can be merged into a single constructor along the following isomorphisms:

$$\begin{aligned} &\mathsf{Tm}\,\mathsf{Tree} \times (\mathsf{Tm}\,\mathsf{Tree} \to \mathsf{Tm}\,\mathsf{Tree} \to \mathsf{Tm}\,\mathsf{Tree}) && \cong \\ &(\mathsf{Tm}\,\top \to \mathsf{Tm}\,\mathsf{Tree}) \times (\mathsf{Tm}\,\mathsf{Tree} \times \mathsf{Tm}\,\mathsf{Tree} \to \mathsf{Tm}\,\mathsf{Tree}) && \cong \\ &\mathsf{Tm}\,(\top \Rightarrow \mathsf{Tree}) \times \mathsf{Tm}\,\big((\mathsf{Tree} \times \mathsf{Tree}) \Rightarrow \mathsf{Tree}\big) && \cong \\ &\mathsf{Tm}\,\Big((\top \Rightarrow \mathsf{Tree}) \times \big((\mathsf{Tree} \times \mathsf{Tree}) \Rightarrow \mathsf{Tree}\big)\Big) && \cong \\ &\mathsf{Tm}\,\big((\top + \mathsf{Tree} \times \mathsf{Tree}) \Rightarrow \mathsf{Tree}\big) && \cong \\ &\mathsf{Tm}\,(\top + \mathsf{Tree} \times \mathsf{Tree}) \to \mathsf{Tm}\,\mathsf{Tree} && = \\ &\mathsf{Tm}\,\big((\lambda X.\top + X \times X)\,\mathsf{Tree}\big) \to \mathsf{Tm}\,\mathsf{Tree} \end{aligned}$$

Definition 125 (Algebra of a type operator)**.** *Assume a type operator* $F : \mathsf{Ty} \to \mathsf{Ty}$*. An* F*-algebra consists of a type* $A : \mathsf{Ty}$ *and a function* $\mathsf{Tm}\,(F\,A) \to \mathsf{Tm}\,A$*.*

An inductive type consists of an F-algebra and an iterator. The type in the F-algebra is what we call the inductive type itself. The constructors of the inductive type are given by the function $\mathsf{Tm}\,(F\,A) \to \mathsf{Tm}\,A$ function in the F-algebra. The iterator encodes that there is a unique F-homomorphism from the inductive type into any other F-algebra. This is why the inductive type is also called the initial F-algebra. (It could be also called the syntax for F, but note that this syntax is internal to a model of our object theory.)

In order to obtain a well-defined notion of F-homomorphism, we need to restrict the type operator F to be positive. We will be even more restrictive, we will only allow strictly positive type operators. There are more strictly positive type operators than polynomial type operators, but less than positive type operators.

Food for thought 126. *Assuming that positive type operators have initial algebras is inconsistent with excluded middle.*

The Tree type is determined by the $\lambda X.\top + X \times X$ type operator, its constructor is

$$\mathsf{con} : \mathsf{Tm}\,(\top + \mathsf{Tree} \times \mathsf{Tree}) \to \mathsf{Tm}\,\mathsf{Tree},$$

its iterator and its computation rule are the following:

$$\begin{aligned} &\mathsf{ite} : \big(\mathsf{Tm}\,(\top + A \times A) \to \mathsf{Tm}\, A\big) \to \mathsf{Tm}\,\mathsf{Tree} \to \mathsf{Tm}\, A \\ &\mathsf{ite}\, f\,(\mathsf{con}\, w) = \mathsf{case}\, w\,\big(\lambda_.f\,(\mathsf{inl}\,\mathsf{tt})\big)\,\Big(\lambda u.f\,\big(\mathsf{inr}\,\big(\mathsf{ite}\, f\,(\mathsf{fst}\, u), \mathsf{ite}\, f\,(\mathsf{snd}\, u)\big)\big)\Big) \end{aligned}$$

The following language contains an inductive type for all F strictly positive type operators. We express the equation for the homomorphism using map.

Definition 127 (Language with inductive types)**.** *A second-order model extends Fin (Definition 91) with the following components:*

$$\begin{aligned}
\mathsf{SPos} &: (\mathsf{Ty} \to \mathsf{Ty}) \to \mathsf{Set}\\
&: \mathsf{SPos}\,(\lambda X.X)\\
&: (A : \mathsf{Ty}) \to \mathsf{SPos}\,(\lambda_.A)\\
&: \mathsf{SPos}\,F \to \mathsf{SPos}\,G \to \mathsf{SPos}\,(\lambda X.F\,X + G\,X)\\
&: \mathsf{SPos}\,F \to \mathsf{SPos}\,G \to \mathsf{SPos}\,(\lambda X.F\,X \times G\,X)\\
&: (C : \mathsf{Ty}) \to \mathsf{SPos}\,F \to \mathsf{SPos}\,(\lambda X.C \Rightarrow F\,X)
\end{aligned}$$

We also have a map *operator:*

$$\begin{aligned}
&\mathsf{map} : (F : \mathsf{Ty} \to \mathsf{Ty}) \to \{\mathsf{SPos}\,F\} \to (f : \mathsf{Tm}\,A \to \mathsf{Tm}\,B) \to \mathsf{Tm}\,(F\,A) \to \mathsf{Tm}\,(F\,B)\\
&\mathsf{map}\,(\lambda X.X) \qquad f\,a = f\,a\\
&\mathsf{map}\,(\lambda_.C) \qquad f\,c = c\\
&\mathsf{map}\,(\lambda X.F\,X + G\,X)\ f\,w = \mathsf{case}\,w\,(\lambda u.\mathsf{inl}\,(\mathsf{map}\,F\,f\,u))\,(\lambda v.\mathsf{inr}\,(\mathsf{map}\,G\,f\,v))\\
&\mathsf{map}\,(\lambda X.F\,X \times G\,X)\ f\,w = \big(\mathsf{map}\,F\,f\,(\mathsf{fst}\,w), \mathsf{map}\,G\,f\,(\mathsf{snd}\,w)\big)\\
&\mathsf{map}\,(\lambda X.C \Rightarrow F\,X)\ \ f\,g = \mathsf{lam}\,\lambda a.\mathsf{map}\,F\,f\,(g \cdot a)
\end{aligned}$$

And inductive types with their constructor, iterator, computation and uniqueness rules:

$$\begin{aligned}
&\mathsf{Ind} \ : (F : \mathsf{Ty} \to \mathsf{Ty}) \to \{\mathsf{SPos\,F}\} \to \mathsf{Ty}\\
&\mathsf{con} \ : (F : \mathsf{Ty} \to \mathsf{Ty}) \to \{\mathsf{SPos\,F}\} \to \mathsf{Tm}\,\big(F\,(\mathsf{Ind}\,F)\big) \to \mathsf{Tm}\,(\mathsf{Ind}\,F)\\
&\mathsf{ite} \ : (F : \mathsf{Ty} \to \mathsf{Ty}) \to \{\mathsf{SPos\,F}\} \to \big(\mathsf{Tm}\,(F\,A) \to \mathsf{Tm}\,A\big) \to \mathsf{Tm}\,(\mathsf{Ind}\,F) \to \mathsf{Tm}\,A\\
&\mathsf{Ind}\beta : \mathsf{ite}\,F\,f\,(\mathsf{con}\,F\,x) = f\,\big(\mathsf{map}\,F\,(\mathsf{ite}\,F\,f)\,x\big)\\
&\mathsf{Ind}\eta : (z : \mathsf{Tm}\,(\mathsf{Ind}\,F) \to \mathsf{Tm}\,A) \to \Big(\big(\lambda x.z\,(\mathsf{con}\,F\,x)\big) = \big(\lambda x.f\,(\mathsf{map}\,F\,z\,x)\big)\Big) \to z = \mathsf{ite}\,F\,f
\end{aligned}$$

Remark 128. *Usually η rules are omitted because (i) they are not needed for running programs; (ii) equality checking in the syntax becomes undecidable in the presence of η for natural numbers. This is not the case for η for finite types [Sch17].*

Inductive types are trees with finite depth. This means that they might have infinitely many branches, but if we follow a branch, then in finite steps we reach a leaf. Note that this does not mean that we can put an element of an inductive type into a hole of finite depth: there are infinitely branching trees where every branch is finite but it has branches of arbitrary length.

Exercise 129. *The inductive type* $\mathsf{Ind}\,(\lambda X.\top + (\mathsf{Nat} \Rightarrow X))$ *contains infinitely branching trees. Define a tree in which the ith branch has height i.*

Exercise 130. *Natural numbers are given by* $\mathsf{Nat} := \mathsf{Ind}\,(\lambda X.\top + X)$*. Define* zero *and* suc *using* con*, define the iterator and prove the computation rules.*

Exercise 131. *Define the following inductive types: lists of natural numbers, binary trees with natural numbers at the leaves, binary trees with natural numbers at the nodes, ternary trees, untyped combinator calculus (without equations), Razor (without equations or types).*

Exercise 132. $\mathsf{Ind}\,F$ *is the fixpoint of the F function:* $F\,(\mathsf{Ind}\,F) \cong \mathsf{Ind}\,F$*.*

Exercise 133. *Show that for every A, we have* $\mathsf{Ind}\,(\lambda X.A) \cong A$*.*

The recursor of Nat can be defined via the iterator: we use the iterator in a way that it not only returns A, but also the concrete natural number on which it was called. For reference, we also list the rules for the iterator:

$$\begin{aligned}
&\mathsf{ite} \ : \{A : \mathsf{Ty}\} \to \mathsf{Tm}\,A \to (\mathsf{Tm}\,A \to \mathsf{Tm}\,A) \to \mathsf{Tm\,Nat} \to \mathsf{Tm}\,A\\
&\mathsf{ite}\beta_1 : \mathsf{ite}\,z\,s\,\mathsf{zero} = z\\
&\mathsf{ite}\beta_2 : \mathsf{ite}\,z\,s\,(\mathsf{suc}\,n) = s\,(\mathsf{ite}\,z\,s\,n)\\
&\mathsf{ite}\eta \ : (z : \mathsf{Tm\,Nat} \to \mathsf{Tm}\,A) \to (z\,\mathsf{zero} = z) \to ((n : \mathsf{Tm\,Nat}) \to z\,(\mathsf{suc}\,n) = s\,(z\,n)) \to z = \mathsf{ite}\,z\,s\\
&\mathsf{rec} \ : \{A : \mathsf{Ty}\} \to \mathsf{Tm}\,A \to (\mathsf{Tm\,Nat} \to \mathsf{Tm}\,A \to \mathsf{Tm}\,A) \to \mathsf{Tm\,Nat} \to \mathsf{Tm}\,A\\
&\mathsf{rec}\,\{A\}\,z\,s\,n := \mathsf{snd}\,\Big(\mathsf{ite}\{\mathsf{Nat} \times A\}\,(\mathsf{zero}, z)\,\big(\lambda w.(\mathsf{suc}\,(\mathsf{fst}\,w), s\,(\mathsf{fst}\,w)\,(\mathsf{snd}\,w))\big)\,n\Big)
\end{aligned}$$

Exercise 134. *Prove the β rules of the recursor:*

$$\mathsf{rec}\beta_1 : \mathsf{rec}\, z\, s\, \mathsf{zero} = z$$
$$\mathsf{rec}\beta_2 : \mathsf{rec}\, z\, s\, (\mathsf{suc}\, n) = s\, n\, (\mathsf{rec}\, z\, s\, n)$$

For the latter we need the η law of the iterator (without this, $\mathsf{rec}\beta_2$ is not derivable [Par89]).

Food for thought 135. *Define the η rule of the recursor. Can it be derived from that of the iterator?*

Food for thought 136. *Define the recursor for an arbitrary inductive type and show that it can be derived from the iterator.*

If we only have inductive types for polynomial type operators, we obtain finitely branching trees.

Food for thought 137. *For every F polynomial type operator, $\mathsf{Ind}\, F$ is either isomorphic to a finite type or isomorphic to* Nat.

Exercise 138 (Cantor's diagonal argument)**.** *Show that if* $(\mathsf{Nat} \Rightarrow \mathsf{Bool}) \cong \mathsf{Nat}$*, then* $\mathsf{true} = \mathsf{false}$.

3.6 Coinductive types

Coinductive types are dual to inductive types.

- Inductive types are determined by their constructors, coinductive types by their destructors.
- The functions which we define out of inductive types using the iterator always *terminate*, the generators creating elements of coinductive types are always *productive*.
- Elements of inductive types are trees with finite depth, while coinductive types generate trees of potentially infinite depth.

Programs running forever (e.g. servers, operating systems, interactive programs), automata, Turing-machines and other machines are elements of coinductive types. They also model parts of object oriented programmign: a class is a coinductive type, the fields/member functions are the destructors, an object is an element of the coinductive type. In the 1990s Turner suggested strong functional programming [**?**] as a style where we separate inductive and coinductive types and there is no general recursion. No one has ever tried programming in such a setting.

The most well-known example of a coinductive type is the type of streams (lists of infinite length).

$$\begin{aligned}
&\mathsf{Stream} && : \mathsf{Ty} \to \mathsf{Ty}\\
&\mathsf{head} && : \mathsf{Tm}\, (\mathsf{Stream}\, A) \to \mathsf{Tm}\, A\\
&\mathsf{tail} && : \mathsf{Tm}\, (\mathsf{Stream}\, A) \to \mathsf{Tm}\, (\mathsf{Stream}\, A)\\
&\mathsf{gen} && : (\mathsf{Tm}\, C \to \mathsf{Tm}\, A) \to (\mathsf{Tm}\, C \to \mathsf{Tm}\, C) \to \mathsf{Tm}\, C \to \mathsf{Tm}\, (\mathsf{Stream}\, A)\\
&\mathsf{Stream}\beta_1 && : \mathsf{head}\, (\mathsf{gen}\, h\, t\, c) = h\, c\\
&\mathsf{Stream}\beta_2 && : \mathsf{tail}\, (\mathsf{gen}\, h\, t\, c) = \mathsf{gen}\, h\, t\, (t\, c)
\end{aligned}$$

Streams have two destructors: head and tail. The tail can be applied any number of times to the stream, so indeed this gives us infinite number of $\mathsf{Tm}\, A$s from a $u : \mathsf{Tm}\, (\mathsf{Stream}\, A)$:

$$\mathsf{head}\, u,\ \ \mathsf{head}\, (\mathsf{tail}\, u),\ \ \mathsf{head}\, (\mathsf{tail}\, (\mathsf{tail}\, u)),\ \ \mathsf{head}\, (\mathsf{tail}\, (\mathsf{tail}\, (\mathsf{tail}\, u))),\ \ \ldots$$

Streams can be made using the generator (coiterator, consructor, corecursor): the input of the generator is a type of seeds (C), functions h and t and a seed (an element of $\mathsf{Tm}\, C$) from which the stream grows out. The h tells us how to compute the current head element from the seed, while t says how to advance the seed (make a step): this is what the β rules express.

The stream containing the natural numbers $0, 1, 2, 3, \ldots$ is given by the following term where $C := \mathsf{Nat}$:

$$\begin{aligned}
&\mathsf{nats} : \mathsf{Tm}\, (\mathsf{Stream}\, \mathsf{Nat})\\
&\mathsf{nats} := \mathsf{gen}\, (\lambda n.n)\, \mathsf{suc}\, \mathsf{zero}
\end{aligned}$$

Indeed,

$$
\begin{aligned}
&\mathsf{head}\ \mathsf{nats} && = \\
&\mathsf{head}\ (\mathsf{gen}\ (\lambda n.n)\ \mathsf{suc}\ \mathsf{zero}) && =(\mathsf{Stream}\beta_1) \\
&(\lambda n.n)\ \mathsf{zero} && = \\
&\mathsf{zero}, \\
&\mathsf{head}\ (\mathsf{tail}\ \mathsf{nats}) && = \\
&\mathsf{head}\ (\mathsf{tail}\ (\mathsf{gen}\ (\lambda n.n)\ \mathsf{suc}\ \mathsf{zero})) && =(\mathsf{Stream}\beta_2) \\
&\mathsf{head}\ (\mathsf{gen}\ (\lambda n.n)\ \mathsf{suc}\ (\mathsf{suc}\ \mathsf{zero})) && =(\mathsf{Stream}\beta_1) \\
&(\lambda n.n)\ (\mathsf{suc}\ \mathsf{zero}) && = \\
&\mathsf{suc}\ \mathsf{zero}, \\
&\mathsf{head}\ (\mathsf{tail}\ (\mathsf{tail}\ \mathsf{nats})) && = \\
&\mathsf{head}\ (\mathsf{tail}\ (\mathsf{tail}\ (\mathsf{gen}\ (\lambda n.n)\ \mathsf{suc}\ \mathsf{zero}))) && =(\mathsf{Stream}\beta_2) \\
&\mathsf{head}\ (\mathsf{tail}\ (\mathsf{gen}\ (\lambda n.n)\ \mathsf{suc}\ (\mathsf{suc}\ \mathsf{zero}))) && =(\mathsf{Stream}\beta_2) \\
&\mathsf{head}\ (\mathsf{gen}\ (\lambda n.n)\ \mathsf{suc}\ (\mathsf{suc}\ (\mathsf{suc}\ \mathsf{zero}))) && =(\mathsf{Stream}\beta_1) \\
&(\lambda n.n)\ (\mathsf{suc}\ (\mathsf{suc}\ \mathsf{zero})) && = \\
&\mathsf{suc}\ (\mathsf{suc}\ \mathsf{zero}), &&
\end{aligned}
$$

and so on.

Exercise 139. *Define pointwise addition on two* Stream Nat*s, and define the* map *function on streams.*

We cannot define the filter function on streams because it is not necessarily productive.

Every strictly positive type operator determines a coinductive type. In the following, we extend the language of inductive type with coinductive types (actually we don't need inductive types, only SPos and map).

Definition 140 (Language with inductive and coinductive types)**.** *A second-order model extends Definition 127 with the following components.*

$$
\begin{aligned}
&\mathsf{Coind} && : \mathsf{SPos}\,\mathsf{F} \to \mathsf{Ty} \\
&\mathsf{des} && : (F : \mathsf{Ty} \to \mathsf{Ty}) \to \{\mathsf{SPos}\,\mathsf{F}\} \to \mathsf{Tm}\,(\mathsf{Coind}\,F) \to \mathsf{Tm}\,\big(F\,(\mathsf{Coind}\,F)\big) \\
&\mathsf{gen} && : (F : \mathsf{Ty} \to \mathsf{Ty}) \to \{\mathsf{SPos}\,\mathsf{F}\} \to \big(\mathsf{Tm}\,A \to \mathsf{Tm}\,(F\,A)\big) \to \mathsf{Tm}\,A \to \mathsf{Tm}\,(\mathsf{Coind}\,F) \\
&\mathsf{Coind}\beta && : \mathsf{des}\,F\,(\mathsf{gen}\,F\,f\,a) = \mathsf{map}\,F\,(\mathsf{gen}\,F\,f)\,(f\,a) \\
&\mathsf{Coind}\eta && : (z : \mathsf{Tm}\,A \to \mathsf{Tm}\,(\mathsf{Coind}\,F)) \to \Big(\big(\lambda z.\mathsf{des}\,F\,(z\,a)\big) = \big(\lambda z.\mathsf{map}\,F\,z\,(f\,a)\big)\Big) \to z = \mathsf{gen}\,F\,f
\end{aligned}
$$

Exercise 141. *Show that the destructors and the generator of streams can be given using* $\mathsf{Stream}\,A := \mathsf{Coind}\,(\lambda X.\,A \times X)$.

Exercise 142. *Define addition and multiplication on conatural numbers (*$\mathsf{Coind}\,(\lambda X.ldotp\top + X)$*)!.*

Exercise 143. *Which inductive type is the dual of streams?*

Exercise 144. *What is the dual of lists, that is,* $\mathsf{Coind}\,(\lambda X.\,\top + A \times X)$*?*

Exercise 145. *Define the coinductive type of machines which can receive a natural number, they can print out a number and there is a button on them. Using the generator, define an summation machine, which adds all the input numbers, returns the sum when asked, and the button resets the number to 0. Define another machine in the same type which prints the maximum of all the input numbers.*

Exercise 146. *A* $\mathsf{Coind}\,F$ *típus az* F *operátor fixpontja: mutassuk meg, hogy* $F\,(\mathsf{Coind}\,F) \cong \mathsf{Coind}\,F$.

Exercise 147. *Show* $\mathsf{Coind}\,(\lambda X.\,A) \cong A$ *for every* A.

Food for thought 148. *The dual of iterator is generator. What is the dual of the recursor?*

3.7 Polymorphism

In the above languages we had to separately define function composition $(B \Rightarrow C) \Rightarrow (A \Rightarrow B) \Rightarrow A \Rightarrow C$ for each types A, B and C; we had to separately define the $\mathsf{filter} : \mathsf{Tm}\,((A \Rightarrow \mathsf{Bool}) \Rightarrow \mathsf{List}\,A \Rightarrow \mathsf{List}\,A)$ function for each type A. We introduce polymorphic types in order to define these terms once and for all for every type. The type of general function composition becomes $\forall\lambda A.\forall\lambda B.\forall\lambda C.(B \Rightarrow C) \Rightarrow (A \Rightarrow B) \Rightarrow A \Rightarrow C$, the type of filter becomes $\forall\lambda A.(A \Rightarrow \mathsf{Bool}) \Rightarrow \mathsf{List}\,A \Rightarrow \mathsf{List}\,A$.

3.7.1 Hindley–Milner

In the following type system we distinguish monorphic (MTy) and polymorphic types (Ty), and the universal quantifier can only appear at the front (at the top of) a polymorphic type. Base types such as Nat are monomorphic.

Definition 149 (A Hindley–Milner style language)**.** *A second-order model contains the following components.*

$$\begin{array}{ll}
\mathsf{MTy} & : \mathsf{Set} \\
\mathsf{Ty} & : \mathsf{Set} \\
\mathsf{Tm} & : \mathsf{Ty} \to \mathsf{Set} \\
- \Rightarrow - & : \mathsf{MTy} \to \mathsf{MTy} \to \mathsf{MTy} \\
\forall & : (\mathsf{MTy} \to \mathsf{Ty}) \to \mathsf{Ty} \\
\mathsf{i} & : \mathsf{MTy} \to \mathsf{Ty} \\
\mathsf{lam} & : \big(\mathsf{Tm}\,(\mathsf{i}\,A) \to \mathsf{Tm}\,(\mathsf{i}\,B)\big) \cong \mathsf{Tm}\,(\mathsf{i}\,(A \Rightarrow B)) : - \cdot - \\
\mathsf{Lam} & : \big((A : \mathsf{MTy}) \to \mathsf{Tm}\,(B\,A)\big) \cong \mathsf{Tm}\,(\forall\,B) : - \bullet -
\end{array}$$

In the above language we have not only term variables, but type variables as well: the operators $\forall$ and Lam bind type variables.

The polymorphic identity function is defined as follows.

$$\begin{array}{l}
\mathsf{id} : \mathsf{Tm}\,\big(\forall\,\lambda A.\mathsf{i}\,(A \Rightarrow A)\big) \\
\mathsf{id} := \mathsf{Lam}\,\lambda A.\mathsf{lam}\,\lambda a.a
\end{array}$$

Although this is not immediately apparent, the above function uses the A input as well because the implicit parameters of lam refer to it. The explicit definition is the following.

$$\mathsf{id} := \mathsf{Lam}\,\{\lambda A.\mathsf{i}\,(A \Rightarrow A)\}\,\big(\lambda A.\mathsf{lam}\,\{A\}\,\{A\}\,(\lambda a.a)\big)$$

Assuming we extend the above language with $\mathsf{Bool} : \mathsf{Ty}$ and $\mathsf{true} : \mathsf{Tm}\,\mathsf{Bool}$ operators, we can run the id program with those inputs as follows.

$$\begin{array}{ll}
\mathsf{id} \bullet \mathsf{Bool} \cdot \mathsf{true} & = \\
(\mathsf{Lam}\,\lambda A.\mathsf{lam}\,\{A\}\,\{A\}\,\lambda a.a) \bullet \mathsf{Bool} \cdot \mathsf{true} & =(\forall\beta) \\
\big((\lambda A.\mathsf{lam}\,\{A\}\,\{A\}\,\lambda a.a)\,\mathsf{Bool}\big) \cdot \mathsf{true} & = \\
(\mathsf{lam}\,\{\mathsf{Bool}\}\,\{\mathsf{Bool}\}\,\lambda a.a) \cdot \mathsf{true} & =(\Rightarrow\beta) \\
(\lambda a.a)\,\mathsf{true} & = \\
\mathsf{true} &
\end{array}$$

Exercise 150. *Define the following programs (derive them in any second-order model).*

$$\begin{array}{ll}
\mathsf{const} & : \mathsf{Tm}\,\big(\forall\lambda A.\forall\lambda B.\mathsf{i}\,(A \Rightarrow B \Rightarrow A)\big) \\
\mathsf{comp} & : \mathsf{Tm}\,\Big(\forall\lambda A.\forall\lambda B.\forall\lambda C.\mathsf{i}\,\big((B \Rightarrow C) \Rightarrow (A \Rightarrow B) \Rightarrow A \Rightarrow C\big)\Big) \\
\mathsf{flip} & : \mathsf{Tm}\,\Big(\forall\lambda A.\forall\lambda B.\forall\lambda C.\mathsf{i}\,\big((A \Rightarrow B \Rightarrow C) \Rightarrow B \Rightarrow A \Rightarrow C\big)\Big)
\end{array}$$

This language does not support (co)inductive types, we have to put them in by hand. Haskell was originally designed as Hindley-Milner extended with a fixpoint operator and recursive types (see next section).

A Hindley–Milner type in general looks like this:

$$\forall\,\lambda A_1.\forall\,\lambda A_2.\ldots.\forall\,\lambda A_n.\mathsf{i}\,(\underbrace{\ldots\ldots\ldots\ldots\ldots\ldots}_{\text{there is no } \forall \text{ in here}})$$

The type $\mathsf{Bool} \Rightarrow \forall\lambda A.\,A$ does not make sense in this language, the $\forall$ has to be in the front. The Hindley-Milner type system is very convenient for programming because types never have to be written out.

Food for thought 151. *Define a type inference algorithm for Hindley–Milner which takes preterms without typing information and produces well-typed terms which have the most general type (E.g. for* const *we obtain* $\forall\lambda A.\,\forall\lambda B.\,A \Rightarrow B \Rightarrow A$ *instead of* $\forall\lambda A.\,A \Rightarrow A \Rightarrow A$*). Preterms do not contain* Lam *or* $- \bullet -$*, these are inserted by the type inference algorithm. See [Hin69, Mil78, Csö12].*

3.7.2 System F

In the next language, $\forall$ can appear anywhere, not only at the front of a type. It was discovered independently by Jean-Yves Girard [Gir72] and John C. Reynolds [Rey74], the former called it System F, the latter called it polymorphic lambda calculus.

Definition 152 (System F)**.** *A second-order model contains the following components:*

$$\begin{array}{ll} \mathsf{Ty} : \mathsf{Set} & \mathsf{Tm} : \mathsf{Ty} \to \mathsf{Set} \\ - \Rightarrow - : \mathsf{Ty} \to \mathsf{Ty} \to \mathsf{Ty} & \mathsf{lam} : (\mathsf{Tm}\, A \to \mathsf{Tm}\, B) \cong \mathsf{Tm}\,(A \Rightarrow B) : - \cdot - \\ \forall : (\mathsf{Ty} \to \mathsf{Ty}) \to \mathsf{Ty} & \mathsf{Lam} : ((X : \mathsf{Ty}) \to \mathsf{Tm}\,(A\,X)) \cong \mathsf{Tm}\,(\forall\, A) : - \bullet - \end{array}$$


For the benefit of the reader, we also list the operations in concice derivation rule style (we don't write Ty and Tm anywhere):

$$\frac{A \qquad B}{A \Rightarrow B} \qquad \frac{x : A \vdash b : B}{\mathsf{lam}\, x.b : A \Rightarrow B} \qquad \frac{f : A \Rightarrow B \qquad a : A}{f \cdot a : B} \qquad \frac{}{(\mathsf{lam}\, x.b) \cdot a = b[x \mapsto a]} \qquad \frac{f : A \Rightarrow B}{f = \mathsf{lam}\, x.f \cdot x}$$

$$\frac{X \vdash A}{\forall X.A} \qquad \frac{X \vdash a : A}{\mathsf{Lam}\, X.a : \forall X.A} \qquad \frac{f : \forall X.A \qquad C}{f \bullet C : A[X \mapsto C]} \qquad \frac{}{(\mathsf{Lam}\, X.a) \bullet C = a[X \mapsto C]} \qquad \frac{f : \forall X.A}{f = \mathsf{Lam}\, X.f \bullet X}$$

Derivation of the polymorphic identity function (we made the implicit arguments of lam explicit):

$$\frac{\dfrac{\overline{A, a : A \vdash a : A}}{A \vdash \mathsf{lam}\,\{A\}\,\{A\}\,(a.a) : A \Rightarrow A}}{\mathsf{Lam}\, A.\, \mathsf{lam}\,\{A\}\,\{A\}\,(a.a) : \forall A.\, A \Rightarrow A}$$



Exercise 153. *Define the following programs (derive them in any second-order model).*

$$\begin{array}{ll} \mathsf{const} & : \mathsf{Tm}\,(\forall \lambda A.\, \forall \lambda B.\, A \Rightarrow B \Rightarrow A) \\ \mathsf{comp} & : \mathsf{Tm}\,\big(\forall \lambda A.\, \forall \lambda B.\, \forall \lambda C.\, (B \Rightarrow C) \Rightarrow (A \Rightarrow B) \Rightarrow A \Rightarrow C\big) \\ \mathsf{comp}' & : \mathsf{Tm}\,\big(\forall \lambda B.\, \forall \lambda C.\, (B \Rightarrow C) \Rightarrow \forall \lambda A.\, (A \Rightarrow B) \Rightarrow A \Rightarrow C\big) \\ \mathsf{S} & : \mathsf{Tm}\,\big(\forall \lambda A.\, \forall \lambda B.\, \forall \lambda C.\, (A \Rightarrow B \Rightarrow C) \Rightarrow (A \Rightarrow B) \Rightarrow A \Rightarrow C\big) \\ \mathsf{flip} & : \mathsf{Tm}\,\big(\forall \lambda A.\, \forall \lambda B.\, \forall \lambda C.\, (A \Rightarrow B \Rightarrow C) \Rightarrow B \Rightarrow A \Rightarrow C\big) \end{array}$$

Exercise 154. *Show that any second-order model of System F gives rise to a second-order model of Hindley-Milner.*

Remark 155. *To rule out trivial solutions to the previous exercise, redo it inside the theory of signatures (see Section 3.12): define a morphism of from the signature of System F to the signature of Hindley–Miler; this also gives rise to a functor between the categories of models.*

All inductive and coiductive types described in Section 3.5, 3.6 are already supported by System F (with their β rules but without η rules). This method is called *Church encoding*, it is a generalisation of how Alonzo Church encoded natural numbers in the untyped lambda calculus (see the next section). The two-element type is defined as follows.

$$\begin{array}{ll} \mathsf{Bool} & := \forall \lambda A.\, A \Rightarrow A \Rightarrow A \\ \mathsf{true} & := \mathsf{Lam}\, \lambda A.\, \mathsf{lam}\, \lambda t.\, \mathsf{lam}\, \lambda f.\, t \\ \mathsf{false} & := \mathsf{Lam}\, \lambda A.\, \mathsf{lam}\, \lambda t.\, \mathsf{lam}\, \lambda f.\, f \\ \mathsf{ite} & : \mathsf{Tm}\,\mathsf{Bool} \to \mathsf{Tm}\,(\forall\, \lambda A.\, A \Rightarrow A \Rightarrow A) \\ \mathsf{ite} & := \lambda b.\, b \\ \mathsf{Bool}\beta_1 & : \mathsf{ite}\,\mathsf{true} \bullet A \cdot t \cdot f = (\lambda b.\, b)\,\mathsf{true} \bullet A \cdot t \cdot f = \mathsf{true} \bullet A \cdot t \cdot f = (\mathsf{Lam}\, \lambda A.\, \mathsf{lam}\, \lambda t.\, \mathsf{lam}\, \lambda f.\, t) \bullet A \cdot t \cdot f = t \\ \mathsf{Bool}\beta_2 & : \mathsf{ite}\,\mathsf{false} \bullet A \cdot t \cdot f = (\lambda b.\, b)\,\mathsf{false} \bullet A \cdot t \cdot f = \mathsf{false} \bullet A \cdot t \cdot f = (\mathsf{Lam}\, \lambda A.\, \mathsf{lam}\, \lambda t.\, \mathsf{lam}\, \lambda f.\, f) \bullet A \cdot t \cdot f = f \end{array}$$

The intuition is that a term in the above Bool type can only do two things: return its first or the second argument. In particular, it cannot look into the type A, it has to work in a uniform (parametric [Rey83, Wad89], natural [Awo10]) way for all As.

Note that Bool cannot be encoded in Hindley–Milner.

Exercise 156. *We defined the type of itertor above so that it can be easily implemented. Show that its type is isomorphic to the type of the usual if-then-else operator:*

$$\big(\mathsf{Tm}\,\mathsf{Bool} \to \mathsf{Tm}\,(\forall\,\lambda A.A \Rightarrow A \Rightarrow A)\big) \cong \big(\{A : \mathsf{Ty}\} \to \mathsf{Tm}\,\mathsf{Bool} \to \mathsf{Tm}\,A \to \mathsf{Tm}\,A \to \mathsf{Tm}\,A\big).$$

Church encoding of a few more types:

empty	$\bot$	$\forall\,\lambda C.C$
unit	$\top$	$\forall\,\lambda C.C \Rightarrow C$
three-element		$\forall\,\lambda C.C \Rightarrow C \Rightarrow C \Rightarrow C$
sum	$A + B$	$\forall\,\lambda C.(A \Rightarrow C) \Rightarrow (B \Rightarrow C) \Rightarrow C$
product	$A \times B$	$\forall\,\lambda C.(A \Rightarrow B \Rightarrow C) \Rightarrow C$
natural numbers	Nat	$\forall\,\lambda C.C \Rightarrow (C \Rightarrow C) \Rightarrow C$
list of As	$\mathsf{List}\,A$	$\forall\,\lambda C.C \Rightarrow (A \Rightarrow C \Rightarrow C) \Rightarrow C$
binary trees	Tree	$\forall\,\lambda C.C \Rightarrow (C \Rightarrow C \Rightarrow C) \Rightarrow C$

Exercise 157. *Derive the constructors and iterators for the above types, show that their computation rules hold.*

Food for thought 158. *Show that any inductive type encoded by a strictly positive functor can be derived in System F (without η rule).*

We can encode the other quantifier:

$$\begin{aligned}&\exists : (\mathsf{Ty} \to \mathsf{Ty}) \to \mathsf{Ty}\\ &\exists\,F := \forall\,\lambda C.(\forall\,\lambda X.F\,X \Rightarrow C) \Rightarrow C\end{aligned}$$

Exercise 159. *Derive the constuctor, destructor and β rule:*

$$\begin{aligned}&\mathsf{mk}\exists : (X : \mathsf{Ty}) \to \mathsf{Tm}\,(F\,X) \to \mathsf{Tm}\,(\exists\,F)\\ &\mathsf{case} : ((X : \mathsf{Ty}) \to \mathsf{Tm}\,(F\,X) \to \mathsf{Tm}\,C) \to \mathsf{Tm}\,(\exists\,F) \to \mathsf{Tm}\,C\\ &\exists\beta \quad : \mathsf{case}\,w\,(\mathsf{mk}\exists\,X\,f) = w\,X\,f\end{aligned}$$

We exemplify the encoding of coinductive types through streams. A stream is given by a type C, a coalgebra on C and an element of C called the seed rfom which the stream grows out.

$$\begin{aligned}&\mathsf{Stream} : \mathsf{Ty} \to \mathsf{Ty}\\ &\mathsf{Stream}\,A := \exists\,\lambda C.\big((C \Rightarrow A) \times (C \Rightarrow C)\big) \times C\\ &\mathsf{head} : \mathsf{Tm}\,(\mathsf{Stream}\,A) \to \mathsf{Tm}\,A\\ &\mathsf{head} := \mathsf{case}\,\big(\lambda X\,w.\mathsf{fst}\,(\mathsf{fst}\,w) \cdot \mathsf{snd}\,w\big)\\ &\mathsf{tail} : \mathsf{Tm}\,(\mathsf{Stream}\,A) \to \mathsf{Tm}\,(\mathsf{Stream}\,A)\\ &\mathsf{tail} := \mathsf{case}\,\Big(\lambda X\,w.\mathsf{mk}\exists\,X\,\big(\mathsf{fst}\,w, \mathsf{snd}\,(\mathsf{fst}\,w) \cdot \mathsf{snd}\,w\big)\Big)\\ &\mathsf{gen} : \{C : \mathsf{Ty}\} \to (\mathsf{Tm}\,C \to \mathsf{Tm}\,A) \to (\mathsf{Tm}\,C \to \mathsf{Tm}\,C) \to \mathsf{Tm}\,C \to \mathsf{Tm}\,(\mathsf{Stream}\,A)\\ &\mathsf{gen}\,\{C\}\,h\,t\,c := \mathsf{mk}\exists\,C\,\big((\mathsf{lam}\,h, \mathsf{lam}\,t), c\big)\end{aligned}$$

Exercise 160. *Prove the computation rules of Church-encoded streams:*

$$\begin{aligned}&\mathsf{Stream}\beta_1 : \mathsf{head}\,(\mathsf{gen}\,h\,t\,c) = h\,c\\ &\mathsf{Stream}\beta_2 : \mathsf{tail}\,(\mathsf{gen}\,h\,t\,c) = \mathsf{gen}\,h\,t\,(t\,c)\end{aligned}$$

Food for thought 161. *Show that any coinductive type encoded by a strictly positive functor can be derived in System F (without η rule).*

Food for thought 162. *If we have internal parametricity [ACKS24, Lor25], the η rules also hold [Wad90]. Can we extend System F with internal parametricity without adding dependent types?*

Abstract types and interfaces can be encoded using existential types [MP88], and thus in System F. For example, if S is a type of Nat-stacks, then we want the following features:

empty	$: \mathsf{Tm}\,S$	create an empty stack
push	$: \mathsf{Tm}\,(\mathsf{Nat} \Rightarrow S \Rightarrow S)$	put a Nat on the top of the stack
pop	$: \mathsf{Tm}\,(S \Rightarrow S)$	remove an element from the top of the stack
top	$: \mathsf{Tm}\,(S \Rightarrow \mathsf{Nat})$	look at what is in the top of the stack
$\mathsf{isEmpty}$	$: \mathsf{Tm}\,(S \Rightarrow \mathsf{Bool})$	let us know if the stack is empty

(Probably top should have type $\mathsf{Tm}\,(S \Rightarrow (\mathsf{Nat}+\top))$, but that is not the point here.) A program which computes a Nat using an abstract stack interface has the following type:

$$\big(\exists\lambda S.\, S \times (\mathsf{Nat} \Rightarrow S \Rightarrow S) \times (S \Rightarrow S) \times (S \Rightarrow \mathsf{Nat}) \times (S \Rightarrow \mathsf{Bool})\big) \Rightarrow \mathsf{Nat}.$$

Exercise 163. *Define a term of the above type which creates a stack, then pushes* 1, 2, 3 *on it, pops one element, and returns what is on the top of the stack. Show that if the following equations hold for our stack implementation, the result will be* 2*:*

$$\mathsf{top} \cdot (\mathsf{pop} \cdot (\mathsf{push} \cdot n \cdot (\mathsf{push} \cdot m \cdot s))) = m.$$

This program behaves uniformly for any stack implementation. Of course, there can be trivial stack implementations which don't behave well. If we want to statically restrict our stack implementation to correct ones, we need dependent types (Section 3.9). Otherwise, we can just assume that the stack implementation behaves well.

Exercise 164. *How do you describe with equations such as the above that a stack implementation behaves correctly?*

3.7.3 Kinds

TODO: translate.

System F-ben vannak polimorf függvények, de nincsenek típus szintű függvények. Például a listák nem adhatók meg, ami egy típusról típusra képező függvény. A következő rendszer ezt kijavítja. A típusokon és a termeken túl van egy újabb szortunk, a fajták (Kind-ok) szortja, a típusok pedig indexelve vannak az ő "típusukkal" (fajtájukkal). A $*$ fajtájú típusok a tulajdonképpeni típusok, nekik lehetnek termei. A $* \Rrightarrow *$ fajtájú típusok a típus-függvények, melyek egy tulajdonképpeni típusból képeznek egy tulajdonképpeni típusba.

Definition 165 (System F_ω)**.**

$$\begin{array}{ll}
\mathsf{Kind} & : \mathsf{Set} \\
\mathsf{Ty} & : \mathsf{Kind} \to \mathsf{Set} \\
- \Rrightarrow - & : \mathsf{Kind} \to \mathsf{Kind} \to \mathsf{Kind} \\
\mathsf{LAM} & : (\mathsf{Ty}\,K \to \mathsf{Ty}\,L) \cong \mathsf{Ty}\,(K \Rrightarrow L) : - \bullet - \\
* & : \mathsf{Kind} \\
\mathsf{Tm} & : \mathsf{Ty} * \to \mathsf{Set} \\
\forall & : (\mathsf{Ty}\,K \to \mathsf{Ty} *) \to \mathsf{Ty} * \\
\mathsf{Lam} & : ((X : \mathsf{Ty}\,K) \to \mathsf{Tm}\,(A\,X)) \cong \mathsf{Tm}\,(\forall\,A) : - \bullet - \\
- \Rightarrow - & : \mathsf{Ty} * \to \mathsf{Ty} * \to \mathsf{Ty} * \\
\mathsf{lam} & : (\mathsf{Tm}\,A \to \mathsf{Tm}\,B) \cong \mathsf{Tm}\,(A \Rightarrow B) : - \cdot -
\end{array}$$

A fajták és típusok a $\Rrightarrow$-val úgy viselkednek, mint egyszerű típuselméletben a típusok és a termek. A System F_ω érdekessége, hogy az egyik szort felhasznál egy operátort ($*$-ot), tehát a szortok nem adhatók meg az operátoroktól elkülönülten.

A lista típus a következőképp Church-kódolható:

$$\begin{array}{l}
\mathsf{List} : \mathsf{Ty}\,(* \Rrightarrow *) \\
\mathsf{List} := \mathsf{LAM}\,\lambda A.\forall\,\lambda B.B \Rightarrow (A \Rightarrow B \Rightarrow B) \Rightarrow B
\end{array}$$

A Haskell bind operátorának a következő a típusa:

$$\forall\,\lambda M.\forall\,\lambda A.\forall\,\lambda B.(A \Rightarrow M \bullet B) \Rightarrow M \bullet A \Rightarrow M \bullet B$$


A λ-kat kihagyva és a $\forall$ által kötött típusok fajtáit odaírva a következőt kapjuk:

$$\forall(M : * \Rrightarrow *).\forall(A : *).\forall(B : *).(A \Rightarrow M \bullet B) \Rightarrow M \bullet A \Rightarrow M \bullet B$$

Exercise 166. *Definiáljuk a Church-kódolt lista típus konstruktorait és iterátorát (fold operátorát)!*

Exercise 167. *Adjuk meg a Church-kódolt lista típus return és bind operátorait és vizsgáljuk meg, hogy teljesítik-e a monád törvényeket!*

The following definition shows that all the languages in the lambda cube [Bar91] can be given as SOGATs. The simply typed lambda calculus (STLC) only includes $\Pi_{*,*}$, and the edges in each dimension add one of the other three Π types, respectively. The calculus of constructions (CC) includes all four Π types.



We don't give names to the maps in the universal properties.

Definition 168 (CC)**.**

$$
\begin{array}{lll}
\square & : \mathsf{Set} & \\
\mathsf{Ty} & : \square \to \mathsf{Set} & \\
* & : \square & \\
\mathsf{Tm} & : \mathsf{Ty}\, * \to \mathsf{Set} & \\
\Pi_{*,*} & : (A : \mathsf{Ty}\, *) \to (\mathsf{Tm}\, A \to \mathsf{Ty}\, *) \to \mathsf{Ty}\, * & \mathsf{Tm}\,(\Pi_{*,*}\, A\, B) \cong (a : \mathsf{Tm}\, A) \to \mathsf{Tm}\,(B\, a) \\
\Pi_{*,\square} & : (A : \mathsf{Ty}\, *) \to (\mathsf{Tm}\, A \to \square) \to \square & \mathsf{Ty}\,(\Pi_{*,\square}\, A\, L) \cong (a : \mathsf{Tm}\, A) \to \mathsf{Ty}\,(L\, a) \\
\Pi_{\square,*} & : (K : \square) \to (\mathsf{Ty}\, K \to \mathsf{Ty}\, *) \to \mathsf{Ty}\, * & \mathsf{Tm}\,(\Pi_{\square,*}\, K\, B) \cong (A : \mathsf{Ty}\, K) \to \mathsf{Tm}\,(B\, A) \\
\Pi_{\square,\square} & : (K : \square) \to (\mathsf{Ty}\, K \to \square) \to \square & \mathsf{Ty}\,(\Pi_{\square,\square}, K\, L) \cong (A : \mathsf{Ty}\, K) \to \mathsf{Ty}\,(L\, A)
\end{array}
$$

Food for thought 169. *Show that all pure type systems are definable as SOGATs. See [CD07].*

3.8 Fixpoint operator for types and terms, untyped calculi

If we have System F-style polymorphism, we don't need to add (co)inductive types by hand into our language. There is another very common way to add features to our language: adding noise, or in other words, making the language less safe. On the other hand, these languages are Turing-complete.

S. 3.8.1 We can add a fixpoint-operator to our language and then we do not need iterators anymore, but we lose that every program terminates: we add meaningless recursive programs which simply loop. The language which has Nat without iterator but with a fixpoint operator is called PCF.

S. 3.8.2 We can add recursive types by saying that every type operator has a fixpoint: we lose the distinction between inductive and coinductive types and now not only terms, but types contain rubbish.

S. 3.8.3 We can remove all types, then we don't even need to add a fixpoint operator, we can just define it. This is the untyped lambda calculus. We have no guarantee that programs are meaningful, but we can implement anything.

3.8.1 PCF

A *fixpoint-operator* is given by $\mathsf{fix} : (\mathsf{Tm}\, A \to \mathsf{Tm}\, A) \to \mathsf{Tm}\, A$ which satisfies the equation $\mathsf{fix}\, f = f\,(\mathsf{fix}\, f)$.

Definition 170 (PCF)**.** *A second-order model of PCF has two sorts (types and type-indexed terms) and the following additional components using concise derivation rule notation:*

$$\frac{A \qquad B}{A \Rightarrow B} \qquad \frac{x : A \vdash b : B}{\mathsf{lam}\, x.b : A \Rightarrow B} \qquad \frac{f : A \Rightarrow B \qquad a : A}{f \cdot a : B} \qquad \frac{}{(\mathsf{lam}\, x.b) \cdot a = b[x \mapsto a]} \qquad \frac{x : A \vdash t : A}{\mathsf{fix}\, x.t : A} \qquad \frac{}{\mathsf{fix}\, x.t = t[x \mapsto \mathsf{fix}\, x.t]}$$

$$\frac{}{\mathsf{Nat}} \qquad \frac{}{\mathsf{zero} : \mathsf{Nat}} \qquad \frac{n : \mathsf{Nat}}{\mathsf{suc}\, n : \mathsf{Nat}} \qquad \frac{b : \mathsf{Nat} \qquad t : A \qquad f : A}{\mathsf{ifZero}\, b\, t\, f : A} \qquad \frac{}{\mathsf{ifZero}\, \mathsf{zero}\, t\, f = t} \qquad \frac{}{\mathsf{ifZero}\,(\mathsf{suc}\, n)\, t\, f = f}$$

$$\frac{n : \mathsf{Nat}}{\mathsf{pred}\, n : \mathsf{Nat}} \qquad \frac{}{\mathsf{pred}\,(\mathsf{suc}\, n) = n} \qquad \frac{}{\mathsf{pred}\, \mathsf{zero} = \mathsf{zero}}$$

Example 171. *We want to define the $x \mapsto x * 2 + 1$ function in a way that it satisfies the following equation:*

$$f = \mathsf{lam}\,\lambda n.\,\mathsf{ifZero}\,n\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,(\mathsf{suc}\,(f \cdot \mathsf{pred}\,n))).$$

This cannot be seen as a definition because f appears on the right hand side of the equation. We fix this by abstracting over the recursive call:

$$\begin{aligned} &g : \mathsf{Tm}\,(\mathsf{Nat} \Rightarrow \mathsf{Nat}) \to \mathsf{Tm}\,(\mathsf{Nat} \Rightarrow \mathsf{Nat}) \\ &g\,f := \mathsf{lam}\,\lambda n.\,\mathsf{ifZero}\,n\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,(\mathsf{suc}\,(f \cdot \mathsf{pred}\,n))) \end{aligned}$$

The fixpoint of g satisfies the desired equation:

$$\begin{aligned} &\mathsf{fix}\,g : \mathsf{Tm}\,(\mathsf{Nat} \Rightarrow \mathsf{Nat}) \\ &\mathsf{fix}\,g && =(\beta \textit{ rule for } \mathsf{fix}) \\ &g\,(\mathsf{fix}\,g) && =(\textit{definition of } g) \\ &\mathsf{lam}\,\lambda n.\,\mathsf{ifZero}\,n\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{pred}\,n))) \end{aligned}$$

We also check that $\mathsf{fix}\,g$ *computes as expected:*

$$\begin{aligned} &\mathsf{fix}\,g \cdot \mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero}) && =(\beta \textit{ rule for } \mathsf{fix}) \\ &\big(\mathsf{lam}\,\lambda n.\,\mathsf{ifZero}\,n\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{pred}\,n)))\big) \cdot \mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero}) && =(\Rightarrow\beta) \\ &\mathsf{ifZero}\,(\mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero}))\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{pred}\,(\mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero})))))) && =(\mathsf{ifZero}\textit{'s } \beta \textit{ rule}) \\ &\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{pred}\,(\mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero})))) && =(\mathsf{pred}\textit{'s } \beta \textit{ rule}) \\ &\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{suc}\,\mathsf{zero})) && =(\beta \textit{ rule for } \mathsf{fix}) \\ &\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{lam}\,\lambda n.\,\mathsf{ifZero}\,n\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{pred}\,n)))) \cdot \mathsf{suc}\,\mathsf{zero})) && =(\Rightarrow\beta) \\ &\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{ifZero}\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{pred}\,(\mathsf{suc}\,\mathsf{zero}))))))) && =(\Rightarrow\beta) \\ &\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{pred}\,(\mathsf{suc}\,\mathsf{zero})))))) && =(\mathsf{pred}\textit{'s } \beta \textit{ rule}) \\ &\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{zero})))) && =(\beta \textit{ rule for } \mathsf{fix}) \\ &\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{lam}\,\lambda n.\,\mathsf{ifZero}\,n\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{pred}\,n)))) \cdot \mathsf{zero})))) && =(\Rightarrow\beta) \\ &\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{ifZero}\,\mathsf{zero}\,(\mathsf{suc}\,\mathsf{zero})\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,g \cdot \mathsf{pred}\,\mathsf{zero}))))))) && =(\mathsf{ifZero}\textit{'s } \beta \textit{ rule}) \\ &\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,(\mathsf{suc}\,\mathsf{zero})))) \end{aligned}$$

Exercise 172. *Define the iterator of natural numbers and show its computation rules.*

Exercise 173. *Show weak equational consistency for any second-order model: that is, if* $\mathsf{zero} = \mathsf{suc}\,\mathsf{zero}$*, then for all A and $u, v : \mathsf{Tm}\,A$, $u = v$.*

Exercise 174. *Show that using a second-order model of PCF, a second-order model of System T without η can be given. See also Remark 155.*

Exercise 175. *Which functions do the following PCF terms define?*

$$\begin{aligned} &\mathsf{fix}\,(\lambda t.\,\mathsf{lam}\,\lambda x.\,x) \\ &\mathsf{fix}\,(\lambda t.\,\mathsf{lam}\,\lambda x.\,\mathsf{ifZero}\,x\,x\,x) \\ &\mathsf{fix}\,\big(\lambda t.\,\mathsf{lam}\,\lambda x.\,\mathsf{ifZero}\,x\,x\,(\mathsf{suc}\,\mathsf{zero})\big) \\ &\mathsf{fix}\,\big(\lambda t.\,\mathsf{lam}\,\lambda x.\,\mathsf{ifZero}\,x\,(\mathsf{suc}\,\mathsf{zero})\,\mathsf{zero}\big) \\ &\mathsf{fix}\,\Big(\lambda t.\,\mathsf{lam}\,\lambda x.\,\mathsf{ifZero}\,x\,x\,\big(\mathsf{suc}\,(t \cdot \mathsf{pred}\,x)\big)\Big) \\ &\mathsf{fix}\,\Big(\lambda t.\,\mathsf{lam}\,\lambda x.\,\mathsf{ifZero}\,x\,\mathsf{zero}\,\big(\mathsf{suc}\,(t \cdot \mathsf{pred}\,x)\big)\Big) \\ &\mathsf{fix}\,\Big(\lambda t.\,\mathsf{lam}\,\lambda x.\,\mathsf{ifZero}\,x\,(\mathsf{suc}\,\mathsf{zero})\,\big(\mathsf{suc}\,(t \cdot \mathsf{pred}\,x)\big)\Big) \end{aligned}$$

The price we had to pay for having all recursive functions is that we have non-productive terms: $\mathsf{fix}\,(\lambda x.\,x) : \mathsf{Tm}\,A$ for any A, and we have $\mathsf{fix}\,(\lambda x.\,x) = (\lambda x.\,x)(\mathsf{fix}\,(\lambda x.\,x)) = \mathsf{fix}\,(\lambda x.\,x)$, so we don't obtain any new information from computing. Similarly, $\mathsf{fix}\,\mathsf{suc} = \mathsf{suc}\,(\mathsf{fix}\,\mathsf{suc}) = \mathsf{suc}\,(\mathsf{suc}\,(\mathsf{fix}\,\mathsf{suc})) = \ldots$, which will be a very large term never terminating. Compare this with $\mathsf{fix}\,(\lambda_.\,t) = (\lambda_.\,t)\,(\mathsf{fix}\,(\lambda_.\,t)) = t$.

3.8.2 Recursive types

We have a fixpoint operator for $F : \mathsf{Ty} \to \mathsf{Ty}$ functions, that is, an operator $\mathsf{Fix} : (\mathsf{Ty} \to \mathsf{Ty}) \to \mathsf{Ty}$. There are two ways to express that $\mathsf{Fix}\, F$ is the fixpoint of F:

- *equirecursive types*, that is, we add the equation $\mathsf{Fix}\, F = F\, (\mathsf{Fix}\, F)$. This makes equality of types undecidable (and thus typechecking undecidable).
- *isorecursive types*: instead of adding an equation in types, we add an isomorphism $\mathsf{Fix}\, F \cong F\, (\mathsf{Fix}\, F)$.

We follow the latter route.

Definition 176 (A language with recursive types)**.** *A second-order model extends Fin (Definition 91) with the following components:*

$$\begin{aligned}
&\mathsf{fix} &&: (\mathsf{Tm}\, A \to \mathsf{Tm}\, A) \to \mathsf{Tm}\, A\\
&\mathsf{fix}\beta &&: \mathsf{fix}\, f = f\, (\mathsf{fix}\, f)\\
&\mathsf{Fix} &&: (\mathsf{Ty} \to \mathsf{Ty}) \to \mathsf{Ty}\\
&\mathsf{con} &&: \mathsf{Tm}\, (F\, (\mathsf{Fix}\, F)) \cong \mathsf{Tm}\, (\mathsf{Fix}\, F) : \mathsf{des}
\end{aligned}$$

Example 177 (Nat)**.** *We define natural numbers as a recursive type. We only write the implicit argument* $\{\lambda X.\, \top + X\}$ *of* con *once.*

$$\begin{aligned}
&\mathsf{Nat} &&:= \mathsf{Fix}\, \lambda X.\, \top + X\\
&\mathsf{zero} &&:= \mathsf{con}\, \{\lambda X.\, \top + X\}\, (\mathsf{inl}\, \mathsf{tt})\\
&\mathsf{suc} &&: \mathsf{Tm}\, \mathsf{Nat} \to \mathsf{Tm}\, \mathsf{Nat}\\
&\mathsf{suc}\, n &&:= \mathsf{con}\, (\mathsf{inr}\, n)\\
&\mathsf{ite} &&: \mathsf{Tm}\, A \to (\mathsf{Tm}\, A \to \mathsf{Tm}\, A) \to \mathsf{Tm}\, (\mathsf{Nat} \Rightarrow A)\\
&\mathsf{ite}\, z\, s &&:= \mathsf{fix}\, \lambda f.\, \mathsf{lam}\, \lambda n.\, \mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (f \cdot m))\, (\mathsf{des}\, n)\\
&\mathsf{Nat}\beta_1 : &&\mathsf{ite}\, z\, s \cdot \mathsf{zero} && =(\textit{definition})\\
&&&\big(\mathsf{fix}\, \lambda f.\, \mathsf{lam}\, \lambda n.\, \mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (f \cdot m))\, (\mathsf{des}\, n)\big) \cdot \mathsf{zero} && =(\mathsf{fix}\beta)\\
&&&\big(\mathsf{lam}\, \lambda n.\, \mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (\mathsf{ite}\, z\, s \cdot m))\, (\mathsf{des}\, n)\big) \cdot \mathsf{zero} && =(\Rightarrow\beta)\\
&&&\mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (\mathsf{ite}\, z\, s \cdot m))\, (\mathsf{des}\, \mathsf{zero}) && =(\textit{definition})\\
&&&\mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (\mathsf{ite}\, z\, s \cdot m))\, (\mathsf{des}\, (\mathsf{con}\, (\mathsf{inl}\, \mathsf{tt}))) && =(\mathsf{Fix}\beta)\\
&&&\mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (\mathsf{ite}\, z\, s \cdot m))\, (\mathsf{inl}\, \mathsf{tt}) && =(+\beta_1)\\
&&&z\\
&\mathsf{Nat}\beta_2 : &&\mathsf{ite}\, z\, s \cdot \mathsf{suc}\, n && =(\textit{definition})\\
&&&\big(\mathsf{fix}\, \lambda f.\, \mathsf{lam}\, \lambda n.\, \mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (f \cdot m))\, (\mathsf{des}\, n)\big) \cdot \mathsf{suc}\, n && =(\mathsf{fix}\beta)\\
&&&\big(\mathsf{lam}\, \lambda n.\, \mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (\mathsf{ite}\, z\, s \cdot m))\, (\mathsf{des}\, n)\big) \cdot \mathsf{suc}\, n && =(\Rightarrow\beta)\\
&&&\mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (\mathsf{ite}\, z\, s \cdot m))\, (\mathsf{des}\, (\mathsf{suc}\, n)) && =(\textit{definition})\\
&&&\mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (\mathsf{ite}\, z\, s \cdot m))\, (\mathsf{des}\, (\mathsf{con}\, (\mathsf{inr}\, n))) && =(\mathsf{Fix}\beta)\\
&&&\mathsf{case}\, (\lambda _.\, z)\, (\lambda m.\, s\, (\mathsf{ite}\, z\, s \cdot m))\, (\mathsf{inr}\, n) && =(+\beta_2)\\
&&&s\, (\mathsf{ite}\, z\, s \cdot n)
\end{aligned}$$

Food for thought 178. *Does* $\mathsf{Nat}\eta$ *hold?*

Example 179 (Stream)**.** *We define streams as a recursive type.*

$$\begin{aligned}
&\mathsf{Stream} &&: \mathsf{Ty} \to \mathsf{Ty}\\
&\mathsf{Stream}\, A &&:= \mathsf{Fix}\, \lambda A.\, A \times X\\
&\mathsf{head} &&: \mathsf{Tm}\, (\mathsf{Stream}\, A) \to \mathsf{Tm}\, A\\
&\mathsf{head}\, t &&:= \mathsf{fst}\, (\mathsf{des}\, t)\\
&\mathsf{tail} &&: \mathsf{Tm}\, (\mathsf{Stream}\, A) \to \mathsf{Tm}\, (\mathsf{Stream}\, A)\\
&\mathsf{tail}\, t &&:= \mathsf{snd}\, (\mathsf{des}\, t)\\
&\mathsf{gen} &&: (\mathsf{Tm}\, C \to \mathsf{Tm}\, A) \to (\mathsf{Tm}\, C \to \mathsf{Tm}\, C) \to \mathsf{Tm}\, (C \Rightarrow \mathsf{Stream}\, A)\\
&\mathsf{gen}\, h\, t &&:= \mathsf{fix}\, \lambda f.\, \mathsf{lam}\, \lambda c.\, \mathsf{con}\, (h\, c, f \cdot t\, c)
\end{aligned}$$

Exercise 180 (long)**.** *Prove the* β *rules for streams.*

Exercise 181 (long). *Show that for a stictly positive* $F : \mathsf{Ty} \to \mathsf{Ty}$*,* $\mathsf{Fix}\, F$ *satisfies all the rules of* $\mathsf{Ind}\, F$ *and* $\mathsf{Coind}\, F$*.*

We have meaningless types such as $D := \mathsf{Fix}\,(\lambda X.X)$ which gives as a $\mathsf{con} : \mathsf{Tm}\, D \to \mathsf{Tm}\, D$ and $\mathsf{des} : \mathsf{Tm}\, D \to \mathsf{Tm}\, D$, but we cannot create any element of D and cannot obtain any information from assumed elements of D.

3.8.3 Untyped lambda calculus

The simplest programming language with binders is the untyped lambda calculus.

Definition 182 (Untyped lambda calculus).

$$\begin{aligned}
&\mathsf{Tm} &&: \mathsf{Set}\\
&- \cdot - &&: \mathsf{Tm} \to \mathsf{Tm} \to \mathsf{Tm}\\
&\mathsf{lam} &&: (\mathsf{Tm} \to \mathsf{Tm}) \to \mathsf{Tm}\\
&\beta &&: \mathsf{lam}\, f \cdot u = f\, u
\end{aligned}$$

A fixpoint combinator:

$$\mathsf{Y} : \mathsf{Tm} := \mathsf{lam}\, \lambda f.\big(\mathsf{lam}\, \lambda x.f \cdot (x \cdot x)\big) \cdot \big(\mathsf{lam}\, \lambda x.f \cdot (x \cdot x)\big).$$

Exercise 183. *Show that* $\mathsf{Y} \cdot f = f \cdot (\mathsf{Y} \cdot f)$*.*

Exercise 184. *Show that there are terms* $\mathsf{zero}, \mathsf{suc}, \mathsf{ite} : \mathsf{Tm}$ *such that* $\mathsf{ite} \cdot z \cdot s \cdot \mathsf{zero} = z$ *and* $\mathsf{ite} \cdot z \cdot s \cdot (\mathsf{suc}\, t) = s \cdot (\mathsf{ite} \cdot z \cdot s \cdot t)$*.*

Exercise 185. *Show that we have similar encoding for all inductive and coinductive types. What about* η *rules?*

We have another untyped language which has one more operator and one more equation, but is first-order:

Definition 186 (Untyped combinator calculus).

$$\begin{aligned}
&\mathsf{Tm} &&: \mathsf{Set}\\
&- \cdot - &&: \mathsf{Tm} \to \mathsf{Tm} \to \mathsf{Tm}\\
&\mathsf{K} &&: \mathsf{Tm}\\
&\mathsf{S} &&: \mathsf{Tm}\\
&\mathsf{K}\beta &&: \mathsf{K} \cdot a \cdot b = a\\
&\mathsf{S}\beta &&: \mathsf{S} \cdot f \cdot g \cdot a = f \cdot a \cdot (g \cdot a)
\end{aligned}$$

See [AKSV23] for the relationship of untyped lambda and combinator calculi.

It is remarkable that Schönfinkel's untyped combinator calculus is still the simplest Turing complete language, even though it was the first such. Note that in contrast with STCC, untyped combinator calculus does not have normalisation.

TODO: add exercises from Hungarian course notes, including fixpoint operator for SK.

3.9 Martin-Löf type theory

Definition 187 (Minimal Martin-Löf type theory (mini-MLTT)).

$$\begin{aligned}
&\mathsf{Ty} &&: \mathsf{Set}\\
&\mathsf{Tm} &&: \mathsf{Ty} \to \mathsf{Set}\\
&\iota &&: \mathsf{Ty}\\
&\Pi &&: (A : \mathsf{Ty}) \to (\mathsf{Tm}\, A \to \mathsf{Ty}) \to \mathsf{Ty}\\
&\mathsf{lam} &&: ((a : \mathsf{Tm}\, A) \to \mathsf{Tm}\,(B\, a)) \cong \mathsf{Tm}\,(\Pi\, A\, B) : - \cdot -
\end{aligned}$$

Definition 188 (Martin-Löf type theory with Π and universes).

$$\begin{aligned}
&\mathsf{Ty} &&: \mathbb{N} \to \mathsf{Set}\\
&\mathsf{Tm} &&: \mathsf{Ty}\, i \to \mathsf{Set}\\
&\Pi &&: (A : \mathsf{Ty}\, i) \to (\mathsf{Tm}\, A \to \mathsf{Ty}\, i) \to \mathsf{Ty}\, i\\
&\mathsf{lam} &&: ((a : \mathsf{Tm}\, A) \to \mathsf{Tm}\,(B\, a)) \cong \mathsf{Tm}\,(\Pi\, A\, B) : - \cdot -
\end{aligned}$$

$$\begin{aligned}
&\mathsf{U} &&: (i : \mathbb{N}) \to \mathsf{Ty}\,(1 + i)\\
&\mathsf{c} &&: \mathsf{Ty}\, i \cong \mathsf{Tm}\,(\mathsf{U}\, i) : \mathsf{El}\\
&\mathsf{Lift} &&: \mathsf{Ty}\, i \to \mathsf{Ty}\,(1 + i)\\
&\mathsf{mk} &&: \mathsf{Tm}\, A \cong \mathsf{Tm}\,(\mathsf{Lift}\, A) : \mathsf{un}
\end{aligned}$$