
CST 347 ?? Real Time OS




Topics

Topics

- Introduction
- Basic Concepts
- Scheduling Criteria
- Scheduling Algorithms
- Thread Scheduling
- Multiple-Processor Scheduling
- Real-Time CPU Scheduling
- Operating Systems Examples
- Algorithm Evaluation

Scheduler/Dispatcher



Scheduling Criteria

Scheduling Criteria

- CPU utilization keep the CPU as busy as possible
- Throughput # of processes that complete their execution per time unit
- Turnaround time amount of time to execute a particular process
- Waiting time amount of time a process has been waiting in the ready queue
- Response time amount of time it takes from when a request was submitted until the first response is produced, not output (for time-sharing environment)

Scheduling Algorithm Optimization Criteria

Scheduling Algorithm Optimization Criteria

- Max CPU utilization
- Max throughput
- Min turnaround time
- Min waiting time
- Min response time

Scheduling Algorithms

Scheduling Algorithms

- First-Come, First-Served (FCFS)
- Shortest-Job-First (SJF) Scheduling
- Priority Scheduling
- Round-Robin Scheduling
- Multilevel Queue Scheduling

First-Come, First-Served (FCFS) Scheduling

First-Come, First-Served (FCFS) Scheduling


<u>Process</u> <u>Burst Time</u>

24

P₂ 3

P₃ 3

- Suppose that the processes arrive in the order: P1, P2, P3
- The Gantt Chart for the schedule is:



Waiting time for P₁ = 0; P₂ = 24; P₃ = 27

Average Wait Time =
$$\frac{0+24+27}{3}$$
 = 17

FCFS Scheduling (Cont.)

FCFS Scheduling (Cont.)

Suppose that the processes arrive in the order:


$$P_2, P_3, P_1$$

The Gantt chart for the schedule is:



- Waiting time for $P_1 = 6$; $P_2 = 0$. $P_3 = 3$
- Average waiting time: (6 + 0 + 3)/3 = 3
- Much better than previous case
- Convoy effect short process behind long process
 - Consider one CPU-bound and many I/O-bound processes

FCFS Scheduling (Cont.)




Shortest-Job-First (SJF) Scheduling

Shortest-Job-First (SJF) Scheduling

- Associate with each process the length of its next CPU burst
 - Use these lengths to schedule the process with the shortest time
- SJF is optimal gives minimum average waiting time for a given set of processes
 - The difficulty is knowing the length of the next CPU request
 - Could ask the user

Example of SJF




Determining Length of Next CPU Burst

Determining Length of Next CPU Burst

- . Can only estimate the length should be similar to the previous one
 - Then pick process with shortest predicted next CPU burst
- Can be done by using the length of previous CPU bursts, using exponential averaging
 - 1. $t_n = \text{actual length} of n^{th} CPU burst$
 - 2. (τ_{n+1}) = predicted value for the next CPU burst
 - 3. $\alpha, 0 \le \alpha \le 1$
 - 4. Define: $\tau_{n-1} = \alpha t_n + (1-\alpha)\tau_n$.
- Commonly, α set to ½
- Preemptive version called shortest-remaining-time-first

Prediction of the Length of the Next CPU Burst



Examples of Exponential Averaging

Examples of Exponential Averaging

- α =0
 - $-\tau_{n+1} = \tau_n$
 - Recent history does not count
- α = 1
 - $\tau_{n+1} = \alpha t_n$
 - Only the actual last CPU burst counts
- If we expand the formula, we get:

$$\tau_{n+1} = \alpha t_n + (1 - \alpha)\alpha t_n - 1 + ...$$

$$+ (1 - \alpha)^j \alpha t_{n-j} + ...$$

$$+ (1 - \alpha)^{n+1} \tau_0$$

• Since both α and $(1 - \alpha)$ are less than or equal to 1, each successive term has less weight than its predecessor

Example of Shortest-remaining-time-first

Example of Shortest-remaining-time-first

Now we add the concepts of varying arrival times and preemption to the analysis

Process Arrival Time Burst Time


P₁ 0 8

P₂ 1 4

P₃ 2 9

P₄ 3 5

· Preemptive SJF Gantt Chart




Average waiting time = [(10-1)+(1-1)+(17-2)+5-3)]/4 = 26/4 = 6.5 msec

Priority Scheduling

- · A priority number (integer) is associated with each process
- The CPU is allocated to the process with the highest priority (smallest integer = highest priority)
 - Preemptive
 - Nonpreemptive
- SJF is priority scheduling where priority is the inverse of predicted next CPU burst time
- Problem = Starvation low priority processes may never execute
- Solution = Aging as time progresses increase the priority of the process


Example of Priority Scheduling



Round Robin (RR)


- Each process gets a small unit of CPU time (time quantum q), usually 10-100 milliseconds. After this time has elapsed, the process is preempted and added to the end of the ready queue.
- If there are n processes in the ready queue and the time quantum is q, then each process gets 1/n of the CPU time in chunks of at most q time units at once. No process waits more than (n-1)q time units.
- Timer interrupts every quantum to schedule next process
- Performance
 - q large ⇒ FIFO
 - q small ⇒ q must be large with respect to context switch, otherwise overhead is too high

Round Robin




Example of RR with Time Quantum = 4

Example of RR with Time Quantum = 4m




The Gantt chart is:




- Typically, higher average turnaround than SJF, but better response
- q should be large compared to context switch time
- q usually 10ms to 100ms, context switch < 10 usec

Time Quantum and Context Switch Time



Turnaround Time Varies With The Time Quantum




Multilevel Queue


Multilevel Queue

- Ready queue is partitioned into separate queues, eg:
 - foreground (interactive)
 - background (batch)
- Process permanently in a given queue
- Each queue has its own scheduling algorithm:
 - foreground RR
 - background FCFS
- Scheduling must be done between the queues:
 - Fixed priority scheduling; (i.e., serve all from foreground then from background).
 Possibility of starvation.
 - Time slice each queue gets a certain amount of CPU time which it can schedule amongst its processes; i.e., 80% to foreground in RR
 - 20% to background in FCFS

Multilevel Queue



Multilevel Queue Scheduling



1EING


Multilevel Feedback Queue

Multilevel Feedback Queue

- A process can move between the various queues;
 aging can be implemented this way
- Multilevel-feedback-queue scheduler defined by the following parameters:
 - number of queues
 - scheduling algorithms for each queue
 - method used to determine when to upgrade a process
 - method used to determine when to demote a process
 - method used to determine which queue a process will enter when that process needs service

preempted and moved to queue Q2

Example of Multilevel Feedback Queue



Thread Scheduling

Thread Scheduling



- Distinction between user-level and kernel-level threads
- When threads supported, threads scheduled, not processes
- Many-to-one and many-to-many models, thread library schedules user-level threads to run on LWP
 - Known as process-contention scope (PCS) since scheduling competition is within the process
 - Typically done via priority set by programmer
- Kernel thread scheduled onto available CPU is systemcontention scope (SCS) – competition among all threads in system

Pthread Scheduling

Pthread Scheduling

- API allows specifying either PCS or SCS during thread creation
 - PTHREAD_SCOPE_PROCESS schedules threads using PCS scheduling
 - PTHREAD_SCOPE_SYSTEM schedules threads using SCS scheduling
- Can be limited by OS Linux and Mac OS X only allow PTHREAD_SCOPE_SYSTEM

Pthread Scheduling API

Pthread Scheduling API

```
#include <pthread.h>
#include <stdio.h>
#define NUM THREADS 5
int main(int argc, char *argv[]) {
   int i, scope;
   pthread t tid[NUM THREADS];
  pthread attr t attr;
   /* get the default attributes */
   pthread attr init(&attr);
   /* first inquire on the current scope */
   if (pthread attr getscope(&attr, &scope) != 0)
      fprintf(stderr, "Unable to get scheduling scope\n");
   else {
      if (scope == PTHREAD SCOPE PROCESS)
         printf("PTHREAD SCOPE PROCESS");
      else if (scope == PTHREAD SCOPE SYSTEM)
         printf("PTHREAD SCOPE SYSTEM");
      else
         fprintf(stderr, "Illegal scope value.\n");
   }
```

Pthread Scheduling API

```
/* set the scheduling algorithm to PCS or SCS */
pthread attr setscope(&attr, PTHREAD SCOPE SYSTEM);
/* create the threads */
for (i = 0; i < NUM THREADS; i++)

pthread create(&tid[i],&attr,runner,NULL);

/* now join on each thread */
for (i = 0; i < NUM THREADS; i++)

pthread join(tid[i], NULL);

}


/* Each thread will begin control in this function */
void *runner(void *param)
{
    /* do some work ... */
pthread exit(0);
}</pre>
```

Multiple-Processor Scheduling

Multiple-Processor Scheduling

- · CPU scheduling more complex when multiple CPUs are available
- Homogeneous processors within a multiprocessor
- Asymmetric multiprocessing only one processor accesses the system data structures, alleviating the need for data sharing
- Symmetric multiprocessing (SMP) each processor is self-scheduling, all processes in common ready queue, or each has its own private queue of ready processes
 - Currently, most common
- Processor affinity process has affinity for processor on which it is currently running
 - soft affinity
 - hard affinity
 - Variations including processor sets

NUMA and CPU Scheduling



Multiple-Processor Scheduling ?? Load Balancing

Multiple-Processor Scheduling - Load Balancing

- If SMP, need to keep all CPUs loaded for efficiency
- Load balancing attempts to keep workload evenly distributed
- Push migration periodic task checks load on each processor, and if found pushes task from overloaded CPU to other CPUs
- Pull migration idle processors pulls waiting task from busy processor

Multicore Processors

Multicore Processors

- Recent trend to place multiple processor cores on same physical chip
- Faster and consumes less power
- Multiple threads per core also growing
 - Takes advantage of memory stall to make progress on another thread while memory retrieve happens

Multithreaded Multicore System

