

Documentation Parkassist

Graphische Programmierung und Simulation

at the Cooperative State University Baden-Württemberg Stuttgart

07.04.2020

Time of Project

24.03.2020 - 07.04.2020

Student ID, Course

8540946; 6430174, STG-TINF17-ITA

Lecturer

Dr. Kai Pinnow

Contents

Acronyms	I
List of Figures	II
List of Tables	III
Listings	IV
1 Introduction	1
2 D1: Time estimate based on three point estimation	2
3 D2: Feasibility study	4
3.1 Simulink model	4
3.2 Test scenario	5
3.3 Results	6
4 D3: Analysis of human velocity profile	8
4.1 Import the measurement data	8
4.2 Data preparation	8
4.3 Extracting negative acceleration	11
4.4 Separating breaking sequences	11
4.5 Result	14
5 D4*: Consideration of uneven parking spaces	15
6 D5: Discussion of inaccuracies in velocity measurement	16
7 D6: Implementation of pulse signal in Simulink	17
7.1 Computation of pulse signal frequency	17
7.2 Pulse signal generation	18
7.3 Integration into car model	19
7.4 Signal demonstration	19
8 D7: Transfer of Simulink model to ASCET	21
9 D8: Implementation of pulse signal in ASCET	23
10 D9: Implementation of unit tests for ASCET model parts	25
10.1 Unit tests for ParkAssistControl	25
10.2 Unit tests for pulse signal frequency generation	25
10.3 Unit tests for pulse signal	26

11 D10: Development and implementation of a system test environment for ASCET simulation	27
12 D11*: Plausibility check comparing measured velocities and distances	28
13 D13*: Impact of inaccuracies	29
14 D14*: Reflection	30

Acronyms

NaN Not a Number

List of Figures

3.1	Simulink model of the differential equations	5
3.2	Simulation results of feasibility study	7
4.1	Impact of applying a moving average filter on the cars velocity	10
4.2	Extracted human velocity profile	10
4.3	Human velocity profile extracted individual braking manoeuvres	12
4.4	Human velocity profile extracted braking manoeuvre 1	13
4.5	Human velocity profile extracted braking manoeuvre 2	13
7.1	Simulink model of the frequency computation subsystem	18
7.2	Simulink model of the pulse generation subsystem	19
7.3	Simulink model of the car including the pulse signal	19
7.4	Demonstration of pulse signal	20
8.1	ASCET Blockdiagramm of car	21
8.2	ASCET Blockdiagramm of driving model	21
8.3	ASCET Blockdiagramm of park assist controller	22
8.4	ASCET Blockdiagramm of park assist controller class	22
9.1	ASCET Blockdiagramm of frequency computation	23
9.2	ASCET Blockdiagramm of frequency computation class	24
9.3	ASCET Blockdiagramm of pulse signal class	24
11.1	ASCET Blockdiagramm of settings	27
11.2	ASCET Blockdiagramm of stopwatch	27

List of Tables

2.1	Three point estimation of effort for meeting requirements	2
10.1	Equivalence classes for unit testing pulse signal frequency generation . . .	25
10.2	Unit test test cases pulse signal frequency generation	26
10.3	Equivalence classes for unit testing pulse signal	26
10.4	Pulse signal test cases	26

Listings

3.1	Execution of the feasibility test	5
4.1	Import measurement data in Matlab	8
4.2	Preprocessing measurement data	9
4.3	Extracting negative acceleration	11
4.4	Separating breaking sequences	11

1 Introduction

In this project Matlab version R2019b and ASCET version 7.4 have been used. The Matlab and Simulink code is in the Matlab subfolder and the ASCET project is in the ASCET subfolder. The report is structured by devoting one chapter to each requirement.

2 D1: Time estimate based on three point estimation

For the three point estimation we use the formuals from this source¹. The expected effort is computed using a weighted mean formula:

$$E = \frac{optimistic + 4 * likely + pessimistic}{6} \quad (2.1)$$

To compute the standard deviation we use the following equation.

$$\sigma = \frac{pessimistic - optimistic}{6} \quad (2.2)$$

In the following the time unit is hours.

Table 2.1 contains our effort estimates for the tasks at hand, the expected value, computed standard deviation and the actually needed time.

Table 2.1: Three point estimation of effort for meeting requirements

Requirement	Optimistic	Likely	Pessimistic	Expected value	σ	Actual
D1	0.75	1	1.5	1.0417	0.125	0.75
D2	0.5	1	1.5	1	0.16667	1.25
D3	1.5	2	3	2.08333	0.25	4
D4	2	3	4	3	0.33333	2
D5	2	3	4	3	0.33333	3
D6	2	2.5	3	2.5	0.16667	5
D7	3	4	5	4	0.33333	3
D8	1.5	2.5	3	2.41667	0.25	1
D9	4	4.5	5	4.5	0.16667	2
D10	3	3.5	4	3.5	0.16667	2.5
D11	1	1.5	2	1.5	0.16667	2
D12	6	7	8	7	0.33333	7
D13	1	1.5	2	1.5	0.16667	1
D14	1.5	2	2.5	2	0.16667	2
Total	29,75	39	48,5	39,04167		36.5

The estimation of the 95 % confidence computed as

¹ https://de.qwe.wiki/wiki/Three-point_estimation

$$[E(project) - 2 * \sigma; E(project) + 2 * \sigma] \quad (2.3)$$

results in a confidence interval of circa [32.879; 45.292].

The total actually needed time is slightly less than the expected value. Some tasks, like D3 (human velocity profile extraction) and D6 (pulse signal in simulink) took significantly longer than expected.

-other tasks less time

Nonetheless the acutally needed time is well within 95 % confidence interval.

3 D2: Feasibility study

The aim of the feasibility study is to analyse whether it is possible to realise smooth braking with the introduced model and parameters based on the given formulas

$$\frac{\partial v}{\partial t} = -c - b * p \quad (3.1)$$

$$\frac{\partial x}{\partial t} = v \quad (3.2)$$

with $c = 1.5 \text{ m/s}^2$ and $b = 10 \text{ m/s}^2$. For that, in the next section a Simulink model is created, based on the equations above. After that, a test scenario to test the feasibility is described and in section 3.3 the results of the study are outlined.

3.1 Simulink model

Figure 3.1 shows the simulink model representing the differential equations above. The parameter p is configured on execution of the simulation in Matlab. The initial velocity v_0 is set to 10 km/h and the initial car position x_0 is set to 0, corresponding to the scenario, that should be tested. Since the output of the first integrator is in m/s, v_0 needs to be divided by 3.6 to convert v_0 from km/h to m/s. The minimal velocity of 0.29 km/h from requirement R5 has been included in the model. Otherwise, the car would not come to a full stop because the velocity would become negative eventually. R5 is realised with a switch, that sets velocity to zero if the computed velocity is below 0.29 km/h, which corresponds to approximately 0.0806 m/s. The velocity is integrated to compute the location, following the second differential equation. The output parameters acceleration (a), velocity (v) and travelled distance (s) are output using the out block. Input parameters are input as constants. In this preliminary test a constant p is used, which is not time-dependent.


```
8 set_param('D2/p','value',sprintf('%f',0.05));
9
10
11 %% Simulate and get output
12 res = sim('D2','SaveOutput','on','SaveState','on');
13 t = res.tout;
14 v = res.yout{1}.Values.Data;
15 s = res.yout{2}.Values.Data;
16 a = res.yout{3}.Values.Data;
17 %convert velocity to km/h
18 v = v*3.6;
```

Listing 3.1: Execution of the feasibility test

3.3 Results

The following figure 3.2 shows the simulation results with a constant brake pressure of 5%. This results in a constant deceleration of -2 m/s^2 . Setting the velocity to zero, when reaching the minimal velocity, has no impact on the computed acceleration. This is the reason, why the acceleration still remains the same, even though the car is not moving anymore.

The velocity linearly decreases from $v_0 = 10 \text{ km/h}$ to zero (except the decrease from minimal velocity to zero, which was expected). The third subplot shows the covered distance of the car, which is clearly under the 2 m mark. Therefore, with a constant brake pressure of 5 % the car can be stopped before reaching 2 m travelled distance with an acceptable deceleration of 2 m/s^2 . In the cruise control project we have discussed that an acceleration of less than 4 m/s^2 is not uncomfortable.

These simulation results demonstrate that it should be possible, with variation of the brake pressure over time, to realise a smooth stop with a human-like brake profile.



Figure 3.2: Simulation results of feasibility study

4 D3: Analysis of human velocity profile

In this section the provided human velocity profile is analysed in order to find a pattern that can be abstracted as a human-like brake profile. This pattern will be used in the following sections and will be adapted to the braking function of the ParkAssist. For the analysis Matlab functions are used, as demanded by requirement D3.

4.1 Import the measurement data

The human velocity profile contains a time dimension and the four wheel velocities. The following listing shows how the measurement data is imported in Matlab. A Matlab library function is used for the import of the textfile. This results in a standard numeric matrix.

```
1 %import velocity data
2 velocity_data = importdata('MeasuredVelocities.txt');
```

Listing 4.1: Import measurement data in Matlab

4.2 Data preparation

Before analysing the data it is necessary to preprocess it. The aim is to make conclusions on a brake profile. Since the brake pressure has a linear influence on the acceleration (model formula) it would be desirable to extract an acceleration curve from the human velocity profile, from which to make deductions on the brake profile. For that, a car acceleration and in consequence car velocity is needed. Therefore a car velocity has to be extracted from the four wheel velocities.

Listing 4.2 shows the matlab script, that does the preprocessing. As a first step, the four wheel velocities are extracted from the measurement data and a mean velocity is calculated (lines 2 and 3) with the following equation:

$$v_{car} = (v_{w1} + v_{w2} + v_{w3} + v_{w4})/4 \quad (4.1)$$

This mean velocity serves as an estimate for the car velocity. It is only an estimate, because friction losses, other physical influences and cornering are not considered. The mean velocity is converted to [m/s] for further calculations in line 4. For analysing the braking behaviour the acceleration can be calculated by differentiating the mean velocity. As can be seen in figure 4.1 in the upper subplot the calculated acceleration is noisy because of noise in the measured velocity. Due to the noise it would be harder to analyse the braking behaviour. Therefore, we used a moving average filter to smoothen the data (line 8). A moving average filter is calculating a mean value of neighbouring elements within a sliding window of a predefined size. Applying a moving average filter results into a filtered graph that can be seen in the lower subplot in figure 4.1. However, applying a moving average filter distorts the acceleration values because the exact value is replaced by the average of the neighbouring elements. This reduces the difference between the values of neighbouring elements. As a result the differentiation of the velocity results in an acceleration that is in our case approximately 10 times smaller than the non-filtered results. Although the values of the acceleration are smaller the relation of the acceleration is not changed. Therefore the filtered data is not used to extract exact acceleration values, but to get an understanding of the acceleration curve during braking.

The moving average filter is applied in line 8. The sliding window has a size of 200 neighbouring elements. This means that for each data point the 200 neighbour points surrounding that point are used in the filtered value computation. The factor 200 is chosen because it is big enough to reduce noise but is also small enough to maintain the general course of the graph. In line 11 and 12 the velocity is differentiated.

```
1 %compute mean velocity of all 4 wheels
2 velocity_per_wheel = velocity_data(:,2:5);
3 mean_velocity = mean(velocity_per_wheel,2);
4 mean_velocity = mean_velocity/3.6;      %convert velocity from km/h to m/s
5 raw_mean_velocity = mean_velocity;      %for demonstration purposes
6
7 %apply moving average filter to smoothen the data
8 mean_velocity = movmean(mean_velocity, 200);
9
10 %differentiate velocity to get acceleration
11 acceleration = diff(mean_velocity);
12 raw_acceleration = diff(raw_mean_velocity);      %for demonstration purposes
```

Listing 4.2: Preprocessing measurement data

Figure 4.1 shows the impact of the moving average filter on the car velocity. The course of the graph still the same, even though the absolute values are smaller than the unfiltered acceleration because of the before mentioned reasons.




Figure 4.1: Impact of applying a moving average filter on the cars acceleration

Figure 4.2 shows the smoothed extracted mean velocity of the car as well as the corresponding acceleration of the car over time.




Figure 4.2: Extracted human velocity profile

4.3 Extracting negative acceleration

As the goal is to analyse the braking behaviour only the negative acceleration is relevant and is thus being extracted from the overall acceleration (line 5). Also, all velocities that are based on a positive acceleration are not considered anymore (line 6). We decided to set those values to Not a Number (NaN) because this way we are still able to plot the velocity and the acceleration over time without cut-outs. The result can be seen in plot REF. `todo create plot`

```
1 %search for negative acceleration and set positive acceleration to NaN
2 %set all velocities that have a positive acceleration to NaN
3 neg_acceleration = acceleration;
4 decreasing_velocity = mean_velocity;
5 neg_acceleration(neg_acceleration>0) = nan;
6 decreasing_velocity(isnan(neg_acceleration)) = nan;
```

Listing 4.3: Extracting negative acceleration

4.4 Separating breaking sequences

For improved visualisation the individual breaking sequences that can be seen in plot 4.3 are stored separately. One breaking sequence consists of multiple consequent velocities. This means that the breaking sequences can be separated by searching for a gap in the velocities. Therefore, the indices of all velocities that are set not NaN are extracted (line 2) and differentiated (line 3). Considered the differentiation, every differentiation that is greater than 1 marks a gap between velocities because indices of one braking sequence are consequent (differentiation equals 1). Furthermore, small breaking sequences are not considered because they are most likely not relevant for recognizing a breaking pattern (line 13). Two individual breaking sequences can be seen in plot 4.4 and plot 4.5.

```
1 %find individual breaking sequences
2 notNaN_velocity = find(~isnan(decreasing_velocity)); % find index of every velocity
               that is not NaN -> one breaking sequence has consequent time steps -> one breaking
               sequence has consequent indices
3 diff_notNaN_velocity = diff(notNaN_velocity); % differentiate indices -> if
               indices are not consequent (unequal 1), a new breaking sequence has begun
4 n = 1; % set start values
5 start = 1;
6
7 %seperate breaking sequences with previous findings
8 for i=1:length(diff_notNaN_velocity)
9     %for every index check if indices are consequent -> equals 1
10     if diff_notNaN_velocity(i) > 1
11         %if not check if a breaking sequence consists of min 500 time
12         %steps, this way small breaking sequences are sorted out
13         if (i-start) > 500
14             %add breaking sequence to section
```

```

15         %i is end of sequence
16         section{n} = notNaN_velocity(start:i);
17         %start for new sequence is end of old sequence + 1
18         start = i+1;
19         %increment n
20         n = n+1;
21     else
22         %if breaking sequence is to small, set start for new sequence
23         %to end of old sequence + 1 anyway
24         start = i+1;
25     end
26 end
27 end

```

Listing 4.4: Separating breaking sequences




Figure 4.3: Human velocity profile extracted individual braking manoeuvres




Figure 4.4: Human velocity profile extracted braking manoeuvre 1




Figure 4.5: Human velocity profile extracted braking manoeuvre 2

4.5 Result

Considering Figures REF, REF and REF, it can be seen that the acceleration is approximately in the shape of a parable with the minimal turning point at XX. For further implementation of the ParkAssist, we will start the breaking process with an acceleration and increase it until we reach approximately REF and will then decrease it.

5 D4*: Consideration of uneven parking spaces

- diagram

- forces need to be considered (Hangabtriebskraft)

- negative slope would increase stopping time and position

- positive slope would make stopping time shorter

- negative slope critical since collision could occur

- therefore brake power would have to be increased or decreased

- physical borders need to be considered

-also when the car is stopped it should not start to roll forwards or backwards. On a plain surface, the brake can be released, after the car is stopped. A brake assist on a positive or negative slope would need to keep holding the brake or engaging the handbrake.

In the model without a minimum velocity, the velocity would become negative on braking instead of the car coming to a full stop.

6 D5: Discussion of inaccuracies in velocity measurement

-inaccuracy of velocity ± 0.1 km/h -also minimal velocity is 0.29 km/h which is not realistic, because velocity does not drop from 0.29 km/h to zero -in human velocity profile 4 tire velocities recorded -mean used to compute car velocity -because of inaccuracy in velocity computed acceleration also has inaccuracy -car driving around corner validate findings by numbers from simulation

7 D6: Implementation of pulse signal in Simulink

In D6 a pulsing information signal is described. This chapter documents the implementation of that signal. Both signals are needed for the frequency computation. The pulsing signal should only be present if the nonzero velocity of the car is ≤ 1 m/s and the position of the car is between 1 and 2 meters. From a frequency of 1 Hz at 1 meter it should rise up to 9 Hz at 1.9 meters. If the traveled distance is greater than 1.9 meters, the signal should become continuous.

This requirement can be divided into two separate components with separate responsibilities.

In the first component it is determined in which state the signal is (off, pulsing, continuous) and in the case of a pulsing signal the frequency of that pulse is computed.

The second component is responsible for outputting the pulse signal corresponding to the output of the first component.

The components are implemented using simulink subsystems which enables re-usability, encapsulation and also creates a better overview when looking at the main simulink model.

7.1 Computation of pulse signal frequency

Figure 7.1 shows the simulink subsystem for the computation of the frequency of the pulse signal. The inputs are the velocity and position of the car. The if-condition determines in which state the signal is.

In the first case the nonzero car velocity is ≤ 1 m/s and the position of the car is > 1.9 meters. In this case, the pulsing signal should provide a continuous output as demanded by requirement D6. The subsystem outputs a value of 10 in that case. This value is the indication for a continuous signal.

In the second case of the if condition the nonzero car velocity is also ≤ 1 m/s but the position of the car is between 1 and 1.9 meters. In this case the frequency of the pulsing signal should be between 1 and 9 Hz depending on the location. For that a lookup table is used, that provides an output frequency that linearly increases from 1 to 9 Hz depending on the position from 1 to 1.9 meters. A linear increase is used, because then the driver

could estimate the position linearly by the signal.

When none of the above mentioned conditions are the case, the subsystem outputs 0, which indicates that the pulsing signal is not present.




Figure 7.1: Simulink model of the frequency computation subsystem

todo output plot

7.2 Pulse signal generation

Figure 7.2 shows the simulink model of the pulse signal generator. This component provides a pulse signal with a variable frequency input. The input is the output of the before described component. Therefore if the input is 10, a continuous signal should be output. This is realised by the if-condition, which, if the input signal is 10 provides a continuous high output.

If the frequency is 0, 0 should be output.

If that is not the case either the pulse signal is generated. The frequency is the input to the integrator. The integrator has a reset input port and will be reset after each period. For each period the output of integrator will start at 0 and will go up to 1. Until the output reaches 0.5 a high pulse will be output (50 % duty cycle). This is the purpose of the less or equal 0.5 check. If the output of the integrator is greater than 0.5 a low pulse is output.




Figure 7.2: Simulink model of the pulse generation subsystem

7.3 Integration into car model

Using subsystems for the developed components makes it easy to include into and extend the existing model, which can be seen in figure 7.3.




Figure 7.3: Simulink model of the car including the pulse signal

7.4 Signal demonstration

todo neu




Figure 7.4: Demonstration of pulse signal

8 D7: Transfer of Simulink model to ASCET

- integration block as combination of multiplication and addition




Figure 8.1: ASCET Blockdiagramm of car




Figure 8.2: ASCET Blockdiagramm of driving model




Figure 8.3: ASCET Blockdiagramm of park assist controller




Figure 8.4: ASCET Blockdiagramm of park assist controller class

9 D8: Implementation of pulse signal in ASCET

- consists of two classes, one class calculates frequency, second class generates pulse signal
- frequency computation class connects two classes, passes calculated frequency to generate pulse signal
- input: velocity and position, dTs
- output: intern output: frequency, pulse signal




Figure 9.1: ASCET Blockdiagram of frequency computation

- important: sequencing
- input: velocity and position, if velocity greater zero and less or equal than 1 and if position greater than 1.9 meters return 10 for continuous pulse, else: check if position greater than 1, then frequency lookup table, else: return zero




Figure 9.2: ASCET Blockdiagram of frequency computation class

- if frequency zero, return 1, else: if frequency 0 return 0, else: integrate frequency, if integrated frequency greater than 0.5 (pulse width changes by changing this parameter, now half of period) return 1 else 0 so half of period signal high, other half low, reset integration if integrated frequency greater than 1 beziehungsweise if periode is over




Figure 9.3: ASCET Blockdiagram of pulse signal class

10 D9: Implementation of unit tests for ASCET model parts

This section covers the unit tests of all components of the ASCET model. The components were designed in a modular way to allow easy unit testing. Also wrapper classes, passing messages into the components, are used to make it possible to unit test the components. This is the only functionality the wrapper classes include. That is necessary to make sure that no new bugs are introduced by the wrapper classes, because they can not be unit tested.

The unit tests are bundled in a package called *test* in the ASCET project. The `assertLib` is imported for the assertions that are used in the unit tests. The unit tests are grouped by component with a static test class for each component. One test case corresponds to one method within the unit test classes.

Test cases are derived by analysing the requirements and finding equivalence classes. The goal of the test case coverage is to cover equivalence class and in addition to that select values that might result in errors based on experience.s

- pulse signal, drive model not possible to unit test because of time component - Messages erklären

10.1 Unit tests for ParkAssistControl

10.2 Unit tests for pulse signal frequency generation

Table 10.1: Equivalence classes for unit testing pulse signal frequency generation

Position	Velocity	Output
irrelevant	$v = 0\text{m/s}$ or $v > 1\text{m/s}$	Zero
$1\text{ m} \leq s \leq 1.9\text{ m}$	$0\text{ m/s} < v \leq 1\text{ m/s}$	$f(s) = -7.889\text{ Hz} + 8.889 * s\text{ Hz}$
$1.9\text{ m} < s \leq 2\text{ m}$	$0\text{ m/s} < v \leq 1\text{ m/s}$	Continuous (10)

Table 10.2 shows the test cases derived from the equivalence classes above.

Table 10.2: Unit test test cases pulse signal frequency generation

Test case name	Velocity [m/s]	Position [m]	Expected frequency
continuousPulse	0.5	1.91	10
noFrequencyBecauseVelocityHigh	1.5	1	1
noFrequencyBecauseVelocityZero	0	1.8	0
noFrequencyBecausePosition	0.9	0.9	0
noFrequencyBecauseVelocityAndPosition	1.1	0.9	0
frequencyLow	1.0	1.0	1
frequencyHigh	1.0	1.9	9
frequencyMid	1.0	1.5	$5.44 < \text{result} < 5.45$

10.3 Unit tests for pulse signal

The table below shows the equivalence classes for the pulse signal.

Table 10.3: Equivalence classes for unit testing pulse signal

Position	Velocity	Pulse Signal
irrelevant	$V = 0\text{m/s}$ oder $V > 1\text{m/s}$	Zero
$1\text{m} \leq X \leq 1.9\text{m}$	$0\text{m/s} < V \leq 1\text{m/s}$	Alternating 0,1
$1.9\text{m} < X \leq 2\text{m}$	$0\text{m/s} < V \leq 1\text{m/s}$	Continuous

-test cases

Table 10.4: Pulse signal test cases

Frequency	dt	Expected result
0	1	0
10	1	1

- Alternating pulse signal not possible to test because dependant of time

11 D10: Development and implementation of a system test environment for ASCET simulation

- wait 5 seconds until starting because ascet experiment environment does not display the first seconds
- in first 5 seconds brake = -0.15 to counter c and b, $v = 0$
- after five seconds set v to 10 km/h and start experiment




Figure 11.1: ASCET Blockdiagramm of settings




Figure 11.2: ASCET Blockdiagramm of stopwatch

12 D11*: Plausibility check comparing measured velocities and distances

-statistically independent ultrasonic distance and velocity -if distance to next object for ultrasonic sensor is known

-al

13 D13*: Impact of inaccuracies

-ultrasonic measurement: what if object is round? -

14 D14*: Reflection

-only 2 meter stop considered -model not realistic