

# Documentation Parkassist

## Graphische Programmierung und Simulation

at the Cooperative State University Baden-Württemberg Stuttgart

07.04.2020

**Time of Project**

24.03.2020 - 07.04.2020

**Student ID, Course**

8540946; 6430174, STG-TINF17-ITA

**Lecturer**

Dr. Kai Pinnow

# Contents

<b>Acronyms</b>	<b>I</b>
<b>List of Figures</b>	<b>II</b>
<b>List of Tables</b>	<b>III</b>
<b>Listings</b>	<b>IV</b>
<b>1 Introduction</b>	<b>1</b>
<b>2 D1: Time estimate based on three point estimation</b>	<b>2</b>
<b>3 D2: Feasibility study</b>	<b>3</b>
3.1 Simulink model . . . . .	3
3.2 Test scenario . . . . .	4
3.3 Results . . . . .	5
<b>4 D3: Analysis of human velocity profile</b>	<b>6</b>
4.1 Import the measurement data . . . . .	6
4.2 Data preparation . . . . .	6
4.3 Extracting negative acceleration . . . . .	8
4.4 Separating breaking sequences . . . . .	8
4.5 Result . . . . .	11
<b>5 D4*: Consideration of uneven parking spaces</b>	<b>12</b>
<b>6 D5: Discussion of inaccuracies in velocity measurement</b>	<b>13</b>
<b>7 D6: Implementation of pulse signal in Simulink</b>	<b>14</b>
7.1 Computation of pulse signal frequency . . . . .	14
7.2 Pulse signal generation . . . . .	15
7.3 Integration into car model . . . . .	16
7.4 Signal demonstration . . . . .	17
<b>8 D7: Transfer of Simulink model to ASCET</b>	<b>18</b>
<b>9 D8: Implementation of pulse signal in ASCET</b>	<b>19</b>
<b>10 D9: Implementation of unit tests for ASCET model parts</b>	<b>20</b>
10.1 Unit tests Frequency Computation . . . . .	20
10.2 Unit tests ParkAssistControll . . . . .	20
10.3 Unit tests Pulse Signal . . . . .	20

<b>11 D10: Development and implementation of a system test environment for ASCET simulation</b>	<b>21</b>
<b>12 D11*: Plausibility check comparing measured velocities and distances</b>	<b>22</b>
<b>13 D13*: Impact of inaccuracies</b>	<b>23</b>
<b>14 D14*: Reflection</b>	<b>24</b>

# Acronyms

NaN      Not a Number

# List of Figures

3.1	Simulink model of the differential equations . . . . .	4
3.2	Simulation results of feasibility study . . . . .	5
4.1	Human velocity profile car acceleration . . . . .	7
4.2	Smoothend data from human velocity profile . . . . .	8
4.3	Human velocity profile extracted individual braking manoeuvres . . . . .	10
4.4	Human velocity profile extracted braking manoeuvre 1 . . . . .	10
4.5	Human velocity profile extracted braking manoeuvre 2 . . . . .	11
7.1	Simulink model of the frequency computation subsystem . . . . .	15
7.2	Simulink model of the pulse generation subsystem . . . . .	16
7.3	Simulink model of the car including the pulse signal . . . . .	16
7.4	Demonstration of pulse signal . . . . .	17

# List of Tables

2.1	Three point estimation of effort for meeting requirements . . . . .	2
10.1	Equivalence classes for unit testing . . . . .	20

# Listings

3.1	Execution of the feasibility test . . . . .	4
4.1	Import measurement data in Matlab . . . . .	6
4.2	Preprocessing measurement data . . . . .	7
4.3	Extracting negative acceleration . . . . .	8
4.4	Separating breaking sequences . . . . .	9

# 1 Introduction

?? matlab version Matlba R2019b ASCET ... ascet version

todo describe block diagram vs script for every necessary requirement



## 2 D1: Time estimate based on three point estimation

Table 2.1: Three point estimation of effort for meeting requirements

Requirement	Optimistic	Likely	Pessimistic	$\langle T \rangle$	$\sigma$	Actual
D1	.	.	.	.	.	

## 3 D2: Feasibility study

The aim of the feasibility study is to analyse whether it is possible to realise a smooth stop with the introduced model and parameters based on the given formulas

$$\frac{\partial v}{\partial t} = -c - b * p \quad (3.1)$$

$$\frac{\partial x}{\partial t} = v \quad (3.2)$$

with  $c = 1.5m/s^2$  and  $b = 10m/s^2$ . For that a Simulink model is created representing the model above in the next section. After that a test scenario to test the feasibility is described and in section 3.3 the results of the study are outlined.

### 3.1 Simulink model

Figure 3.1 shows the simulink model representing the differential equations above. The parameter  $p$  is configured on execution of the simulation in Matlab. The initial velocity  $v_0$  is set to 10 km/h, corresponding to the scenario, that should be tested. Since the output of the integrator is in m/s,  $v_0$  needs to be divided by 3.6 to convert  $v_0$  from km/h to m/s. The minimal velocity of 0.29 km/h from requirement R5 has been included in the model. Otherwise, the car would not come to a full stop and the velocity would become negative eventually. This is realised by a switch, that sets velocity to zero if the computed velocity is below 0.29 km/h, which corresponds to approximately 0.0806 m/s. The velocity is integrated to compute the location, following the second differential equation. The output parameters acceleration (a), velocity (v) and travelled distance (s) are output using the out block. Input parameters are input as constants. In this preliminary test a constant  $p$  is used, which is not time-dependent.




Figure 3.1: Simulink model of the differential equations

## 3.2 Test scenario

The goal of this scenario is to check whether it is possible, with the given model, to realize a smooth stop with a position  $< 2$  m. The idea is to demonstrate, that a full stop before 2 m can be realised with a reasonable brake pedal pressure and a reasonable deceleration. If, for example a stop before 2 m could only be realised with 100 % brake pressure, that would mean that a smooth stop can not be realised.

It is not necessary to realise a human-like smooth stop, but to show that that is possible. Therefore the proposed test scenario is to run the model and find a reasonable small brake pressure where the car comes to a full stop with a position  $< 2$  m. This would show the feasibility of the task. Creating a human-like brake profile where the brake parameter  $p$  can be adjusted over time is not an objective of this feasibility study.

The execution of this scenario is automated using a matlab script, which parametrizes the model and displays the outputs. Listing ?? shows the script that executes the simulation and stores the results. The code to create the result plots has been excluded. In lines one to eight the simulation is parametrized. A stop time of 2 seconds is chosen because the car will come to a stop before.

todo solver begründen

The constant brake pressure is set to 5 %. This value results in a stop before the car traveled 2 meters of distance and is also reasonably small.

```
1 %% Parametrize Model
2 set_param('D2','StopTime','2');
3 %set solver
4 set_param('D2','Solver',['ode',sprintf('%d',8)]);
5 %set simulation step size
6 set_param('D2','FixedStep',sprintf('%f',0.01));
7 %set brake pressure parameter
8 set_param('D2/p','value',sprintf('%f',0.05));
9
```

```

10
11 %% Simulate and get output
12 res = sim('D2', 'SaveOutput', 'on', 'SaveState', 'on');
13 t = res.tout;
14 v = res.yout{1}.Values.Data;
15 s = res.yout{2}.Values.Data;
16 a = res.yout{3}.Values.Data;
17 %convert velocity to km/h
18 v = v*3.6;

```

Listing 3.1: Execution of the feasibility test

### 3.3 Results

The following figure 3.2 shows the simulation results with a constant brake pressure of 5%. This results in a constant deceleration of  $-2 \text{ m/s}^2$ . (todo acceleration remains the same but velocity does not increase) The velocity linearly decreases from  $v_0 = 10 \text{ km/h}$  to zero (except the decrease from minimal velocity to zero, which was expected). The third plot shows the covered distance of the car, which is clearly under the 2 m mark. Therefore with a constant brake pressure of 5 % the car can be stopped before reaching 2 m travelled distance with an acceptable deceleration of  $2 \text{ m/s}^2$ .

These simulation results demonstrate show that it should be possible, with variation of the brake pressure over time, to realise a smooth stop with a human-like brake profile. todo vllt mehr begründen




Figure 3.2: Simulation results of feasibility study

## 4 D3: Analysis of human velocity profile

In this section the provided human velocity profile is analysed in order to find a pattern that shows how a human is breaking a car. This pattern will be used in the following sections and will be adapted to the braking function of the ParkAssist. The analysis is divided into four steps.

-um auf bremsen rückzuschließen, beschleunigung berechnen, weil bremsen geht in beschleunigung ein

### 4.1 Import the measurement data

The measurement data is imported in Matlab.

```
1 %import velocity data
2 velocity_data = importdata('MeasuredVelocities.txt');
```

Listing 4.1: Import measurement data in Matlab

### 4.2 Data preparation

Before analysing the data it is necessary to preprocess it. First the four velocities of each wheel are extracted from the measurement data and a mean velocity is calculated (see line 1,2).

$$v_{car} = (v_{w1} + v_{w2} + v_{w3} + v_{w4}) * 4 \quad (4.1)$$

The mean velocity is converted to [m/s] for further calculations. For analysing the braking behaviour the acceleration is calculated. This can be done by differentiating the velocity (see line 11). As can be seen in figure 4.1 in the upper plot the calculated acceleration is ?? as cause of minor variations in the velocity. Due to the ?? it would be hard to analyse the braking behaviour. Therefore, we used a moving average filter to smoothen the data (line 8). A moving average filter is calculating a mean value of neighbourhood elements

within a sliding window of a predefined size. Applying a moving average filter results in a smoother graph as can be seen in the lower plot in figure 4.1.

-linear dependance between acceleration and brake pedal

```

1 %compute mean velocity of all 4 wheels
2 velocity_per_wheel = velocity_data(:,2:5);
3 mean_velocity = mean(velocity_per_wheel,2);
4 mean_velocity = mean_velocity/3.6;      %convert velocity from km/h to m/s
5 raw_mean_velocity = mean_velocity;      %for demonstration purposes
6
7 %apply moving average filter to smoothen the data
8 mean_velocity = movmean(mean_velocity, 200);
9
10 %differentiate velocity to get acceleration
11 acceleration = diff(mean_velocity);
12 raw_acceleration = diff(raw_mean_velocity);      %for demonstration purposes

```

Listing 4.2: Preprocessing measurement data




Figure 4.1: Human velocity profile car acceleration




Figure 4.2: Smoothend data from human velocity profile

### 4.3 Extracting negative acceleration

As the goal is to analyse the braking behaviour only the negative acceleration is relevant and is thus being extracted from the overall acceleration (line 5). Also, all velocities that are based on a positive acceleration are not considered anymore (line 6). We decided to set those values to Not a Number (NaN) because this way we are still able to plot the velocity and the acceleration over time without cut-outs. The result can be seen in plot REF. todo create plot

```

1 %search for negative acceleration and set positive acceleration to NaN
2 %set all velocities that have a positive acceleration to NaN
3 neg_acceleration = acceleration;
4 decreasing_velocity = mean_velocity;
5 neg_acceleration(neg_acceleration > 0) = nan;
6 decreasing_velocity(isnan(neg_acceleration)) = nan;

```

Listing 4.3: Extracting negative acceleration

### 4.4 Separating breaking sequences

For improved visualisation the individual breaking sequences that can be seen in plot 4.3 are stored separately. One breaking sequence consists of multiple consequent velocities.

This means that the breaking sequences can be separated by searching for a gap in the velocities. Therefore, the indices of all velocities that are set not NaN are extracted (line 2) and differentiated (line 3). Considered the differentiation, every differentiation that is greater than 1 marks a gap between velocities because indices of one braking sequence are consequent (differentiation equals 1). Furthermore, small breaking sequences are not considered because they are most likely not relevant for recognizing a breaking pattern (line 13). Two individual breaking sequences can be seen in plot 4.4 and plot 4.5.

```
1 %find individual breaking sequences
2 notNaN_velocity = find(~isnan(decreasing_velocity)); % find index of every velocity
   that is not NaN -> one breaking sequence has consequent time steps -> one breaking
   sequence has consequent indices
3 diff_notNaN_velocity = diff(notNaN_velocity); % differentiate indices -> if
   indices are not consequent (unequal 1), a new breaking sequence has begun
4 n = 1; % set start values
5 start = 1;
6
7 %seperate breaking sequences with previous findings
8 for i=1:length(diff_notNaN_velocity)
9     %for every index check if indices are consequent -> equals 1
10    if diff_notNaN_velocity(i) > 1
11        %if not check if a breaking sequence consists of min 500 time
12        %steps, this way small breaking sequences are sorted out
13        if (i-start) > 500
14            %add breaking sequence to section
15            %i is end of sequence
16            section{n} = notNaN_velocity(start:i);
17            %start for new sequence is end of old sequence + 1
18            start = i+1;
19            %increment n
20            n = n+1;
21        else
22            %if breaking sequence is to small, set start for new sequence
23            %to end of old sequence + 1 anyway
24            start = i+1;
25        end
26    end
27 end
```

Listing 4.4: Separating breaking sequences






Figure 4.3: Human velocity profile extracted individual braking manoeuvres




Figure 4.4: Human velocity profile extracted braking manoeuvre 1




Figure 4.5: Human velocity profile extracted braking manoeuvre 2

## 4.5 Result

Considering Figures REF, REF and REF, it can be seen that the acceleration is approximately in the shape of a parable with the minimal turning point at XX. For further implementation of the ParkAssist, we will start the breaking process with an acceleration and increase it until we reach approximately REF and will then decrease it.

## 5 D4\*: Consideration of uneven parking spaces

- diagram

- forces need to be considered (hangabtriebskraft)

- negative slope would increase stopping time and position

- positive slope would make stopping time shorter

- negative slope critical since collision could occur

- therefore brake power would have to be increased or decreased

- physical borders need to be considered

-also when the car is stopped it should not start to roll forwards or backwards. On a plain surface, the brake can be released, after the car is stopped. A brake assist on a positive or negative slope would need to keep holding the brake or engaging the handbrake.

In the model without a minimum velocity, the velocity would become negative on braking instead of the car coming to a full stop.

## 6 D5: Discussion of inaccuracies in velocity measurement

-inaccuracy of velocity  $\pm 0.1$  km/h -also minimal velocity is 0.29 km/h which is not realistic, because velocity does not drop from 0.29 km/h to zero -in human velocity profile 4 tire velocities recorded -mean used to compute car velocity -because of inaccuracy in velocity computed acceleration also has inaccuracy -car driving around corner validate findings by numbers from simulation

## 7 D6: Implementation of pulse signal in Simulink

In D6 a pulsing information signal is described. This chapter documents the implementation of that signal. Both signals are needed for the frequency computation. The pulsing signal should only be present if the nonzero velocity of the car is  $\leq 1$  m/s and the position of the car is between 1 and 2 meters. From a frequency of 1 Hz at 1 meter it should rise up to 9 Hz at 1.9 meters. If the traveled distance is greater than 1.9 meters, the signal should become continuous.

This requirement can be divided into two separate components with separate responsibilities.

In the first component it is determined in which state the signal is (off, pulsing, continuous) and in the case of a pulsing signal the frequency of that pulse is computed.

The second component is responsible for outputting the pulse signal corresponding to the output of the first component.

The components are implemented using simulink subsystems which enables re-usability, encapsulation and also creates a better overview when looking at the main simulink model.

### 7.1 Computation of pulse signal frequency

Figure 7.1 shows the simulink subsystem for the computation of the frequency of the pulse signal. The inputs are the velocity and position of the car. The if-condition determines in which state the signal is.

In the first case the nonzero car velocity is  $\leq 1$  m/s and the position of the car is  $> 1.9$  meters. In this case, the pulsing signal should provide a continuous output as demanded by requirement D6. The subsystem outputs a value of 10 in that case. This value is the indication for a continuous signal.

In the second case of the if condition the nonzero car velocity is also  $\leq 1$  m/s but the position of the car is between 1 and 1.9 meters. In this case the frequency of the pulsing signal should be between 1 and 9 Hz depending on the location. For that a lookup table is used, that provides an output frequency that linearly increases from 1 to 9 Hz depending on the position from 1 to 1.9 meters. A linear increase is used, because then the driver

could estimate the position linearly by the signal.

When none of the above mentioned conditions are the case, the subsystem outputs 0, which indicates that the pulsing signal is not present.




Figure 7.1: Simulink model of the frequency computation subsystem

todo output plot

## 7.2 Pulse signal generation

Figure 7.2 shows the simulink model of the pulse signal generator. This component provides a pulse signal with a variable frequency input. The input is the output of the before described component. Therefore if the input is 10, a continuous signal should be output. This is realised by the if-condition, which, if the input signal is 10 provides a continuous high output.

If that is not the case ... todo




Figure 7.2: Simulink model of the pulse generation subsystem

### 7.3 Integration into car model

Using subsystems for the developed components makes it easy to include into and extend the existing model, which can be seen in figure 7.3.




Figure 7.3: Simulink model of the car including the pulse signal

## 7.4 Signal demonstration




Figure 7.4: Demonstration of pulse signal



## 8 D7: Transfer of Simulink model to ASCET

- integration block as combination of multiplication and addition

## **9 D8: Implementation of pulse signal in ASCET**

# 10 D9: Implementation of unit tests for ASCET model parts

- modular design for unit tests
- pulse signal, drive model not possible to unit test because of time component

Table 10.1: Equivalence classes for unit testing

Status ParkAssist	Position	Velocity
Off	0, 1, 1.5, 1.9, 2	$V = 0\text{m/s}$ oder $V > 1\text{m/s}$
On	1, 1.5, 1.9	$0\text{m/s} < V \leq 1\text{m/s}$

## 10.1 Unit tests Frequency Computation

## 10.2 Unit tests ParkAssistControll

## 10.3 Unit tests Pulse Signal

# **11 D10: Development and implementation of a system test environment for ASCET simulation**

- wait 5 seconds until starting because ascet experiment environment does not display the first seconds
- in first 5 seconds brake = -0.15 to counter c and b,  $v = 0$
- after five seconds set  $v$  to 10 km/h and start experiment

## 12 D11\*: Plausibility check comparing measured velocities and distances

-statistically independent ultrasonic distance and velocity -if distance to next object for ultrasonic sensor is known

-al

# 13 D13\*: Impact of inaccuracies

-ultrasonic measurement: what if object is round? -

# 14 D14\*: Reflection

-only 2 meter stop considered -model not realistic