

Require: a request r : address, platform header, number, body, bulk and test flags

1: **if** r .address is a known VPN or proxy address **then refuse**

2: $p \leftarrow r$.header[HTTP_PLATFORM]

▷ A : the platform is a client claim; a header saying iOS or Android skips lines 4–5

3: **if** $p = \text{web}$ **then**

4: **if** reCAPTCHA v3 score(r) < 0.5 **then refuse**

5: **if** origin(r) $\notin$ allowed domains **then refuse**

6: **if not** r .bulk **and** country(r .number) $\notin$ allow-list **then refuse**

▷ D : premium ranges inside an allowed country pass; G : the bulk flag needs no credential

7: **if not** r .test **and** (body too long **or** number excluded) **then refuse**

▷ G : the test flag needs no credential

8: **if** sends(r .number, 1 min) ≥ 1 **then refuse**

9: **if** requests(r .address, 1 min) ≥ 5 **then refuse**

▷ B : a fresh address per request; nothing throttles a subnet or an ASN

10: **if** requests(p , country, window) $\geq$ static cap **then refuse**

▷ E : every cap is per key; nothing bounds the total or the spend

11: increment the counters read in lines 8–10

▷ F : read, then write: two racing instances both pass

12: send the SMS to r .number

▷ C : the number is never validated or priced before it is paid for

13: **return** the control that refused, or success

▷ H : each threshold can be probed, and registered numbers enumerated