procedure PROCESSREQUEST(r) ▷ a refusal releases every claim taken so far

establish the platform from the app attestation; refuse a proxy address or an invalid attestation ▷ Step 0

refuse unless r carries a valid signed session bound to its fingerprint, with at most 3 requests in 10 min ▷ Step 1

refuse a denylisted fingerprint or address; take one slot each for the address, its /24 and its ASN ▷ Step 2

if r is a web request **then** refuse a low reCAPTCHA score or a foreign origin ▷ Steps 3–4

check the number before paying for it: refuse a country off the allow-list, a premium prefix or a dead number; note sequential bursts and VoIP; read the verdict stage v of its block ▷ Step 5

refuse an invalid body or an excluded number; the bulk and test flags need an internal credential ▷ Step 6

$s \leftarrow$ Equation (1); $t \leftarrow$ TIER(s); for a client without verified history, raise t to challenge if $v = 1$ and to downgrade if $v = 2$ ▷ Step 7

if t = block **then refuse**; **if** t = challenge **then return** the challenge ▷ a solved one scores -20 on retry

take the number's backoff slot: 60 s doubling to 1 h, five sends a day ▷ Step 8

take the source caps, scaled by the adaptive multiplier ▷ Step 9

set the operating mode from the hourly budget: elevated above 80%, emergency at 100% ▷ Step 10

reserve the hourly count, the spend and the block's counter slot in one operation; past the quota, raise t for a client without verified history ▷ Step 11

send by SMS, or by push or WhatsApp if t = downgrade, after a wait if t = delay; write the state

return one uniform body after at least 400 ms ▷ the same body for sent, dropped and refused

procedure ONOUTCOME(send, outcome) ▷ verified, failed or undelivered; applied once per transition

count the outcome on every key of the send: address, /24, ASN, fingerprint, session, country, prefix and number

denylist a fine key for 24 h once it has 50 resolved sends and fewer than 10% verified

if verified **then** mark the number trusted ▷ verified history exempts a client from both destination policies

update the block's conversion statistic, and on a verification its speed statistic, each floored at $-ch$

if either statistic crosses h **then** issue a verdict for 1 h (stage 1, or stage 2 if one is active) and reset both