

# CS15: Hash Tables

[illegible]

From: [https://ascii.co.uk/art/dj#google\\_vignette](https://ascii.co.uk/art/dj#google_vignette)

# Introduction

Hash tables are often a very fast way to store and retrieve data. The basic idea of hashing is to use an array of buckets — places to put information — and insert values based on an integer value computed from a key values. The key to efficient hashing (pun!) is a good function to tell you which bucket to use for a given key. For this lab, we will explore a bad and a good hash function, and we'll also implement two strategies to handle when a bucket is already in use (collision).

## Review

## Collisions

Recall that the input value to a hash function is a key to hash, and the output of the hash function (after compression) is an index of your array. What happens when something is already present at that index? This is

known as a **collision**. We will explore two methods of collision resolution in this lab — **linear probing** and **chaining**.

## Linear Probing

For linear probing, you simply search for the next open index. So, if your hash function outputs the index 3, and something is occupying 3, then you search at index 4, then 5, and so on. Make sure to wrap around if you go over the end of the table! In other words:

```
1 indexForKey(x) = (hashFunction(x) + attempt) % table_size
```

where we start with attempt 0, and keep going until we find an empty slot.

## Chaining

Handle collisions by storing a linked list in each slot of the array. If there is a collision, simply add the element to the back of the linked list at that slot.

## The Lab

### Introduction

Hector Hash and his friends are out at a disco. Hector wants to remember his night out by storing his favorite songs played that night in a hash table. He wants to be able to quickly retrieve information associated with these songs to request them at future discos. In particular, he wants to associate each song name with the position that song has on the Billboard top 30 chart, and also the tempo of the song in beats per minute (so a DJ can do a good job blending them). While discussing hash functions with his friends, Hector and the group come up with two hash function ideas:

1. Use the length of the song name as the hash value.
2. Use the C++ `std::hash` facility.

The friends also disagree on which way of handling collisions is best. They consider probing and chaining as options. Hector has started writing a class which implements both ideas for the hash function, as well as both collision resolution techniques, but he needs your help to finish the job!

## Representing Songs

For the table, Hector is using C++ `strings` to represent the song titles (the keys), and the following `struct` to represent the values:

```

1 struct SongInfo {
2     int chartPosition;
3     int bpm;
4
5     /* Constructors for struct */
6     SongInfo()
7     {
8         chartPosition = bpm = -1;
9     }
10
11    SongInfo(int position, int tempo)
12    {
13        chartPosition = position;
14        bpm = tempo;
15    }
16 };

```

## Hash Table Classes

Hector is writing two hash table classes, `FunkeyChainingTable` and `FunkeyLinearTable`, which maintain a hash table that handles collisions with chaining and linear probing, respectively.

### Funkey Details

You'll notice a few details in the `FunkeyChainingTable` and `FunkeyLinearTable` classes. For instance,

```

1 typedef std::string KeyType;
2 typedef SongInfo ValueType;

```

These type definitions allow us to abstract the hash table classes over the details of the key and value type. In the implementation, the only code that depends on knowing the types is the print function, which could be removed after debugging. Then we could make this a template! Similarly, defined in `HashFunction.h`

```

1 enum HashFunction { BAD_HASH_FUNCTION, GOOD_HASH_FUNCTION };

```

This allows us to use variables of type `HashFunction`, whose values are either `GOOD_HASH_FUNCTION` or `BAD_HASH_FUNCTION`. This is simply a convenience to make our code more readable.

## FunkeyChainingTable

Hector is using `chainedTable`, a `std::vector`, to implement chaining:

```
1 std::vector<std::list<ChainNode>> chainedTable;
```

Each index of the of the `vector` holds a `std::list` of `ChainNodes`. Declaring a `FunkeyChainingTable` instance will create, resize, and initialize `chainedTable` to empty `lists`.

Index	Chain (std::list of ChainNodes)
0	[ ]
1	[ ]
2	[ ]
3	[ ]
4	[ ]

After a few calls to `insertChaining`, `chainedTable` might look something like this:

Index	Chain (std::list of ChainNodes)
0	"Song A": {5, 128}
1	[ ]
2	[ ]
3	"Song B": {30, 117} → "Song C": {21, 126}
4	[ ]

## FunkeyLinearTable

Hector is using `linearTable`, a `std::vector`, to implement linear probing:

```
1 std::vector<TableEntry> linearTable;
```

Each index of the of the `vector` holds a `TableEntry`. Declaring a `FunkeyLinearTable` instance will create, resize, and initialize `linearTable` to empty `TableEntrys`.

Index	0	1	2	3	4
Bucket	Empty	Empty	Empty	Empty	Empty

After a few calls to `insertProbing`, `linearTable` might look something like this:

Index	0	1	2	3	4
Bucket	Empty	"Song A": {5, 128}	"Song C": {30, 117}	Empty	"Song B": {21, 126}

## Functions to Write

Your job will be to write the functions described below (along with any helper functions you'd like to write). The functions you will write for this lab are:

```
1 FunkeyLinearTable::insertProbing(KeyType key, ValueType value,
2 HashFunction hashFunction);
```

Adds a song and its information to the hash table using either the GOOD\_HASH\_FUNCTION or the BAD\_HASH\_FUNCTION. This function handles collisions by using the linear probing method.

```
1 FunkeyChainingTable::insertChaining(KeyType key, ValueType value,
2 HashFunction hashFunction);
```

Adds a song and its information to the hash table using either the GOOD\_HASH\_FUNCTION or the BAD\_HASH\_FUNCTION. This function handles collisions by using the chaining method.

Finally:

```
1 FunkeyLinearTable::expand();
2 FunkeyChainingTable::expand();
```

Expand both tables to accommodate more values. You should expand when the load factor, which is the number of items in the table divided by the table capacity, exceeds something like 0.7.

## Other Notes

Make a directory for this lab and get the files from the usual place. You can use the `make` command to compile and link the files. The executable generated is named `funkey`.

You will need to submit the following files:

```
main.cpp
FunkeyChainingTable.cpp
FunkeyChainingTable.h
FunkeyLinearTable.cpp
FunkeyLinearTable.h
Makefile
README
```

You must submit them using Gradescope to the assignment `lab_hash_tables`. Submit these files directly, do not try to submit them in a folder.

Well done!