


Deep Open Intent Classification with Adaptive Decision Boundary

Hanlei Zhang, Hua Xu, Ting-En Lin

전북대학교 IT정보공학과
202018392
박나현

Open world classification

- 기존 심층 신경망에서는 학습한 class에 대한 확률만 출력가능
- Open set recognition
 - 모델을 학습할 때 처음 보는 class에 대한 데이터가 나타났을 때 학습 class 중 하나가 아닌 'unknown'으로 분류를 할 수 있는 기능을 수행하는 방법



Open intent classification

- Goal
 - To classify the **n-class** known intents into their corresponding classes correctly while identifying the $(n + 1)^{th}$ class open intent

User utterances	Intent Label
Book a flight from LA to Madrid.	Book flight
Can you get me a table at Steve's?	Restaurant reservation
Book Delta ticket Madison to Atlanta.	Book flight
Schedule me a table at Red Lobster.	Restaurant reservation
...	...
Can you tell me the name of this song?	Open
Look up the calories in an apple.	Open

} n개의 class로 분류

} n+1번째 새로운 class = open intent

기존 문제를 해결

기존문제


- need to design specific classifiers for identifying the open class and perform poorly with the common classifier.
- It is a complicated and time-consuming process to manually select the optimal decision condition.

제안한 모델에서 해결

- model architecture 변경 불필요
- 자동적으로 decision boundary 학습

Model architecture

- Use known intents as prior knowledge
- Propose a novel post-processing method to learn the adaptive decision boundary (ADB) for open intent classification



Intent Representation

- Use BERT model to extract deep intent features
- **Mean pooling**
 - to synthesize the high-level semantic features in one sentence
 - Get the averaged representation $\mathbf{x}_i \in \mathbb{R}^H$

$$\mathbf{x}_i = \text{mean-pooling}([CLS, T_1, \dots, T_N])$$


- **Dense layer**
 - To further strengthen feature extraction capability
 - Get the intent representation $\mathbf{z}_i \in \mathbb{R}^D$ Dimension of the intent representation

$$\mathbf{z}_i = h(\mathbf{x}_i) = \sigma(W_h \mathbf{x}_i + b_h)$$

ReLU

$$W_h \in \mathbb{R}^{H \times D} \text{ and } b_h \in \mathbb{R}^D$$

Hidden layer size




Pre-training

- Due to lack of open intent samples, we use known intents as prior knowledge to pre-train the model.
- Use Simple softmax loss to learn the intent feature z_i

$$\mathcal{L}_s = -\frac{1}{N} \sum_{i=1}^N \log \frac{\exp(\phi(z_i)^{y_i})}{\sum_{j=1}^K \exp(\phi(z_i)^j)}$$

$\phi(\cdot)$: linear classifier

$\phi(\cdot)^j$: j번째 output logits



Adaptive Decision Boundary learning

- **Decision Boundary Formulation**

- Known intent label with their corresponding labels


$$S = \{(z_i, y_i), \dots, (z_N, y_N)\}$$

- The centroid is the mean vector of embedded samples in S_k

- S_k : set of examples labeled with class k

centroid $c_k \in \mathbb{R}^D$

$$c_k = \frac{1}{|S_k|} \sum_{(z_i, y_i) \in S_k} z_i,$$



Adaptive Decision Boundary learning

- For each known intent z_i , we aim to satisfy the following constraints



$$\forall z_i \in S_k, \underbrace{\|z_i - c_k\|_2}_{\text{Euclidean distance}} \leq \underbrace{\Delta_k}_{\text{radius}},$$

- we hope examples belonging to class k are constrained in the ball area with centroid and radius.
- We use Softplus activation function as mapping between radius and the learnable parameter.

- SoftPlus

- Sigmoid 적분값, relu함수 부드럽게
- Learned radius 항상 0이상

$$\Delta_k = \log(1 + e^{\hat{\Delta}_k})$$



Adaptive Decision Boundary learning

- The suitable decision boundaries should satisfy **two conditions**
 - They should be broad enough to surround known intent samples as much as possible
 - They need to be tight enough to prevent the open intent samples from being identified as known intents

Adaptive Decision Boundary learning

- Boundary learning

- The decision boundaries should be adaptive to the intent feature space to balance both empirical and open space risk

- Open space risk : the classifier should not cover too much empty space

- Boundary Loss

$$\mathcal{L}_b = \frac{1}{N} \sum_{i=1}^N [\delta_i (\|z_i - c_{y_i}\|_2 - \Delta_{y_i}) + (1 - \delta_i) (\Delta_{y_i} - \|z_i - c_{y_i}\|_2)]$$
$$\delta_i := \begin{cases} 1, & \text{if } \|z_i - c_{y_i}\|_2 > \Delta_{y_i}, \\ 0, & \text{if } \|z_i - c_{y_i}\|_2 \leq \Delta_{y_i}. \end{cases}$$

	Empirical risk	Open space risk	결과
원 밖에 known intent	↑	↓	Boundary 늘리기
원 안에 Known intent	↓	↑	Open intent 포함


Adaptive Decision Boundary learning

- Update the boundary parameters

$$\widehat{\Delta}_k := \widehat{\Delta}_k - \eta \frac{\partial \mathcal{L}_b}{\partial \widehat{\Delta}_k}$$

Learning rate of the boundary parameter

$$\frac{\partial \mathcal{L}_b}{\partial \widehat{\Delta}_k} = \frac{\sum_{i=1}^N \delta' (y_i = k) \cdot (-1)^{\delta_i}}{\sum_{i=1}^N \delta' (y_i = k)} \cdot \frac{1}{1 + e^{-\widehat{\Delta}_k}},$$




- Boundary loss로 boundary를 intent feature space에 적용하고 적절한 decision boundary를 학습 가능

Open Classification with Decision Boundary

- After training, we use the centroids and the learned decision boundaries of each known class

- 가정

- Known intent samples are constrained in the closed ball area produced by their corresponding centroids and decision boundaries.
- The open intent samples are outside any of the bounded spherical areas



$$\hat{y} = \begin{cases} \text{open, if } \overbrace{d(\mathbf{z}_i, \mathbf{c}_k)}^{\text{Euclidean distance}} > \Delta_k, \forall k \in \mathcal{Y}; \\ \arg \min_{k \in \mathcal{Y}} d(\mathbf{z}_i, \mathbf{c}_k), \text{ otherwise,} \end{cases}$$

Intent label $\mathcal{Y} = \{1, 2, \dots, K\}$

Experiments

- Dataset

Dataset	Classes	#Training	#Validation	#Test	Vocabulary Size	Length (max / mean)
BANKING	77	9,003	1,000	3,080	5,028	79 / 11.91
OOS	150	15,000	3,000	5,700	8,376	28 / 8.31
StackOverflow	20	12,000	2,000	6,000	17,182	41 / 9.18

- BANKING**

Table 1: Statistics of BANKING, OOS and StackOverflow datasets. # indicates the total number of sentences.

- A fine-grained dataset in the banking domain

- OOS**

- A dataset for intent classification and out-of-scope prediction

- StackOverflow**

- Processed dataset, which has 20 different classes and 1000 samples for each class

Results

- Experimental setting
 - The number of known classes are varied with the proportions of 25%, 50%, and 75% in the training set.

		BANKING		OOS		StackOverflow	
Methods		Accuracy	F1-score	Accuracy	F1-score	Accuracy	F1-score
25%	MSP	43.67	50.09	47.02	47.62	28.67	37.85
	DOC	56.99	58.03	74.97	66.37	42.74	47.73
	OpenMax	49.94	54.14	68.50	61.99	40.28	45.98
	DeepUnk	64.21	61.36	81.43	71.16	47.84	52.05
	ADB	78.85	71.62	87.59	77.19	86.72	80.83
50%	MSP	59.73	71.18	62.96	70.41	52.42	63.01
	DOC	64.81	73.12	77.16	78.26	52.53	62.84
	OpenMax	65.31	74.24	80.11	80.56	60.35	68.18
	DeepUnk	72.73	77.53	83.35	82.16	58.98	68.01
	ADB	78.86	80.90	86.54	85.05	86.40	85.83
75%	MSP	75.89	83.60	74.07	82.38	72.17	77.95
	DOC	76.77	83.34	78.73	83.59	68.91	75.06
	OpenMax	77.45	84.07	76.80	73.16	74.42	79.78
	DeepUnk	78.52	84.31	83.71	86.23	72.33	78.28
	ADB	81.08	85.96	86.32	88.53	82.78	85.99

Results

Macro F1-score

		BANKING		OOS		StackOverflow	
	Methods	Open	Known	Open	Known	Open	Known
25%	MSP	41.43	50.55	50.88	47.53	13.03	42.82
	DOC	61.42	57.85	81.98	65.96	41.25	49.02
	OpenMax	51.32	54.28	75.76	61.62	36.41	47.89
	DeepUnk	70.44	60.88	87.33	70.73	49.29	52.60
	ADB	84.56	70.94	91.84	76.80	90.88	78.82
50%	MSP	41.19	71.97	57.62	70.58	23.99	66.91
	DOC	55.14	73.59	79.00	78.25	25.44	66.58
	OpenMax	54.33	74.76	81.89	80.54	45.00	70.49
	DeepUnk	69.53	77.74	85.85	82.11	43.01	70.51
	ADB	78.44	80.96	88.65	85.00	87.34	85.68
75%	MSP	39.23	84.36	59.08	82.59	33.96	80.88
	DOC	50.60	83.91	72.87	83.69	16.76	78.95
	OpenMax	50.85	84.64	76.35	73.13	44.87	82.11
	DeepUnk	58.54	84.75	81.15	86.27	37.59	81.00
	ADB	66.47	86.29	83.92	88.58	73.86	86.80

Discussion

Boundary Learning Process




Figure 3: The boundary learning process.

Balance between empirical risk and open space risk

Effect of Decision Boundary




Figure 4: Influence of the learned decision boundary.

Performance of open classification is sensitive to the size of the decision boundaries

Thank you

Baselines

- **OpenMax**

- 신경망의 학습이 모두 끝난 후, 후처리를 통한 open set recognition
- Open intent 부족으로 threshold 0.5를 default하여 사용

- DOC

- MSO

- DeepUnk





Figure 1: Overall Network of DOC





Figure 2: Open space risk of sigmoid function and desired decision boundary $d_i = T$ and probability threshold t_i .



이상 감지 (anomaly detection)

- 다수의 class를 고려하여 이상적이지 않은 데이터들의 집합을 찾는 것이라고 볼 수 있다
- 이상값은 데이터 내에서 정상적인 패턴을 따르지 않는 값을 말한다.
- 이상치와 노이즈 차이



심층신경망 분류모델 한계

- 학습한 클래스에 대한 확률만 출력 가능
- Closed set classification



Discussion

- Effect of labeled Data




Figure 5: Influence of the labeled ratio on three datasets with different known class proportions (25%, 50%, 75%).