```c
#include <stdio.h>
#include <stdlib.h>

struct Node {
  int data;
  struct Node* next;
};

struct Node* remove_below_threshold(struct Node* head, int threshold) {
  struct Node** curr = &head;
  while (*curr) {
    if ((*curr)->data < threshold) {
      struct Node* temp = *curr;
      *curr = (*curr)->next;
      free(temp);
    } else {
      curr = &(*curr)->next;
    }
  }
  return head;
}
struct Node* insert_at_index(struct Node* head, int data, int index) {
  if (index < 0) return head;

  struct Node** curr = &head;
  for (int i = 0; *curr && i < index; i++) {
    curr = &(*curr)->next;
  }

  if (index > 0 && *curr == NULL) return head;

  struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
  if (!newNode) return head;

  newNode->data = data;
  newNode->next = *curr;
  *curr = newNode;

  return head;
}

struct Node* merge_sorted_lists(struct Node* head1, struct Node* head2) {
  struct Node dummy = {0, NULL};
  struct Node* tail = &dummy;

  while (head1 && head2) {
    struct Node** minNode = (head1->data <= head2->data) ? &head1 : &head2;
    tail->next = *minNode;
    *minNode = (*minNode)->next;
    tail = tail->next;
  }
```

```
    tail->next = head1 ? head1 : head2;
    return dummy.next;
}
```