```java
import java.util.Arrays;
import java.util.Scanner;

public class lab4{
    public static void main(String[] args) {
      Scanner input = new Scanner(System.in);
      System.out.println("4 köşenin (x,y) koordinatlarini girin (toplam 8 değer:)");

      double x1 = input.nextDouble(), y1 = input.nextDouble();
      double x2 = input.nextDouble(), y2 = input.nextDouble();
      double x3 = input.nextDouble(), y3 = input.nextDouble();
      double x4 = input.nextDouble(), y4 = input.nextDouble();

      if(isCollinear(x1,y1,x2,y2,x3,y3) || isCollinear(x1,y1,x2,y2,x4,y4) ||
        isCollinear(x1,y1,x3,y3,x4,y4) || isCollinear(x2,y2,x3,y3,x4,y4)){
        System.out.println("Alan hesabi yapilamaz, noktalar ayni çizgi üzerinde!");
        return;
      }

      double a1 = y1 - y3;
      double b1 = x3 - x1;
      double c1 = a1 * x1 + b1* y1;

      double a2 = y2 - y4;
      double b2 = x4 - x2;
      double c2 = a2 * x2 + b2 * y2;

      double determinant = a1 * b2 - a2 * b1;

      double interX = (b2 * c1 - b1 * c2) / determinant;
      double interY = (a1 * c2 - a1 * c1) / determinant;

      double[] areas = new double[4];
      areas[0] = calculateTriangleArea(x1,y1,x2,y2, interX, interY);
      areas[1] = calculateTriangleArea(x2,y2,x3,y2, interX, interY);
      areas[2] = calculateTriangleArea(x3,y3,x4,y4, interX, interY);
      areas[3] = calculateTriangleArea(x4,y4,x1,y1, interX, interY);

      Arrays.sort(areas);
      System.out.println("Küçükten büyüğe üçgen alanlari: ");
      for(double area: areas){
        System.out.printf("%.2f", area);
      }
    }

    public static boolean isCollinear(double x1,double y1, double x2,double y2, double x3, double y3){
        return Math.abs(x1 *(y2-y3) + x2 * (y3-y1) + x3 * (y1-y2)) < 1e-9;
    }

    public static double calculateTriangleArea(double x1, double y1, double x2, double y2, double x3, double y3){
        return Math.abs(x1 *(y2-y3) + x2 * (y3-y1) + x3 * (y1-y2) / 2.0);
```

}

}