

safety on the large scale.

## Solar Power Generation Analysis and Forecasting on Real World Data Using LSTM and

Autoregressive CNN

Murat Göl (mgol@metu.edu.tr)

Models

METU POWER LAB

Power IOT

Nail Tosun (nail.tosun@metu.edu.tr)

(egemen.sert@metu.edu.tr)


Egemen Sert


PowerLab Research Group, METU, ANKARA

## **Abstract** Generated power of a solar panel is volatile and susceptible to environmental conditions. In this study, we analyzed variables affecting the generated power of a 17.5 kW real world solar power plant using quantitative methods. Methods show the importance of five relevant variables over the generated power: irradiance, time, panel temperature, ambient temperature and cloudiness. After designating the relevant variables, we trained three different models to predict in-day solar power forecasts of the plant. Our models are able to predict future power output of the solar power plant with less than 10% RMSE without requiring additional sensor data, e.g. camera to observe clouds. With the achieved accuracy, our study promises: fast, scalable and effective solutions to solar power plant owners and may facilitate grid

## Conclusion

Careful inspection of variables and selection of models enable accurate predictions on future generated power output of the solar power plants. We have developed a low cost method to infer the power output 1 hour early with 7.8% RMSE using Autoregressive CNN. Method promises low cost grid safety solutions.





**Figure**: Effect of relevant variables over the generated power of a 17.5kW solar power plant over six months.




Figure: Loss curve of each model under each windows size (WS) and prediction length (FS). Dashed line indicates 10% RMSE boundary.




Table: MSE of the best model for each window size where green denotes model «wavenet\_2», blue denotes model «wavenet\_4» and red denotes model «wavenet\_8>.

