

Informed search algorithms

From AIMA Slides


Outline

- Best-first search
- Greedy best-first search
- A* search
- Heuristics
- Local search algorithms
- Hill-climbing search
- Simulated annealing search
- Local beam search
- Genetic algorithms

Best-first search

- Idea: use an **evaluation function** $f(n)$ for each node
 - estimate of "desirability"
 - Expand most desirable unexpanded node
- Implementation:
Order the nodes in fringe in decreasing order of desirability
- Special cases:
 - greedy best-first search
 - A* search

Romania with step costs in km



Greedy best-first search

- Evaluation function $f(n) = h(n)$ (**h**euristic)
- = estimate of cost from n to *goal*
- e.g., $h_{SLD}(n)$ = straight-line distance from n to Bucharest
- Greedy best-first search expands the node that **appears** to be closest to goal

Greedy best-first search example



Greedy best-first search example



Greedy best-first search example



Greedy best-first search example



Properties of greedy best-first search

- **Complete?** No – can get stuck in loops, e.g., lasi → Neamt → lasi → Neamt →
- **Time?** $O(b^m)$, but a good heuristic can give dramatic improvement
- **Space?** $O(b^m)$ -- keeps all nodes in memory
- **Optimal?** No

A* search

- Idea: avoid expanding paths that are already expensive
- Evaluation function $f(n) = g(n) + h(n)$
- $g(n)$ = cost so far to reach n
- $h(n)$ = estimated cost from n to goal
- $f(n)$ = estimated total cost of path through n to goal


A* search example




A* search example



A* search example




A* search example



A* search example



A* search example




Admissible heuristics

- A heuristic $h(n)$ is **admissible** if for every node n , $h(n) \leq h^*(n)$, where $h^*(n)$ is the **true** cost to reach the goal state from n .
- An admissible heuristic **never overestimates** the cost to reach the goal, i.e., it is **optimistic**.
- Example: $h_{SLD}(n)$ (never overestimates the actual road distance)
- Theorem:** If $h(n)$ is admissible, A* using TREE-SEARCH is optimal

Optimality of A* (proof)


- Suppose some suboptimal goal G_2 has been generated and is in the fringe. Let n be an unexpanded node in the fringe such that n is on a shortest path to an optimal goal G .



- $f(G_2) = g(G_2)$ since $h(G_2) = 0$
- $g(G_2) > g(G)$ since G_2 is suboptimal
- $f(G) = g(G)$ since $h(G) = 0$
- $f(G_2) > f(G)$ from above

Optimality of A* (proof)

- Suppose some suboptimal goal G_2 has been generated and is in the fringe. Let n be an unexpanded node in the fringe such that n is on a shortest path to an optimal goal G .




- $f(G_2) > f(G)$ from above
 - $h(n) \leq h^*(n)$ since h is admissible
 - $g(n) + h(n) \leq g(n) + h^*(n)$
 - $f(n) \leq f(G)$
- Hence $f(G_2) > f(n)$, and A* will never select G_2 for expansion

Consistent heuristics

- A heuristic is **consistent** if for every node n , every successor n' of n generated by any action a ,

$$h(n) \leq c(n, a, n') + h(n')$$


- If h is consistent, we have
- $$\begin{aligned} f(n') &= g(n') + h(n') \\ &= g(n) + c(n, a, n') + h(n') \\ &\geq g(n) + h(n) \\ &= f(n) \end{aligned}$$



- i.e., $f(n)$ is non-decreasing along any path.
- Theorem:** If $h(n)$ is consistent, A* using GRAPH-SEARCH is optimal

Optimality of A*

- A* expands nodes in order of increasing f value
- Gradually adds "f-contours" of nodes
- Contour i has all nodes with $f=f_i$, where $f_i < f_{i+1}$




Properties of A*

- Complete?** Yes (unless there are infinitely many nodes with $f \leq f(G)$)
- Time?** Exponential
- Space?** Keeps all nodes in memory
- Optimal?** Yes

Admissible heuristics

E.g., for the 8-puzzle:

- $h_1(n)$ = number of misplaced tiles
- $h_2(n)$ = total Manhattan distance (i.e., no. of squares from desired location of each tile)




- $h_1(S) = ?$
- $h_2(S) = ?$

Admissible heuristics

E.g., for the 8-puzzle:

- $h_1(n)$ = number of misplaced tiles
- $h_2(n)$ = total Manhattan distance
(i.e., no. of squares from desired location of each tile)



- $h_1(S) = ?$ 8
- $h_2(S) = ?$ $3+1+2+2+2+3+3+2 = 18$

Dominance

- If $h_2(n) \geq h_1(n)$ for all n (both admissible)
- then h_2 **dominates** h_1
- h_2 is better for search
- Typical search costs (average number of nodes expanded):
- $d=12$ IDS = 3,644,035 nodes
A(h_1) = 227 nodes
A(h_2) = 73 nodes
- $d=24$ IDS = too many nodes
A(h_1) = 39,135 nodes
A(h_2) = 1,641 nodes

Relaxed problems

- A problem with fewer restrictions on the actions is called a **relaxed problem**
- The cost of an optimal solution to a relaxed problem is an admissible heuristic for the original problem
- If the rules of the 8-puzzle are relaxed so that a tile can move **anywhere**, then $h_1(n)$ gives the shortest solution
- If the rules are relaxed so that a tile can move to **any adjacent square**, then $h_2(n)$ gives the shortest solution

Local search algorithms

- In many optimization problems, the **path** to the goal is irrelevant; the goal state itself is the solution
- State space = set of "complete" configurations
- Find configuration satisfying constraints, e.g., n-queens
- In such cases, we can use **local search algorithms**
- keep a single "current" state, try to improve it

Example: n -queens

- Put n queens on an $n \times n$ board with no two queens on the same row, column, or diagonal




Hill-climbing search

- "Absent-minded blind man climbs a hill"
- Will he reach the highest peak?

```
function HILL-CLIMBING(problem) returns a state that is a local maximum
inputs: problem, a problem
local variables: current, a node
                 neighbor, a node
current ← MAKE-NODE(INITIAL-STATE[problem])
loop do
  neighbor ← a highest-valued successor of current
  if VALUE[neighbor] ≤ VALUE[current] then return STATE[current]
  current ← neighbor
```

Hill-climbing search

- Problem: depending on initial state, can get stuck in local maxima




Hill-climbing search: 8-queens problem

18	12	14	13	13	12	14	14
14	16	13	15	12	14	12	16
14	12	18	13	15	12	14	14
15	14	14	17	15	13	16	13
17	14	17	15	17	14	16	16
17	17	16	18	15	15	15	15
18	14	17	15	15	14	15	16
14	14	13	17	12	14	12	18

- h = number of pairs of queens that are attacking each other, either directly or indirectly
- $h = 17$ for the above state

Hill-climbing search: 8-queens problem



- A local minimum with $h = 1$

Simulated annealing search

- Idea: escape local maxima by allowing some "bad" moves but **gradually decrease** their frequency

```

function SIMULATED-ANNEALING(problem, schedule) returns a solution state
inputs: problem, a problem
       schedule, a mapping from time to "temperature"
local variables: current, a node
                next, a node
                T, a "temperature" controlling prob. of downward steps

current ← MAKE-NODE(INITIAL-STATE[problem])
for t ← 1 to ∞ do
    T ← schedule[t]
    if T = 0 then return current
    next ← a randomly selected successor of current
     $\Delta E \leftarrow \text{VALUE}[\text{next}] - \text{VALUE}[\text{current}]$ 
    if  $\Delta E > 0$  then current ← next
    else current ← next only with probability  $e^{\Delta E / T}$ 
    
```

Properties of simulated annealing search

- One can prove: If T decreases slowly enough, then simulated annealing search will find a global optimum with probability approaching 1
- Widely used in VLSI layout, airline scheduling, etc

Local beam search

- Keep track of k states rather than just one
- Start with k randomly generated states
- At each iteration, all the successors of all k states are generated
- If any one is a goal state, stop; else select the k best successors from the complete list and repeat.

Genetic algorithms

- A successor state is generated by combining two parent states
- Start with k randomly generated states (**population**)
- A state is represented as a string over a finite alphabet (often a string of 0s and 1s)
- Evaluation function (**fitness function**). Higher values for better states.
- Produce the next generation of states by selection, crossover, and mutation

Genetic algorithms



- Fitness function: number of non-attacking pairs of queens (min = 0, max = $8 \times 7/2 = 28$)
- $24/(24+23+20+11) = 31\%$
- $23/(24+23+20+11) = 29\%$ etc

Genetic algorithms

