

```
In [1]: import numpy as np
import matplotlib.pyplot as plt

# Dataset generation

data_dict = {'CSE':33, 'ECE':28, 'EEE':30}

courses = list(data_dict.keys())

values = list(data_dict.values())

fig = plt.figure(figsize = (10, 5))


# Bar plot
plt.bar(courses, values, color = 'green', width = 0.5)

plt.xlabel("Courses offered")

plt.ylabel("No. of students enrolled")

plt.title("Students enrolled in different courses")

plt.show()
```



```
In [2]: import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import itertools
```

```
In [4]: import pandas as pd


plotdata = pd.DataFrame({
    "2018": [57, 67, 77, 83],
    "2019": [68, 73, 80, 79],
    "2020": [73, 78, 80, 85]},
    index=["Django", "Gafur", "Tommy", "Ronnie"])

plotdata.plot(kind="bar", figsize=(15, 8))

plt.title("FIFA ratings")
plt.xlabel("Footballer")
```

```
plt.ylabel("Ratings")
```

Out[4]: Text(0, 0.5, 'Ratings')



```
In [5]: import pandas as pd

plotdata = pd.DataFrame({
    "2018": [57, 67, 77, 83],
    "2019": [68, 73, 80, 79],
    "2020": [73, 78, 80, 85]},
```

```
index=["Django", "Gafur", "Tommy", "Ronnie"])


plotdata.plot(kind='bar', stacked=True, figsize=(15, 8))

plt.title("FIFA ratings")

plt.xlabel("Footballer")

plt.ylabel("Ratings")
```

Out[5]: Text(0, 0.5, 'Ratings')



```
In [8]: import numpy as np
import matplotlib.pyplot as plt


# creating the dataset
data = {'C':20, 'C++':15, 'Java':30, 'Python':35}

courses = list(data.keys())
values = list(data.values())

fig = plt.figure(figsize = (10, 5))

# creating the bar plot
plt.bar(courses, values, color = 'blue', width = 0.4)

plt.xlabel("Courses offered")
plt.ylabel("No. of students enrolled")
plt.title("Students enrolled in different courses")
plt.show()
```



```
In [15]: import pandas as pd
from matplotlib import pyplot as plt

# Read CSV into pandas
data = pd.read_csv("C:/Users/USER/Desktop/MLLABDOCS-11OCT2021/CARS-02.csv")
data.head()
df = pd.DataFrame(data)

name = df['car'].head(12)
price = df['price'].head(12)

# Figure Size
fig = plt.figure(figsize=(10, 7))

# Horizontal Bar Plot
plt.bar(name[0:10], price[0:10])

# Show Plot
plt.show()
```

KeyError

Traceback (most recent call last)

```

~\anaconda3\lib\site-packages\pandas\core\indexes\base.py in get_loc(self, key, method, tolerance)
    2894         try:
-> 2895             return self._engine.get_loc(casted_key)
    2896         except KeyError as err:

```

```

pandas\_libs\index.pyx in pandas._libs.index.IndexEngine.get_loc()

```

```

pandas\_libs\index.pyx in pandas._libs.index.IndexEngine.get_loc()

```

```

pandas\_libs\hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjectHashTable.get_item()

```

```

pandas\_libs\hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjectHashTable.get_item()

```

KeyError: 'car'

The above exception was the direct cause of the following exception:

```

KeyError                                Traceback (most recent call last)
<ipython-input-15-e1ec922caf80> in <module>
      7 df = pd.DataFrame(data)
      8
----> 9 name = df['car'].head(12)
     10 price = df['price'].head(12)
     11

```

```

~\anaconda3\lib\site-packages\pandas\core\frame.py in __getitem__(self, key)
    2900         if self.columns.nlevels > 1:
    2901             return self._getitem_multilevel(key)
-> 2902         indexer = self.columns.get_loc(key)
    2903         if is_integer(indexer):
    2904             indexer = [indexer]

```

```

~\anaconda3\lib\site-packages\pandas\core\indexes\base.py in get_loc(self, key, method, tolerance)
    2895         return self._engine.get_loc(casted_key)
    2896         except KeyError as err:
-> 2897             raise KeyError(key) from err
    2898
    2899         if tolerance is not None:

```

KeyError: 'car'

```

In [22]: import pandas as pd
        from matplotlib import pyplot as plt

        # Read CSV into pandas
        data = pd.read_csv("C:/Users/USER/Desktop/MLLABDOCS-11OCT2021/CARS-02.csv")

```

```
data.head()
df = pd.DataFrame(data)
```

```
-----
KeyError                                Traceback (most recent call last)
~\anaconda3\lib\site-packages\pandas\core\indexes\base.py in get_loc(self, key, method, tolerance)
    2894         try:
-> 2895             return self._engine.get_loc(casted_key)
    2896         except KeyError as err:
```

```
pandas\_libs\index.pyx in pandas._libs.index.IndexEngine.get_loc()
```

```
pandas\_libs\index.pyx in pandas._libs.index.IndexEngine.get_loc()
```

```
pandas\_libs\hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjectHashTable.get_item()
```

```
pandas\_libs\hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjectHashTable.get_item()
```

KeyError: 0

The above exception was the direct cause of the following exception:

```
KeyError                                Traceback (most recent call last)
<ipython-input-22-b876da49bdf2> in <module>
      7 df = pd.DataFrame(data)
      8
----> 9 df[data[0]]

~\anaconda3\lib\site-packages\pandas\core\frame.py in __getitem__(self, key)
    2900         if self.columns.nlevels > 1:
    2901             return self._getitem_multilevel(key)
-> 2902         indexer = self.columns.get_loc(key)
    2903         if is_integer(indexer):
    2904             indexer = [indexer]

~\anaconda3\lib\site-packages\pandas\core\indexes\base.py in get_loc(self, key, method, tolerance)
    2895         return self._engine.get_loc(casted_key)
    2896         except KeyError as err:
-> 2897             raise KeyError(key) from err
    2898
    2899         if tolerance is not None:
```

KeyError: 0