

5. List

October 18, 2022

1 Introduction

- List is a heterogeneous collection which allows us to put many objects in a single object
- Lists are ordered and we have an index to access.
- Lists are created using square brackets.
- List items are ordered, changeable, and allow duplicate values.

```
[1]: cities = ["bangalore", "mumbai", "delhi", "kolkata"]
```

```
[2]: print(cities)
```

```
['bangalore', 'mumbai', 'delhi', 'kolkata']
```

```
[3]: type(cities)
```

```
[3]: list
```

```
[4]: even_nos = [2, 40, 16, 8, 10, 62, 74, 98, 32]
```

```
[5]: type(even_nos)
```

```
[5]: list
```

```
[6]: multi = ["hi", 78, True, 3.14, "sorry"]    # list can contain different types of ↵  
      ↪objects
```

```
[7]: type(multi)
```

```
[7]: list
```

2 Length of List

- Use len function

```
[8]: len(cities)
```

```
[8]: 4
```

```
[9]: len(even_nos)
```

```
[9]: 9
```

3 Empty List

```
[10]: e1 = list()
```

```
[11]: len(e1)
```

```
[11]: 0
```

```
[12]: type(e1)
```

```
[12]: list
```

```
[13]: e12 = []
```

4 Accessing elements of the List

- Elements of the List can be accessed using **indexing**
- We can use the index operator `[]` (square brackets) to access an item in a list.
- In Python, indices start at 0(zero). So, a list having 5 elements will have an index from 0 to 4.
- Trying to access indexes other than these will raise an **IndexError**.
- The index must be an integer. We can't use float or other types, this will result in **TypeError**.
- Python allows negative indexing for its sequences. The index of -1 refers to the last item, -2 to the second last item and so on.

```
[14]: cities
```

```
[14]: ['bangalore', 'mumbai', 'delhi', 'kolkata']
```

```
[15]: cities[0]
```

```
[15]: 'bangalore'
```

```
[16]: cities[1]
```

```
[16]: 'mumbai'
```

```
[17]: cities[2]
```

```
[17]: 'delhi'
```

```
[18]: cities[3]
```

```
[18]: 'kolkata'
```

```
[19]: cities[-1]
```

```
[19]: 'kolkata'
```

```
[20]: cities[-2]
```

```
[20]: 'delhi'
```

```
[21]: cities[4]
```

```
-----  
IndexError                                Traceback (most recent call last)  
Cell In [21], line 1  
----> 1 cities[4]  
  
IndexError: list index out of range
```

```
[22]: cities[-5]
```

```
-----  
IndexError                                Traceback (most recent call last)  
Cell In [22], line 1  
----> 1 cities[-5]  
  
IndexError: list index out of range
```

5 List Slicing

- We can access a range of items in a list by using the slicing operator : (colon).

```
[23]: even_nos
```

```
[23]: [2, 40, 16, 8, 10, 62, 74, 98, 32]
```

```
[24]: len(even_nos)
```

```
[24]: 9
```

```
[26]: even2 = even_nos[2:8]
```

```
[27]: even2
```

```
[27]: [16, 8, 10, 62, 74, 98]
```

```
[28]: even_nos[:6]
```

```
[28]: [2, 40, 16, 8, 10, 62]
```

```
[29]: even_nos[3:]
```

```
[29]: [8, 10, 62, 74, 98, 32]
```

6 Modifying a List

- Lists are mutable, meaning their elements can be changed
- We can use the assignment operator = to change an item or a range of items.

```
[30]: cities
```

```
[30]: ['bangalore', 'mumbai', 'delhi', 'kolkata']
```

```
[31]: cities[2] = 'pune'
```

```
[32]: cities
```

```
[32]: ['bangalore', 'mumbai', 'pune', 'kolkata']
```

6.1 Modify using index range

```
[34]: cities
```

```
[34]: ['bangalore', 'mumbai', 'pune', 'kolkata']
```

```
[35]: cities[1:3]
```

```
[35]: ['mumbai', 'pune']
```

```
[36]: cities[1:3] = ["chennai", "jaipur"]
```

```
[37]: cities
```

```
[37]: ['bangalore', 'chennai', 'jaipur', 'kolkata']
```

7 Properties of Lists

1. Heterogeneous (any data type!)
2. Ordered (numbered from 0 to n-1)
3. Have random access to any element (Using index)
4. Number of elements can change very easily.
5. Lists are mutable

8 Methods of List

1. `append(elem)`
2. `extend(L)`
3. `insert(i, elem)`
4. `remove(elem)`
5. `pop([i])`
6. `clear()`
7. `index(elem)`
8. `count(elem)`
9. `sort()`
10. `reverse()`

8.1 `append(elem)`

- Add item `elem` at the end of the list

```
[38]: cities
```

```
[38]: ['bangalore', 'chennai', 'jaipur', 'kolkata']
```

```
[39]: cities.append("pune")
```

```
[40]: cities
```

```
[40]: ['bangalore', 'chennai', 'jaipur', 'kolkata', 'pune']
```

8.2 `extend(L)`

- Add all items in given list `L` to the end

```
[41]: cities2 = ["mysore", "nagpur", "bhopal"]
```

```
[42]: cities
```

```
[42]: ['bangalore', 'chennai', 'jaipur', 'kolkata', 'pune']
```

```
[43]: cities.extend(cities2)
```

```
[44]: cities
```

```
[44]: ['bangalore',  
      'chennai',  
      'jaipur',  
      'kolkata',  
      'pune',  
      'mysore',  
      'nagpur',
```

```
'bhopal']
```

8.3 insert(i, elem)

- Insert item elem at position i

```
[50]: cities
```

```
[50]: ['bangalore',  
      'mumbai',  
      'mumbai',  
      'chennai',  
      'jaipur',  
      'kolkata',  
      'pune',  
      'mysore',  
      'nagpur',  
      'Surat',  
      'bhopal']
```

```
[48]: cities.insert(1, "mumbai")
```

```
[49]: cities.insert(-1, "Surat")
```

```
[51]: cities
```

```
[51]: ['bangalore',  
      'mumbai',  
      'mumbai',  
      'chennai',  
      'jaipur',  
      'kolkata',  
      'pune',  
      'mysore',  
      'nagpur',  
      'Surat',  
      'bhopal']
```

8.4 remove(elem)

- Remove first item that is equal to elem, from the list

```
[52]: cities
```

```
[52]: ['bangalore',  
      'mumbai',  
      'mumbai',
```

```
'chennai',  
'jaipur',  
'kolkata',  
'pune',  
'mysore',  
'nagpur',  
'Surat',  
'bhopal']
```

```
[53]: cities.remove('mumbai')
```

```
[54]: cities
```

```
[54]: ['bangalore',  
'mumbai',  
'chennai',  
'jaipur',  
'kolkata',  
'pune',  
'mysore',  
'nagpur',  
'Surat',  
'bhopal']
```

8.5 pop([i])

- Remove and return item at position i (last item if i is not provided)

```
[55]: cities
```

```
[55]: ['bangalore',  
'mumbai',  
'chennai',  
'jaipur',  
'kolkata',  
'pune',  
'mysore',  
'nagpur',  
'Surat',  
'bhopal']
```

```
[56]: cities.pop()
```

```
[56]: 'bhopal'
```

```
[57]: cities
```

```
[57]: ['bangalore',  
      'mumbai',  
      'chennai',  
      'jaipur',  
      'kolkata',  
      'pune',  
      'mysore',  
      'nagpur',  
      'Surat']
```

```
[58]: cities.pop(3)
```

```
[58]: 'jaipur'
```

```
[59]: cities
```

```
[59]: ['bangalore',  
      'mumbai',  
      'chennai',  
      'kolkata',  
      'pune',  
      'mysore',  
      'nagpur',  
      'Surat']
```

```
[60]: c = cities.pop()
```

```
[61]: c
```

```
[61]: 'Surat'
```

8.6 index(elem)

- Return index of first item that is equal to elem

```
[66]: cities
```

```
[66]: ['bangalore',  
      'mumbai',  
      'chennai',  
      'kolkata',  
      'pune',  
      'mysore',  
      'nagpur',  
      'mumbai']
```

```
[67]: cities.index('mumbai')
```


[67]: 1

```
[64]: cities.index('chennai')
```

[64]: 2

```
[65]: cities.append("mumbai")
```

8.7 count(elem)

- Return the number of items that is equal to elem

```
[68]: cities.count('mumbai')
```

[68]: 2

8.8 sort()

- Sort items in a list in ascending order
- To sort in descending order use `reverse = True`

```
[71]: cities
```

```
[71]: ['bangalore',  
      'chennai',  
      'kolkata',  
      'mumbai',  
      'mumbai',  
      'mysore',  
      'nagpur',  
      'pune']
```

```
[70]: cities.sort()
```

```
[73]: cities
```

```
[73]: ['pune',  
      'nagpur',  
      'mysore',  
      'mumbai',  
      'mumbai',  
      'kolkata',  
      'chennai',  
      'bangalore']
```

```
[80]: cities.sort(reverse = True)
```

```
[74]: cities
```

```
[74]: ['pune',  
       'nagpur',  
       'mysore',  
       'mumbai',  
       'mumbai',  
       'kolkata',  
       'chennai',  
       'bangalore']
```

8.9 reverse()

- Reverse the order of items in a list

```
[118]: cities = ['bangalore',  
                 'mumbai',  
                 'Surat',  
                 'chennai',  
                 'jaipur',  
                 'kolkata',  
                 'pune',  
                 'nagpur',  
                 'Surat', 'pune']
```

```
[121]: cities
```

```
[121]: ['bangalore',  
       'mumbai',  
       'Surat',  
       'chennai',  
       'jaipur',  
       'kolkata',  
       'nagpur',  
       'Surat',  
       'pune']
```

```
[76]: cities.reverse()
```

```
[77]: cities
```

```
[77]: ['Surat',  
       'nagpur',  
       'pune',  
       'kolkata',  
       'jaipur',  
       'chennai',
```

```
'Surat',  
'mumbai',  
'bangalore']
```

8.10 clear()

- Remove all items and empty the list

```
[78]: cities.clear()
```

```
[79]: cities
```

```
[79]: []
```

9 Deleting a List

- Use del

```
[81]: even_nos
```

```
[81]: [2, 40, 16, 8, 10, 62, 74, 98, 32]
```

```
[82]: del even_nos
```

```
[83]: even_nos
```

```
-----  
NameError                                Traceback (most recent call last)  
Cell In [83], line 1  
----> 1 even_nos  
  
NameError: name 'even_nos' is not defined
```

10 Operators on List

1. Membership
2. Arithmetic

10.1 Membership

- in
- not in

```
[84]: multi
```

```
[84]: ['hi', 78, True, 3.14, 'sorry']
```

```
[85]: 78 in multi
```

```
[85]: True
```

```
[86]: 40 not in multi
```

```
[86]: True
```

```
[87]: 'hi' not in multi
```

```
[87]: False
```

```
[88]: True in multi
```

```
[88]: True
```

10.2 Arithmetic

- +
- *

```
[89]: p = [1, 2, 3]  
      q = [4, 5, 6]
```

```
[90]: p + q
```

```
[90]: [1, 2, 3, 4, 5, 6]
```

```
[91]: p * 3
```

```
[91]: [1, 2, 3, 1, 2, 3, 1, 2, 3]
```

11 Nested Lists

- List as a List element or we can say list inside a list
- Nested lists are accessed using nested indexing.

```
[92]: nest1 = ["Monday", "Today", [1, 2, 3]]
```

```
[93]: nest1[0]
```

```
[93]: 'Monday'
```

```
[94]: nest1[2]
```

```
[94]: [1, 2, 3]
```

```
[95]: nest1[2][0]
```

```
[95]: 1
```

A matrix can be represented using a nested list

```
[96]: mx = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
```

```
[97]: mx
```

```
[97]: [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
```

```
[98]: mx[0][2]
```

```
[98]: 3
```

12 split and join methods of String

12.1 split()

- The `split()` method splits a string into a **list**.
- You can specify the separator with **sep**, default separator is any whitespace.
- Maximum number of splits to do can be specified with **maxsplit**.

```
[99]: sentence = "When the winter comes, the lone wolf dies but the pack survives."
```

```
[101]: words = sentence.split()
```

```
[102]: words
```

```
[102]: ['When',  
       'the',  
       'winter',  
       'comes',  
       'the',  
       'lone',  
       'wolf',  
       'dies',  
       'but',  
       'the',  
       'pack',  
       'survives.']
```

```
[103]: sentence
```

```
[103]: 'When the winter comes, the lone wolf dies but the pack survives.'
```

```
[104]: sentence.split(",")
```

```
[104]: ['When the winter comes', ' the lone wolf dies but the pack survives.']
```

```
[105]: sentence.split(maxsplit=2) #maxsplit: Maximum number of splits to do.
```

```
[105]: ['When', 'the', 'winter comes, the lone wolf dies but the pack survives.']
```

12.2 join()

- The join() method takes all items in an iterable and joins them into one string.
- A string must be specified as the separator.
- Syntax: string.join(iterable)

```
[106]: sentence_list = ['When',  
    'the',  
    'winter',  
    'comes',  
    'the',  
    'lone',  
    'wolf',  
    'dies',  
    'but',  
    'the',  
    'pack',  
    'survives.']
```

```
[111]: " ".join(sentence_list)
```

```
[111]: 'Whenhithehiwinterhicomes,hithehilonehiwolfdieshibuthithehipackhisurvives.'
```

```
[108]: seperator = " "
```

```
[109]: seperator.join(sentence_list)
```

```
[109]: 'When the winter comes, the lone wolf dies but the pack survives.'
```

13 For Loop on List

```
[112]: sentence_list
```

```
[112]: ['When',  
    'the',  
    'winter',  
    'comes',  
    'the',
```

```
'lone',  
'wolf',  
'dies',  
'but',  
'the',  
'pack',  
'survives.']
```

```
[113]: for i in sentence_list:  
        print(i)  
        print('.-'*4)
```

```
When  
.-.-.-.-  
the  
.-.-.-.-  
winter  
.-.-.-.-  
comes,  
.-.-.-.-  
the  
.-.-.-.-  
lone  
.-.-.-.-  
wolf  
.-.-.-.-  
dies  
.-.-.-.-  
but  
.-.-.-.-  
the  
.-.-.-.-  
pack  
.-.-.-.-  
survives.  
.-.-.-.-
```

13.1 Nested For Loop

```
[114]: matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
```

```
[117]: for i in matrix:  
        print(i)  
        for j in i:  
            print('\t',j+2)  
            print('\n'*10)
```

[1, 2, 3]
 3
 \\\\/\\\/\\\/\\\/\\\/\\/
 4
 \\\\/\\\/\\\/\\\/\\\/\\/
 5
 \\\\/\\\/\\\/\\\/\\\/\\/
 [4, 5, 6]
 6
 \\\\/\\\/\\\/\\\/\\\/\\/
 7
 \\\\/\\\/\\\/\\\/\\\/\\/
 8
 \\\\/\\\/\\\/\\\/\\\/\\/
 [7, 8, 9]
 9
 \\\\/\\\/\\\/\\\/\\\/\\/
 10
 \\\\/\\\/\\\/\\\/\\\/\\/
 11
 \\\\/\\\/\\\/\\\/\\\/\\/