



**Address:- office no 126, Raut Arcade, opp
Subway near railway station virar east.**

Cont No. 9834617404

HTML

HTML is an acronym which stands for Hyper Text Markup Language which is used for creating web pages and web applications. Let's see what is meant by Hypertext Markup Language, and Web page.

Hyper Text: HyperText simply means "Text within Text." A text has a link within it, is a hypertext. Whenever you click on a link which brings you to a new webpage, you have clicked on a hypertext. HyperText is a way to link two or more web pages (HTML documents) with each other.

Markup language: A markup language is a computer language that is used to apply layout and formatting conventions to a text document. Markup language makes text more interactive and dynamic. It can turn text into images, tables, links, etc.

Web Page: A web page is a document which is commonly written in HTML and translated by a web browser. A web page can be identified by entering an URL. A Web page can be of the static or dynamic type. With the help of HTML only, we can create static web pages.

Features of HTML

It is a very easy and simple language. It can be easily understood and modified.

It is very easy to make an effective presentation with HTML because it has a lot of formatting tags.

It is a markup language, so it provides a flexible way to design web pages along with the text.

HTML Formatting

HTML Formatting is a process of formatting text for better look and feel. HTML provides us ability to format text without using CSS. There are many formatting tags in HTML. These tags are used to make text bold, italicized, or underlined. There are almost 14 options available that how text appears in HTML and XHTML.

This is a physical tag, which is used to bold the text written between it.

This is a logical tag, which tells the browser that the text is important.

<i>

This is a physical tag which is used to make text italic.

This is a logical tag which is used to display content in italic.

<mark>

This tag is used to highlight text.

<u> This tag is used to underline text written between it.

<strike>

This tag is used to draw a strikethrough on a section of text. (Not supported in HTML5)

<sup>

It displays the content slightly above the normal line.

<sub>

It displays the content slightly below the normal line.

This tag is used to display the deleted content.

<ins>

This tag displays the content which is added

<big>

This tag is used to increase the font size by one conventional unit.

<small>

This tag is used to decrease the font size by one unit from base font size.

HTML Heading

A HTML heading or HTML h tag can be defined as a title or a subtitle which you want to display on the webpage. When you place the text within the heading tags

<h1>.....</h1>, it is displayed on the browser in the bold format and size of the text depends on the number of heading.

Paragraph

HTML paragraph or HTML p tag is used to define a paragraph in a webpage.

Emphasized text

This tag is used to emphasize the text, and displayed the text in italic form. The text written between `<em>` and `</em>` tag will italicized the text.

Code tags

The HTML `<code>` `</code>` element is used to display the part of computer code. It will display the content in monospaced font.

Address tag

An HTML `<address>` tag defines the contact information about the author of the content.

The content written between <address> and </address> tag, then it will be displayed in italic font.

HTML Anchor

The HTML anchor tag defines a hyperlink that links one page to another page. It can create hyperlink to other web page as well as files, location, or any URL. The "href" attribute is the most important attribute of the HTML a tag. and which links to destination page or URL

Appearance of HTML anchor tag

An unvisited link is displayed underlined and blue.

A visited link displayed underlined and purple.

An active link is underlined and red.

HTML Image

HTML img tag is used to display image on the web page. HTML img tag is an empty tag that contains attributes only, closing tags are not used in HTML image element.

HTML Table

HTML table tag is used to display data in tabular form (row * column). There can be many columns in a row.

We can create a table to display data in tabular form, using <table> element, with the help of <tr> , <td>, and <th> elements.

In Each table, table row is defined by <tr> tag, table header is defined by <th>, and table data is defined by <td> tags.

HTML tables are used to manage the layout of the page e.g. header section, navigation bar, body content, footer section etc. But it is

recommended to use div tag over table to manage the layout of the page .

<table>

It defines a table.

<tr>

It defines a row in a table.

<th>

It defines a header cell in a table.

<td>

It defines a cell in a table.

<caption>

It defines the table caption.

<tbody>

It is used to group the body content in a table.

<thead>

It is used to group the header content in a table.

<tfoot>

It is used to group the footer content in a table.

Table with colspan

If you want to make a cell span more than one column, you can use the colspan attribute.

Table with cell padding

You can specify padding for table header and table data by two ways:

By cellpadding attribute of table in HTML

By padding property in CSS

Table with rowspan

If you want to make a cell span more than one row, you can use the rowspan attribute.

It will divide a cell into multiple rows. The number of divided rows will depend on rowspan values.

HTML <template> tag

HTML <template> tag is used to hold the client-side content that will not render at the time of page load, but it can be instantiated during runtime using JavaScript.

The content of the template will not be displayed until it is not activated using JavaScript. The browser processes the content of the <template> element while loading the page to ensure that the content is valid, the contents are not rendered, however.

It can also be useful when you want to use same content multiple times in your HTML document without any change

Textarea

The HTML <textarea> tag is used to define a multi-line text input control.

It can hold unlimited number of characters and the texts are displayed in a fixed-width font (usually courier)

Time Tag

HTML <time> tag is used to define date and time. It displays time value in a 24 hour clock or a precise date in a Gregorian calendar in HTML.

Unordered List | HTML Bulleted List

HTML Unordered List or Bulleted List displays elements in bulleted format . We can use unordered list where we do not need to display items in any particular order. The HTML ul tag is used for the unordered list. There can be 4 types of bulleted list:

disc

circle

square

none

Video Tag

HTML 5 supports <video> tag also. The HTML video tag is used for streaming video files such as a movie clip, song clip on the web page.

Currently, there are three video formats supported for HTML video tag:

mp4

webM

ogg

HTML Video Tag

Let's see the list of HTML 5 video tag attributes.

controls

It defines the video controls which is displayed with play/pause buttons.

height

It is used to set the height of the video player.

width

It is used to set the width of the video player.

poster It specifies the image which is displayed on the screen when the video is not played.

autoplay

It specifies that the video will start playing as soon as it is ready.

loop

It specifies that the video file will start over again, every time when it is completed.

muted

It is used to mute the video output.

src

It specifies the source URL of the video file.

HTML Video Tag Attribute Example

Let's see the example of video tag in HTML where we are using height, width, autoplay, controls and loop attributes.

```
<video width="320" height="240" controls  
autoplay loop>
```

```
  <source src="movie.mp4"  
type="video/mp4">
```

Your browser does not support the html video tag.

```
</video>
```

HTML SVG

The HTML SVG is an acronym which stands for Scalable Vector Graphics.

HTML SVG is a modularized language which is used to describe graphics in XML. It describes

two-dimensional vector and mixed vector/raster graphics in XML. It is a W3C recommendation. SVG images and their behaviors are defined in XML text files. So as XML files, you can create and edit an SVG image with text editor, but generally drawing programs like inkspace are preferred to create it

```
<svg width="100" height="100">  
  <circle cx="50" cy="50" r="40"  
stroke="yellow" stroke-width="4" fill="red" />  
</svg>
```

HTML Canvas Tag

The HTML canvas element provides HTML a bitmapped surface to work with. It is used to draw graphics on the web page.

The HTML 5 <canvas> tag is used to draw graphics using scripting language like JavaScript.

The <canvas> element is only a container for graphics, you must need a scripting language to draw the graphics. The <canvas> element allows for dynamic and scriptable rendering of 2D shapes and bitmap images.

Example

```
<canvas id = "mycanvas" width ="200" height  
="100"> </canvas>
```

HTML Ordered List | HTML Numbered List

HTML Ordered List or Numbered List displays elements in numbered format. The HTML ol tag is used for ordered list. We can use ordered list to represent items either in numerical order format or alphabetical order format, or any format where an order is emphasized. There can be different types of numbered list:

Numeric Number (1, 2, 3)

Capital Roman Number (I II III)

Small Roman Number (i ii iii)

Capital Alphabet (A B C)

Small Alphabet (a b c)

HTML Description List | HTML Definition List

HTML Description List or Definition List displays elements in definition form like in dictionary. The <dl>, <dt> and <dd> tags are used to define description list.

The 3 HTML description list tags are given below:

<dl> tag defines the description list.

<dt> tag defines data term.

<dd> tag defines data definition (description).

HTML Form

An HTML form is a section of a document which contains controls such as text fields,

password fields, checkboxes, radio buttons, submit button, menus etc.

An HTML form facilitates the user to enter data that is to be sent to the server for processing such as name, email address, password, phone number, etc. .

Why use HTML Form

HTML forms are required if you want to collect some data from of the site visitor.

For example: If a user want to purchase some items on internet, he/she must fill the form such as shipping address and credit/debit card details so that item can be sent to the given address.

HTML Form Tags

Let's see the list of HTML 5 form tags.

`<form>`

It defines an HTML form to enter inputs by the used side.

<input>

It defines an input control.

<textarea>

It defines a multi-line input control.

<label>

It defines a label for an input element.

<fieldset>

It groups the related element in a form.

<legend>

It defines a caption for a <fieldset> element.

<select>

It defines a drop-down list.

<optgroup>

It defines a group of related options in a drop-down list.

<option>

It defines an option in a drop-down list.

<button>

It defines a clickable button.

Class Attribute in HTML

The HTML class attribute is used to specify a single or multiple class names for an HTML element. The class name can be used by CSS and JavaScript to do some tasks for HTML elements. You can use this class in CSS with a specific class, write a period (.) character, followed by the name of the class for selecting elements.

HTML Id Attribute

The id attribute is used to specify the unique ID for an element of the HTML document. It allocates the unique identifier which is used by the CSS and the JavaScript for performing certain tasks.

HTML iframes

HTML Iframe is used to display a nested webpage (a webpage within a webpage). The HTML <iframe> tag defines an inline frame, hence it is also called as an Inline frame.

An HTML iframe embeds another document within the current HTML document in the rectangular region.

The webpage content and iframe contents can interact with each other using JavaScript.

Iframe Syntax

An HTML iframe is defined with the <iframe> tag:

```
<iframe src="URL"></iframe>
```

```
<iframe src="https://alvinitolutions.in/"  
style="height:300px;width:400px"></iframe>
```

HTML Audio Tag

HTML audio tag is used to define sounds such as music and other audio clips. Currently there are three supported file format for HTML 5 audio tag.

mp3

wav

ogg

HTML <frame> tag (Not supported in HTML5)

HTML <frame> tag define the particular area within an HTML file where another HTML web page can be displayed.

```
<frameset cols="25%,50%,25%">
```

```
<frame src="frame1.html" >
```

```
<frame src="frame2.html">
```

```
<frame src="frame3.html">
```

```
</frameset>
```

Marquee HTML

The Marquee HTML tag is a non-standard HTML element which is used to scroll a image or text horizontally or vertically.

HTML Progress Tag

HTML <progress> tag is used to display the progress of a task. It provides an easy way for web developers to create progress bar on the website. It is mostly used to show the progress of a file uploading on the web page.

```
<progress value="80"  
max="100"></progress>
```

HTML Section Tag

The HTML <section> tag is used to define sections in a document. When you put your content on a web page, it may contains many chapters, headers, footers, or other sections on a web page that is why HTML <section> tag is used.

HTML Div Tag

The HTML <div> tag is used to group the large section of HTML elements together.

HTML Section Tag

The HTML <section> tag is used to define sections in a document. When you put your content on a web page, it may contains many chapters, headers, footers, or other sections on a web page that is why HTML <section> tag is used.

HTML Div Tag

The HTML <div> tag is used to group the large section of HTML elements together.