



Learning JavaScript

PRAVEEN NAIR

What is JavaScript?

Used to program the behavior of web pages
JavaScript was invented by Brendan Eich in 1995.

JavaScript code is inserted between `<script>` and `</script>` tags.

Javascript was developed by Netscape

JavaScript vs VBScript (Microsoft)

Javascript supports all browser, vbscript supports IE

Originally Sun Microsystem and now Oracle

First Program

```
let a=10; // line break also works  
let b=20;  
let c = a + b;  
console.log(c);
```

Comments // and /*

```
let name='John';  
    let age=20  
    /*  
console.log(name)  
*/
```

Printing using backtick

```
let n=2;  
let s = `Price of an apple is ${n}`;  
document.write(s)
```

.....

Also called template literals....try multiline

Math Operators

Addition + (also concatenates string)

Subtraction -

Multiplication *

Division /

Remainder %

Exponentiation **

Comparison Operators

Operator	Description	Comparing	Returns
==	equal to	x == 8	FALSE
		x == 5	TRUE
		x == "5"	TRUE
===	equal value and equal type	x === 5	TRUE
		x === "5"	FALSE
!=	not equal	x != 8	TRUE
!==	not equal value or not equal type	x !== 5	FALSE
		x !== "5"	TRUE
		x !== 8	TRUE
>	greater than	x > 8	FALSE
<	less than	x < 8	TRUE
>=	greater than or equal to	x >= 8	FALSE
<=	less than or equal to	x <= 8	TRUE

Logical Operators

Logical NOT (!)

Logical AND (&&)

Logical OR (||)

Precedence of AND && is higher than OR ||

Conditional branching: if

```
let n = 7
if (n%2==0){
  console.log("Even Number")
}
else{
  console.log("Odd Number")
}
```

while loop

```
while (condition) {  
    ...  
}
```

For loop

```
for (let i = 0; i < 3; i++) {  
  console.log(i);  
}
```

Try break and continue

JavaScript Functions

```
function showMsg() {  
    console.log( 'Hello World!' );  
}
```

```
showMsg();
```

Passing arguments

```
function sum(a, b) {  
  c = a + b;  
  console.log(c);  
}  
sum(1, 2);
```

Returning Values

```
function sum(a, b) {  
  return a + b;  
}  
  
let result = sum(1, 2);  
console.log( result ); // 3
```

Variables

let

const (constant, can't be changed)

Var –

var is function scoped and let is block scoped. Variable declared by let cannot be redeclared

Variables are case-sensitive, try camelCase, titlecase, with dash

Data Types (Primitive/Value type)

1. `let n=2;`
2. `let s = "Hello World";` //double or single quote
3. `let flag = true;` //true or false - boolean
4. `let name;` //undefined
5. `let cost=null;`

Type conversion

```
let value = true;  
console.log(typeof value); // Boolean  
value = String(value);
```

```
let numStr="34";  
num = Number(numStr); // becomes a number 123
```

```
console.log(Boolean(num))
```

/* Values that are intuitively “empty”, like 0, an empty string, null, undefined, and NaN, become false. Other values become true.*/

Data Types (Reference Type)

1. Objects
2. Arrays
3. Functions

Function Expressions

```
let sayHello = function() {  
    console.log( "Hello World" );  
};
```

```
sayHello();
```

Arrow functions

```
let result = (a, b) => {  
  let c = a + b  
  return c  
};
```

```
let result = function(a, b) {  
  let c = a + b  
  return c;  
};
```

```
console.log(result(3, 2) );
```

Arrow Functions Recap

```
let a = b = 10  
const fnc = () => a + b //no braces and return is needed
```

```
let a = b = 10  
const fnc = () => return a + b //can't use return without braces
```

```
let a = 10;  
const fnc = x => x + 20; //no brackets for x needed  
console.log(fnc(a));
```

```
let a = (b = 10);  
const fnc = () => {  
  return a + b; //return is needed if braces are used  
};
```

Objects – Keyed Collections

```
let student = {  
  name: "Smitha",  
  age: 30  
};  
console.log(student.name) // student["house address"]  
console.log(student.age)  
Console.log(student)
```

Objects – Spread Operator

```
const student = {  
  name:"John",  
  age:21  
}  
  
//spread operator  
const obj = {...student,city:"NYC"}  
console.log(obj)
```

Objects – return

```
let a = b = 10  
  const fnc = () => ({name:'John'}) //need bracket if returning obj  
  console.log(fnc());
```


Array Items – foreach, map

```
let fruits = ["apple", "mango", "orange"];
  fruits.forEach((value,index,arr) => {
    console.log(value,index,arr);
  });
let fruits = ["apple", "mango", "orange"];
  fruits.map((value, index, arr) => {
    console.log(value, index, arr);
  });
```

Array Items – Spread Operator

```
const names = ["Vivek","Shivam","Aman"]
```

```
const arr = [...names,"Suresh"]
```

```
console.log(arr)
```

Array Items – filter and find

```
let score = [34, 12, 67, 89, 30];  
  let result = score.filter((v) => {  
    return v > 40;  
  });  
  console.log(result);  
.....  
let empnum = [1003, 1005, 1006, 1034];  
  let result = empnum.find((v) => {  
    return v == 1003;  
  });  
  console.log(result);
```

Reduce method

```
function calculateTotal() {  
  let total = cart.reduce((sum, item) => sum + item.price * item.quantity, 0);  
  return total;  
}
```

Array Items – some method

```
let marks = [10,60,80,40]
  let result = marks.some((value)=>{
    return value > 30
  })
  console.log(result)
```

Array Items – every method

```
let marks = [10,60,80,40]
  let result = marks.every((value)=>{
    return value > 30
  })
  console.log(result)
```

console.table

```
let array = ["a","b"]
```

```
console.table(array)
```

Array of Objects

```
<script>
  const products = [
    { name: "Product 1", price: 300 },
    { name: "Product 2", price: 100 },
    { name: "Product 3", price: 500 },
  ];
  const cart = [];
  let item = products[0];
  item.quantity = 2;
  item.total = item.quantity * item.price;
  cart.push(item);
  item = products[2];
  item.quantity = 3;
  item.total = item.quantity * item.price;
  cart.push(item);
  console.log(cart);
  let orderValue = cart.reduce((sum, value) => {
    return sum + value.total;
  }, 0);
  console.log("Order Value is", orderValue);
</script>
```


(IIFE) immediately invoked function expression

```
(function functionName() {  
  console.log("Hello World");  
})();
```

```
(function functionName() {  
  console.log("Hello World");  
})();
```

Array from method

```
<script>
```

```
  let arr = Array.from("aeiou");
```

```
  document.write(arr);
```

```
</script>
```

Ternary/conditional operator ‘?’

```
let isEligible = (age > 18) ? true : false;
```

Try multiple condition
condition1

 ? true_expression1

 : condition2

 ? true_expression2

 : else_expression2

Switch statement

```
let price = 40;

switch (price) {
  case 30:
    console.log( 'Too Cheap' );
    break;

  case 40:
    console.log( 'Perfect Price' );
    break;

  case 50:
    console.log( 'Too Costly' );
    break;

  default:
    console.log( "I don't know the price" );
}
```

Functions (...args) vs arguments

```
<script>
function sum(){
  let sum=0
  for (let i=0;i<arguments.length;i++){
    sum = sum + arguments[i]
  }
  console.log(sum)
}
sum(2,3,4,5)
```

```
.....
function sum(...args) {
  let sum = 0;
  for (let i = 0; i < args.length; i++) {
    sum = sum + args[i];
  }
  console.log(sum);
}
sum(2, 3, 4, 5);
```

```
</script>
```

Module Import/Export - multiple

```
function add(x,y){  
  return x+y  
}  
function subtract(x,y){  
  return x-y  
}  
  
export {add, subtract}  
  
.....  
import {add,subtract} from "./calc.js"  
  let sum = add(4,5)  
  console.log(sum)  
  let difference = subtract(8,3)  
  console.log(difference)
```