```sql
-- find top 5 batsman in ipl
SELECT batter, SUM(total_run) AS 'run'
FROM nishu.ipl
GROUP BY batter
ORDER BY run DESC LIMIT 5;
-- find the 2nd highest six hitter in ipl

SELECT batter,COUNT(*) AS 'num_sixes'
FROM nishu.ipl
WHERE batsman_run= 6
GROUP BY batter
ORDER BY num_sixes DESC LIMIT 1,1;

-- TOP 5 BATSMAN WITH HIGEST STRIKERATE WHO HAVE PLAYED MORE THAN 1000
BALLS
SELECT batter, SUM(batsman_run), COUNT(batsman_run),
ROUND((SUM(batsman_run)/COUNT(batsman_run))*100,2) AS 'sr'
FROM nishu.ipl
GROUP BY batter
HAVING COUNT(batsman_run) > 1000
ORDER BY sr DESC LIMIT 5;

-- revision
-- WHERE CLAUSE BASIC FILTERING
-- Q1
SELECT * FROM nishu.ipl
WHERE BattingTeam = 'Rajasthan Royals';

-- Q2
SELECT batter , bowler , batsman_run , total_run
FROM nishu.ipl
WHERE batsman_run > 4;

-- Q3
SELECT *
FROM nishu.ipl
WHERE total_run = 6;

-- Q4
SELECT *
FROM nishu.ipl
WHERE batsman_run IN (1 ,3);

SELECT *
FROM nishu.ipl
WHERE batsman_run BETWEEN 1 AND 3;

-- Q5
SELECT *
FROM nishu.ipl
WHERE BattingTeam = 'Mumbai Indians' AND batsman_run >4;

-- ORDER BY CLAUSE
-- Q1
SELECT batter , batsman_run , total_run
FROM nishu.ipl
ORDER BY batsman_run ASC;
```

```sql
-- Q2
SELECT batter , batsman_run , total_run
FROM nishu.ipl
ORDER BY batsman_run DESC;

-- Q3
SELECT BattingTeam , total_run
FROM nishu.ipl
ORDER BY BattingTeam ASC, total_run DESC;

-- Q4
SELECT *
FROM nishu.ipl
WHERE batsman_run >0
ORDER BY batsman_run DESC;

-- GROUP BY CLAUSE
-- Q1
SELECT BattingTeam , SUM(total_run) AS runs
FROM nishu.ipl
GROUP BY BattingTeam
ORDER BY runs DESC LIMIT 5;
SELECT SUM(total_run)
FROM nishu.ipl;

-- Q2
SELECT BattingTeam , COUNT(*) AS total_delivery
FROM nishu.ipl
GROUP BY BattingTeam
ORDER BY total_delivery DESC;

-- Q3
SELECT batter , SUM(batsman_run)
FROM nishu.ipl
GROUP BY batter;

-- Q4
SELECT bowler , SUM(total_run)
FROM nishu.ipl
GROUP BY bowler;

-- Q5
SELECT kind , COUNT(*) AS total_wicket
FROM nishu.ipl
WHERE isWicketDelivery = 1
GROUP BY kind
ORDER BY total_wicket DESC LIMIT 2;

-- Q6
SELECT extra_type , SUM(extras_run) AS extra_runs
FROM nishu.ipl
GROUP BY extra_type;

-- Q7
SELECT BattingTeam , COUNT(*) AS total_deliveries
FROM nishu.ipl
GROUP BY BattingTeam
ORDER BY total_deliveries DESC;
```

```sql
-- Q8
SELECT BattingTeam , SUM(total_run) AS total
FROM nishu.ipl
GROUP BY BattingTeam
ORDER BY total DESC;

 -- WHERE + GROUP BY
 -- Q1
 SELECT batter , SUM(batsman_run)
 FROM nishu.ipl
WHERE batsman_run> 0
GROUP BY batter;

-- Q2
SELECT SUM(total_run ) AS total_run, (BattingTeam)
FROM nishu.ipl
WHERE innings = 1
GROUP BY BattingTeam;

-- Q3
SELECT SUM(batsman_run) AS total_run , batter
FROM nishu.ipl
WHERE BattingTeam = 'Royal Challengers Bangalore'
GROUP BY batter;

-- Q4
SELECT COUNT(*) AS total_deliveries , batter
FROM nishu.ipl
WHERE batsman_run > 0
GROUP BY batter;

-- Q5
SELECT SUM(total_run) AS total_run , BattingTeam
FROM nishu.ipl
WHERE overs >=10
GROUP BY BattingTeam;

-- Q6
SELECT COUNT(isWicketDelivery) AS total_wicket , BattingTeam
FROM nishu.ipl
WHERE isWicketDelivery = 1
GROUP BY BattingTeam;

-- HAVING CLAUSE
-- Q1
SELECT SUM(batsman_run) AS total_run , batter
FROM nishu.ipl
GROUP BY batter
HAVING SUM(batsman_run) > 500;

-- Q2
SELECT BattingTeam , SUM(total_run) AS total
FROM nishu.ipl
GROUP BY BattingTeam
HAVING total>10000;

-- Q3
```

```sql
SELECT bowler , COUNT(*) AS delivery
FROM nishu.ipl
GROUP BY bowler
HAVING delivery >1000;

-- Q4
SELECT batter , SUM(batsman_run) AS total_run
FROM nishu.ipl
GROUP BY batter
HAVING total_run BETWEEN 1000 AND 2000;

-- WHERE + GROUP BY + HAVING
-- Q1
SELECT batter , SUM(batsman_run) AS total
FROM nishu.ipl
WHERE batsman_run > 0
GROUP BY batter
HAVING total > 300;

-- Q2
SELECT BattingTeam , SUM(total_run) AS total
FROM nishu.ipl
WHERE innings = 1
GROUP BY BattingTeam
HAVING total > 5000;

-- Q3
SELECT bowler , SUM(total_run) AS total
FROM nishu.ipl
WHERE total_run > 0
GROUP BY bowler
HAVING SUM(total_run) >2000;

SELECT bowler , COUNT(*) AS total
FROM nishu.ipl
WHERE total_run > 0
GROUP BY bowler
HAVING COUNT(*) >2000;

-- Q4
SELECT BattingTeam , SUM(batsman_run) AS total
FROM nishu.ipl
WHERE batsman_run IN (4 ,6)
GROUP BY BattingTeam
HAVING total >1000;

-- Q5
SELECT batter , SUM(total_run) AS total
FROM nishu.ipl
GROUP BY batter
HAVING total > 500
ORDER BY total DESC;

-- Q6
SELECT BattingTeam , COUNT(*) AS delivery
FROM nishu.ipl
GROUP BY BattingTeam
HAVING delivery > 5000
```

```
ORDER BY delivery DESC;

-- CHALLENGING QUESTIONS WITHOUT USING JOIN CTE WINDOW OR SUBQUERIES
-- Q1
SELECT SUM(total_run) AS total , batter
FROM nishu.ipl
GROUP BY batter
HAVING total > 1000
ORDER BY total DESC;

-- Q2
SELECT kind , COUNT(*) AS dismissal
FROM nishu.ipl
WHERE isWicketDelivery = 1
GROUP BY kind
HAVING dismissal > 100;

-- Q3
SELECT SUM(total_run) AS total , BattingTeam
FROM nishu.ipl
WHERE innings = 2
GROUP BY BattingTeam
HAVING total > 5000
ORDER BY total DESC;

-- Q4
SELECT SUM(total_run) AS total , batter
FROM nishu.ipl
WHERE BattingTeam = 'Chennai Super Kings'
GROUP BY batter
HAVING total > 500
ORDER BY total DESC;

-- Q5
SELECT BattingTeam , SUM(extras_run) AS extra
FROM nishu.ipl
GROUP BY BattingTeam
HAVING extra > 300
ORDER BY extra DESC;

-- Q6
SELECT COUNT(*) AS delivery , batter
FROM nishu.ipl
GROUP BY batter
HAVING delivery > 1000
ORDER BY delivery DESC;

-- Q7
SELECT BattingTeam , SUM(batsman_run) AS total
FROM nishu.ipl
WHERE batsman_run >= 4
GROUP BY BattingTeam
HAVING total > 2000
ORDER BY total DESC;

-- COMPLETE DOSTO , KEEP GROWING
```