Disclaimer

- The material provided in this document is not my original work and is a summary of some one else's work(s).
- A simple Google search of the title of the document will direct you to the original source of the material.
- I do not guarantee the accuracy, completeness, timeliness, validity, non-omission, merchantability or fitness of the contents of this document for any particular purpose.
- Downloaded from najeebkhan.github.io

Message Scheduling for the FlexRay protocol

The Dynamic Segment

03

Presented By

Message Scheduling for the FlexRay protocol

The Dynamic Segment

03

Presented By Najeeb 2013 - 5 - 30

Outline



- Introduction
- Message Schedule for the DS
- **Message Grouping**
- Optimal Scheduling of Messages
- **Results**
- **Conclusion**

Introduction



Introduction

03

We discuss the scheduling of messages in the dynamic segment of the FlexRay

Introduction

- We discuss the scheduling of messages in the dynamic segment of the FlexRay
- In this paper bounds on the generation times and the timing requirements of the signals is taken into consideration to propose a reservation-based scheduling approach that preserves the flexible medium access of the DS





 \bowtie FC \rightarrow SS + DS + SW +NIT



- \bowtie FC \rightarrow SS + DS + SW +NIT
- The smallest time unit in the DS is the minislot (MS) with a duration of T_{MS} (in milliseconds), and the DS contains a fixed number of N_{DS} MS




- \bowtie FC \rightarrow SS + DS + SW +NIT
- The smallest time unit in the DS is the minislot (MS) with a duration of T_{MS} (in milliseconds), and the DS contains a fixed number of N_{DS} MS
- If a message is transmitted in a DYS, then the length of the DYS is equal to the number of MS needed for message transmission. Otherwise, the length of the DYS is one MS



- \bowtie FC \rightarrow SS + DS + SW +NIT
- The smallest time unit in the DS is the minislot (MS) with a duration of T_{MS} (in milliseconds), and the DS contains a fixed number of N_{DS} MS
- If a message is transmitted in a DYS, then the length of the DYS is equal to the number of MS needed for message transmission. Otherwise, the length of the DYS is one MS
- The arbitration procedure ensures that only frames with a FID that equals the current value of the slot counter can be transmitted



- \bowtie FC \rightarrow SS + DS + SW +NIT
- The smallest time unit in the DS is the minislot (MS) with



be transmitted

CB

The length of a sporadic message can be computed, including the signal data s in multiples of two-byte words, the FlexRay framing overhead s*4bits + OF, and the communication-free DYS idle phase as



The length of a sporadic message can be computed, including the signal data s in multiples of two-byte words, the FlexRay framing overhead s*4bits + OF, and the communication-free DYS idle phase as

$$l_m^n = \lceil (s_m^n \cdot 16 \text{ bits} + s_m^n \cdot 4 \text{ bits} + O_F) \tau_{\text{bit}} / T_{\text{MS}} \rceil$$



03


ightharpoonupPrevious work on the scheduling of DS uses DM approach and also assumes that T_C , T_{SS} and T_{DS} are pre-determined



- ightharpoonupPrevious work on the scheduling of DS uses DM approach and also assumes that T_C , T_{SS} and T_{DS} are pre determined
- Real How DM fails?




M_1^n	lm_1^n	dm_1^n	FID
	[MS]	[ms]	
M_1^1	2	15	1
M_1^2	2	15	2
M_1^3	2	15	3
M_1^4	2	15	4
M_1^5	40	15	5
M_{1}^{6}	40	15	6
M_1^{7}	40	15	7
M_1^8	112	25	8



FlexRay Software Architecture

FlexRay Software Architecture





03

 \bowtie A reservation R for a node n is a 4-tuple (n,rp,w,l) with the reservation period rp ∈ N, the offset w ∈ {0,...,rp-1} and the reservation length l ∈ N

- \bowtie A reservation R for a node n is a 4-tuple (n,rp,w,l) with the reservation period rp ∈ N, the offset w ∈ {0,...,rp-1} and the reservation length l ∈ N
- \bowtie R stands for 1 MS that are reserved at all FCs (z*rp+w), z ∈ N₀, while 1 MS is reserved in the remaining FCs

- \bowtie A reservation R for a node n is a 4-tuple (n,rp,w,l) with the reservation period rp ∈ N, the offset w ∈ {0,...,rp-1} and the reservation length l ∈ N
- \bowtie R stands for 1 MS that are reserved at all FCs (z*rp+w), z ∈ N₀, while 1 MS is reserved in the remaining FCs
- Bandwidth reservation per FC for a given R is $B_R = 1/rp$ MS


- \bowtie A reservation R for a node n is a 4-tuple (n,rp,w,l) with the reservation period rp ∈ N, the offset w ∈ {0,...,rp-1} and the reservation length l ∈ N
- \bowtie R stands for 1 MS that are reserved at all FCs (z*rp+w), z ∈ N₀, while 1 MS is reserved in the remaining FCs
- Bandwidth reservation per FC for a given R is $B_R = 1/rp$ MS
- Reach reservation is associated with a FID

03

A reservatio
 with the res
 {0,...,rp−1} ar

R stands for (z*rp+w), z remaining Fo

Randwidth $B_R = 1/rp MS$







CB

If Tc is chosen larger than d, transmitting M multiple times in the same FC does not guarantee that M meets the deadline




- If Tc is chosen larger than d, transmitting M multiple times in the same FC does not guarantee that M meets the deadline
- Hence, it must hold that Tc ≤ dmin, where dmin is the minimum deadline among all sporadic message deadlines.





admonany (ip. i) ie = am and hence ip ann, ie i




- (≈ Additionally (rp+1) " 1c ≤ am and nence rp=am/1c-1

Example Revisited



Example Revisited





Performance Metrics



CB

Cycle Load L_j: The maximum number of MS that is reserved for message transmission in FC j for an arbitrary assignment of FIDs, considering that at most one FID can be assigned per message

CB

- Cycle Load L_j: The maximum number of MS that is reserved for message transmission in FC j for an arbitrary assignment of FIDs, considering that at most one FID can be assigned per message
- \subset L_j includes both the case where no message is transmitted for an FID (duration of 1 MS) and the case where a message is transmitted

CB

- Cycle Load L_j: The maximum number of MS that is reserved for message transmission in FC j for an arbitrary assignment of FIDs, considering that at most one FID can be assigned per message
- CR L_j includes both the case where no message is transmitted for an FID (duration of 1 MS) and the case where a message is transmitted

$$L_j = \sum_{R \in \mathcal{R}_j} l + \left(|\mathcal{M}_{\mathrm{S}}| - \sum_{R \in \mathcal{R}_j} 1 \right) = \sum_{R \in \mathcal{R}_j} (l - 1) + |\mathcal{M}_{\mathrm{S}}|.$$

Where
$$j = (z \cdot rp + w)$$





We define the maximum cycle load as



We define the maximum cycle load as

$$L_{\max} = \max_{j \in \{1, \dots, rp\}} (Lj)$$



We define the maximum cycle load as

$$L_{\max} = \max_{j \in \{1, \dots, rp\}} (Lj)$$

then, we choose N_{DS} = L_{max} and minimize L_{max} to determine a feasible schedule with the shortest possible DS





Randwidth Reservation: Indicate the number of MS reserved per FC for each node n∈N and for all of the nodes

03

Randwidth Reservation: Indicate the number of MS reserved per FC for each node n∈N and for all of the nodes

$$B^{n} = \sum_{R \in \mathcal{R}^{n}} (l/rp)$$

$$\sum_{n=1}^{N} B^{n}$$

Message Grouping

CS

```
Algorithm 4.1 (Check and Add)
Input: M_l^n, \mathcal{G}_q^n, \mathcal{G}^n.
Init: result = more\_fit

if (P_{q,l}^n < 0 \text{ or } RM_{q,l}^n < 1)

result = no\_fit

else

\mathcal{G}_q^n := \mathcal{G}_q^n \cup \{M_l^n\} \text{ and } \mathcal{G}^n = \mathcal{G}^n \cup \mathcal{G}_q^n

if (RM_{q,l}^n = 1)

result = last\_fit

return result
```

Message Grouping

CB

```
\begin{aligned} &\textbf{Algorithm 4.2 (Group)} \\ &\textbf{Input: } LM_{\mathrm{S}}^{n}, M_{\mathrm{c}}^{n}, \mathcal{G}_{q}^{n}, \mathcal{G}^{n} \\ &(\textbf{while } M_{\mathrm{c}}^{n} < \textbf{last}(LM_{\mathrm{S}}^{n})) \\ &M_{\mathrm{c}}^{n} = \textbf{next}(M_{\mathrm{c}}^{n})) \\ &temp\mathcal{G}_{q}^{n} = \mathcal{G}_{q}^{n} \\ &\text{result = } \textbf{Check and } \textbf{Add}(M_{\mathrm{c}}^{n}, temp\mathcal{G}_{q}^{n}, \mathcal{G}^{n}) \\ &\textbf{if (result = } more\_fit \text{ and } M_{\mathrm{c}}^{n} \neq \textbf{last}(LM_{\mathrm{S}}^{n})) \\ &tempM_{\mathrm{c}}^{n} = M_{\mathrm{c}}^{n} \\ &\textbf{Group } (LM_{\mathrm{S}}^{n}, tempM_{\mathrm{c}}^{n}, temp\mathcal{G}_{q}^{n}, \mathcal{G}^{n}) \end{aligned}
```

cate N={1,2}. We assume that the groups in G have been computed as

No. 1991 (1992)	50: AMP (a)
$\mathcal{G}_1 = \{M_1^1\}, pm_1^1 = 3, dm_1^1 = 5$	$\mathcal{G}_2 = \{M_1^1, M_2^1\},\$
$R_1 = (1, \bar{2}, w_1, 2\bar{0})$	$R_2 = (1, 2, w_2, 30)$
$\mathcal{G}_3 = \{M_2^1\}, pm_2^1 = 5, dm_2^1 = 7$	$\mathcal{G}_4 = \{M_3^1\}, pm_3^1 = 4, dm_3^1 = 6$
$R_3 = (1, \bar{4}, w_3, 3\bar{0})$	$R_4 = (1, 3, w_4, 10)$
$\mathcal{G}_5 = \{M_1^2\}, pm_1^2 = 3, dm_1^2 = 7$	$\mathcal{G}_6 = \{M_1^2, M_2^2\}$
$R_5 = (2, 2, w_5, 22)$	$R_6 = (2, 2, w_6, 48)$
$\mathcal{G}_7 = \{M_1^2, M_2^2, M_3^2\}$	$\mathcal{G}_8 = \{M_1^2, M_3^2\}$
$R_7 = (2, 2, w_7, 48)$	$R_8 = (2, 2, w_8, 30)$
$\mathcal{G}_9 = \{M_1^2, M_4^2\}$	$\mathcal{G}_{10} = \{M_2^2\}, pm_2^2 = 7, dm_2^2 = 9$
$R_9 = (2, 2, w_9, 42)$	$R_{10} = (2, \bar{6}, w_{10}, \bar{48})$
$\mathcal{G}_{11} = \{M_3^2\}, pm_3^2 = 7, dm_3^2 = 9$	$\mathcal{G}_{12} = \{M_4^2\}, pm_4^2 = 5, dm_4^2 = 5$
$R_{11} = (2, 6, w_{11}, 30)$	$R_{12} = (2, 4, w_{12}, 42)$

cate N={1,2}. We assume that the groups in G have been computed as

- Let N={1,2}. We assume that the groups in G have been computed as
- Our goal is now to determine G_S and the offsets wi of the corresponding reservations such that Lmax(and, thus, the required duration T_{DS} of the DS) is minimized





- We formulate integer programming problems with two components to find the optimal message schedule
 - The first component addresses the selection of the message groups and the corresponding reservations. gi $\in \{0,1\}$ takes the value of 1 if Gi $\in G_S$ and is 0 otherwise
 - The second component is determining the reservation offsets. $x_{i,k} \in \{0,1\}$ takes the value of 1 if w_i =k and is 0 otherwise, where k=0,..., rp_i -1

Consider a reservation R_i that corresponds to $\mathcal{G}_i \in \mathcal{G}$. The contribution of R_i to L_j , $j=1,\ldots,G_{\mathrm{RP}}-1$, is given as follows.

- 1) $g_i = 0$: Then, $\mathcal{G}_i \notin \mathcal{G}^S$ and R_i does not add to L_j .
- 2) $g_i = 1$ and $x_{i,k} = 1$ for $k = j \mod rp_i$: Then, $w_i = k$ and l_i MS are reserved for R_i in L_j .
- 3) $g_i = 1$ and $x_{i,k} = 0$ for $k = j \mod rp_i$: Then, $w_i \neq k$ and one MS is reserved for R_i in L_j .

Accordingly, we can express the cycle load L_j as follows:

$$L_j = \sum_{\mathcal{G}_i \in \mathcal{G}} g_i \cdot (x_{i,k} \cdot l_i + (1 - x_{i,k}) \cdot 1)$$



03

Assuming without loss of generality that $L_{max} = L_0$, the expression to be minimized is



Assuming without loss of generality that $L_{max} = L_0$, the expression to be minimized is

$$\min_{X} L_0 = \min_{X} \sum_{\mathcal{G}_i \in \mathcal{G}} g_i \cdot x_{i,0} \cdot l_i + g_i (1 - x_{i,0}) \cdot 1$$



Assuming without loss of generality that $L_{max} = L_0$, the expression to be minimized is

$$\min_{X} L_0 = \min_{X} \sum_{\mathcal{G}_i \in \mathcal{G}} g_i \cdot x_{i,0} \cdot l_i + g_i (1 - x_{i,0}) \cdot 1$$

With the constraints

03

Assuming without loss of generality that $L_{max} = L_0$, the expression to be minimized is


$$\min_{X} L_0 = \min_{X} \sum_{\mathcal{G}_i \in \mathcal{G}} g_i \cdot x_{i,0} \cdot l_i + g_i (1 - x_{i,0}) \cdot 1$$

With the constraints

$$egin{aligned} orall M_m^n, & \sum_{i,M_m^n \in \mathcal{G}_i} g_i = 1 \ \end{aligned}$$
 for $i=1,\ldots,|\mathcal{G}|, & \sum_{k=0}^{rp_i-1} x_{i,k} = g_i \ \end{aligned}$ for $j=1,\ldots,G_{\mathrm{RP}}-1, \quad L_j \leq L_0.$


03

○ Plot of the maximum cycle load Lmax, against the arrival rate






Plot of the computational time, against the arrival rate










Plot of the computational time, against the arrival rate (Extended Message Set)



Thank You