

Nama : Adridinan Najmi Faza  
NIM : H1D025059  
Shift Awal/Akhir : B/H

1. Berikan 1 Contoh perintah alter dan modify dalam satu syntax

**BEFORE**

```
MariaDB [penjualan_barang]> desc pelanggan;
```

Field	Type	Null	Key	Default	Extra
id_pelanggan	varchar(10)	NO	PRI	NULL	
nama	varchar(40)	NO		NULL	
Alamat	varchar(255)	YES		NULL	
Pekerjaan	varchar(50)	YES		NULL	
No_ktp	varchar(20)	YES		NULL	
No_telp	varchar(15)	YES		NULL	

6 rows in set (0.015 sec)

```
MariaDB [penjualan_barang]> alter table pelanggan modify no_ktp char(20);  
Query OK, 0 rows affected (0.034 sec)  
Records: 0 Duplicates: 0 Warnings: 0
```

**AFTER**

```
MariaDB [penjualan_barang]> desc pelanggan;
```

Field	Type	Null	Key	Default	Extra
id_pelanggan	varchar(10)	NO	PRI	NULL	
nama	varchar(40)	NO		NULL	
Alamat	varchar(255)	YES		NULL	
Pekerjaan	varchar(50)	YES		NULL	
no_ktp	char(20)	YES		NULL	
No_telp	varchar(15)	YES		NULL	

6 rows in set (0.015 sec)

**Syntax:**

```
MariaDB [penjualan_barang]> alter table pelanggan modify no_ktp char(20);  
Query OK, 0 rows affected (0.034 sec)  
Records: 0 Duplicates: 0 Warnings: 0
```

## 2. Berikan 1 Contoh penggunaan drop table

**BEFORE**

```
MariaDB [penjualan_barang]> show tables;
+-----+
| Tables_in_penjualan_barang |
+-----+
| barang                      |
| detail_jual                 |
| nota_penjualan              |
| pelanggan                   |
+-----+
4 rows in set (0.001 sec)
```

```
MariaDB [penjualan_barang]> drop table detail_jual;
Query OK, 0 rows affected (0.010 sec)
```

**AFTER**

```
MariaDB [penjualan_barang]> show tables;
+-----+
| Tables_in_penjualan_barang |
+-----+
| barang                      |
| nota_penjualan              |
| pelanggan                   |
+-----+
3 rows in set (0.001 sec)

MariaDB [penjualan_barang]> |
```

### Syntax:

```
MariaDB [penjualan_barang]> drop table detail_jual;
```

```
Query OK, 0 rows affected (0.010 sec)
```

### 3. Berikan 1 Contoh penerapan rename table

```
MariaDB [penjualan_barang]> show tables;
```

**BEFORE**

```
+-----+
| Tables_in_penjualan_barang |
+-----+
| barang                      |
| nota_penjualan              |
| pelanggan                   |
+-----+
```

```
3 rows in set (0.001 sec)
```

```
MariaDB [penjualan_barang]> rename table pelanggan to customers;
Query OK, 0 rows affected (0.012 sec)
```

**AFTER**

```
MariaDB [penjualan_barang]> show tables;
```

```
+-----+
| Tables_in_penjualan_barang |
+-----+
| barang                      |
| customers                   |
| nota_penjualan              |
+-----+
```

```
3 rows in set (0.001 sec)
```

```
MariaDB [penjualan_barang]> |
```

#### Syntax:

```
MariaDB [penjualan_barang]> rename table pelanggan to customers;
```

```
Query OK, 0 rows affected (0.012 sec)
```