```
create database Employee;
use Employee;
create table Department (
        deptid int primary key ,
        deptname varchar(60)
);
create table Location (
        locationid int primary key,
   location varchar(50)
   );
create table employees (
        employeeid int primary key,
   employeename varchar(40),
   gender enum('m','f'),
   age int,
   hiredate date,
   designation varchar(60),
   deptid int,
   locationid int,
   salary decimal(10.2)
   );



show tables ;
desc employees;
alter table employees add email varchar(60);
alter table employees modify designation varchar(200);
```

```
alter table employees drop age;
alter table employees rename column hiredate to date_of_joining;

rename table department to department_info;
rename table location to locations;
desc department_info;
desc locations;



truncate table employees;


desc employees;


drop table employees;


 show tables;


 drop database employee;


create database employee;


use employee;
create table Department (
        dept_id int primary key unique ,
        dept_name varchar(60) not null
);
select * from department;
```

```
create table location(
        location_id int primary key unique auto_increment,
   location_name varchar(45) not null
   );



create table employees (
        employeeid int primary key unique ,
   employeename varchar(40) not null,
   gender enum('m','f'),
   age int check (age >= 18),
   hiredate date default(current_date),
   designation varchar(60),
   dept_id int unique,
   foreign key(dept_id)references department (dept_id),
   location_id int unique,
   foreign key(location_id)references location(location_id),
   salary decimal(10,2)
   );


   create database Employee;
use Employee;
create table Department (
        deptid int primary key ,
        deptname varchar(60)
);
create table Location (
        locationid int primary key,
```

```
   location varchar(50)
   );
create table employees (
        employeeid int primary key,
   employeename varchar(40),
   gender enum('m','f'),
   age int,
   hiredate date,
   designation varchar(60),
   deptid int,
   locationid int,
   salary decimal(10.2)
   );



show tables ;
desc employees;
alter table employees add email varchar(60);
alter table employees modify designation varchar(200);
alter table employees drop age;
alter table employees rename column hiredate to date_of_joining;

rename table department to department_info;
rename table location to locations;
desc department_info;
desc locations;
```

```
truncate table employees;

desc employees;

drop table employees;

 show tables;

 drop database employee;

create database employee;

use employee;
create table Department (
        dept_id int primary key unique ,
        dept_name varchar(60) not null
);
select * from department;

create table location(
        location_id int primary key unique auto_increment,
   location_name varchar(45) not null
   );



create table employees (
        employeeid int primary key unique ,
```

```
  employeename varchar(40) not null,
  gender enum('m','f'),
  age int check (age >= 18),
  hiredate date default(current_date),
  designation varchar(60),
  dept_id int unique,
  foreign key(dept_id)references department (dept_id),
  location_id int unique,
  foreign key(location_id)references location(location_id),
  salary decimal(10,2)
  );
create database Employee;
use Employee;
create table Department (
        deptid int primary key ,
        deptname varchar(60)
);
create table Location (
        locationid int primary key,
  location varchar(50)
  );
create table employees (
        employeeid int primary key,
  employeename varchar(40),
  gender enum('m','f'),
  age int,
  hiredate date,
  designation varchar(60),
```

```
  deptid int,
  locationid int,
  salary decimal(10.2)
  );
```

```
show tables ;
desc employees;
alter table employees add email varchar(60);
alter table employees modify designation varchar(200);
alter table employees drop age;
alter table employees rename column hiredate to date_of_joining;

rename table department to department_info;
rename table location to locations;
desc department_info;
desc locations;


truncate table employees;


desc employees;


drop table employees;


 show tables;
```

```
 drop database employee;


create database employee;


use employee;
create table Department (
        dept_id int primary key unique ,
        dept_name varchar(60) not null
);
select * from department;


create table location(
        location_id int primary key unique auto_increment,
   location_name varchar(45) not null
   );



create table employees (
        employeeid int primary key unique ,
   employeename varchar(40) not null,
   gender enum('m','f'),
   age int check (age >= 18),
   hiredate date default(current_date),
   designation varchar(60),
   dept_id int unique,
   foreign key(dept_id)references department (dept_id),
   location_id int unique,
   foreign key(location_id)references location(location_id),
```

```
salary decimal(10,2)

);

select * from employees;
```