

New to Gradio? Start here: **Getting Started**

See the Release History

← Video

Progress →

Examples

gradio.Examples(examples, inputs, ...)


Description

This class is a wrapper over the Dataset component and can be used to create Examples for Blocks / Interfaces. Populates the Dataset component with examples and assigns event listener so that clicking on an example populates the input/output components. Optionally handles example caching for fast inference.

Initialization

Parameter	Description
examples list[Any] list[list[Any]] str required	example inputs that can be clicked to populate specific components. Should be nested list, in which the outer list consists of samples and each inner list consists of an input corresponding to each input component. A string path to a directory of examples can also be provided but it should be within the directory with the python file running the gradio app. If there are multiple input components and a directory is provided, a log.csv file must be present in the directory to link corresponding inputs.
<pre>inputs Component list[Component] required</pre>	the component or list of components corresponding to the examples

ımeter	Description
outputs	optionally, provide the component or list of components
Component list[Component] None	corresponding to the output of the examples. Required if
default: None	cache_examples is True.
fn	optionally, provide the function to run to generate the outputs
Callable None	corresponding to the examples. Required if Cache_examples is
default: None	True.
cache_examples	if True, caches examples for fast runtime. If True, then fn and
bool	outputs must be provided. If fn is a generator function, then the
default: False	last yielded value will be used as the output.
examples_per_page	how many examples to show per page.
int	
default: 10	
label	the label to use for the examples component (by default,
str None	"Examples")
default: "Examples"	
elem_id	an optional string that is assigned as the id of this component in
str None	the HTML DOM.
default: None	
run_on_click	if cache_examples is False, clicking on an example does not run
bool	the function when an example is clicked. Set this to True to run
default: False	the function when an example is clicked. Has no effect if
	cache_examples is True.
preprocess	if True, preprocesses the example input before running the
bool	prediction function and caching the output. Only applies if
default: True	cache_examples is True.



Demos

```
import gradio as gr
import os

def combine(a, b):
    return a + " " + b

def mirror(x):
    return x
```

Guides




Image Classification With Vision Transformers

Create Your Own Friends With A Gan

← Video Progress →



