

New to Gradio? Start here: **Getting Started**

See the **Release History**

← Chatbot

CheckboxGroup →

# Checkbox

gradio.Checkbox(...)

## Description

Creates a checkbox that can be set to `True` or `False`.

## Behavior

As input: passes the status of the checkbox as a `bool` into the function.

As output: expects a `bool` returned from the function and, if it is True, checks the checkbox.

## Initialization

Parameter	Description
<div>value</div> <div><i>bool   Callable</i></div> <div>default: False</div>	if True, checked by default. If callable, the function will be called whenever the app loads to set the initial value of the component.
<div>label</div> <div><i>str   None</i></div> <div>default: None</div>	The label for this component. Appears above the component and is also used as the header if there are a table of examples for this component. If None and used in a <code>gr.Interface</code> , the label will be the name of the parameter this component is assigned to.
<div>info</div> <div><i>str   None</i></div> <div>default: None</div>	additional component description.



<div>every</div> <div>float   None</div> <div>default: None</div>	<p>If <code>value</code> is a callable, run the function 'every' number of seconds while the client connection is open. Has no effect otherwise.</p> <p>Queue must be enabled. The event can be accessed (e.g. to cancel it) via this component's <code>.load_event</code> attribute.</p>
<div>show_label</div> <div>bool   None</div> <div>default: None</div>	<p>if True, will display label.</p>
<div>container</div> <div>bool</div> <div>default: True</div>	<p>If True, will place the component in a container - providing some extra padding around the border.</p>
<div>scale</div> <div>int   None</div> <div>default: None</div>	<p>relative width compared to adjacent Components in a Row. For example, if Component A has <code>scale=2</code>, and Component B has <code>scale=1</code>, A will be twice as wide as B. Should be an integer.</p>
<div>min_width</div> <div>int</div> <div>default: 160</div>	<p>minimum pixel width, will wrap if not sufficient screen space to satisfy this value. If a certain scale value results in this Component being narrower than <code>min_width</code>, the <code>min_width</code> parameter will be respected first.</p>
<div>interactive</div> <div>bool   None</div> <div>default: None</div>	<p>if True, this checkbox can be checked; if False, checking will be disabled. If not provided, this is inferred based on whether the component is used as an input or output.</p>
<div>visible</div> <div>bool</div> <div>default: True</div>	<p>If False, component will be hidden.</p>
<div>elem_id</div> <div>str   None</div> <div>default: None</div>	<p>An optional string that is assigned as the id of this component in the HTML DOM. Can be used for targeting CSS styles.</p>

<div>elem_classes</div> <div><i>list[str]   str   None</i></div> <div>default: None</div>	An optional list of strings that are assigned as the classes of this component in the HTML DOM. Can be used for targeting CSS styles.
<div>render</div> <div><i>bool</i></div> <div>default: True</div>	If False, component will not render be rendered in the Blocks context. Should be used if the intention is to assign event listeners now but render the component later.

## Shortcuts

Class	Interface String Shortcut	Initialization
<code>gradio.Checkbox</code>	"checkbox"	Uses default values

## Demos

```

sentence_builder      titanic_survival

import gradio as gr

def sentence_builder(quantity, animal, countries, place, activity_list, morning):
    return f"""The {quantity} {animal}s from {" and ".join(countries)} went to the {place}
    where they {" and ".join(activity_list)} until the {"morning" if morning else "night"}"""

demo = gr.Interface(
    sentence_builder,
    [
        gr.Slider(1, 20, step=1, label="Quantity"), gr.Cat("Choose between 1 and 20")
    ]
)

```

## Event Listeners

## Description

Event listeners allow you to capture and respond to user interactions with the UI components you've defined in a Gradio Blocks app. When a user interacts with an element, such as changing



a slider value or uploading an image, a function is called.

### Supported Event Listeners

The **Checkbox** component supports the following event listeners. Each event listener takes the same parameters, which are listed in the **Event Arguments** table below.

Listener	Description
<code>gradio.Checkbox.change(fn, ...)</code>	Triggered when the value of the Checkbox changes either because of user input (e.g. a user types in a textbox) OR because of a function update (e.g. an image receives a value from the output of an event trigger). See <code>.input()</code> for a listener that is only triggered by user input.
<code>gradio.Checkbox.input(fn, ...)</code>	This listener is triggered when the user changes the value of the Checkbox.
<code>gradio.Checkbox.select(fn, ...)</code>	Event listener for when the user selects or deselects the Checkbox. Uses event data <code>gradio.SelectData</code> to carry <code>value</code> referring to the label of the Checkbox, and <code>selected</code> to refer to state of the Checkbox. See <code>EventData</code> documentation on how to use this event data

### Event Arguments

Parameter	Description
<div><code>fn</code></div> <div><i>Callable   None   Literal['decorator']</i></div> <div><b>default: "decorator"</b></div>	the function to call when this event is triggered. Often a machine learning model's prediction function. Each parameter of the function corresponds to one input component, and the function should return a single value or a tuple of values, with each element in the tuple corresponding to one output component.
<div><code>inputs</code></div> <div><i>Component   list[Component]   set[Component]   None</i></div> <div><b>default: None</b></div>	List of <code>gradio.components</code> to use as inputs. If the function takes no inputs, this should be an empty list.
<div><code>outputs</code></div> <div><i>Component   list[Component]   None</i></div> <div><b>default: None</b></div>	List of <code>gradio.components</code> to use as outputs. If the function returns no outputs, this should be an empty list.



Parameter	Description
<div>api_name</div> <div><i>str   None   Literal[False]</i></div> <div>default: None</div>	defines how the endpoint appears in the API docs. Can be a string, None, or False. If set to a string, the endpoint will be exposed in the API docs with the given name. If None (default), the name of the function will be used as the API endpoint. If False, the endpoint will not be exposed in the API docs and downstream apps (including those that <code>gr.load</code> this app) will not be able to use this event.
<div>scroll_to_output</div> <div><i>bool</i></div> <div>default: False</div>	If True, will scroll to output component on completion
<div>show_progress</div> <div><i>Literal[('full', 'minimal', 'hidden')]</i></div> <div>default: "full"</div>	If True, will show progress animation while pending
<div>queue</div> <div><i>bool   None</i></div> <div>default: None</div>	If True, will place the request on the queue, if the queue has been enabled. If False, will not put this event on the queue, even if the queue has been enabled. If None, will use the queue setting of the gradio app.
<div>batch</div> <div><i>bool</i></div> <div>default: False</div>	If True, then the function should process a batch of inputs, meaning that it should accept a list of input values for each parameter. The lists should be of equal length (and be up to length <code>max_batch_size</code> ). The function is then <i>required</i> to return a tuple of lists (even if there is only 1 output component), with each list in the tuple corresponding to one output component.
<div>max_batch_size</div> <div><i>int</i></div> <div>default: 4</div>	Maximum number of inputs to batch together if this is called from the queue (only relevant if batch=True)



Parameter	Description
<div>preprocess</div> <div><i>bool</i></div> <div><b>default: True</b></div>	If False, will not run preprocessing of component data before running 'fn' (e.g. leaving it as a base64 string if this method is called with the <code>Image</code> component).
<div>postprocess</div> <div><i>bool</i></div> <div><b>default: True</b></div>	If False, will not run postprocessing of component data before returning 'fn' output to the browser.
<div>cancel<span>s</span></div> <div><i>dict[str, Any]   list[dict[str, Any]]   None</i></div> <div><b>default: None</b></div>	A list of other events to cancel when this listener is triggered. For example, setting <code>cancel<span>s</span>=[click_event]</code> will cancel the <code>click_event</code> , where <code>click_event</code> is the return value of another components <code>.click</code> method. Functions that have not yet run (or generators that are iterating) will be cancelled, but functions that are currently running will be allowed to finish.
<div>every</div> <div><i>float   None</i></div> <div><b>default: None</b></div>	Run this event 'every' number of seconds while the client connection is open. Interpreted in seconds. Queue must be enabled.
<div>trigger_mode</div> <div><i>Literal[('once', 'multiple', 'always_last')]   None</i></div> <div><b>default: None</b></div>	If "once" (default for all events except <code>.change()</code> ) would not allow any submissions while an event is pending. If set to "multiple", unlimited submissions are allowed while pending, and "always_last" (default for <code>.change()</code> event) would allow a second submission after the pending event is complete.
<div>js</div> <div><i>str   None</i></div> <div><b>default: None</b></div>	Optional frontend js method to run before running 'fn'. Input arguments for js method are values of 'inputs' and 'outputs', return should be a list of values for output components.



## Parameter

## Description

`concurrency_limit`

*int | None | Literal['default']*

**default: "default"**

If set, this is the maximum number of this event that can be running simultaneously. Can be set to None to mean no concurrency\_limit (any number of this event can be running simultaneously). Set to "default" to use the default concurrency limit (defined by the `default_concurrency_limit` parameter in `Blocks.queue()`, which itself is 1 by default).

`concurrency_id`

*str | None*

**default: None**

If set, this is the id of the concurrency group. Events with the same concurrency\_id will be limited by the lowest set concurrency\_limit.

`show_api`

*bool*

**default: True**

whether to show this event in the "view API" page of the Gradio app, or in the ".view\_api()" method of the Gradio clients. Unlike setting api\_name to False, setting show\_api to False will still allow downstream apps to use this event. If fn is None, show\_api will automatically be set to False.

[← Chatbot](#)

[CheckboxGroup →](#)