## Installing your own package

**DEVELOPING PYTHON PACKAGES** 



James Fulton
Climate informatics researcher



## Why should you install your own package?

Inside example\_script.py

import mysklearn

```
home/
-- mysklearn <-- in same directory
  |-- __init__.py
  |-- preprocessing
  |-- normalize.py
     |-- standardize.py
  |-- regression
     |-- __init__.py
     |-- regression.py
   -- utils.py
-- example_script.py <-- in same directory</pre>
```

## Why should you install your own package?

Inside example\_script.py

import mysklearn

```
Traceback (most recent call last):
   File "<stdin>", line 1, in <module>
ModuleNotFoundError: No module named 'mysklearn'
```

Directory tree

```
home/
-- mypackages
   |-- mysklearn <---
       |-- __init__.py
       |-- preprocessing
       | |-- normalize.py
          |-- standardize.py
       |-- regression
          |-- __init__.py
          |-- regression.py
-- myscripts
    `-- example_script.py
```

## setup.py

- Is used to install the package
- Contains metadata on the package

## Package directory structure

```
mysklearn/
|-- __init__.py
|-- preprocessing
    |-- __init__.py
    |-- normalize.py
    |-- standardize.py
|-- regression
    |-- __init__.py
    |-- regression.py
|-- utils.py
```

## Package directory structure

```
mysklearn/ <-- outer directory
-- mysklearn <--- inner source code directory
    |-- __init__.py
    |-- preprocessing
       |-- __init__.py
        |-- normalize.py
        |-- standardize.py
    |-- regression
        |-- __init__.py
        |-- regression.py
    |-- utils.py
```

## Package directory structure

```
mysklearn/ <-- outer directory
-- mysklearn <--- inner source code directory
    |-- __init__.py
    |-- preprocessing
      |-- __init__.py
       |-- normalize.py
       |-- standardize.py
    |-- regression
       |-- __init__.py
       |-- regression.py
    |-- utils.py
-- setup.py <-- setup script in outer
```

## Inside setup.py

```
# Import required functions
from setuptools import setup
# Call setup function
setup(
    author="James Fulton",
    description="A complete package for linear regression.",
    name="mysklearn",
    version="0.1.0",
```

version number = (major number). (minor number). (patch number)

## Inside setup.py

```
# Import required functions
from setuptools import setup, find_packages
# Call setup function
setup(
    author="James Fulton",
    description="A complete package for linear regression.",
    name="mysklearn",
    version="0.1.0",
    packages=find_packages(include=["mysklearn", "mysklearn.*"]),
```

#### **Editable installation**

```
pip install -e .
```

- . = package in current directory
- -e = editable

```
mysklearn/ <-- navigate to here
-- mysklearn
    |-- __init__.py
    |-- preprocessing
      |-- __init__.py
        |-- normalize.py
        |-- standardize.py
    |-- regression
        |-- __init__.py
        |-- regression.py
    |-- utils.py
-- setup.py
```

## Let's practice!

DEVELOPING PYTHON PACKAGES



# Dealing with dependencies

**DEVELOPING PYTHON PACKAGES** 



James Fulton
Climate informatics researcher



## What are dependencies?

- Other packages you import inside your package
- Inside mymodule.py:

```
# These imported packages are dependencies
import numpy as np
import pandas as pd
...
```

## Adding dependencies to setup.py

```
from setuptools import setup, find_packages

setup(
    ...
    install_requires=['pandas', 'scipy', 'matplotlib'],
)
```



## Controlling dependency version

```
from setuptools import setup, find_packages
setup(
    install_requires=[
         'pandas>=1.0',
         'scipy==1.1',
         'matplotlib>=2.2.1,<3'</pre>
```

## Controlling dependency version

```
from setuptools import setup, find_packages
setup(
   install_requires=[
        'pandas>=1.0',  # good
       'scipy==1.1',  # bad
        'matplotlib>=2.2.1,<3' # good</pre>
```

- Allow as many package versions as possible
- Get rid of unused dependencies

## Python versions

```
from setuptools import setup, find_packages

setup(
    ...
    python_requires='>=2.7, !=3.0.*, !=3.1.*',
)
```

## Choosing dependency and package versions

- Check the package history or release notes
  - e.g. the NumPy release notes
- Test different versions

#### Release Notes

- 1.19.0
  - Highlights
  - Expired deprecations
    - numpy.insert and numpy.delete can no longer be passed an axis on 0d arrays
    - numpy.delete no longer ignores out-of-bounds indices
    - numpy.insert and numpy.delete no longer accept non-integral indices
    - numpy.delete no longer casts boolean indices to integers
  - Compatibility notes
    - Changed random variate stream from numpy.random.Generator.dirichlet
    - Scalar promotion in **PyArray\_ConvertToCommonType**
    - Fasttake and fastputmask slots are deprecated and NULL'ed
    - np.ediff1d casting behaviour with to\_end and to\_begin
    - Converting of empty array-like objects to NumPy arrays
    - Removed multiarray.int\_asbuffer



## Making an environment for developers

```
pip freeze
```

```
alabaster==0.7.12
appdirs==1.4.4
argh==0.26.2
...
wrapt==1.11.2
yapf==0.29.0
zipp==3.1.0
```

## Making an environment for developers

Save package requirements to a file

```
pip freeze > requirements.txt
```

Install requirements from file

```
pip install -r requirements.txt
```

```
mysklearn/
-- mysklearn
    |-- __init__.py
    |-- preprocessing
       |-- __init__.py
        |-- normalize.py
        |-- standardize.py
    |-- regression
        |-- __init__.py
        |-- regression.py
    |-- utils.py
-- setup.py
-- requirements.txt <-- developer environment
```

## Let's practice!

DEVELOPING PYTHON PACKAGES



# Including licences and writing READMEs

**DEVELOPING PYTHON PACKAGES** 



James Fulton
Climate informatics researcher



## Why do I need a license?

• To give others permission to use your code



## Open source licenses

- Find more information here
- Allow users to
  - use your package
  - modify your package
  - distribute versions of your package

<sup>&</sup>lt;sup>1</sup> https://choosealicense.com



#### What is a README?

- The "front page" of your package
- Displayed on Github or PyPl

#### What to include in a README

#### **README** sections

- Title
- Description and Features
- Installation
- Usage examples
- Contributing
- License

#### **README format**

#### Markdown (commonmark)

- Contained in README.md file
- Simpler
- Used in this course and in the wild

#### reStructuredText

- Contained in README.rst file
- More complex
- Also common in the wild

Contents of README.md

What it looks like when rendered

#### Contents of README.md

# mysklearn
mysklearn is a package for complete
\*\*linear regression\*\* in Python.

You can find out more about this package on [DataCamp](https://datacamp.com)

What it looks like when rendered

#### mysklearn

mysklearn is a package for complete **linear** regression in python.

You can find out more about this package on DataCamp



#### Contents of README.md

```
# mysklearn
mysklearn is a package for complete
**linear regression** in Python.

You can find out more about this package
on [DataCamp](https://datacamp.com)

## Installation
You can install this package using
```

What it looks like when rendered

#### mysklearn

mysklearn is a package for complete **linear** regression in python.

You can find out more about this package on DataCamp

#### Installation

You can install this package using

Contents of README.md

```
# mysklearn
mysklearn is a package for complete
**linear regression** in Python.
You can find out more about this package
on [DataCamp](https://datacamp.com)
## Installation
You can install this package using
. . .
pip install mysklearn
```

What it looks like when rendered

#### mysklearn

mysklearn is a package for complete **linear** regression in python.

You can find out more about this package on DataCamp

#### Installation

You can install this package using

pip install mysklearn

## Adding these files to your package

```
mysklearn/
-- mysklearn
   |-- __init__.py
   |-- preprocessing
    |-- ...
   |-- regression
     |-- ...
   |-- utils.py
|-- setup.py
-- requirements.txt
-- LICENSE <--- new files
-- README.md <--- added to top directory
```

#### MANIFEST.in

Lists all the extra files to include in your package distribution.



#### MANIFEST.in

Contents of MANIFEST.in

```
include LICENSE
include README.md
```

```
mysklearn/
-- mysklearn
    |-- __init__.py
    |-- preprocessing
      -- ...
   |-- regression
    | |-- ...
   |-- utils.py
-- setup.py
-- requirements.txt
-- LICENSE
-- README.md
-- MANIFEST.in <---
```

## Let's practice!

DEVELOPING PYTHON PACKAGES



# Publishing your package

**DEVELOPING PYTHON PACKAGES** 



James Fulton
Climate informatics researcher



## PyPl

#### **Python Package Index**

- pip installs packages from here
- Anyone can upload packages
- You should upload your package as soon as it might be useful

<sup>&</sup>lt;sup>1</sup> https://pypi.org/



#### Distributions

- Distribution package a bundled version of your package which is ready to install.
- Source distribution a distribution package which is mostly your source code.
- Wheel distribution a distribution package which has been processed to make it faster to install.

#### How to build distributions

```
python setup.py sdist bdist_wheel
```

- sdist = source distribution
- bdist\_wheel = wheel distribution

```
mysklearn/
|-- mysklearn
|-- setup.py
|-- requirements.txt
-- LICENSE
-- README.md
|-- dist
    |-- mysklearn-0.1.0-py3-none-any.whl
    |-- mysklearn-0.1.0.tar.gz
|-- build
-- mysklearn.egg-info
```

## Getting your package out there

Upload your distributions to PyPI

```
twine upload dist/*
```

Upload your distributions to TestPyPI

```
twine upload -r testpypi dist/*
```

```
mysklearn/
l-- mysklearn
|-- setup.py
|-- requirements.txt
-- LICENSE
-- README.md
|-- dist
    |-- mysklearn-0.1.0-py3-none-any.whl
    |-- mysklearn-0.1.0.tar.gz
l-- build
|-- mysklearn.egg-info
```

## How other people can install your package

Install package from PyPI

```
pip install mysklearn
```

Install package from TestPyPI

## Let's practice!

DEVELOPING PYTHON PACKAGES

