

NAKUJA ROCKET SAFETY CODE

- 1. **Materials**. I will use only lightweight materials such as paper, wood, rubber, plastic, fiberglass, or when necessary ductile metal, for the construction of my rocket.
- 2. **Motors**. I will be allowed to fabricate the motor only after the motor design is reviewed by the team. I will always wear protective eyewear (safety goggles) while fabricating the motor. I will prepare the means of fire protection, such as fire extinguisher and water. I will keep the materials of propellant (chemicals) in a safe place. I will not dispose of any harmful chemicals to the environment
- 3. **Static Tests** I will always wear protective eyewear (safety goggles). I will prepare the means of fire protection, such as fire extinguisher and water. I will take the distance from at least 30m from the test stand. I will ensure if the safety interlock is active to avoid the accidental arming of the motor. I will fire the motor only in the designated place by the team. I will ensure if the fire is not directed to dry grass on the ground to prevent the fire from spreading.
- 4. **Ignition System.** I will launch my rockets with an electrical launch system, and with electrical motor igniters that are installed in the motor only after my rocket is at the launch pad or in a designated prepping area. My launch system will have a safety interlock that is in series with the launch switch that is not installed until my rocket is ready for launch, and will use a launch switch that returns to the "off" position when released. The function of onboard energetics and firing circuits will be inhibited except when my rocket is in the launching position. I will take any protective measures to prevent the circuit from short circuit (by rain, dust, etc.)
- 5. **Misfires**. If my rocket does not launch when I press the button of my electrical launch system, I will remove the launcher's safety interlock or disconnect its battery and will wait 60 seconds after the last launch attempt before allowing anyone to approach the rocket. I will stop the launch in case of bad weather.
- 6. Launch Safety. I will use a 5-second countdown before launch. I will ensure that a means is available to warn participants and spectators in the event of a problem. I will ensure that no person is closer to the launch pad than allowed by the accompanying Minimum Distance Table. When arming onboard energetics and firing circuits I will ensure that no person is at the pad except safety personnel and those required for arming and disarming operations. I will check the stability of my rocket before the flight and will not fly it if it cannot be determined to be stable. When conducting a simultaneous launch of more than a high-power rocket I will observe the additional requirements of NFPA 1127.
- 7. **Launcher**. I will launch my rocket from a stable device that provides rigid guidance until the rocket has attained a speed that ensures a stable flight, and that is pointed to within 20 degrees of vertical. If the



wind speed exceeds 5 miles per hour I will use a launcher length that permits the rocket to attain a safe velocity before separation from the launcher. I will use a blast deflector to prevent the motor's exhaust from hitting the ground. I will ensure that dry grass is cleared around each launch pad by the accompanying Minimum Distance table, and will increase this distance by a factor of 1.5 and clear that area of all combustible material if the rocket motor being launched uses titanium sponge in the propellant.

- 8. **Size**. My rocket will not contain any combination of motors that total more than 40,960 N-sec (9208 pound- seconds) of total impulse. My rocket will not weigh more at liftoff than one-third of the certified average thrust of the high-power rocket motor(s) intended to be ignited at launch.
- 9. **Flight Safety**. I will not launch my rocket at targets, into clouds, near airplanes, nor on trajectories that take it directly over the heads of spectators or beyond the boundaries of the launch site, and will not put any flammable or explosive payload in my rocket. I will not launch my rockets if wind speeds exceed 20 miles per hour. I will comply with Federal Aviation Administration airspace regulations when flying and will ensure that my rocket will not exceed any applicable altitude limit in effect at that launch site. I will comply with the altitude limit regulated by KAA.
- 10. Launch Site. I will launch my rocket outdoors, in an open area where trees, power lines, occupied buildings, and persons not involved in the launch do not present a hazard, and that is at least as large on its smallest dimension as one-half of the maximum altitude to which rockets are allowed to be flown at that site or 1500 feet, whichever is greater, or 1000 feet for rockets with a combined total impulse of less than 160 N-sec, a total liftoff weight of fewer than 1500 grams, and a maximum expected altitude of fewer than 610 meters (2000 feet).
- 11. Launcher Location. My launcher will be 1500 feet from any occupied building or from any public highway on which traffic flow exceeds 10 vehicles per hour, not including traffic flow related to the launch. It will also be no closer than the appropriate Minimum Personnel Distance from the accompanying table from any boundary of the launch site.
- 12. **Recovery System**. I will use a recovery system such as a parachute in my rocket so that all parts of my rocket return safely and undamaged and can be flown again, and I will use only flame-resistant or fireproof recovery system wadding in my rocket.
- 13. **Recovery Safety**. I will not attempt to recover my rocket from power lines, tall trees, or other dangerous places, fly it under conditions where it is likely to recover in spectator areas or outside the launch site, nor attempt to catch it as it approaches the ground.
- 14. **Improvement Order**. If I will be given the improvement order by the supervisor, I will comply with the instruction.



Agreement on Nakuja rocket safety code

I have read all the description in the Nakuja rock	et safety code and hereby agree to the code.
Name	
Affiliation	
Email	
Phone	
Date	
Signature	